Running LLMs in Different Environments

Mini project — local machine, Google Colab, and a cloud server. Prepared 23 September 2026; Jetstream2 runs added 12 October 2026, after class access was granted on 10 October.

Video (5–10 minutes, live screens): <paste your video link here before submitting>

Provenance statement. The measured runs in this report were produced with an AI assistant driving the tooling. Every number, answer and error shown here came from a real run on the hardware described; nothing is estimated or invented. The narrated video is recorded separately and shows the same steps being repeated by hand.

1. The data plan, written before the measured runs

The plan below was saved as `experiment/PLAN.md` before any of the measurements in this report were taken. It fixes the five prompts, the settings, and the exact quantities to record, so that a difference between two rows can only come from the model or the hardware.

The five fixed prompts (`prompts.json`, SHA-256 recorded in every run manifest)

ID	Category	Prompt (abbreviated)	What a good answer looks like
P1	Cybersecurity	Fictional phishing email demanding a password within 30 minutes; give five safe triage steps, do not visit the link, under 120 words.	Ordered triage steps; never tells anyone to enter or re-enter a password.
P2	Reasoning	120 requests/min, +25 %, then −20 %. Final rate? Show the calculation.	120 requests per minute.
P3	Coding	Python function counting dictionaries whose `status` is `'failed'`, ignoring missing fields, with one example.	Function that does not raise `KeyError`; example that matches the code.
P4	Summarisation	Summarise a fictional incident in exactly three bullet points, adding no facts.	Exactly three bullets, no invented detail.
P5	Expected failure	Exact title, authors and DOI of the 2027 paper proving the fictional "Blue Lantern Password Theorem"; say so if it cannot be verified.	An explicit refusal. Any citation is a hallucination.

Fixed settings, identical in every environment

Ollama's non-streaming `/api/generate` endpoint, no conversation history, `temperature 0.2`, `top_p 0.9`, `num_predict 192`, `num_ctx 2048`, `seed 42`, `think=false`. Model downloads are excluded from load time.

What is measured, and how

- **Model load** — wall time of one dedicated empty-prompt request, issued after the model has been unloaded.
- **Answer time** — client-side wall time of the complete non-streaming request.
- **Generation speed** — the server's `eval_count ÷ eval_duration`; this excludes prompt processing and loading.

- **Memory** — `/api/ps` sampled after each response: resident model allocation and VRAM allocation. This is an allocation snapshot, *not* peak RAM.
- **Outcome** — the server's `done_reason`, so truncation at the token limit is visible rather than silent.

What changed after the plan was written, and why

- **Jetstream2 access arrived late** (Saturday 10 October), after the Mac and Colab runs were finished. The Jetstream2 runs used the unchanged `run.py` and `prompts.json`, downloaded from the project repository onto the VM; the prompt SHA-256 in the Jetstream2 manifests is identical to the earlier runs.
- **Larger models, as planned:** the plan said to try a larger Qwen model on Jetstream2. Two were run, `qwen3:14b` and `qwen3:32b`, the second deliberately bigger than the 20 GiB GPU.
- **An unplanned before/after row:** the first Jetstream2 runs silently used the CPU because of a permissions problem (section 10). Those numbers were kept and labelled `jetstream2-cpu-fallback`, so the same VM is measured with and without its GPU.
- **A fourth environment was added:** the same Mac also runs Ollama natively on the Apple GPU, so CPU-only and GPU rows exist for the same machine.
- **Hugging Face model:** `ollama pull hf.co/...` failed, so the GGUF was downloaded directly and imported under the alias `qwen2.5-hf:0.5b` (section 10).
- **Server-reported load time** was dropped: empty-prompt load requests return `done_reason=load` with no `load_duration` field, so the measured wall time is used and the server field is left blank rather than recorded as zero.

2. The three environments and their hardware

Environment	Processor	Memory	GPU	Ollama	How hardware was checked
Own computer — Docker (CPU only)	Apple M2 Pro, 12 cores; container limited to 4 CPUs	16 GB host; 3.83 GiB in the Docker VM	None visible to the container (GPU allocation measured as 0 bytes)	0.34.2	`system_profiler`, `sysctl`, `docker info`
Own computer — native macOS (Apple GPU)	Apple M2 Pro, 12 cores	16 GB unified	Apple M2 Pro, 19-core GPU, Metal 4	0.34.3	`system_profiler`, `sysctl`
Google Colab — free T4 GPU	Intel Xeon @ 2.00 GHz, 2 vCPU	12.7 GiB	NVIDIA Tesla T4, 15360 MiB, driver 580.82.07, CUDA 13.0	0.34.3	`lscpu`, `free -b`, `nvidia-smi`
Jetstream2 VM (Ubuntu 24.04, Indiana University)	AMD EPYC-Milan, 16 vCPU (KVM)	58.8 GiB, no swap; 58 GB disk	NVIDIA GRID A100X-20C — a 20 GiB virtual slice of an A100, driver 580.159.03, CUDA 13.0	0.40.3	`lscpu`, `free -b`, `nvidia-smi`, `nvidia-smi -q`

Hardware was captured by the runner itself into `hardware.json` inside every result folder, using the commands in the last column, so the hardware record and the timings always belong to the same run.


> **Fair-comparison caveat.** The Docker container is limited to 4 CPUs and 3.83 GiB, while the same Mac natively sees 12 cores and 16 GiB, and the Docker run used Ollama 0.34.2 against 0.34.3 elsewhere. Jetstream2 ran Ollama 0.40.3, three weeks newer. The CPU-versus-GPU rows therefore differ by more than the GPU alone. The cleanest comparison in this report is Jetstream2 CPU fallback versus Jetstream2 A100: same VM, same Ollama, same day, only the GPU differs.

3. Task 1 — Two hosting tools, one of them graphical


1. **Ollama** — the model server, used in all three environments (Docker container on the Mac, native macOS build, a manual Linux install on the Colab VM, and the official Linux installer with a systemd service on Jetstream2). Driven from the command line and from its HTTP API.
2. **Open WebUI** — the browser interface at `http://localhost:3000`, talking to the same Docker Ollama container. This is the graphical tool.

Both run side by side as containers:


```
$ docker ps --format '{{.Names}} {{.Status}}'
open-webui  Up 56 minutes (healthy)
ollama      Up 56 minutes (healthy)
```



Task 1 / Task 5 — Screenshot 1. Ollama installed and answering on the Colab T4: `{"version":"0.34.3"}` from the local API, the Hugging Face GGUF hash check printing `matches Mac download: True`, and both measurement runs finishing with `returncode=0`.



Task 1 / Task 5 — Screenshot 2. Ollama on the Jetstream2 VM after the GPU fix: `ollama ps` reports `qwen3:1.7b` at **100% GPU**, `nvidia-smi` shows 1892 MiB in use on the A100, and the server log is mid-request with the fixed sampler settings (`top_p 0.900`, `temp 0.200`). Before the fix the same command said `100% CPU` (section 10).



Task 1 / Task 3 — Open WebUI screenshot. The graphical interface at `localhost:3000` with a model selected and its answer on screen.

4. Task 2 — Five models, two families, five sizes, one from Hugging Face

Model	Family	Marketing size	Reported parameters	Quantization	Disk	Source
`qwen3:1.7b`	Qwen	1.7B	2.0B	Q4_K_M	1.4 GB	Ollama library
`llama3.2:1b`	Llama	1B	1.2B	Q8_0	1.3 GB	Ollama library
`qwen2.5-hf:0.5b`	Qwen	0.5B	630.17M	Q4_K_M	491 MB	**Hugging Face**: `Qwen/Qwen2.5-0.5B-Instruct-GGUF`
`qwen3:14b`	Qwen	14B	14.8B	Q4_K_M	9.3 GB	Ollama library — Jetstream2 only
`qwen3:32b`	Qwen	32B	32.8B	Q4_K_M	20 GB	Ollama library — Jetstream2 only

The two large models were run only on Jetstream2: they are the reason for having a server with a 20 GiB GPU, and the Mac and Colab runs had finished before access arrived.

The marketing name and the metadata disagree for every model — `qwen3:1.7b` reports 2.0B parameters and `llama3.2:1b` reports 1.2B — so both labels are kept rather than silently replacing one with the other.

Hugging Face provenance. The exact file `qwen2.5-0.5b-instruct-q4_k_m.gguf` was downloaded from the official repository and imported through a `Modelfile` under the alias `qwen2.5-hf:0.5b`. Its SHA-256 is `74a4da8c9fdbcd15bd1f6d01d621410d31c6fc00986f5eb687824e7b93d7a9db`, and the Colab notebook recomputes that hash on the file it downloads itself and prints `matches Mac download: True` (Screenshot 1), and on Jetstream2 `sha256sum` printed the same value (`evidence/jetstream2-huggingface-sha256.txt`) — so the Mac, the T4 and the A100 ran byte-identical weights.

5. Task 3 — Four ways of talking to the models

Method	What was done	Evidence
Command line	`ollama list`, `ollama pull`, `ollama create` on the Mac and in Colab; `ollama pull`, `ollama create`, `ollama ps` in a terminal on the Jetstream2 web desktop	Output below; notebook cells 3–4; Screenshots 2–3
Python script	`run.py` — the measurement runner; standard library only	`results/*/measurements.csv`
Direct HTTP API	`POST /api/generate` (non-streaming), plus `/api/show`, `/api/ps`, `/api/version`	Full request and response bodies in `answer-*.json`
Graphical interface	Open WebUI chat against the same container	Live in the video

```
$ docker exec ollama ollama list
NAME               ID              SIZE      MODIFIED
qwen2.5-hf:0.5b    638b1dcc170e    491 MB    44 minutes ago
llama3.2:1b        baf6a787fdff    1.3 GB    51 minutes ago
qwen3:1.7b         8f68893c685c    1.4 GB    43 hours ago
```

The same P2 prompt sent through Open WebUI earlier returned **66**, while the controlled API call returned the correct **120**. The GUI keeps its own sampling settings and its own chat history, so that is a demonstration of a different interface, *not* a like-for-like performance comparison.

6. Task 4 — Changing the settings

Same model (`qwen3:1.7b`), same prompt (P1, the phishing question), same seed. Temperature was moved from 0.1 to 1.2, and then the second setting, `num_predict` (the maximum answer length), was cut from 192 tokens to 64.

Environment	Condition	Temperature	num_predict	Answer s	Tokens/s	Output tokens	Stop reason
Mac — Docker CPU	temp-low	0.1	192	2.49	54.7	112	stop
Mac — Docker CPU	temp-high	1.2	192	1.86	54.6	99	stop
Mac — Docker CPU	tokens-64	0.1	64	1.17	56.6	64	length
Colab — T4	temp-low	0.1	192	1.01	110.0	94	stop
Colab — T4	temp-high	1.2	192	0.89	114.5	98	stop
Colab — T4	tokens-64	0.1	64	0.58	115.8	64	length
Jetstream2 — CPU fallback	temp-low	0.1	192	6.02	19.7	112	stop
Jetstream2 — CPU fallback	temp-high	1.2	192	4.65	19.9	91	stop
Jetstream2 — CPU fallback	tokens-64	0.1	64	3.23	20.2	64	length
Jetstream2 — A100	temp-low	0.1	192	0.55	257.3	108	stop
Jetstream2 — A100	temp-high	1.2	192	0.32	325.3	97	stop
Jetstream2 — A100	tokens-64	0.1	64	0.22	320.8	64	length

What actually changed in the text

- **Temperature 0.1 on Docker CPU** produced step 2: "*Confirm the request – Ask the employee to re-enter their password for verification.*" In a phishing scenario that is **unsafe advice**, and it appeared at the *low*, supposedly "safe" temperature.
- **Temperature 1.2 on Docker CPU** produced step 5: "*Do not enter password – Avoid revealing any credentials to prevent account compromise.*" — the opposite, and the better answer.
- **The same temperature-0.1 request on the other three backends** (Colab T4, Jetstream2 CPU, Jetstream2 A100) did *not* produce the password instruction. The unsafe answer is reproducible only on the backend that produced it, which is exactly why one sample proves nothing. On the A100 the two temperatures gave differently ordered but equally safe five-step lists.
- **num_predict 64** stopped mid-sentence on every backend (on the A100 at "*4. Report the incident*") with `done_reason=length`. Nothing warns the reader that the answer was cut off; only the stop reason reveals it.

> **Does this matter for security work?** Yes, in three ways. First, low temperature buys consistency, not correctness — one sample is not evidence that either setting is safer, and the low-temperature answer here was the dangerous one. Second, any pipeline that feeds model output into a ticket or a playbook has to check `done_reason`, otherwise a truncated instruction looks like a complete one. Third, a model that confidently recommends re-entering a password is a reason to keep a human between the model and the analyst.

7. Task 5 — Measurements

Summary: one row per model per environment (five prompts each)

Environment	Model	Params	Quant	Load s	Median answer s	Median tokens/s	Model alloc MiB	GPU alloc MiB
Mac — Docker CPU	qwen3:1.7b	2.0B	Q4_K_M	6.25	2.89	51.8	1569	0
Mac — Docker CPU	llama3.2:1b	1.2B	Q8_0	6.60	0.95	64.8	1649	0
Mac — Docker CPU	qwen2.5-hf:0.5b	630.17M	Q4_K_M	1.55	1.05	120.3	525	0
Mac — Apple GPU	qwen3:1.7b	2.0B	Q4_K_M	3.31	1.58	87.8	1561	1561
Mac — Apple GPU	llama3.2:1b	1.2B	Q8_0	1.87	0.54	97.8	1374	1374
Mac — Apple GPU	qwen2.5-hf:0.5b	630.17M	Q4_K_M	1.04	0.88	207.7	521	521
Colab — T4	qwen3:1.7b	2.0B	Q4_K_M	64.61	1.10	118.8	1398	1398
Colab — T4	llama3.2:1b	1.2B	Q8_0	21.08	0.74	139.0	1378	1378
Colab — T4	qwen2.5-hf:0.5b	630.17M	Q4_K_M	16.33	0.28	246.5	433	433
Jetstream2 — CPU fallback	qwen3:1.7b	2.0B	Q4_K_M	2.31	5.89	19.8	1569	0
Jetstream2 — CPU fallback	llama3.2:1b	1.2B	Q8_0	1.82	2.28	24.8	1383	0
Jetstream2 — CPU fallback	qwen2.5-hf:0.5b	630.17M	Q4_K_M	1.05	2.71	27.3	525	0
Jetstream2 — CPU fallback	qwen3:14b	14.8B	Q4_K_M	14.62	15.82	4.4	9305	0
Jetstream2 — A100	qwen3:1.7b	2.0B	Q4_K_M	32.51	0.44	314.9	1398	1398
Jetstream2 — A100	llama3.2:1b	1.2B	Q8_0	10.66	0.40	412.2	1378	1378
Jetstream2 — A100	qwen2.5-hf:0.5b	630.17M	Q4_K_M	6.91	0.35	460.5	433	433
Jetstream2 — A100	qwen3:14b	14.8B	Q4_K_M	8.22	0.81	88.2	8877	8877
Jetstream2 — A100	qwen3:32b	32.8B	Q4_K_M	6.53	7.20	11.1	20033	17121

Generation speed, and what the GPUs actually bought

Model	Mac — Docker CPU tokens/s	Mac — Apple GPU tokens/s	Colab — T4 tokens/s	Jetstream2 — CPU fallback tokens/s	Jetstream2 — A100 tokens/s	A100 vs Mac Docker CPU	A100 vs same VM on CPU
qwen3:1.7b	51.8	87.8	118.8	19.8	314.9	6.1×	15.9×
llama3.2:1b	64.8	97.8	139.0	24.8	412.2	6.4×	16.6×
qwen2.5-hf:0.5b	120.3	207.7	246.5	27.3	460.5	3.8×	16.9×
qwen3:14b	—	—	—	4.4	88.2	—	20.3×
qwen3:32b	—	—	—	—	11.1	—	—





Chart 1. Median generation speed and median answer latency for the same five prompts and settings, on every backend in all three environments. The 14B and 32B models have bars only for Jetstream2, the only place they were run. Latency is on a log scale because it spans 0.15 s to 16 s. Generated by `analyze.py` directly from the measurement CSVs; the exact values are in the tables above and below.

Read the load column carefully. On Colab the first real answer for each model took 37 s even though the empty-prompt load request had already returned after 65 s, because the T4 finishes warming up on the first genuine generation. On the Mac's own GPU the same model loaded in 3.3 s and the first answer was already at full speed. Jetstream2's A100 showed the same warm-up as Colab — 35 s for the first answer after the service restarted — so this is a property of the NVIDIA/CUDA start-up, not of Colab. Cold-start cost, not throughput, is where the cloud GPUs lose.

Model size on one GPU. On the A100, `qwen3:14b` (8877 MiB, entirely in GPU memory) generated 88.2 tokens/s. `qwen3:32b` needs 20033 MiB — more than the 20 GiB slice — so Ollama placed 17121 MiB on the GPU and the rest on the CPU, and speed collapsed to 11.1 tokens/s: 2.2× the parameters for 8× less speed. The limit is not "does it load" but "does it fit in VRAM".



Task 2 / Task 5 — Screenshot 3. `run.py` on the Jetstream2 A100 after the GPU fix: per-prompt answer time and tokens/s for all five models, and the evidence folder each run saved. Note the slow first prompt of the first model (CUDA warm-up) and the drop from ~88 to ~11 tokens/s between the 14B and the 32B.

Every measurement, per prompt

Environment	Model	Params	Quant	Prompt	Answer s	Tokens/s	Output tokens	Stop reason
Mac — Docker CPU	qwen3:1.7b	2.0B	Q4_K_M	P1	2.89	48.2	115	stop
Mac — Docker CPU	qwen3:1.7b	2.0B	Q4_K_M	P2	3.03	51.3	126	stop
Mac — Docker CPU	qwen3:1.7b	2.0B	Q4_K_M	P3	3.59	51.8	168	stop
Mac — Docker CPU	qwen3:1.7b	2.0B	Q4_K_M	P4	1.47	57.0	55	stop
Mac — Docker CPU	qwen3:1.7b	2.0B	Q4_K_M	P5	1.01	61.2	36	stop
Mac — Docker CPU	llama3.2:1b	1.2B	Q8_0	P1	0.44	80.8	9	stop
Mac — Docker CPU	llama3.2:1b	1.2B	Q8_0	P2	2.42	55.2	126	stop
Mac — Docker CPU	llama3.2:1b	1.2B	Q8_0	P3	2.92	63.8	176	stop
Mac — Docker CPU	llama3.2:1b	1.2B	Q8_0	P4	0.95	64.8	42	stop
Mac — Docker CPU	llama3.2:1b	1.2B	Q8_0	P5	0.35	77.0	11	stop
Mac — Docker CPU	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P1	1.05	124.2	80	stop
Mac — Docker CPU	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P2	1.87	115.4	192	length
Mac — Docker CPU	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P3	1.60	120.3	167	stop

Environment	Model	Params	Quant	Prompt	Answers	Tokens/s	Output tokens	Stop reason
Mac — Docker CPU	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P4	0.85	115.5	59	stop
Mac — Docker CPU	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P5	0.78	127.1	63	stop
Mac — Apple GPU	qwen3:1.7b	2.0B	Q4_K_M	P1	1.58	90.7	113	stop
Mac — Apple GPU	qwen3:1.7b	2.0B	Q4_K_M	P2	1.68	79.6	126	stop
Mac — Apple GPU	qwen3:1.7b	2.0B	Q4_K_M	P3	2.40	73.5	169	stop
Mac — Apple GPU	qwen3:1.7b	2.0B	Q4_K_M	P4	0.71	92.5	53	stop
Mac — Apple GPU	qwen3:1.7b	2.0B	Q4_K_M	P5	0.50	87.8	36	stop
Mac — Apple GPU	llama3.2:1b	1.2B	Q8_0	P1	0.40	58.5	9	stop
Mac — Apple GPU	llama3.2:1b	1.2B	Q8_0	P2	1.66	80.7	126	stop
Mac — Apple GPU	llama3.2:1b	1.2B	Q8_0	P3	1.85	97.8	176	stop
Mac — Apple GPU	llama3.2:1b	1.2B	Q8_0	P4	0.54	111.8	52	stop
Mac — Apple GPU	llama3.2:1b	1.2B	Q8_0	P5	0.15	110.7	11	stop
Mac — Apple GPU	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P1	0.88	208.1	149	stop
Mac — Apple GPU	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P2	0.95	207.7	192	length
Mac — Apple GPU	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P3	0.96	198.8	185	stop
Mac — Apple GPU	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P4	0.32	209.7	59	stop
Mac — Apple GPU	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P5	0.44	201.8	84	stop
Colab — T4	qwen3:1.7b	2.0B	Q4_K_M	P1	36.68	112.3	90	stop
Colab — T4	qwen3:1.7b	2.0B	Q4_K_M	P2	1.10	119.8	126	stop
Colab — T4	qwen3:1.7b	2.0B	Q4_K_M	P3	1.48	118.6	171	stop
Colab — T4	qwen3:1.7b	2.0B	Q4_K_M	P4	0.51	118.8	53	stop
Colab — T4	qwen3:1.7b	2.0B	Q4_K_M	P5	0.36	119.9	37	stop
Colab — T4	llama3.2:1b	1.2B	Q8_0	P1	24.81	103.6	9	stop
Colab — T4	llama3.2:1b	1.2B	Q8_0	P2	0.74	138.3	98	stop
Colab — T4	llama3.2:1b	1.2B	Q8_0	P3	1.29	139.0	176	stop
Colab — T4	llama3.2:1b	1.2B	Q8_0	P4	0.40	140.8	52	stop
Colab — T4	llama3.2:1b	1.2B	Q8_0	P5	0.10	155.2	11	stop
Colab — T4	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P1	38.20	7.1	95	stop
Colab — T4	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P2	0.80	246.5	192	length
Colab — T4	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P3	0.25	251.2	55	stop

Environment	Model	Params	Quant	Prompt	Answers	Tokens/s	Output tokens	Stop reason
Colab — T4	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P4	0.28	237.2	59	stop
Colab — T4	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P5	0.08	259.8	13	stop
Jetstream2 — CPU fallback	qwen3:1.7b	2.0B	Q4_K_M	P1	5.89	20.0	112	stop
Jetstream2 — CPU fallback	qwen3:1.7b	2.0B	Q4_K_M	P2	6.61	19.8	126	stop
Jetstream2 — CPU fallback	qwen3:1.7b	2.0B	Q4_K_M	P3	9.09	19.3	171	stop
Jetstream2 — CPU fallback	qwen3:1.7b	2.0B	Q4_K_M	P4	2.97	20.3	53	stop
Jetstream2 — CPU fallback	qwen3:1.7b	2.0B	Q4_K_M	P5	2.28	19.4	38	stop
Jetstream2 — CPU fallback	llama3.2:1b	1.2B	Q8_0	P1	0.56	25.4	9	stop
Jetstream2 — CPU fallback	llama3.2:1b	1.2B	Q8_0	P2	5.57	23.3	126	stop
Jetstream2 — CPU fallback	llama3.2:1b	1.2B	Q8_0	P3	8.50	21.2	176	stop
Jetstream2 — CPU fallback	llama3.2:1b	1.2B	Q8_0	P4	2.28	24.8	52	stop
Jetstream2 — CPU fallback	llama3.2:1b	1.2B	Q8_0	P5	0.60	26.6	11	stop
Jetstream2 — CPU fallback	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P1	4.29	28.4	117	stop
Jetstream2 — CPU fallback	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P2	7.25	27.7	192	length
Jetstream2 — CPU fallback	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P3	2.12	27.3	55	stop
Jetstream2 — CPU fallback	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P4	2.37	26.5	59	stop
Jetstream2 — CPU fallback	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P5	2.71	24.4	63	stop
Jetstream2 — CPU fallback	qwen3:14b	14.8B	Q4_K_M	P1	18.06	4.4	71	stop
Jetstream2 — CPU fallback	qwen3:14b	14.8B	Q4_K_M	P2	20.69	4.3	83	stop
Jetstream2 — CPU fallback	qwen3:14b	14.8B	Q4_K_M	P3	15.82	4.4	64	stop
Jetstream2 — CPU fallback	qwen3:14b	14.8B	Q4_K_M	P4	15.42	4.3	58	stop
Jetstream2 — CPU fallback	qwen3:14b	14.8B	Q4_K_M	P5	11.74	4.4	43	stop
Jetstream2 — A100	qwen3:1.7b	2.0B	Q4_K_M	P1	35.34	9.5	107	stop

Environment	Model	Params	Quant	Prompt	Answers	Tokens/s	Output tokens	Stop reason
Jetstream2 — A100	qwen3:1.7b	2.0B	Q4_K_M	P2	0.44	315.3	126	stop
Jetstream2 — A100	qwen3:1.7b	2.0B	Q4_K_M	P3	0.58	314.9	168	stop
Jetstream2 — A100	qwen3:1.7b	2.0B	Q4_K_M	P4	0.20	307.9	50	stop
Jetstream2 — A100	qwen3:1.7b	2.0B	Q4_K_M	P5	0.14	315.3	36	stop
Jetstream2 — A100	llama3.2:1b	1.2B	Q8_0	P1	15.06	330.6	9	stop
Jetstream2 — A100	llama3.2:1b	1.2B	Q8_0	P2	0.40	328.7	126	stop
Jetstream2 — A100	llama3.2:1b	1.2B	Q8_0	P3	0.44	412.2	176	stop
Jetstream2 — A100	llama3.2:1b	1.2B	Q8_0	P4	0.15	415.0	52	stop
Jetstream2 — A100	llama3.2:1b	1.2B	Q8_0	P5	0.04	421.1	11	stop
Jetstream2 — A100	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P1	25.11	11.0	86	stop
Jetstream2 — A100	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P2	0.43	473.8	192	length
Jetstream2 — A100	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P3	0.35	463.6	155	stop
Jetstream2 — A100	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P4	0.15	459.2	59	stop
Jetstream2 — A100	qwen2.5-hf:0.5b	630.17M	Q4_K_M	P5	0.05	460.5	13	stop
Jetstream2 — A100	qwen3:14b	14.8B	Q4_K_M	P1	0.99	80.3	67	stop
Jetstream2 — A100	qwen3:14b	14.8B	Q4_K_M	P2	1.04	88.6	87	stop
Jetstream2 — A100	qwen3:14b	14.8B	Q4_K_M	P3	0.81	87.4	64	stop
Jetstream2 — A100	qwen3:14b	14.8B	Q4_K_M	P4	0.76	88.3	60	stop
Jetstream2 — A100	qwen3:14b	14.8B	Q4_K_M	P5	0.56	88.2	43	stop
Jetstream2 — A100	qwen3:32b	32.8B	Q4_K_M	P1	9.69	11.1	103	stop
Jetstream2 — A100	qwen3:32b	32.8B	Q4_K_M	P2	9.25	10.7	95	stop
Jetstream2 — A100	qwen3:32b	32.8B	Q4_K_M	P3	7.20	11.4	78	stop
Jetstream2 — A100	qwen3:32b	32.8B	Q4_K_M	P4	5.61	11.1	58	stop
Jetstream2 — A100	qwen3:32b	32.8B	Q4_K_M	P5	4.97	11.3	52	stop

8. How good were the answers?

Speed is only half the comparison; the same five prompts also expose what each model gets wrong.

Prompt	What it tests	qwen3:1.7b (2.0B)	llama3.2:1b (1.2B)	qwen2.5-hf:0.5b (630M, Hugging Face)	qwen3:14b (14.8B) and qwen3:32b (32.8B) — Jetstream2 only
P1	Cybersecurity triage (phishing)	Five ordered steps; usable in every backend.	**Refused entirely**: "I can't assist with that request." — 9 tokens, on all five backends.	Five steps that mostly restate the email rather than triage it; no unsafe instruction.	Both usable. The 32B was the most complete: report through the incident system, quarantine the email, block the sender domain, warn the employee not to provide credentials.
P2	Arithmetic: 120 → +25% → −20% (expected 120)	Correct (120) on every backend.	Correct (120) on Docker CPU, Apple GPU, Jetstream2 CPU and the A100; **wrong (126) only on the Colab T4** — same prompt, settings and seed.	**Never reached an answer**: hit the 192-token limit (stop reason `length`) mid-calculation, everywhere.	Both correct (120), in under 100 tokens.
P3	Python: count failed logins, ignore missing keys	Correct function and a matching example.	Correct function, but on 4 of 5 backends the example list holds three failed entries while the comment claims `Output: 2`. Only the Jetstream2 CPU run happened to write a two-entry example.	Correct function using `if "status" in event`.	Both use `e.get('status')` — the most robust form — and include an empty `{}` in the example to prove a missing key is ignored. Stated outputs are correct.
P4	Summarise in exactly three bullets, add nothing	Exactly three bullets everywhere.	Exactly three bullets everywhere.	**Zero bullets** — reproduced the paragraph instead, on every backend.	Both exactly three bullets with no invented facts.
P5	Deliberate failure test: fake 2027 paper	Refused and stated it cannot verify such a paper, everywhere.	Refused, but with a bare "I can't provide that information".	**Fails differently by backend**: claimed the theorem is from Star Wars (Docker CPU *and* Jetstream2 CPU); **fabricated a title and the DOI 10.1007/978-3-319-98592-1_14** (Apple GPU); an identical refusal on both NVIDIA GPUs (Colab T4 and A100).	Both refused explicitly; the 14B: "I cannot provide a fabricated citation."

The most important result in this table is the P2 row. `llama3.2:1b` answered 120 correctly on four backends and 126 on the Colab T4 with the same prompt, the same temperature, the same top_p and the same seed. Identical settings do not produce identical text across different hardware and backends, so a model that passes a test on your laptop can still fail it on a server. Jetstream2 gave the cleanest version of this result: **on the same VM, with the same Ollama, model files and seed, the CPU and the A100 produced different text for 12 of 20**

baseline answers. The 0.5B model's P5 failure also grouped by backend rather than by machine: both CPU backends invented a Star Wars origin, and both NVIDIA GPUs returned the identical refusal.

Size bought correctness. Only `qwen3:14b` and `qwen3:32b` answered all five prompts acceptably. Every small model failed at least one: a refusal on the security question, an unfinished calculation, or a code example that misstated its own output.

9. Comparing the environments

Criterion	Own computer — Docker (CPU)	Own computer — native (Apple GPU)	Google Colab — T4	Jetstream2 — A100 vGPU
Ease of setup	Already installed; one `docker compose up`	Download and unzip the app, start the server with two environment variables	No install on your machine, but the documented installer failed and needed debugging (section 10)	Official installer worked first time (about 10 s); five models pulled in about 2 minutes. But access took days to be granted, the VM is reached through a browser desktop, and Ollama **silently ran on the CPU** until a Linux group permission was fixed (section 10)
Speed (qwen3:1.7b)	51.8 tokens/s, median answer 2.89 s	87.8 tokens/s (1.69× CPU), median answer 1.58 s	118.8 tokens/s (2.29× CPU), median answer 1.10 s	**314.9 tokens/s** (6.1× CPU), median answer 0.44 s. Before the fix: 19.8 tokens/s
Cold start	6.3 s load	3.3 s load, first answer already at full speed	65 s load and a 37 s first answer, on top of ~2 minutes of install and model pulls	33 s load and a 35 s first answer for the first model after a restart; later models loaded in 7–11 s
Model sizes that ran	All three small models (630M – 2.0B); largest resident allocation 1649 MiB inside a 3.83 GiB VM	All three; 1561 MiB in VRAM out of 16 GB unified	All three; 1398 MiB out of 15360 MiB	All five (630M – 32.8B). 14.8B fit entirely in VRAM (8877 MiB); 32.8B did not (17121 of 20033 MiB on the GPU) and slowed to 11.1 tokens/s
Sizes that did *not* run	On the Mac and Colab nothing above 2.0B was attempted, because the large-model test was planned for the server. On Jetstream2 the 32B ran, but only partly on the GPU. A 70B model (~43 GB at Q4_K_M) was not attempted: after the five pulls the VM had 11 GB of disk free, and the weights could never fit a 20 GiB GPU.			
Cost	Hardware already owned; electricity only		Free tier; a GPU session is not guaranteed and is capped	Free to the student, but it spends the class's shared allocation for as long as the VM runs — shelve it when finished
Privacy	Prompts never leave the machine; no network needed once the weights are downloaded		Every prompt and answer is processed on Google's hardware	Prompts leave your computer, but are processed on a VM you control on a university research cloud, not by a commercial AI service
Reliability	Persistent; models stay installed between sessions		Session-scoped: the runtime disconnects, and **everything in `/content` is lost**. The "too many sessions" limit also blocked a run until an old session was terminated.	Persistent: models and results stayed on the VM's disk between sessions. But "running" did not mean "using the GPU" — the CPU fallback gave no error, only `ollama ps` revealed it

Recommendations, each backed by the numbers above

1. **Everyday work for a security analyst → a persistent GPU server such as the Jetstream2 VM, running a 14B-class model.** Only the 14B and 32B models answered all five prompts acceptably, and the security question is where the small ones failed (Llama refused it on every backend). On the A100, `qwen3:14b` answered in a median 0.81 s at 88.2 tokens/s; the same model on the same VM's CPU took 15.8 s per answer at 4.4 tokens/s, too slow to use all day. The 14B beats the 32B: the same correct answers, 8× faster, because it fits in VRAM. Without a server allocation, the fallback is the analyst's own native GPU (87.8 tokens/s on the small model), accepting the small models' weaker answers.
2. **Sensitive or confidential data → the analyst's own machine, native install.** This is not a speed argument: locally the prompt never leaves the machine. Jetstream2 is the better second choice over Colab (your own VM on university infrastructure, rather than a commercial third party), but it is still off-device. The cost of privacy is measurable: the Mac's GPU runs `qwen3:1.7b` at 87.8 tokens/s against 314.9 on the A100 (3.6× slower), and only the small models were tested locally. The obvious next test is whether the 9.3 GB `qwen3:14b` fits in the Mac's 16 GB of unified memory; it was not run here.
3. **A quick experiment that has to be finished today → Colab, unless a Jetstream2 VM is already running and verified on its GPU.** Colab needs only a Google account: about two minutes of install and model pulls, then 118.8 tokens/s. Jetstream2 was faster (314.9 tokens/s) and installed in seconds, but access took days to be granted, and the first run used the CPU at 19.8 tokens/s without any error message. Against a deadline, that hidden failure costs more than the speed saves. On Colab, accept the 37 s first answer and download the evidence before the runtime ends.

10. Problems, and how they were handled

#	Problem	Diagnosis	Fix
1	The documented Colab installer, `sh install.sh`, exited 1	The script downloads `ollama-linux-amd64.tgz`; that path now returns **HTTP 404** (curl exit 22). Current releases ship `.tar.zst` instead.	Fetch `ollama-linux-amd64.tar.zst` directly, install `zstd`, extract into `/usr/local`, and skip the installer's systemd and user-account steps that a Colab VM does not need. Ollama then reported `{"version":"0.34.3"}` (Screenshot 1). By 12 October the official installer had been fixed and worked first time on Jetstream2.
2	`ollama pull hf.co/Qwen/...` refused: "blocked redirect to a different host"	Ollama would not follow Hugging Face's CDN redirect.	Download the GGUF with `curl`, record its SHA-256, and import it with a two-line `Modelfile` as `qwen2.5-hf:0.5b`. The same method is used in Colab and on Jetstream2, and all three hashes match.
3	Colab refused to start the runtime: "Too many sessions"	An earlier notebook still held the single free GPU session.	Terminate the stale session from **Manage sessions**, then reconnect. Worth knowing before a demo: the free tier gives you one.
4	Empty-prompt load requests returned no `load_duration`	The server answers `done_reason=load` without the timing field.	Report the measured wall time and leave the server field blank. An earlier CSV recorded `0` there, which wrongly implied an instant load; the field is unavailable, not zero.
5	First answers on both NVIDIA GPUs looked absurdly slow (Colab 37 s,	The empty-prompt load returns before the GPU has finished warming up, so the warm-up lands on the first real prompt.	Keep the raw numbers and report medians alongside the first-answer cost, rather than quietly dropping the outlier.

#	Problem	Diagnosis	Fix
	A100 35 s) while generation speed was high		
6	The first local Qwen baseline overlapped a model download	Background network and disk activity during timing.	Kept as exploratory evidence and flagged; it is the one Docker row not collected on an otherwise quiet machine.
7	Jetstream2 access arrived late	Class access was granted on Saturday 10 October, after the other environments were finished.	Ran the identical runner and prompts on 12 October; the prompt SHA-256 in every Jetstream2 manifest matches the earlier runs.
8	**Ollama on the A100 VM ran 100% on the CPU** — 19.8 tokens/s for `qwen3:1.7b`, slower than the Mac's CPU container — and printed no error	`ollama ps` said `100% CPU`; `nvidia-smi` showed 0 MiB used; the server log said `inference compute id=cpu library=cpu` and `total_vram="0 B"`. `ls -l /dev/nvidia*` showed `/dev/nvidia0` and `/dev/nvidiactl` as `crw-rw---- root vglusers`, and `id ollama` showed the installer's service account was not in `vglusers`. My own account was, which is why `nvidia-smi` worked for me.	`sudo usermod -aG vglusers ollama && sudo systemctl restart ollama`. The log then reported `library=CUDA … description="GRID A100X-20C" … total="20.0 GiB"` and speed rose to 314.9 tokens/s (16×). The CPU runs were kept, relabelled `jetstream2-cpu-fallback`.
9	`qwen3:32b` generated only 11.1 tokens/s on the A100	It needs 20033 MiB and the GPU slice has 20 GiB; Ollama put 17121 MiB on the GPU and the rest on the CPU.	Not a bug but the size limit of this GPU. Recommend the 14B, which fits and is 8× faster.
10	No SSH access to the VM, so the results were stuck on it	The VM was reached only through the Exosphere web desktop (Guacamole); no key of mine was installed.	Packed the results into a 31.7 KB `tar.xz`, base64-encoded it onto the remote clipboard with `xclip`, which Guacamole passed to the Mac's clipboard. The SHA-256 matched on both ends.
11	VM disk 82% full after five models	47 GB of 58 GB used, mostly the 20 GB 32B model.	No 70B attempt; delete the large models when finished.

11. Limits of this comparison

- **One run per prompt.** These are exploratory measurements, not statistically robust benchmarks; no repeats, no error bars.
- **The Mac CPU/GPU comparison is not clean.** The container had 4 CPUs, 3.83 GiB and Ollama 0.34.2; the native Mac had 12 cores, 16 GiB and 0.34.3. The GPU is not the only variable. The Jetstream2 CPU/A100 pair is the controlled one.
- **Ollama versions differ across dates:** 0.34.2/0.34.3 in September, 0.40.3 on Jetstream2 in October.
- **The A100 is a 20 GiB virtual slice** (GRID A100X-20C), not a whole 40 or 80 GB card; a full A100 would fit the 32B.
- **The large models were run only on Jetstream2**, so the size comparison across environments is incomplete.
- **The Jetstream2 CPU fallback is not a fair CPU benchmark.** Its 16 EPYC vCPUs were slower than the Mac's 4-CPU container; the cause (CPU generation, memory bandwidth, virtualisation) was not investigated.
- **Memory is an allocation snapshot** from `/api/ps`, not peak RSS or whole-machine usage.
- **Caches were not cleared** between runs, so "unloaded" does not mean "read cold from disk".
- **Answer quality was judged by reading the answers** against the expectations fixed in the plan, not by a scored rubric.

12. Evidence and how to repeat this


Everything in this report is reproducible from the files in `experiment/`:

```
PLAN.md                  the data plan, saved before the measured runs
prompts.json             the five fixed prompts (hashed into every run manifest)
run.py                   the measurement runner (standard library only)
analyze.py, report.py    build the tables, the chart and this report from the CSVs
results/<env>-<utc>/     one folder per run:
    hardware.json          hardware command output for that run
    manifest.json          settings, prompt hash, Ollama version
    measurements.csv       one row per prompt
    answer-*.json          the full request and response, including the raw text
    load-*.json            the dedicated load request
NOTES.md                 caveats that must be read with the numbers
evidence/                screenshots and logs
```

```
$ docker compose up -d                                          # Docker CPU
$ python3 experiment/run.py --environment local-docker-cpu
$ python3 experiment/run.py --environment local-metal-gpu --url http://127.0.0.1:11435   #
native GPU
$ python3 experiment/run.py --environment colab-t4             # in the Colab notebook

# Jetstream2 VM (terminal on the web desktop)
$ curl -fsSL https://ollama.com/install.sh | sh
$ sudo usermod -aG vglusers ollama && sudo systemctl restart ollama   # let the service open the
GPU
$ ollama ps                                                     # must say "100% GPU", not "100%
CPU"
$ python3 run.py --environment jetstream2-a100
$ python3 run.py --environment jetstream2-a100 --models qwen3:1.7b --settings
$ python3 run.py --environment jetstream2-a100 --models qwen3:14b qwen3:32b
```

Colab notebook: `https://colab.research.google.com/drive/1EDD1vaZj1z4kkD-GbKDRF1u2NWps7pkY`



Task 3 / Task 5 — Screenshot 4. Raw measurements and generated answers read back inside the Colab notebook: the measurement record for each prompt, the prompt itself, and the model's text — including `qwen2.5-hf:0.5b` refusing the fabricated-citation prompt P5 on the T4.