

## Assignment 9 || String In-built functions

Arjun Patel – FRN13J1124/006

Q1) strlen

```
#include <stdio.h>
#include <string.h>

int main() {
    char str[] = "Hello, Firstbit solutions!";
    printf("Length: %d\n", strlen(str));
    return 0;
}
```

```
● PS D:\Firstbit Solutions\C Pro
($?) { .\1_strlen }
Length: 26
○ PS D:\Firstbit Solutions\C Pro
```

Q2) strcpy

```
#include <stdio.h>
#include <string.h>

int main() {
    char src[] = "ArjunPatel";
    char dest[strlen(src)];
    strcpy(dest, src);
    printf("Copied String: %s\n", dest);
    printf("Copied String: %s\n", src);
    return 0;
}
```

```
($?) { .\2_strcpy }
Copied String: ArjunPatel
Copied String: ArjunPatel
○ PS D:\Firstbit Solutions\C Programming\Assignment
```

Q3) strncpy

```
//copy only n char to dest str
#include <stdio.h>
#include <string.h>

int main() {
    char src[] = "0123456789";
    // printf("%d", strlen(src));
    char dest[strlen(src)];
    strncpy(dest, src, 5);
    dest[5] = '\0';
    printf("Copied String: %s\n", dest); //01234
    return 0;
}
```

```
PS D:\Firstbit Solutions\C Prog
f ($?) { .\3_strncpy }
Copied String: 01234
```

Q4) strcat

```
#include <stdio.h>
#include <string.h>

int main() {
    char str1[50] = "Arjun ";
    char str2[] = "Patel!";
    strcat(str1, str2); //it will concat str2 in str1
    printf("Concatenated String: %s\n", str1); //Arjun Patel!
    // printf("Concatenated String: %s\n", str2); //Patel!
    return 0;
}
```

```
PS D:\Firstbit Solutions\C Programming> cd "d:\
($?) { .\4_strcat }
Concatenated String: Arjun Patel!
```

Q5) strncat

```
#include <stdio.h>
#include <string.h>

//concat string upto n char
```

```

int main() {
    char str1[50] = "Arjun ";
    char str2[] = "Patel";
    strncat(str1, str2, 3);
    printf("Concatenated String: %s\n", str1); //Arjun Pat --> str1
+ 3 char from str2
    return 0;
}

```

```

● PS D:\Firstbit Solutions\C Programmi
f ($?) { .\5_strncat }
Concatenated String: Arjun Pat

```

Q6) strcmp

```

#include <stdio.h>
#include <string.h>

//return 1 if str1>str2, -1 if str1<str2, 0 if str1=str2

int main() {
    char str1[] = "cccc";
    char str2[] = "bbbb";
    int result = strcmp(str1, str2);
    if (result < 0)
        printf("str1 is less than str2\n"); //this will executed
    else if (result > 0)
        printf("str1 is greater than str2\n");
    else
        printf("str1 is equal to str2\n");
    return 0;
}

```

```

● PS D:\Firstbit Solutions\C Programmi
($?) { .\6_strcmp }
str1 is greater than str2

```

Q8) strncmp

```

#include <stdio.h>
#include <string.h>

//compare only n chars of str2

```

```

int main() {
    char str1[] = "arjun";
    char str2[] = "arjunpatel";
    int n = 4;
    int result = strncmp(str1, str2, n);
    if (result == 0)
        printf("The first %d characters are equal\n", n);
    else
        printf("The first %d characters are not equal\n", n);
    return 0;
}

```

```

• PS D:\Firstbit Solutions\C Programming> cd "d:
f ($?) { .\7_strncmp }
The first 4 characters are equal

```

Q9)strchr → it will find last occurrence of char in given string

```

#include <stdio.h>
#include <string.h>

//it will find last occurrence of char in given string

int main() {
    char str[] = "Hello, World!";
    printf("base address %u\n", str); //1994389066
    char *ptr = strchr(str, 'o');
    printf("%u\n", ptr); //1994389084
    if (ptr)
        printf("Last occurrence at position: %ld\n", ptr - str);
    //84-66 = 8
    else
        printf("Character not found\n");
    return 0;
}

```

```

base address 620756138
620756146
Last occurrence at position: 8

```

Q10)strstr -> Finds the first occurrence of a substring in a string.

```

#include <stdio.h>
#include <string.h>

//Finds the first occurrence of a substring in a string.

int main() {
    char str[] = "Arjun Patel";
    char find[] = "Patel";
    char *ptr = strstr(str, find);
    if (ptr)
        printf("%s starts from index : %d\n", find, ptr - str);
    else
        printf("Substring not found\n");
    return 0;
}

```

```

PS D:\Firstbit Solutions\C Programming\Assignments\Assi
rstr.c -o 10_strstr } ; if ($?) { .\10_strstr }
Patel starts from index position: 6

```

Q11) **strdup** -> Duplicates a string (non-standard, available in POSIX).

It will work with dynamic memory we can free memory after task completion.

```

#include <stdio.h>
#include <string.h>
#include <stdlib.h>

//Duplicates a string (non-standard, available in POSIX).

int main() {
    char str[] = "Hello";
    char *dup = strdup(str);
    char cpy[strlen(str)];
    strcpy(cpy, str);
    printf("Duplicated String: %s\n", cpy);
    printf("Duplicated String: %s\n", dup);
    free(dup); // Remember to free memory
    printf("Duplicated String: %s\n", dup);
}

```

```
    return 0;
}
```

```
Duplicated String: Hello
Duplicated String: Hello
Duplicated String: É`ãûðø
```

Q12) **strtok** -> Splits a string into tokens based on delimiters.

```
#include <stdio.h>
#include <string.h>

// Splits a string into tokens based on delimiters.

int main() {
    char str[] = "Hello World! C is more, fun.";
    printf("%u \n",str);
    char *token = strtok(str, " ,.!");

    printf("value of token %u \n", token);
    while (token) {
        printf("%s\n", token);
        printf("%u\n", token);
        token = strtok(NULL, " #,!."); // Get next token
    }
    printf("\n%s\n", str);
    printf("%u\n", str);
    return 0;
}
```

```
2252339680
value of token 22523396
Hello
2252339680
World
2252339686
C
2252339693
is
2252339695
more
2252339698
fun
2252339704
○
Hello
2252339680
```

Q13) memstr

```
#include <stdio.h>
#include <string.h>

//Fills a string (or memory block) with a specific character.

int main() {
    char str[20] = "Arjun Patel";
    memset(str, '-', 5); // Replace first 3 characters with '-'
    printf("Modified String: %s\n", str);
    return 0;
}
```

```
● PS D:\Firstbit Solutions\C Programming> cd "d:\Firstbit Solutions\C Pr
f ($?) { .\13_memset }
Modified String: ----- Patel
○ PS D:\Firstbit Solutions\C Programming\Assignments\Assignment 9>
```

Q14) memcap

```
#include <stdio.h>
#include <string.h>

int main() {
    char str1[] = "Hello";
    char str2[] = "Hello";
    int result = memcmp(str1, str2, 5);
    if (result == 0)
```

```

        printf("Blocks are identical\n");
    else
        printf("Blocks are different\n");
    return 0;
}

```

```

● PS D:\Firstbit Solutions\C Programming> cd "d:
f ($?) { .\14_memcap }
Blocks are identical

```

Q15) toupper (char)

```

#include<stdio.h>
#include<ctype.h>
#include<string.h>

int main(){
    char str[] = "Arjun Patel";
    int n = strlen(str);
    // printf("%d \n", n);
    printf("%d \n", strlen(str));

    char str2[strlen(str)+1];
    // printf("%d \n", strlen(str2));
    // printf("%c", toupper(c));
    for (int i = 0; i < strlen(str); i++)
    {
        str2[i] = toupper(str[i]);
    }
    str2[strlen(str)] = '\0';
    printf("%s", str2);
    return 0;
}

```

```

● PS D:\Firstbit Solutions\C Programming> cd "d
if ($?) { .\15_toupper }
11
ARJUN PATEL

```

Q16) tolower(char)

```

#include<stdio.h>
#include<ctype.h>
#include<string.h>

```



```

int main(){
    char str[] = "ARJUN Patel";
    int n = strlen(str);
    // printf("%d \n", n);
    printf("%d \n", strlen(str));

    char str2[strlen(str)+1];
    // printf("%d \n", strlen(str2));
    // printf("%c", toupper(c));
    for (int i = 0; i < strlen(str); i++)
    {
        str2[i] = tolower(str[i]);
    }
    str2[strlen(str)] = '\0';
    printf("%s", str2);
    return 0;
}

```

● PS D:\Firstbit Solutions\C Programming> cd "d:\Firstbit  
 if (\$?) { .\16\_tolower }  
 11  
 arjun patel

Q17)strupr

```

#include<stdio.h>
#include<string.h>
int main(){
    char str[] = "Arjun Patel";
    printf("%s",strupr(str));

    return 0;
}

```

● PS D:\Firstbit Solutions\C Programming> cd "d:\Firstbit  
 deRunnerFile } ; if (\$?) { .\tempCode  
 ARJUN PATEL

Q18)strlwr

```

#include<stdio.h>
#include<string.h>
int main(){
    char str[] = "ARJUN PATEL";
    printf("%s",strlwr(str));

    return 0;
}

```

```
}
```

```
PS D:\Firstbit Solutions\C Programming> cd
f ($?) { .\18_strlwr }
arjun patel
```

Q19) strpbrk :

// strpbrk(const char \*str, const char \*accept)

// Finds first character matching any in accept

```
#include<stdio.h>
#include<string.h>

// strpbrk(const char *str, const char *accept)
// Finds first character matching any in accept

int main(){
    char str[] = "Arjun Patel";
    char *pos = strpbrk(str, "Patel"); // points to 'p'

    printf("%u \n", str);
    printf("%u \n", pos);
    return 0;
}
```

```
PS D:\Firstbit Solutions\C Programming> cd
if ($?) { .\19_strpbrk }
3466590012
3466590018
```

Q20) strspn

// Gets length of initial segment matching accept

// cCopySize\_t len = strspn("Hello", "Hel"); // returns 3

```
// strspn(const char *str, const char *accept)
// Gets length of initial segment matching accept
// cCopySize_t len = strspn("Hello", "Hel"); // returns 3

#include<stdio.h>
#include<string.h>
int main(){
    char str[] = "Arjun Patel";
```

```

    int len = strspn(str, "Arjun b");
    printf("%d", len);
    return 0;
}

```

```

• PS D:\Firstbit Solutions\C Programming
f ($?) { .\20_strspn }
6

```

Q21) strcspn

```

// strcspn(const char *str, const char *reject)

// Gets length of initial segment not matching reject

// cCopySize_t len = strcspn("Hello", "o"); // returns 4

#include<stdio.h>
#include<string.h>
int main(){
    char str[] = "Arjun Patel";
    int len = strcspn(str, "P");

    printf("%d", len);
    return 0;
}

```

```

• PS D:\Firstbit Solutions\C Programming
if ($?) { .\21_strcspn }
6

```

Q22) memmove

```

// memmove(void *dest, const void *src, size_t n)

// Copies n bytes (safe for overlapping regions)

// cCopychar str[] = "Hello";
// memmove(str+1, str, 4);

//A r j u n   P a t e l
//0 1 2 3 4 5 6 7 8 9 10

#include<stdio.h>
#include<string.h>

int main(){
    char str[] = "Arjun Patel";

```

```

    memmove(str+1, str+6, 5);
    // memmove(dest, src, 6);
    //its replaces
    printf("%s", str);
    return 0;
}

```

```

● PS D:\Firstbit Solutions\C Programming> cd "d:\Firstbit Solutions"
deRunnerFile } ; if ($?) { .\tempCodeRunnerFile }
APatelPatel

```

Q23) memcmp

```

// memcmp(const void *str1, const void *str2, size_t n)

// Compares n bytes of memory

// cCopychar s1[] = "Hello";
// char s2[] = "Help";
// int result = memcmp(s1, s2, 4);

#include<stdio.h>
#include<string.h>
int main(){
    char str[] = "Arjun Patel";
    char str2[] = "Arjsf";

    int res = memcmp(str, str2, 4);

    //memcmp returns 0 if 4 bytes is same as cmp string, else returns 1
    printf("%d \n", res);
    return 0;
}

```

```

● PS D:\Firstbit Solutions\C Programming> cd "d:\Firstbit Solutions"
f ($?) { .\23_memcmp }
1

```

Q24) memcpy

```

// memcpy(void *dest, const void *src, size_t n)

// Copies n bytes from src to dest

// cCopychar src[] = "Hello";
// char dest[6];
// memcpy(dest, src, 6);

#include<stdio.h>

```

```
#include<string.h>
int main(){
    char str[] = "Hello world";
    char dest[strlen(str)+1];
    memcpy(dest, str, 4);
    dest[4] = '\0';

    printf("%s \n", dest);

    return 0;
}
```

```
PS D:\Firstbit Solutions\C Programming>
f ($?) { .\24_memcpy }
Hell
```

Q25)sprintf

```
// sprintf(char *str, const char *format, ...)

// Writes formatted data to string

// cCopychar str[50];
// sprintf(str, "Value is %d", 123);

#include<stdio.h>
#include<string.h>
int main(){
    char str[] = "Arjun Patel";
    sprintf(str, "value is %d", 123);
    printf("%s", str);
    return 0;
}
```

```
PS D:\Firstbit Solutions\C Programming> cd ".
if ($?) { .\25_sprintf }
value is 123
```

Q26) snprintf

```
// snprintf(char *str, size_t size, const char *format, ...)

// Writes formatted data to string with size limit

// cCopychar str[50];
// snprintf(str, 50, "Value is %d", 123);
```

```
#include<stdio.h>
#include<string.h>
int main(){
    char str[] = "Arjun Patel";
    snprintf(str, 12, "Value is %d", 12345);
    printf("%s", str);
    return 0;
}
```

```
● PS D:\Firstbit Solutions\C Programming> cd "d:\
; if ($?) { .\26_snprintf }
Value is 12
```

-----**END**-----