

[Get started](#)[Open in app](#)[Follow](#)

569K Followers



Multi Class Text Classification with LSTM using TensorFlow 2.0

Recurrent Neural Networks, Long Short Term Memory



Susan Li · Dec 8, 2019 · 7 min read

A lot of innovations on NLP have been how to add context into word vectors. One of the common ways of doing it is using Recurrent Neural Networks. The following are the concepts of Recurrent Neural Networks:


- They make use of sequential information.



Get started

Open in app


- RNNs are ideal for text and speech analysis.
- The most commonly used RNNs are LSTMs.



Source: <https://colah.github.io/posts/2015-08-Understanding-LSTMs/>

The above is the architecture of Recurrent Neural Networks.

- “A” is one layer of feed-forward neural network.
- If we only look at the right side, it does recurrently to pass through the element of each sequence.
- If we unwrap the left, it will exactly look like the right.




Source: <https://colah.github.io/posts/2015-08-Understanding-LSTMs/>



Get started

Open in app


- we input each word, words relate to each other in some ways.
- We make predictions at the end of the article when we see all the words in that article.
- RNNs, by passing input from last output, are able to retain information, and able to leverage all information at the end to make predictions.



<https://colah.github.io/posts/2015-08-Understanding-LSTMs>

- This works well for short sentences, when we deal with a long article, there will be a long term dependency problem.

Therefore, we generally do not use vanilla RNNs, and we use Long Short Term Memory instead. LSTM is a type of RNNs that can solve this long term dependency problem.



[Get started](#)[Open in app](#)

Now we are going to solve a BBC news document classification problem with LSTM using [TensorFlow 2.0](#) & [Keras](#). The data set can be found [here](#).

- First, we import the libraries and make sure our TensorFlow is the right version.

```
1 import csv
2 import tensorflow as tf
3 import numpy as np
4 from tensorflow.keras.preprocessing.text import Tokenizer
5 from tensorflow.keras.preprocessing.sequence import pad_sequences
6 from nltk.corpus import stopwords
7 STOPWORDS = set(stopwords.words('english'))
8
9 print(tf.__version__)
```

import.py hosted with ❤ by GitHub

[view raw](#)

2.0.0

- Put the hyperparameters at the top like this to make it easier to change and edit.
- We will explain how each hyperparameter works when we get there.

```
1 vocab_size = 5000
2 embedding_dim = 64
3 max_length = 200
4 trunc_type = 'post'
5 padding_type = 'post'
6 oov_tok = '<OOV>'
7 training_portion = .8
```

hyperparameter.py hosted with ❤ by GitHub

[view raw](#)

hyperparameter.py

- Define two lists containing articles and labels. In the meantime, we remove stopwords.

[Get started](#)[Open in app](#)

```
4 with open("bbc-text.csv", 'r') as csvfile:
5     reader = csv.reader(csvfile, delimiter=',')
6     next(reader)
7     for row in reader:
8         labels.append(row[0])
9         article = row[1]
10        for word in STOPWORDS:
11            token = ' ' + word + ' '
12            article = article.replace(token, ' ')
13            article = article.replace(' ', ' ')
14        articles.append(article)
15 print(len(labels))
16 print(len(articles))
```

articles_labels.py hosted with ❤ by GitHub

[view raw](#)

articles_labels.py

2225
2225

There are 2,225 news articles in the data, we split them into training set and validation set, according to the parameter we set earlier, 80% for training, 20% for validation.

```
1 train_size = int(len(articles) * training_portion)
2
3 train_articles = articles[0: train_size]
4 train_labels = labels[0: train_size]
5
6 validation_articles = articles[train_size:]
7 validation_labels = labels[train_size:]
8
9 print(train_size)
10 print(len(train_articles))
11 print(len(train_labels))
12 print(len(validation_articles))
13 print(len(validation_labels))
```

train_valid.py hosted with ❤ by GitHub

[view raw](#)

[Get started](#)[Open in app](#)

```
1780
1780
1780
445
445
```

Tokenizer does all the heavy lifting for us. In our articles that it was tokenizing, it will take 5,000 most common words. `oov_token` is to put a special value in when an unseen word is encountered. This means we want `<OOV>` to be used for words that are not in the `word_index`. `fit_on_text` will go through all the text and create dictionary like this:

```
1 tokenizer = Tokenizer(num_words = vocab_size, oov_token=oov_tok)
2 tokenizer.fit_on_texts(train_articles)
3 word_index = tokenizer.word_index
4 dict(list(word_index.items())[0:10])
```

tokenize.py hosted with ❤ by GitHub

[view raw](#)

tokenize.py

```
{'<OOV>': 1,
 'said': 2,
 'mr': 3,
 'would': 4,
 'year': 5,
 'also': 6,
 'people': 7,
 'new': 8,
 'us': 9,
 'one': 10}
```

We can see that “<OOV>” is the most common token in our corpus, followed by “said”, followed by “mr” and so on.



Get started

Open in app

```
train_sequences = tokenizer.texts_to_sequences(train_articles)
print(train_sequences[10])
```

```
[2432, 1, 225, 4995, 22, 642, 587, 225, 4995, 1, 1, 1662, 1, 1, 2432, 22, 565, 1, 1, 140, 278, 1, 140, 27
8, 796, 822, 662, 2308, 1, 1144, 1693, 1, 1720, 4996, 1, 1, 1, 1, 1, 4737, 1, 1, 122, 4513, 1, 2, 2875, 15
06, 352, 4738, 1, 52, 341, 1, 352, 2173, 3961, 41, 22, 3794, 1, 1, 1, 1, 543, 1, 1, 1, 835, 631, 2367, 34
7, 4739, 1, 365, 22, 1, 787, 2368, 1, 4301, 138, 10, 1, 3665, 682, 3531, 1, 22, 1, 414, 822, 662, 1, 90, 1
3, 633, 1, 225, 4995, 1, 599, 1, 1693, 1021, 1, 4997, 807, 1863, 117, 1, 1, 1, 2975, 22, 1, 99, 278, 1, 16
08, 4998, 543, 492, 1, 1446, 4740, 778, 1320, 1, 1860, 10, 33, 642, 319, 1, 62, 478, 565, 301, 1507, 22, 4
79, 1, 1, 1665, 1, 797, 1, 3067, 1, 1365, 6, 1, 2432, 565, 22, 2972, 4734, 1, 1, 1, 1, 1, 850, 39, 1824, 6
75, 297, 26, 979, 1, 882, 22, 361, 22, 13, 301, 1507, 1343, 374, 20, 63, 883, 1096, 4302, 247]
```

Figure 1

When we train neural networks for NLP, we need sequences to be in the same size, that's why we use padding. If you look up, our `max_length` is 200, so we use `pad_sequences` to make all of our articles the same length which is 200. As a result, you will see that the 1st article was 426 in length, it becomes 200, the 2nd article was 192 in length, it becomes 200, and so on.

```
train_padded = pad_sequences(train_sequences, maxlen=max_length,
padding=padding_type, truncating=trunc_type)
```

```
print(len(train_sequences[0]))
print(len(train_padded[0]))
```

```
print(len(train_sequences[1]))
print(len(train_padded[1]))
```

```
print(len(train_sequences[10]))
print(len(train_padded[10]))
```

```
425
200
192
200
186
200
```



Get started

Open in app

example, for the 11th article, it was 186 in length, we padded to 200, and we padded at the end, that is adding 14 zeros.

```
print(train_padded[10])
```

```
[2432  1  225 4995  22  642  587  225 4995  1  1 1662  1  1
 2432  22  565  1  1 140  278  1 140  278  796  822  662 2308
  1 1144 1693  1 1720 4996  1  1  1  1  1 4737  1  1
 122 4513  1  2 2875 1506  352 4738  1  52  341  1  352 2173
3961  41  22 3794  1  1  1  1  543  1  1  1  835  631
2367  347 4739  1  365  22  1  787 2368  1 4301  138  10  1
3665  682 3531  1  22  1  414  822  662  1  90  13  633  1
 225 4995  1  599  1 1693 1021  1 4997  807 1863  117  1  1
  1 2975  22  1  99  278  1 1608 4998  543  492  1 1446 4740
 778 1320  1 1860  10  33  642  319  1  62  478  565  301 1507
 22  479  1  1 1665  1  797  1 3067  1 1365  6  1 2432
 565  22 2972 4734  1  1  1  1  1  850  39 1824  675  297
 26  979  1  882  22  361  22  13  301 1507 1343  374  20  63
 883 1096 4302  247  0  0  0  0  0  0  0  0  0  0
  0  0  0  0]
```

Figure 2

And for the 1st article, it was 426 in length, we truncated to 200, and we truncated at the end as well.

Then we do the same for the validation sequences.

```
1 validation_sequences = tokenizer.texts_to_sequences(validation_articles)
2 validation_padded = pad_sequences(validation_sequences, maxlen=max_length, padding='padding')
3
4 print(len(validation_sequences))
5 print(validation_padded.shape)
```

val_tok.py hosted with ❤ by GitHub

[view raw](#)

val_tok.py

[Get started](#)[Open in app](#)

Now we are going to look at the labels. Because our labels are text, so we will tokenize them, when training, labels are expected to be numpy arrays. So we will turn list of labels into numpy arrays like so:

```
label_tokenizer = Tokenizer()
label_tokenizer.fit_on_texts(labels)

training_label_seq =
np.array(label_tokenizer.texts_to_sequences(train_labels))
validation_label_seq =
np.array(label_tokenizer.texts_to_sequences(validation_labels))

print(training_label_seq[0])
print(training_label_seq[1])
print(training_label_seq[2])
print(training_label_seq.shape)

print(validation_label_seq[0])
print(validation_label_seq[1])
print(validation_label_seq[2])
print(validation_label_seq.shape)
```

```
[4]
[2]
[1]
(1780, 1)
[5]
[4]
[3]
(445, 1)
```

Before training deep neural network, we should explore what our original article and article after padding look like. Running the following code, we explore the 11th article, we can see that some words become “<OOV>”, because they did not make to the top 5,000.



Get started

Open in app

```
def decode_article(text):
    return ' '.join([reverse_word_index.get(i, '?') for i in text])
print(decode_article(train_padded[10]))
print('---')
print(train_articles[10])
```

```
berlin <OOV> anti nazi film german movie anti nazi <OOV> <OOV> drawn <OOV> <OOV> berlin film festival <OOV>
> <OOV> final days <OOV> final days member white rose movement <OOV> 21 arrested <OOV> brother hans <OOV>
<OOV> <OOV> <OOV> <OOV> tyranny <OOV> <OOV> director marc <OOV> said feeling responsibility keep legacy <O
OV> going must <OOV> keep ideas alive added film drew <OOV> <OOV> <OOV> <OOV> trial <OOV> <OOV> <OOV> east
germany secret police discovery <OOV> behind film <OOV> worked closely <OOV> relatives including one <OOV>
sisters ensure historical <OOV> film <OOV> members white rose <OOV> group first started <OOV> anti nazi <O
OV> summer <OOV> arrested dropped <OOV> munich university calling day <OOV> <OOV> <OOV> regime film <OOV>
six days <OOV> arrest intense trial saw <OOV> initially deny charges ended <OOV> appearance one three germ
an films <OOV> top prize festival south african film version <OOV> <OOV> opera <OOV> shot <OOV> town <OOV>
language also <OOV> berlin festival film entitled u <OOV> <OOV> <OOV> <OOV> <OOV> story set performed 40 s
trong music theatre <OOV> debut film performance film first south african feature 25 years second nominate
d golden bear award ? ? ? ? ? ? ? ? ? ? ? ?
---
berlin cheers anti-nazi film german movie anti-nazi resistance heroine drawn loud applause berlin film fes
tival. sophie scholl - final days portrays final days member white rose movement. scholl 21 arrested be
headed brother hans 1943 distributing leaflets condemning abhorrent tyranny adolf hitler. director mar
c rothemund said: feeling responsibility keep legacy scholls going. must somehow keep ideas alive add
ed. film drew transcripts gestapo interrogations scholl trial preserved archive communist east germany se
cret police. discovery inspiration behind film rothemund worked closely surviving relatives including on
e scholl sisters ensure historical accuracy film. scholl members white rose resistance group first starte
d distributing anti-nazi leaflets summer 1942. arrested dropped leaflets munich university calling day re
ckoning adolf hitler regime. film focuses six days scholl arrest intense trial saw scholl initially deny
charges ended defiant appearance. one three german films vying top prize festival. south african film ver
sion bizet tragic opera carmen shot cape town xhosa language also premiered berlin festival. film entitled
u-carmen ekhayelitsha carmen khayelitsha township story set. performed 40-strong music theatre troupe debu
t film performance. film first south african feature 25 years second nominated golden bear award.
```

Figure 3

Now its the time to implement LSTM.

- We build a `tf.keras.Sequential` model and start with an embedding layer. An embedding layer stores one vector per word. When called, it converts the sequences of word indices into sequences of vectors. After training, words with similar meanings often have the similar vectors.
- The Bidirectional wrapper is used with a LSTM layer, this propagates the input forwards and backwards through the LSTM layer and then concatenates the outputs. This helps LSTM to learn long term dependencies. We then fit it to a dense neural network to do classification.


[Get started](#)
[Open in app](#)

- We add a Dense layer with 6 units and `softmax` activation. When we have multiple outputs, `softmax` converts outputs layers into a probability distribution.

```

1  model = tf.keras.Sequential([
2      # Add an Embedding layer expecting input vocab of size 5000, and output embedding di
3      tf.keras.layers.Embedding(vocab_size, embedding_dim),
4      tf.keras.layers.Bidirectional(tf.keras.layers.LSTM(embedding_dim)),
5      #   tf.keras.layers.Bidirectional(tf.keras.layers.LSTM(32)),
6      # use ReLU in place of tanh function since they are very good alternatives of each c
7      tf.keras.layers.Dense(embedding_dim, activation='relu'),
8      # Add a Dense layer with 6 units and softmax activation.
9      # When we have multiple outputs, softmax convert outputs layers into a probability c
10     tf.keras.layers.Dense(6, activation='softmax')
11 ])
12 model.summary()
```

lstm_model.py hosted with ❤ by GitHub

[view raw](#)

lstm_model.py

Model: "sequential"

Layer (type)	Output Shape	Param #
=====		
embedding (Embedding)	(None, None, 64)	320000

bidirectional (Bidirectional)	(None, 128)	66048

dense (Dense)	(None, 64)	8256

dense_1 (Dense)	(None, 6)	390
=====		
Total params: 394,694		
Trainable params: 394,694		
Non-trainable params: 0		

Figure 4

[Get started](#)[Open in app](#)

what we put in LSTM. We can also stack LSTM layer but I found the results worse.

```
print(set(labels))
```

```
{'tech', 'politics', 'sport', 'business', 'entertainment'}
```

We have 5 labels in total, but because we did not one-hot encode labels, we have to use `sparse_categorical_crossentropy` as loss function, it seems to think 0 is a possible label as well, while the tokenizer object which tokenizes starting with integer 1, instead of integer 0. As a result, the last Dense layer needs outputs for labels 0, 1, 2, 3, 4, 5 although 0 has never been used.

If you want the last Dense layer to be 5, you will need to subtract 1 from the training and validation labels. I decided to leave it as it is.

I decided to train 10 epochs, and it is plenty of epochs as you will see.

```
model.compile(loss='sparse_categorical_crossentropy',  
optimizer='adam', metrics=['accuracy'])
```

```
num_epochs = 10  
history = model.fit(train_padded, training_label_seq,  
epochs=num_epochs, validation_data=(validation_padded,  
validation_label_seq), verbose=2)
```

```
Train on 1780 samples, validate on 445 samples
```

```
Epoch 1/10
```

```
1780/1780 - 10s - loss: 1.6322 - accuracy: 0.2635 - val_loss: 1.4729 - val_accuracy: 0.2674
```

```
Epoch 2/10
```

```
1780/1780 - 5s - loss: 1.0612 - accuracy: 0.5809 - val_loss: 0.7554 - val_accuracy: 0.7393
```

```
Epoch 3/10
```

```
1780/1780 - 5s - loss: 0.3791 - accuracy: 0.8685 - val_loss: 0.3497 - val_accuracy: 0.8809
```

```
Epoch 4/10
```

```
1780/1780 - 5s - loss: 0.1476 - accuracy: 0.9556 - val_loss: 0.2603 - val_accuracy: 0.9146
```

```
Epoch 5/10
```

```
1780/1780 - 5s - loss: 0.0444 - accuracy: 0.9910 - val_loss: 0.3338 - val_accuracy: 0.9101
```

```
Epoch 6/10
```

```
1780/1780 - 5s - loss: 0.0000 - accuracy: 1.0000 - val_loss: 0.3338 - val_accuracy: 0.9101
```



Get started

Open in app

```

1780/1780 - 5s - loss: 0.0016 - accuracy: 1.0000 - val_loss: 0.2476 - val_accuracy: 0.9371
Epoch 9/10
1780/1780 - 5s - loss: 0.0011 - accuracy: 1.0000 - val_loss: 0.2752 - val_accuracy: 0.9371
Epoch 10/10
1780/1780 - 5s - loss: 7.9578e-04 - accuracy: 1.0000 - val_loss: 0.2882 - val_accuracy: 0.9348

```

Figure 5

```


def plot_graphs(history, string):
    plt.plot(history.history[string])
    plt.plot(history.history['val_'+string])
    plt.xlabel("Epochs")
    plt.ylabel(string)
    plt.legend([string, 'val_'+string])
    plt.show()

```

```

plot_graphs(history, "accuracy")
plot_graphs(history, "loss")

```




[Get started](#)[Open in app](#)

Figure 6

We probably only need 3 or 4 epochs. At the end of the training, we can see that there is a little bit overfitting.

In the future posts, we will work on improving the model.

[Jupyter notebook](#) can be found on [Github](#). Enjoy the rest of the weekend!

References:

Coursera | Online Courses From Top Universities. Join for Free

1000+ courses from schools like Stanford and Yale - no application required. Build career skills in data science...

www.coursera.org

O'Reilly Strata Data Conference 2019 - New York, New York

Selection from O'Reilly Strata Data Conference 2019 - New York, New York [Video]

learning.oreilly.co

[Get started](#)[Open in app](#)

Every Thursday, the Variable delivers the very best of Towards Data Science: from hands-on tutorials and cutting-edge research to original features you don't want to miss. [Take a look.](#)

[Get this newsletter](#)[Machine Learning](#)[NLP](#)[Tensorflow2](#)[Tensorflow Tutorial](#)[Lstm](#)[About](#) [Write](#) [Help](#) [Legal](#)

Get the Medium app

