

Assignment 8

Module-8 CCNA - VLANs and Inter-VLAN Routing

1. Host A and Host B sit in two different subnets. The path between the subnets of these two hosts runs through three different Layer 3 forwarding devices (routers and Layer 3 switches). A network engineer uses the APIC-EM Path Trace ACL Analysis tool to analyze the path used for Host A to send packets to Host B. Which part of the function is done specifically by the ACL Analysis or ACL Trace part of the tool?
 - A. Discovery of the topology that exists between the two hosts
 - B. Analysis of the Layer 3 forwarding decisions in the path from Host A to B
 - C. Analysis of the Layer 2 forwarding decisions in the path from Host A to B
 - D. Analysis of the impact of ACLs on the packets that would flow from Host A to B

Ans : D. Analysis of the impact of ACLs on the packets that would flow from Host A to B

2. Which IPv6 address is the equivalent of the IPv4 interface loopback address 127.0.0.1?
 - A. ::1
 - B. ::
 - C. 2000::/3
 - D. 0::/10

Ans : A. ::1

3. Which command is used to apply an ACL to an interface?
 - A. access-group
 - B. ip access-group
 - C. ip access-list
 - D. ip access-class
 - E. access-class
 - F. access-list

Ans : B. ip access-group

4. Which command and mode will successfully configure a hostname of R1 on a Cisco IOS router?

- A. Router(config)#name R1
- B. Router# hostname R1
- C. Router(config)#hostname R1
- D. Router#name R1
- E. Router>hostname R1
- F. Router>name R1

Ans : C. Router(config)#hostname R1

5. Which of the following reserved IPv4 addresses has binary 0s in all of the host bit positions?

- A. Local broadcast address
- B. Loopback address
- C. Directed broadcast address
- D. Network address
- E. All zeros address

Ans : D. Network address