1.
Write a PL/SQL block that declares two variables: one for a user's name (VARCHAR2) and one for their age (NUMBER). Assign values and print both using DBMS_OUTPUT.PUT_LINE.

Ans:

```
DECLARE
  message varchar2(100):= 'Hello, World!';
  name varchar2(100):='Diya Patel';
  age int :=25;
BEGIN
  dbms_output.put_line(name);
  dbms_output.put_line(age);

END;
/
```

Output:

```
Diya Patel
25
```

2.
Create a PL/SQL block that uses an IF statement to check if a given order amount is above 500. If yes, print 'Eligible for free delivery', else print 'Delivery charges apply'.

Ans:

```
DECLARE
  amount float:=3500;
BEGIN

  if amount>500 then
```

```
    dbms_output.put_line('eligible');
  else
    dbms_output.put_line('not eligible');
  end if;
END;
/
```

Output:

```
eligible
```

4. Declare a cursor in PL/SQL to select all product names from a table called PRODUCTS. Fetch each product name and print it using DBMS_OUTPUT.PUT_LINE.

Hint: Assume the PRODUCTS table has a column PRODUCT_NAME.

Ans:

```
DELIMITER //

CREATE PROCEDURE getPnameByRow()
BEGIN
    DECLARE cpid INT;
    DECLARE cname VARCHAR(100);
    DECLARE done INT DEFAULT 0;

    DECLARE productcursor CURSOR FOR
        SELECT pid, pname FROM product;

    DECLARE CONTINUE HANDLER FOR NOT FOUND
```

```
        SET done = 1;

    OPEN productcursor;

    ploop: LOOP
        FETCH productcursor INTO cpid, cname;

        IF done = 1 THEN
            LEAVE ploop;
        END IF;

        SELECT cpid AS Product_ID, cname AS Product_Name;

    END LOOP;

    CLOSE productcursor;
END //

DELIMITER ;
```