

HRMS Mobile App API — Complete Documentation (v1)

Base URL (dev): `http://localhost:5000` · **App base path:** `/api/app` · **Auth:** OTP (mobile linked to Temporary Employee).

Every response uses the envelope: `{ success, message, data, errors, timestamp }`.

Development OTP: the app always shows the OTP screen; the backend accepts **any 4-digit OTP** and sends **no SMS** (`OTP_MODE=development`). Switching to production needs no app changes.

Endpoint List — HRMS Mobile App API (`/api/app`)

Group	Method	Endpoint	Auth
Authentication	POST	<code>/api/app/auth/login</code>	None (public)
Authentication	POST	<code>/api/app/auth/verify-otp</code>	None (public)
Authentication	POST	<code>/api/app/auth/refresh</code>	None (public)
Authentication	POST	<code>/api/app/auth/logout</code>	Bearer access token
Authentication	GET	<code>/api/app/auth/session</code>	Bearer access token
Authentication	GET	<code>/api/app/auth/me</code>	Bearer access token
Registration	POST	<code>/api/app/profile/personal</code>	Bearer access token
Registration	POST	<code>/api/app/profile/address</code>	Bearer access token
Registration	POST	<code>/api/app/profile/family</code>	Bearer access token
Registration	POST	<code>/api/app/profile/bank</code>	Bearer access token
Registration	POST	<code>/api/app/profile/education</code>	Bearer access token
Registration	POST	<code>/api/app/profile/experience</code>	Bearer access token
Registration	POST	<code>/api/app/profile/documents</code>	Bearer access token
Registration	POST	<code>/api/app/profile/document</code>	Bearer access token
Registration	GET	<code>/api/app/profile/progress</code>	Bearer access token
Registration	POST	<code>/api/app/profile/submit</code>	Bearer access token
Registration	GET	<code>/api/app/profile/status</code>	Bearer access token
Registration	PUT	<code>/api/app/profile/update</code>	Bearer access token
Dashboard	GET	<code>/api/app/dashboard</code>	Bearer access token (approved employees only)
Dashboard	GET	<code>/api/app/profile</code>	Bearer access token (approved employees only)
Dashboard	GET	<code>/api/app/profile/documents</code>	Bearer access token (approved employees only)
Dashboard	GET	<code>/api/app/attendance</code>	Bearer access token (approved employees only)
Dashboard	GET	<code>/api/app/leave</code>	Bearer access token (approved employees only)

Dashboard	POST	/api/app/leave/apply	Bearer access token (approved employees only)
Dashboard	GET	/api/app/payroll	Bearer access token (approved employees only)
Dashboard	GET	/api/app/notifications	Bearer access token (approved employees only)
Dashboard	GET	/api/app/holiday	Bearer access token (approved employees only)

Authentication

Login

Group: Authentication

Endpoint	POST /api/app/auth/login
Method	POST
Authentication	None (public)

Headers

Content-Type: application/json

Request body

```
{
  "mobile": "9876543210"
}
```

Validation rules

- **mobile** is required.
- Mobile must be linked to an existing Temporary Employee ID.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
    "sessionId": "a1b2c3d4e5f6",
    "otpRequired": true,
    "otpLength": 4,
    "expiresIn": 300,
    "otpMode": "development",
    "devOtp": "1111"
  },
  "errors": [],
}
```

```
"timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

400 MOBILE_REQUIRED

```
{
  "success": false,
  "message": "Mobile number is required.",
  "data": null,
  "errors": [
    {
      "code": "MOBILE_REQUIRED",
      "message": "Mobile number is required."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

404 EMPLOYEE_NOT_FOUND

```
{
  "success": false,
  "message": "Employee not found.",
  "data": null,
  "errors": [
    {
      "code": "EMPLOYEE_NOT_FOUND",
      "message": "Employee not found."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

HTTP status codes

- 200 OK
- 400
- 404

cURL

```
curl -s -X POST http://localhost:5000/api/app/auth/login \
-H 'Content-Type: application/json' \
-d '{"mobile": "9876543210"}'
```

Notes

- Development mode returns `devOtp` and accepts any 4-digit code. No SMS is sent.
- Navigate to the OTP screen with the returned `sessionId`.

Verify OTP

Group: Authentication

Endpoint	POST /api/app/auth/verify-otp
Method	POST
Authentication	None (public)

Headers

```
Content-Type: application/json
```

Request body

```
{
  "sessionId": "a1b2c3d4e5f6",
  "otp": "1234"
}
```

Validation rules

- `sessionId` from /login is required.
- `otp` must be a 4-digit numeric string.
- Session expires in 5 minutes / after 5 attempts.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
    "accessToken": "eyJhbGciOi...",
    "refreshToken": "eyJhbGciOi...",
    "tokenType": "Bearer",
    "expiresIn": 43200,
    "refreshExpiresIn": 2592000,
    "registrationCompleted": false,
    "currentStep": 1,
    "approvalStatus": "Draft"
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

400 INVALID_SESSION

```
{
  "success": false,
```

```
"message": "Invalid or expired session.",
"data": null,
"errors": [
  {
    "code": "INVALID_SESSION",
    "message": "Invalid or expired session."
  }
],
"timestamp": "2026-06-25T12:00:00.000Z"
}
```

400 OTP_EXPIRED

```
{
  "success": false,
  "message": "OTP expired.",
  "data": null,
  "errors": [
    {
      "code": "OTP_EXPIRED",
      "message": "OTP expired."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

400 INVALID_OTP

```
{
  "success": false,
  "message": "Enter any 4-digit code.",
  "data": null,
  "errors": [
    {
      "code": "INVALID_OTP",
      "message": "Enter any 4-digit code."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

429 TOO_MANY_ATTEMPTS

```
{
  "success": false,
  "message": "Too many attempts.",
  "data": null,
  "errors": [
    {
      "code": "TOO_MANY_ATTEMPTS",
      "message": "Too many attempts."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

HTTP status codes

- 200 OK
- 400
- 429

cURL

```
curl -s -X POST http://localhost:5000/api/app/auth/verify-otp \
-H 'Content-Type: application/json' \
-d '{"sessionId":"a1b2c3d4e5f6","otp":"1234"}'
```

Notes

- Store `accessToken` + `refreshToken` securely.
- `currentStep` tells the app which registration step to open.

Refresh Token

Group: Authentication

Endpoint	POST /api/app/auth/refresh
Method	POST
Authentication	None (public)

Headers

```
Content-Type: application/json
```

Request body

```
{
  "refreshToken": "eyJhbGciOi..."
}
```

Validation rules

- `refreshToken` must be valid and unexpired.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
    "accessToken": "eyJhbGciOi...",
```

```

    "tokenType": "Bearer",
    "expiresIn": 43200
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}

```

Error responses

400 REFRESH_TOKEN_REQUIRED

```

{
  "success": false,
  "message": "A refresh token is required.",
  "data": null,
  "errors": [
    {
      "code": "REFRESH_TOKEN_REQUIRED",
      "message": "A refresh token is required."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}

```

401 REFRESH_TOKEN_INVALID

```

{
  "success": false,
  "message": "Session expired. Please log in again.",
  "data": null,
  "errors": [
    {
      "code": "REFRESH_TOKEN_INVALID",
      "message": "Session expired. Please log in again."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}

```

HTTP status codes

- 200 OK
- 400
- 401

cURL

```

curl -s -X POST http://localhost:5000/api/app/auth/refresh \
  -H 'Content-Type: application/json' \
  -d '{"refreshToken":"eyJhbGciOi..."}'

```

Notes

- Call inside a 401 interceptor, then retry the original request.

Logout

Group: Authentication

Endpoint	POST /api/app/auth/logout
Method	POST
Authentication	Bearer access token

Headers

```
Content-Type: application/json
Authorization: Bearer <accessToken>
```

Request body

None

Validation rules

- Send the access token in the Authorization header.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {},
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

401 NO_TOKEN

```
{
  "success": false,
  "message": "Not authorized – no token provided.",
  "data": null,
  "errors": [
    {
      "code": "NO_TOKEN",
      "message": "Not authorized – no token provided."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

HTTP status codes

- 200 OK
- 401

cURL

```
curl -s -X POST http://localhost:5000/api/app/auth/logout \  
-H 'Content-Type: application/json' \  
-H 'Authorization: Bearer <accessToken>'
```

Notes

- Tokens are stateless — clear them from secure storage after calling.

Session

Group: Authentication

Endpoint	GET /api/app/auth/session
Method	GET
Authentication	Bearer access token

Headers

```
Content-Type: application/json  
Authorization: Bearer <accessToken>
```

Request body

None.

Validation rules

- Valid access token required.

Success response (200)

```
{  
  "success": true,  
  "message": "Success",  
  "data": {  
    "loggedIn": true,  
    "registrationCompleted": false,  
    "currentStep": 4,  
    "completionPercentage": 62,  
    "approvalStatus": "Draft"  
  },  
  "errors": [],  
}
```

```
"timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

401 TOKEN_INVALID

```
{
  "success": false,
  "message": "Session expired. Please log in again.",
  "data": null,
  "errors": [
    {
      "code": "TOKEN_INVALID",
      "message": "Session expired. Please log in again."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

HTTP status codes

- 200 OK
- 401

cURL

```
curl -s -X GET http://localhost:5000/api/app/auth/session \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer <accessToken>'
```

Notes

- Call on splash to decide navigation: not logged in / resume registration / pending approval / dashboard.

Get Me

Group: Authentication

Endpoint	GET /api/app/auth/me
Method	GET
Authentication	Bearer access token

Headers

```
Content-Type: application/json
Authorization: Bearer <accessToken>
```

Request body

None.

Validation rules

- Valid access token required.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
    "tempEmployeeId": "VE-TEMP-000002",
    "name": "Om Patel",
    "mobile": "9876543210",
    "email": "om@example.com",
    "branch": "Ahmedabad",
    "approvalStatus": "Draft",
    "registrationCompleted": false,
    "currentStep": 4,
    "completionPercentage": 62,
    "employeeId": null,
    "isApproved": false
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

401 TOKEN_INVALID

```
{
  "success": false,
  "message": "Session expired.",
  "data": null,
  "errors": [
    {
      "code": "TOKEN_INVALID",
      "message": "Session expired."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

HTTP status codes

- 200 OK
- 401

cURL

```
curl -s -X GET http://localhost:5000/api/app/auth/me \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer <accessToken>'
```

Notes

- Returns the onboarding identity; after approval `employeeId` is populated.

Registration

Save Personal

Group: Registration

Endpoint	POST /api/app/profile/personal
Method	POST
Authentication	Bearer access token

Headers

```
Content-Type: application/json
Authorization: Bearer <accessToken>
```

Request body

```
{
  "firstName": "Om",
  "middleName": "",
  "lastName": "Patel",
  "dob": "1998-05-10",
  "gender": "Male",
  "maritalStatus": "Single",
  "nationality": "Indian",
  "bloodGroup": "O+",
  "email": "om@example.com"
}
```

Validation rules

- Editable until approval.

Success response (200)

```
{
  "success": true,
  "message": "Success",
}
```

```

"data": {
  "saved": true,
  "currentStep": 2,
  "completedSteps": [
    1
  ],
  "completionPercentage": 14,
  "totalSteps": 7,
  "canSubmit": false,
  "approvalStatus": "Draft"
},
"errors": [],
"timestamp": "2026-06-25T12:00:00.000Z"
}

```

Error responses

403 ALREADY_APPROVED

```

{
  "success": false,
  "message": "Your profile is approved and can no longer be edited here.",
  "data": null,
  "errors": [
    {
      "code": "ALREADY_APPROVED",
      "message": "Your profile is approved and can no longer be edited here."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}

```

HTTP status codes

- 200 OK
- 403

cURL

```

curl -s -X POST http://localhost:5000/api/app/profile/personal \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer <accessToken>' \
-d '{"firstName":"Om","middleName":"","lastName":"Patel","dob":"1998-05-10","gender":"Male","marita

```

Notes

- Draft is saved immediately; nothing is lost if the app closes.

Save Address

Group: Registration

Endpoint	POST /api/app/profile/address
Method	POST
Authentication	Bearer access token

Headers

```
Content-Type: application/json
Authorization: Bearer <accessToken>
```

Request body

```
{
  "present": {
    "line1": "12 MG Road",
    "line2": "",
    "area": "Navrangpura",
    "landmark": "Near Park",
    "city": "Ahmedabad",
    "district": "Ahmedabad",
    "state": "Gujarat",
    "country": "India",
    "pincode": "380009"
  },
  "sameAsPresent": true
}
```

Validation rules

- Editable until approval.
- Set `sameAsPresent:true` to copy present → permanent.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
    "saved": true,
    "currentStep": 3,
    "completedSteps": [
      1,
      2
    ],
    "completionPercentage": 29,
    "totalSteps": 7,
    "canSubmit": false,
    "approvalStatus": "Draft"
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

_Standard envelope with `success:false` _

HTTP status codes

- `200 OK`

cURL

```
curl -s -X POST http://localhost:5000/api/app/profile/address \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer <accessToken>' \
-d '{"present":{"line1":"12 MG Road","line2":"","area":"Navrangpura","landmark":"Near Park","city":
```

Notes

- Structured address is composed into `presentAddress` / `permanentAddress` .

Save Family / Nominee

Group: Registration

Endpoint	POST /api/app/profile/family
Method	POST
Authentication	Bearer access token

Headers

```
Content-Type: application/json
Authorization: Bearer <accessToken>
```

Request body

```
{
  "fatherSpouseName": "Ramesh Patel",
  "emergencyContactName": "Ramesh Patel",
  "emergencyContact": "9876500000",
  "relationship": "Father",
  "nominee": {
    "name": "Ramesh Patel",
    "relationship": "Father",
    "share": 100
  }
}
```

Validation rules

- Editable until approval.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
    "saved": true,
    "currentStep": 4,
    "completedSteps": [
      1,
      2,
      3
    ],
    "completionPercentage": 43,
    "totalSteps": 7,
    "canSubmit": false,
    "approvalStatus": "Draft"
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

_Standard envelope with `success:false` _

HTTP status codes

- `200 OK`

cURL

```
curl -s -X POST http://localhost:5000/api/app/profile/family \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer <accessToken>' \
-d '{"fatherSpouseName":"Ramesh Patel","emergencyContactName":"Ramesh Patel","emergencyContact":"98"
```

Notes

- Standard response envelope: { success, message, data, errors, timestamp }.

Save Bank

Group: Registration

Endpoint	POST /api/app/profile/bank
Method	POST
Authentication	Bearer access token

Headers

```
Content-Type: application/json
Authorization: Bearer <accessToken>
```

Request body

```
{
  "bankName": "HDFC Bank",
  "accountNumber": "50100123456789",
  "ifsc": "HDFC0001234",
  "accountHolderName": "Om Patel",
  "bankBranch": "Navrangpura",
  "accountType": "Savings"
}
```

Validation rules

- Editable until approval.
- `accountNumber` and `ifsc` complete this step.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
    "saved": true,
    "currentStep": 5,
    "completedSteps": [
      1,
      2,
      3,
      4
    ],
    "completionPercentage": 57,
    "totalSteps": 7,
    "canSubmit": false,
    "approvalStatus": "Draft"
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

_Standard envelope with `success:false` _

HTTP status codes

- `200 OK`

cURL

```
curl -s -X POST http://localhost:5000/api/app/profile/bank \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer <accessToken>' \
-d '{"bankName":"HDFC Bank","accountNumber":"50100123456789","ifsc":"HDFC0001234","accountHolderName":"HDFC Bank"}'
```

Notes

- Standard response envelope: { success, message, data, errors, timestamp }.

Save Education

Group: Registration

Endpoint	POST /api/app/profile/education
Method	POST
Authentication	Bearer access token

Headers

```
Content-Type: application/json
Authorization: Bearer <accessToken>
```

Request body

```
{
  "education": [
    {
      "degree": "B.Tech",
      "institution": "GTU",
      "year": "2020",
      "grade": "8.2 CGPA"
    }
  ]
}
```

Validation rules

- Editable until approval.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
```

```

    "saved": true,
    "currentStep": 6,
    "completedSteps": [
      1,
      2,
      3,
      4,
      5
    ],
    "completionPercentage": 71,
    "totalSteps": 7,
    "canSubmit": false,
    "approvalStatus": "Draft"
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}

```

Error responses

_Standard envelope with `success:false` _

HTTP status codes

- `200 OK`

cURL

```

curl -s -X POST http://localhost:5000/api/app/profile/education \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer <accessToken>' \
-d '{"education":[{"degree":"B.Tech","institution":"GTU","year":"2020","grade":"8.2 CGPA"}]}'

```

Notes

- Standard response envelope: { success, message, data, errors, timestamp }.

Save Experience

Group: Registration

Endpoint	POST /api/app/profile/experience
Method	POST
Authentication	Bearer access token

Headers

```

Content-Type: application/json
Authorization: Bearer <accessToken>

```

Request body

```
{
  "experience": [
    {
      "company": "Acme Corp",
      "role": "Developer",
      "from": "2020-07",
      "to": "2023-06"
    }
  ]
}
```

Validation rules

- Editable until approval. Optional step.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
    "saved": true,
    "currentStep": 7,
    "completedSteps": [
      1,
      2,
      3,
      4,
      5,
      6
    ],
    "completionPercentage": 86,
    "totalSteps": 7,
    "canSubmit": false,
    "approvalStatus": "Draft"
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

_Standard envelope with `success:false` _

HTTP status codes

- `200 OK`

cURL

```
curl -s -X POST http://localhost:5000/api/app/profile/experience \
-H 'Content-Type: application/json' \
```

```
-H 'Authorization: Bearer <accessToken>' \
-d '{"experience":[{"company":"Acme Corp","role":"Developer","from":"2020-07","to":"2023-06"}]}'
```

Notes

- Standard response envelope: { success, message, data, errors, timestamp }.

Save Documents (bulk)

Group: Registration

Endpoint	POST /api/app/profile/documents
Method	POST
Authentication	Bearer access token

Headers

```
Content-Type: application/json
Authorization: Bearer <accessToken>
```

Request body

```
{
  "photo": "data:image/jpeg;base64,...",
  "documents": {
    "aadhaarDoc": {
      "name": "aadhaar.jpg",
      "dataUrl": "data:image/jpeg;base64,..."
    },
    "panDoc": {
      "name": "pan.jpg",
      "dataUrl": "..."
    },
    "bankProof": {
      "name": "passbook.jpg",
      "dataUrl": "..."
    }
  }
}
```

Validation rules

- Editable until approval.
- Required for submission: photo, aadhaarDoc, panDoc, bankProof.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
    "saved": true,
    "currentStep": 7,
    "completedSteps": [
      1,
      2,
      3,
      4,
      5,
      6,
      7
    ],
    "completionPercentage": 100,
    "totalSteps": 7,
    "canSubmit": true,
    "approvalStatus": "Draft"
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

_Standard envelope with `success:false` . _

HTTP status codes

- `200 OK`

cURL

```
curl -s -X POST http://localhost:5000/api/app/profile/documents \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer <accessToken>' \
-d '{"photo":"data:image/jpeg;base64,...","documents":{"aadhaarDoc":{"name":"aadhaar.jpg","dataUrl"}}

```

Notes

- Prefer per-file uploads via POST /profile/document for large images.

Upload Single Document

Group: Registration

Endpoint	<code>POST /api/app/profile/document</code>
Method	POST
Authentication	Bearer access token

Headers

```
Content-Type: application/json
Authorization: Bearer <accessToken>
```

Request body

```
{
  "type": "aadhaar",
  "name": "aadhaar.jpg",
  "dataUrl": "data:image/jpeg;base64,..."
}
```

Validation rules

- **type** is required: aadhaar | pan | photo | signature | passbook | degree | experience | other.
- **dataUrl** (base64) is required.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
    "uploaded": "aadhaarDoc",
    "currentStep": 7,
    "completedSteps": [
      1,
      2,
      3,
      4,
      5,
      6
    ],
    "completionPercentage": 86,
    "totalSteps": 7,
    "canSubmit": false,
    "approvalStatus": "Draft"
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

400 TYPE_REQUIRED

```
{
  "success": false,
  "message": "Document type is required.",
  "data": null,
  "errors": [
    {
```

```

    "code": "TYPE_REQUIRED",
    "message": "Document type is required."
  }
],
"timestamp": "2026-06-25T12:00:00.000Z"
}

```

400 CONTENT_REQUIRED

```

{
  "success": false,
  "message": "Document content is required.",
  "data": null,
  "errors": [
    {
      "code": "CONTENT_REQUIRED",
      "message": "Document content is required."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}

```

HTTP status codes

- 200 OK
- 400

cURL

```

curl -s -X POST http://localhost:5000/api/app/profile/document \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer <accessToken>' \
-d '{"type": "aadhaar", "name": "aadhaar.jpg", "dataUrl": "data:image/jpeg;base64,..."}'

```

Notes

- **photo** is stored as the profile photo; others are kept under their document key.

Progress

Group: Registration

Endpoint	GET /api/app/profile/progress
Method	GET
Authentication	Bearer access token

Headers

```
Content-Type: application/json
Authorization: Bearer <accessToken>
```

Request body

None.

Validation rules

- Valid access token required.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
    "currentStep": 5,
    "completedSteps": [
      1,
      2,
      3,
      4
    ],
    "completionPercentage": 71,
    "totalSteps": 7,
    "canSubmit": false,
    "approvalStatus": "Draft"
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

Standard envelope with `success:false`.

HTTP status codes

- `200 OK`

cURL

```
curl -s -X GET http://localhost:5000/api/app/profile/progress \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer <accessToken>'
```

Notes

- Drives the registration stepper UI and the “Send For Approval” button state.

Submit For Approval

Group: Registration

Endpoint	POST /api/app/profile/submit
Method	POST
Authentication	Bearer access token

Headers

```
Content-Type: application/json
Authorization: Bearer <accessToken>
```

Request body

None.

Validation rules

- All mandatory fields + documents must be present.
- Cannot submit an already-approved profile.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
    "approvalStatus": "Pending Approval",
    "submittedAt": "2026-06-25T12:00:00.000Z"
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

422 VALIDATION_FAILED

```
{
  "success": false,
  "message": "Please complete all required fields and documents before submitting.",
  "data": null,
  "errors": [
    {
      "code": "VALIDATION_FAILED",
      "message": "Please complete all required fields and documents before submitting."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

400 ALREADY_APPROVED

```
{
  "success": false,
  "message": "Your profile is already approved.",
  "data": null,
  "errors": [
    {
      "code": "ALREADY_APPROVED",
      "message": "Your profile is already approved."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

HTTP status codes

- 200 OK
- 422
- 400

cURL

```
curl -s -X POST http://localhost:5000/api/app/profile/submit \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer <accessToken>'
```

Notes

- On success the record enters the HR website “Pending Approval” queue.
- 422 returns an `errors[]` array of missing fields/documents.

Approval Status

Group: Registration

Endpoint	GET /api/app/profile/status
Method	GET
Authentication	Bearer access token

Headers

```
Content-Type: application/json
Authorization: Bearer <accessToken>
```

Request body

None.

Validation rules

- Valid access token required.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
    "approvalStatus": "Pending Approval",
    "completionPercentage": 100
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

_Standard envelope with `success:false` _

HTTP status codes

- `200 OK`

cURL

```
curl -s -X GET http://localhost:5000/api/app/profile/status \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer <accessToken>'
```

Notes

- Values: Draft | Pending Approval | Approved | Rejected | Changes Requested.
- If Rejected / Changes Requested, a `remarks` field is included.

Update Profile

Group: Registration

Endpoint	<code>PUT /api/app/profile/update</code>
Method	PUT
Authentication	Bearer access token

Headers

```
Content-Type: application/json
Authorization: Bearer <accessToken>
```

Request body

```
{
  "email": "new@example.com",
  "presentAddress": "12 MG Road, Ahmedabad"
}
```

Validation rules

- Before approval edits the draft; after approval edits limited Employee fields.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
    "currentStep": 5,
    "completedSteps": [
      1,
      2,
      3,
      4
    ],
    "completionPercentage": 71,
    "totalSteps": 7,
    "canSubmit": false,
    "approvalStatus": "Draft"
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

Standard envelope with `success:false`

HTTP status codes

- `200 OK`

cURL

```
curl -s -X PUT http://localhost:5000/api/app/profile/update \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer <accessToken>' \
-d '{"email":"new@example.com","presentAddress":"12 MG Road, Ahmedabad"}'
```

Notes

- Standard response envelope: { success, message, data, errors, timestamp }.

Dashboard

Dashboard

Group: Dashboard

Endpoint	GET /api/app/dashboard
Method	GET
Authentication	Bearer access token (approved employees only)

Headers

```
Content-Type: application/json
Authorization: Bearer <accessToken>
```

Request body

None.

Validation rules

- Available only after HR approval.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
    "employeeId": "VE-AHM-001",
    "name": "Om Patel",
    "designation": "Developer",
    "department": "IT",
    "company": "Vision Enterprise",
    "branch": "Ahmedabad",
    "todayAttendance": {
      "status": "Present",
      "clockIn": "09:05",
      "clockOut": "18:10"
    },
    "pendingLeaveRequests": 1,
    "latestPayrollNet": 42000
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

403 NOT_APPROVED

```
{
  "success": false,
  "message": "Dashboard is available only after HR approval.",
  "data": null,
  "errors": [
    {
      "code": "NOT_APPROVED",
      "message": "Dashboard is available only after HR approval."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

HTTP status codes

- 200 OK
- 403

cURL

```
curl -s -X GET http://localhost:5000/api/app/dashboard \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer <accessToken>'
```

Notes

- Redirect to the appropriate screen unless approvalStatus === Approved.

Employee Profile

Group: Dashboard

Endpoint	GET /api/app/profile
Method	GET
Authentication	Bearer access token (approved employees only)

Headers

```
Content-Type: application/json
Authorization: Bearer <accessToken>
```

Request body

None.

Validation rules

- Available only after HR approval.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
    "employeeId": "VE-AHM-001",
    "name": "Om Patel",
    "email": "om@example.com",
    "mobile": "9876543210",
    "department": "IT",
    "designation": "Developer",
    "company": {
      "id": 2,
      "name": "Vision Enterprise"
    },
    "branch": {
      "id": 5,
      "name": "Ahmedabad"
    }
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

403 NOT_APPROVED

```
{
  "success": false,
  "message": "Dashboard is available only after HR approval.",
  "data": null,
  "errors": [
    {
      "code": "NOT_APPROVED",
      "message": "Dashboard is available only after HR approval."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

HTTP status codes

- 200 OK
- 403

cURL

```
curl -s -X GET http://localhost:5000/api/app/profile \
-H 'Content-Type: application/json' \
```

```
-H 'Authorization: Bearer <accessToken>'
```

Notes

- Standard response envelope: { success, message, data, errors, timestamp }.

Profile Documents

Group: Dashboard

Endpoint	GET /api/app/profile/documents
Method	GET
Authentication	Bearer access token (approved employees only)

Headers

```
Content-Type: application/json
Authorization: Bearer <accessToken>
```

Request body

None.

Validation rules

- Available only after HR approval.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
    "photo": "data:image/jpeg;base64,...",
    "documents": {
      "aadhaarDoc": {
        "name": "aadhaar.jpg"
      },
      "panDoc": {
        "name": "pan.jpg"
      }
    }
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

403 NOT_APPROVED

```
{
  "success": false,
  "message": "Dashboard is available only after HR approval.",
  "data": null,
  "errors": [
    {
      "code": "NOT_APPROVED",
      "message": "Dashboard is available only after HR approval."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

HTTP status codes

- 200 OK
- 403

cURL

```
curl -s -X GET http://localhost:5000/api/app/profile/documents \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer <accessToken>'
```

Notes

- Standard response envelope: { success, message, data, errors, timestamp }.

Attendance

Group: Dashboard

Endpoint	GET /api/app/attendance
Method	GET
Authentication	Bearer access token (approved employees only)

Headers

```
Content-Type: application/json
Authorization: Bearer <accessToken>
```

Request body

None.

Validation rules

- Available only after HR approval.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
    "summary": {
      "totalRecords": 22,
      "presentDays": 20
    },
    "records": [
      {
        "date": "2026-06-24",
        "status": "Present",
        "clockIn": "09:05",
        "clockOut": "18:10",
        "hoursWorked": 8.5
      }
    ]
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

403 NOT_APPROVED

```
{
  "success": false,
  "message": "Dashboard is available only after HR approval.",
  "data": null,
  "errors": [
    {
      "code": "NOT_APPROVED",
      "message": "Dashboard is available only after HR approval."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

HTTP status codes

- 200 OK
- 403

cURL

```
curl -s -X GET http://localhost:5000/api/app/attendance \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer <accessToken>'
```

Notes

- Standard response envelope: { success, message, data, errors, timestamp }.

Leave List

Group: Dashboard

Endpoint	GET /api/app/leave
Method	GET
Authentication	Bearer access token (approved employees only)

Headers

```
Content-Type: application/json
Authorization: Bearer <accessToken>
```

Request body

None.

Validation rules

- Available only after HR approval.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
    "requests": [
      {
        "id": 12,
        "leaveType": "Casual",
        "fromDate": "2026-06-20",
        "toDate": "2026-06-21",
        "days": 2,
        "reason": "Personal",
        "status": "Pending",
        "appliedOn": "2026-06-18"
      }
    ]
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

403 NOT_APPROVED

```
{
  "success": false,
  "message": "Dashboard is available only after HR approval.",
  "data": null,
  "errors": [
    {
      "code": "NOT_APPROVED",
      "message": "Dashboard is available only after HR approval."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

HTTP status codes

- 200 OK
- 403

cURL

```
curl -s -X GET http://localhost:5000/api/app/leave \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer <accessToken>'
```

Notes

- Standard response envelope: { success, message, data, errors, timestamp }.

Apply Leave

Group: Dashboard

Endpoint	POST /api/app/leave/apply
Method	POST
Authentication	Bearer access token (approved employees only)

Headers

```
Content-Type: application/json
Authorization: Bearer <accessToken>
```

Request body

```
{
  "leaveType": "Casual",
  "fromDate": "2026-07-01",
  "toDate": "2026-07-02",
  "days": 2,
  "reason": "Family function"
}
```

Validation rules

- `leaveType` , `fromDate` , `toDate` are required.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
    "id": 31,
    "status": "Pending"
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

422 VALIDATION_FAILED

```
{
  "success": false,
  "message": "leaveType, fromDate and toDate are required.",
  "data": null,
  "errors": [
    {
      "code": "VALIDATION_FAILED",
      "message": "leaveType, fromDate and toDate are required."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

403 NOT_APPROVED

```
{
  "success": false,
  "message": "Dashboard is available only after HR approval.",
  "data": null,
  "errors": [
    {
      "code": "NOT_APPROVED",
      "message": "Dashboard is available only after HR approval."
    }
  ],
}
```

```
"timestamp": "2026-06-25T12:00:00.000Z"
}
```

HTTP status codes

- 200 OK
- 422
- 403

cURL

```
curl -s -X POST http://localhost:5000/api/app/leave/apply \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer <accessToken>' \
-d '{"leaveType":"Casual","fromDate":"2026-07-01","toDate":"2026-07-02","days":2,"reason":"Family f
```

Notes

- Standard response envelope: { success, message, data, errors, timestamp }.

Payroll

Group: Dashboard

Endpoint	GET /api/app/payroll
Method	GET
Authentication	Bearer access token (approved employees only)

Headers

```
Content-Type: application/json
Authorization: Bearer <accessToken>
```

Request body

None.

Validation rules

- Available only after HR approval.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
```

```

    "payslips": [
      {
        "id": 5,
        "month": "June",
        "year": 2026,
        "basicSalary": 21000,
        "allowances": 15000,
        "deductions": 4000,
        "netSalary": 42000,
        "paymentStatus": "pending",
        "payslipGenerated": false
      }
    ]
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}

```

Error responses

403 NOT_APPROVED

```

{
  "success": false,
  "message": "Dashboard is available only after HR approval.",
  "data": null,
  "errors": [
    {
      "code": "NOT_APPROVED",
      "message": "Dashboard is available only after HR approval."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}

```

HTTP status codes

- 200 OK
- 403

cURL

```

curl -s -X GET http://localhost:5000/api/app/payroll \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer <accessToken>'

```

Notes

- Standard response envelope: { success, message, data, errors, timestamp }.

Notifications

Group: Dashboard

Endpoint	GET /api/app/notifications
Method	GET
Authentication	Bearer access token (approved employees only)

Headers

```
Content-Type: application/json
Authorization: Bearer <accessToken>
```

Request body

None.

Validation rules

- Available only after HR approval.

Success response (200)

```
{
  "success": true,
  "message": "Success",
  "data": {
    "notifications": [
      {
        "id": 9,
        "type": "announcement",
        "title": "Holiday",
        "message": "Office closed on Friday",
        "read": false,
        "timestamp": "2026-06-24 10:00"
      }
    ]
  },
  "errors": [],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

403 NOT_APPROVED

```
{
  "success": false,
  "message": "Dashboard is available only after HR approval.",
  "data": null,
  "errors": [
    {
      "code": "NOT_APPROVED",
      "message": "Dashboard is available only after HR approval."
    }
  ]
}
```

```
],  
  "timestamp": "2026-06-25T12:00:00.000Z"  
}
```

HTTP status codes

- 200 OK
- 403

cURL

```
curl -s -X GET http://localhost:5000/api/app/notifications \  
-H 'Content-Type: application/json' \  
-H 'Authorization: Bearer <accessToken>'
```

Notes

- Standard response envelope: { success, message, data, errors, timestamp }.

Holidays

Group: Dashboard

Endpoint	GET /api/app/holiday
Method	GET
Authentication	Bearer access token (approved employees only)

Headers

```
Content-Type: application/json  
Authorization: Bearer <accessToken>
```

Request body

None.

Validation rules

- Available only after HR approval.

Success response (200)

```
{  
  "success": true,  
  "message": "Success",  
  "data": {  
    "holidays": []  
  }  
}
```

```
},
"errors": [],
"timestamp": "2026-06-25T12:00:00.000Z"
}
```

Error responses

403 NOT_APPROVED

```
{
  "success": false,
  "message": "Dashboard is available only after HR approval.",
  "data": null,
  "errors": [
    {
      "code": "NOT_APPROVED",
      "message": "Dashboard is available only after HR approval."
    }
  ],
  "timestamp": "2026-06-25T12:00:00.000Z"
}
```

HTTP status codes

- 200 OK
- 403

cURL

```
curl -s -X GET http://localhost:5000/api/app/holiday \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer <accessToken>'
```

Notes

- Holiday calendar source is configurable; returns an empty list until configured.