

ENERGY TECH CRANE PVT. LTD.

Product Catalogue

EOT, Gantry & Goliath Cranes and Hoists · 1–125 Ton · IS:3177 / IS:4137 / FEM
1.001

Ahmedabad, Gujarat · ISO 9001:2015 Certified

19 Products · 11 Categories · Pan-India Delivery & Erection

Single Girder EOT Crane

Electric Overhead Travelling crane with a single rolled/box-section main girder — the most economical solution for capacities up to 20 Ton. Designed to IS:3177 & IS:807, load-tested at 125% SWL and delivered pan-India from our Ahmedabad works.

Specification	Value
Capacity	1 – 20 Ton
Span	Up to 45 m
Lift Height	Up to 15 m
Duty Class	Class II (M5)
Hoisting Speed	Normal: 2 – 3 MPM / VVFD: 0.3 – 2.5 MPM through VVFD Drive
CT Speed	Normal: 10 – 12 MPM / VVFD: 1.7 – 12 MPM through VVFD Drive
LT Speed	Normal: 15 – 18 MPM / VVFD: 1.5 – 15 MPM through VVFD Drive
Control	Pendant / Radio Remote / Cabin
Power Feed	DSL Busbar / Festoon cable
Standards	IS:3177 · IS:807 · FEM 1.001

energytechcrane.com · +91 91040 05104 / +91 82008 32843

Double Girder EOT Crane

Electric Overhead Travelling crane with a twin box-girder bridge for heavy capacities up to 100 Ton and demanding duty cycles. Designed to IS:3177 & IS:807, load-tested at 125% SWL and delivered pan-India from our Ahmedabad works.

Specification	Value
Capacity	5 – 125 Ton
Span	Up to 45 m
Lift Height	Up to 30 m
Duty Class	Class II / III / IV (M5–M8)
Hoisting Speed	Normal: 2 – 3 MPM / VVFD: 0.3 – 2.5 MPM through VVFD Drive
CT Speed	Normal: 10 – 12 MPM / VVFD: 1.7 – 12 MPM through VVFD Drive
LT Speed	Normal: 15 – 18 MPM / VVFD: 1.5 – 15 MPM through VVFD Drive
Control	Pendant / Radio Remote / Cabin
Power Feed	DSL Busbar / Festoon cable
Standards	IS:3177 · IS:807 · FEM 1.001

energytechcrane.com · +91 91040 05104 / +91 82008 32843

EOT Crane with Gantry Girder — Single Girder

Complete lifting package: a single-girder EOT crane supplied together with ETC-fabricated gantry girders, columns and rail — perfect when your shed has no crane-ready structure. One vendor, one responsibility, one guarantee.

Specification	Value
Crane Capacity	1 – 20 Ton
Span	Up to 45 m
Gantry Girder	IS:2062 plate, camber to IS:800
Columns	Fabricated / built-up sections
Rail	CR-60 / CR-80 with clamps
Lift Height	Up to 15 m
Hoisting Speed	Normal: 2 – 3 MPM / VVFD: 0.3 – 2.5 MPM through VVFD Drive
CT Speed	Normal: 10 – 12 MPM / VVFD: 1.7 – 12 MPM through VVFD Drive
LT Speed	Normal: 15 – 18 MPM / VVFD: 1.5 – 15 MPM through VVFD Drive
Control	Pendant / Radio Remote
Standards	IS:3177 · IS:800 · IS:807
Erection	Turnkey by ETC team

energytechcrane.com · +91 91040 05104 / +91 82008 32843

EOT Crane with Gantry Girder — Double Girder

Complete lifting package: a double-girder EOT crane supplied together with ETC-fabricated gantry girders, columns and rail — perfect when your shed has no crane-ready structure. One vendor, one responsibility, one guarantee.

Specification	Value
Crane Capacity	5 – 125 Ton
Span	Up to 45 m
Gantry Girder	IS:2062 plate, camber to IS:800
Columns	Fabricated / built-up sections
Rail	CR-60 / CR-80 with clamps
Lift Height	Up to 30 m
Hoisting Speed	Normal: 2 – 3 MPM / VVFD: 0.3 – 2.5 MPM through VVFD Drive
CT Speed	Normal: 10 – 12 MPM / VVFD: 1.7 – 12 MPM through VVFD Drive
LT Speed	Normal: 15 – 18 MPM / VVFD: 1.5 – 15 MPM through VVFD Drive
Control	Pendant / Radio Remote
Standards	IS:3177 · IS:800 · IS:807
Erection	Turnkey by ETC team

EOT Without Main Girder — Single Track

Underslung / monorail-style EOT system where the hoist trolley runs directly on a single runway beam fixed to your roof structure — no main bridge girder needed. The most headroom-efficient lifting solution for light sheds.

Specification	Value
Capacity	1 – 20 Ton
Span	Up to 45 m
Track	Single runway beam
Beam Section	ISMB / rolled I as per load
Lift Height	Up to 15 m
Hoisting Speed	Normal: 2 – 3 MPM / VVFD: 0.3 – 2.5 MPM through VVFD Drive
CT Speed	Normal: 10 – 12 MPM / VVFD: 1.7 – 12 MPM through VVFD Drive
LT Speed	Normal: 15 – 18 MPM / VVFD: 1.5 – 15 MPM through VVFD Drive
Hoist	Wire rope / chain hoist
Travel	Push / geared / motorised
Suspension	Roof truss / ceiling mounted
Control	Pendant push-button
Standards	IS:3832 · IS:800

EOT Without Main Girder — Double Track

Underslung / monorail-style EOT system where the hoist trolley runs directly on twin parallel runway beams fixed to your roof structure — no main bridge girder needed. The most headroom-efficient lifting solution for light sheds.

Specification	Value
Capacity	5 – 125 Ton
Span	Up to 45 m
Track	Twin runway beams
Beam Section	ISMB / rolled I as per load
Lift Height	Up to 30 m
Hoisting Speed	Normal: 2 – 3 MPM / VVFD: 0.3 – 2.5 MPM through VVFD Drive
CT Speed	Normal: 10 – 12 MPM / VVFD: 1.7 – 12 MPM through VVFD Drive
LT Speed	Normal: 15 – 18 MPM / VVFD: 1.5 – 15 MPM through VVFD Drive
Hoist	Wire rope / chain hoist
Travel	Push / geared / motorised
Suspension	Roof truss / ceiling mounted
Control	Pendant push-button
Standards	IS:3832 · IS:800

Single Girder Gantry Crane

A-frame gantry crane travelling on floor-level rails — no building structure needed. Single girder design for economical outdoor and yard duty up to 20 Ton. Built to IS:3177 / IS:807, load-tested at 125% SWL.

Specification	Value
Capacity	1 – 20 Ton
Span	Up to 45 m
Lift Height	Up to 15 m
Hoisting Speed	Normal: 2 – 3 MPM / VVFD: 0.3 – 2.5 MPM through VVFD Drive
CT Speed	Normal: 10 – 12 MPM / VVFD: 1.7 – 12 MPM through VVFD Drive
LT Speed	Normal: 15 – 18 MPM / VVFD: 1.5 – 15 MPM through VVFD Drive
Legs	Fabricated A-frame, braced
Travel	Rail-mounted, geared drives
Cantilever	One / both sides optional
Duty	Outdoor — wind-rated design
Control	Pendant / Radio Remote
Standards	IS:3177 · IS:807 · IS:875 (wind)

Double Girder Gantry Crane

A-frame gantry crane travelling on floor-level rails — no building structure needed. Twin box girders for heavy yard duty up to 80 Ton with full-span hook coverage. Built to IS:3177 / IS:807, load-tested at 125% SWL.

Specification	Value
Capacity	5 – 125 Ton
Span	Up to 45 m
Lift Height	Up to 30 m
Hoisting Speed	Normal: 2 – 3 MPM / VVFD: 0.3 – 2.5 MPM through VVFD Drive
CT Speed	Normal: 10 – 12 MPM / VVFD: 1.7 – 12 MPM through VVFD Drive
LT Speed	Normal: 15 – 18 MPM / VVFD: 1.5 – 15 MPM through VVFD Drive
Legs	Fabricated A-frame, braced
Travel	Rail-mounted, geared drives
Cantilever	One / both sides optional
Duty	Outdoor — wind-rated design
Control	Pendant / Radio Remote
Standards	IS:3177 · IS:807 · IS:875 (wind)

Single Girder Goliath Crane

Heavy-duty rail-mounted Goliath crane with rigid vertical legs for capacities up to 25 Ton — the standard machine for precast yards, shipbuilding blocks and heavy stockyards. IS:3177 design, 125% SWL tested.

Specification	Value
Capacity	1 – 20 Ton
Span	Up to 45 m
Lift Height	Up to 15 m
Hoisting Speed	Normal: 2 – 3 MPM / VVFD: 0.3 – 2.5 MPM through VVFD Drive
CT Speed	Normal: 10 – 12 MPM / VVFD: 1.7 – 12 MPM through VVFD Drive
LT Speed	Normal: 15 – 18 MPM / VVFD: 1.5 – 15 MPM through VVFD Drive
Legs	Rigid box-type, vertical
Long Travel	8-wheel / 16-wheel bogies
Hoist	Crab-mounted winch
Duty Class	Class III / IV (M7–M8)
Control	Cabin + Radio Remote
Standards	IS:3177 · IS:807 · IS:875

Double Girder Goliath Crane

Heavy-duty rail-mounted Goliath crane with rigid vertical legs for capacities up to 100 Ton — the standard machine for precast yards, shipbuilding blocks and heavy stockyards. IS:3177 design, 125% SWL tested.

Specification	Value
Capacity	5 – 125 Ton
Span	Up to 45 m
Lift Height	Up to 30 m
Hoisting Speed	Normal: 2 – 3 MPM / VVFD: 0.3 – 2.5 MPM through VVFD Drive
CT Speed	Normal: 10 – 12 MPM / VVFD: 1.7 – 12 MPM through VVFD Drive
LT Speed	Normal: 15 – 18 MPM / VVFD: 1.5 – 15 MPM through VVFD Drive
Legs	Rigid box-type, vertical
Long Travel	8-wheel / 16-wheel bogies
Hoist	Crab-mounted winch
Duty Class	Class III / IV (M7–M8)
Control	Cabin + Radio Remote
Standards	IS:3177 · IS:807 · IS:875

Single Girder Semi Goliath Crane

Hybrid crane: one end runs on an elevated gantry rail on your building column, the other on a leg travelling on a floor rail. Perfect for extending crane coverage into bays where overhead rails exist on only one side. Up to 15 Ton capacity, IS:3177 design.

Specification	Value
Capacity	1 – 20 Ton
Span	Up to 45 m
Lift Height	Up to 15 m
Hoisting Speed	Normal: 2 – 3 MPM / VVFD: 0.3 – 2.5 MPM through VVFD Drive
CT Speed	Normal: 10 – 12 MPM / VVFD: 1.7 – 12 MPM through VVFD Drive
LT Speed	Normal: 15 – 18 MPM / VVFD: 1.5 – 15 MPM through VVFD Drive
Elevated Side	End carriage on gantry rail
Floor Side	A-frame leg on CR rail
Hoist	WRH
Control	Pendant / Radio Remote
Duty Class	Class II / III
Standards	IS:3177 · IS:807

Double Girder Semi Goliath Crane

Hybrid crane: one end runs on an elevated gantry rail on your building column, the other on a leg travelling on a floor rail. Perfect for extending crane coverage into bays where overhead rails exist on only one side. Up to 40 Ton capacity, IS:3177 design.

Specification	Value
Capacity	5 – 125 Ton
Span	Up to 45 m
Lift Height	Up to 30 m
Hoisting Speed	Normal: 2 – 3 MPM / VVFD: 0.3 – 2.5 MPM through VVFD Drive
CT Speed	Normal: 10 – 12 MPM / VVFD: 1.7 – 12 MPM through VVFD Drive
LT Speed	Normal: 15 – 18 MPM / VVFD: 1.5 – 15 MPM through VVFD Drive
Elevated Side	End carriage on gantry rail
Floor Side	A-frame leg on CR rail
Hoist	Crab winch unit
Control	Pendant / Radio Remote
Duty Class	Class II / III
Standards	IS:3177 · IS:807

Single Girder Circular Crane

Electric crane that travels on a curved rail mounted atop a circular structure — storage tank, clarifier, digester or silo — giving 360° coverage of the vessel below from a fixed centre point, without a straight-line runway. Designed to IS:3177 & IS:807, load-tested at 125% SWL and delivered pan-India from our Ahmedabad works.

Specification	Value
Capacity	1 – 20 Ton
Span	Up to 45 m
Track Diameter	6 – 40 m (matched to structure)
Lift Height	Up to 15 m
Duty Class	Class II (M5)
Hoisting Speed	Normal: 2 – 3 MPM / VVFD: 0.3 – 2.5 MPM through VVFD Drive
Radial (CT) Speed	Normal: 10 – 12 MPM / VVFD: 1.7 – 12 MPM through VVFD Drive
LT Speed	Normal: 15 – 18 MPM / VVFD: 1.5 – 15 MPM through VVFD Drive
Control	Pendant / Radio Remote / Cabin
Power Feed	Curved DSL Busbar / Festoon cable
Standards	IS:3177 · IS:807 · FEM 1.001

Double Girder Circular Crane

Twin box-girder electric crane that travels on a curved rail mounted atop a large circular structure — storage tank, clarifier, digester or silo — for heavy capacities and demanding duty cycles requiring full 360° coverage. Designed to IS:3177 & IS:807, load-tested at 125% SWL and delivered pan-India from our Ahmedabad works.

Specification	Value
Capacity	5 – 125 Ton
Span	Up to 45 m
Track Diameter	10 – 60 m (matched to structure)
Lift Height	Up to 30 m
Duty Class	Class II / III / IV (M5–M8)
Hoisting Speed	Normal: 2 – 3 MPM / VVFD: 0.3 – 2.5 MPM through VVFD Drive
Radial (CT) Speed	Normal: 10 – 12 MPM / VVFD: 1.7 – 12 MPM through VVFD Drive
LT Speed	Normal: 15 – 18 MPM / VVFD: 1.5 – 15 MPM through VVFD Drive
Control	Pendant / Radio Remote / Cabin
Power Feed	Curved DSL Busbar / Festoon cable
Standards	IS:3177 · IS:807 · FEM 1.001

Wire Rope Hoist

Compact electric wire rope hoist to IS:3832 — machined rope drum, grade IWRC rope, fail-safe DC brake and Class II/III duty gearbox. The lifting heart of every ETC single-girder crane, also supplied loose for monorails and existing cranes.

Specification	Value
Capacity	0.5 – 30 Ton
Lift Height	6 / 9 / 12 m (custom up to 30 m)
Rope Reeving	2/1 · 4/1 · 4/2
Hoist Speed	3.5 – 8 m/min (dual speed optional)
CT Speed	20 m/min
Duty Class	Class II / III per IS:3832
Motor	Crane-duty, S4 40% CDF
Brake	DC electromagnetic disc
Standards	IS:3832 · FEM 1.001

Electric Chain Hoist

Light, fast and precise electric chain hoist with grade-80 alloy load chain, slip-clutch overload protection and low-voltage pendant control. Ideal from 250 kg to 10 Ton for assembly lines, machine shops and maintenance bays.

Specification	Value
Capacity	0.25 – 10 Ton
Lift Height	3 / 6 / 9 m (custom available)
Chain	Grade 80 alloy, case hardened
Chain Falls	1 / 2 fall
Hoist Speed	4 – 8 m/min (dual speed optional)
Motor Duty	40% CDF crane duty
Suspension	Hook / lug / trolley
Control Voltage	42 V pendant
Protection	IP-54 (IP-65 optional)

Crab Unit Assembly

Complete cross-travel trolley (crab) for double-girder cranes: fabricated frame, hoisting winch with machined drum, CT drive, and full electricals — assembled, tested and ready to drop onto your bridge rails. 5 to 100 Ton.

Specification	Value
Capacity	5 – 100 Ton
Rail Gauge	1.6 – 3.5 m (as per bridge)
Hoist Speed	1.5 – 8 m/min
CT Speed	15 – 20 m/min
Reeving	4/2 · 8/2 true vertical lift
Drum	Machined, grooved, seamless
Frame	Stress-relieved fabrication
Brakes	Twin hoist brakes optional
Standards	IS:3177 · FEM 1.001

energytechcrane.com · +91 91040 05104 / +91 82008 32843

End Carriage — L-Block

L-Block end carriages with machined block-type wheel housings — the modern, maintenance-friendly standard where wheel assemblies swap out in under an hour. Supplied in pairs with LT drives, buffers and rail sweeps.

Specification	Value
Capacity	Up to 50 Ton
Capacity Range	Up to 50 Ton
Wheel Dia	160 – 400 mm
Wheel Type	Forged EN-8/EN-9, double flanged
Housing	Machined L-block, bolt-on
Drive	SEW-style geared motor / ETC drive
Buffer	Rubber / spring / hydraulic
Span Connection	Machined mating faces
Wheel Change	< 1 hour, no girder lift
Standards	IS:3177 · IS:807

End Carriage — Open Type

Classic open-type fabricated end carriages with through-shaft wheels in plummer blocks — rugged, field-repairable and economical for heavy duty. Supplied in pairs with LT drives, buffers and rail sweeps.

Specification	Value
Capacity	Up to 100 Ton
Capacity Range	Up to 100 Ton
Wheel Dia	250 – 630 mm
Wheel Type	Forged EN-8/EN-9, double flanged
Housing	Fabricated box, plummer blocks
Drive	SEW-style geared motor / ETC drive
Buffer	Rubber / spring / hydraulic
Span Connection	Machined mating faces
Wheel Change	Standard workshop procedure
Standards	IS:3177 · IS:807