$c \to D^0$ fragmentation functions

October 12, 2026

The code has three FF: `BCFY`, `KniehlKramer` and `HymnD`.

1 Variables

The fragmentation fraction z_h is the fraction of the charm quark momentum carried by the D^0,

$$p_{D^0} = z_h \, p_c, \tag{1}$$

where p_{D^0} is the transverse momentum we measure (`pD0`) and p_c the one of the charm quark (`pc`). Every integrand is multiplied by

$$\frac{D(z_h, m_T)}{z_h^2}, \qquad z_h \in [z_{h,\min}, z_{h,\max}] = [0.05,\, 1], \tag{2}$$

and z_h is one of the variables of the Monte Carlo integration (VEGAS). The limits are `z_h_min` and `z_h_max` in `src/setup.cpp`.

The FF is taken at the fragmentation scale

$$m_T = \kappa \sqrt{p_{D^0}^2 + m_c^2}, \qquad \kappa = \texttt{SCALE_FACTOR}\ (\text{default } 1), \tag{3}$$

with $m_c = 1.5$ GeV. The scale cannot be below m_c: if it is, the code uses $m_T = m_c$. The scale variation uses $\kappa = 0.5$ and 2.

2 How the FF gets into the calculation

The three FFs are tables in the LHAPDF format (`lhagrid1`), on a grid in z_h and m_T. They are read by the same function, `MakeLHAPDFGridInterpolator(file, flavor, m_T)` in `src/lhapdf_grid.cpp`:

1. it takes the column of the charm quark (PDG id 4),
2. it interpolates linearly in m_T between the two closest grid values. If m_T is outside the grid, it uses the closest grid value,
3. the table has $z_h \, D(z_h, m_T)$, so it divides by z_h,
4. it gives back an `Interpolator` for $D(z_h)$ at this m_T.

This is done once per run in `src/setup.cpp`, because m_T depends only on p_{D^0}. The result is stored in `param.D_frag_interp`. In `src/integrands.cpp` all the integrands end with the same line:

```
return kernel * fragmentation(z_h, par);      // D(z_h) / z_h^2
```

Then, the FF can be changed without modifying the integrands.

3 The fragmentation functions in this code

3.1 BCFY (Braaten–Cheung–Fleming–Yuan)

File `input/BCFY_EKO/bcfy_eko_0000.dat`. At the lowest scale, $m_T = 1.5$ GeV, it is the BCFY function, and it is evolved to higher scales with DGLAP (EKO). The grid has 200 points in z_h from 0.05 to 1 and 30 points in m_T from 1.5 to 50 GeV.

At this scale it is the sum of the part for the D^0 produced directly and the part for $D^{*0} \to D^0$, with the formulae of Braaten, Cheung, Fleming and Yuan, Phys. Rev. D **51** (1995) 4819 (arXiv:hep-ph/9409316). The parameter is $r = 0.1$ and the weights of the two parts are 0.168 and 0.39. Each of the two parts is normalized to one before it is multiplied by its weight, as in Cacciari and Nason, JHEP **09** (2003) 006, so that $\int_0^1 dz_h \, D(z_h) = 0.168 + 0.39 = 0.558$.

3.2 Kniehl–Kramer

File `input/KK_EKO/kk_eko_0000.dat`, with the same grid and the same evolution as BCFY. At $m_T = 1.5\,\text{GeV}$ it is the function of Kniehl and Kramer, Phys. Rev. D **74** (2006) 037502 (arXiv:hep-ph/0607306), with $N = 0.694$ and $\epsilon = 0.101$.

3.3 HymnD

File `input/HymnD/prompt-D0-1-109_0000.dat`, the central member of the set of Epele, Hekhorn, Helenius, Paukkunen and Zurita, "Towards new D meson fragmentation functions" (arXiv:2609.10327). The set has 100 more members (replicas), which give the uncertainty band of the FF: `run_scripts/run_members.sh` with `MEMBER_SET=HymnD` runs the calculation once per member. All members are in `input/HymnD/` as `prompt-D0-1-109_NNNN.dat`.

4 How to choose the FF

The FF is the fourth argument of the programs,

```
./build/bin/D0 <dipole_file> <pD0> <y> <BCFY|KniehlKramer|HymnD> <channel>
```

and in the workflows it is chosen with environment variables (the defaults are in `run_scripts/config.sh`):

Variable	Default	
`FRAG_TYPE`	`HymnD`	FF of one workflow script
`SCALE_FACTOR`	`1.0`	κ of the fragmentation scale
`SCALE_FACTORS`	`0.5 2.0`	values of κ in `run_scale_variation.sh`
`HYMND_FILE`	central member	file of `HymnD`
`BCFY_EKO_FILE`	`input/BCFY_EKO/bcfy_eko_0000.dat`	file of `BCFY`
`KK_EKO_FILE`	`input/KK_EKO/kk_eko_0000.dat`	file of `KniehlKramer`

For example:

```
CHANNEL=0n0n FRAG_TYPE=BCFY ./run_scripts/run_nucleus.sh
```

The results go to a folder with the name of the FF, `output/<CHANNEL>/central_values/<FRAG>/`.

5 How to add another FF

5.1 A table in the LHAPDF format

Example:

```
HYMND_FILE=path/to/my_ff_0000.dat FRAG_TYPE=HymnD ./run_scripts/run_nucleus.sh
```

To add it with its own name:

1. Add the name to `enum class FragmentationType` in `src/def.hpp`.
2. In `src/setup.cpp`, add the name where `frag_tag` is read, and a line where the FF is built:

   ```
   d_frag_interp = MakeLHAPDFGridInterpolator("input/MyFF/my_ff_0000.dat",
                                              4, frag_scale);
   ```

3. If you want it in the plots of `plotting_scripts/pPb_bins.py` and `PbPb_bins.py`, add it to `FRAG_SCHEMES` in `pPb_bins.py`.

The file must have this form (the lines before the first `--` are not read):

```
---
z_h values (one line)
m_T values in GeV (one line)
flavors (one line, it must contain 4)
z_h*D for every flavor, one line per (z_h, m_T): first all m_T for the first z_h, ...
---
```

5.2 A formula

If the FF is a formula and does not depend on the scale, no file is needed. Write a function like `MakeKniehlKramerInterpolator()` that fills two vectors and gives back the interpolator:

```
std::vector<double> z_h_vals(n), dvals(n);
for (int i = 0; i < n; i++) {
    z_h_vals[i] = 0.05 + (1.0 - 0.05) * i / (n - 1.0);
    dvals[i]    = my_D(z_h_vals[i]);
}
return std::unique_ptr<Interpolator>(new Interpolator(z_h_vals, dvals));
```

and then follow the steps above.

Careful

- The interpolator must give $D(z_h)$. LHAPDF tables have $z_h D$, and `MakeLHAPDFGridInterpolator()` already divides by z_h.
- The grid must cover z_h from 0.05 to 1 and m_T from $m_c = 1.5$ GeV to about 24 GeV. Below the grid the code uses the lowest value of m_T, above it the highest.