GOMS/KLM PROCESS (Hiruna)

GOMS Process:

1. Goal - User selecting a dog
2. Operators :
    - K
    - P
    - P_1
    - H
    - M
    - R
3. Method 1 - Browse through the website to select
4. Method 2 - Filter the listing to selective dog breeds, color, age and select
5. Selection rules –

    - If the user is already signed in, just entering the URL for an admin sends you to the dashboard directly and not the homepage, as it avoids unnecessary steps and is faster.
    - If the user is not signed in. The user must sign in with the button at the top right of the home page, as access to messaging requires authentication.
    - After reading the selected dog description the user finalizes his preference if YES he presses the appointment form
    - If he does not like the dog after reading he navigates back to the dog listings

KLM Process:

Assume that user is already in the homepage of the website

Operators –

- K - keystroke (0.28s)
- P - Moving the mouse (1.10s)
- P_1 – Clicking the mouse (0.20s)
- H - Hand movement between mouse/keyboard (0.4)
- M - Mentally Preparing (1.35s)
- R - System Response (1.0s assumed)

Method 1 :

- Mentally prepare to browse - M
- Move mouse to listing page - P
- Click listing page - P1

- Page Load - R
- Scroll through listings - K
- Mentally Scan through dogs - M
- Move mouse near a dog - P
- Click the dog - P1
- Wait for it to load - R
- Mentally review dog information - M
- Move mouse to appointment button - P
- Click it - P1

Total Time – 10.23 seconds

Method 2 :

- Mentally decide dog preference - M
- Move mouse near filter - P
- Click it - P1
- Select Filters - K
- Wait for results - R
- Move mouse to dog - P
- Click it - P1
- Wait for load - R
- Read details - M
- Move mouse to appointment button - P
- Click it - P1

Total Time – 8.88 seconds

Best Method – Method 2 (less time)

Conclusion - Based on the KLM calculations, Method 2 is the faster approach, with a total completion time of 8.88 seconds compared to 10.23 seconds for Method 1. This suggests that using search and filtering functions improves efficiency when selecting a dog, particularly when the user already knows their preferred criteria and browsing without filters takes up a lot of time in scrolling .