

# TFYA17 Project

Transmission properties in a short biased quantum wire

Patrik Hallsjö, Felix Faber

1 Introduction

2 Theory

3 Results

4 Conclusion

# Table of Contents

1 Introduction

2 Theory

3 Results

4 Conclusion

# Introduction

- This project was dedicated to study an electron transport in a biased quantum wire.
- The goals were to construct a solver for the potential and to calculate the transmission and reflection coefficients for an electron sent towards the potential.

The potential used in this presentation:

$$V(x) = \beta V_{sd} + V_g \tanh(s(x - \Delta x_1)) \\ - (V_{sd} + V_g) \tanh(s(x - \Delta x_2))$$

## Remark

- $\beta$  = Potential drop, if 0.5 then symmetric as in our case.
- $V_{sd}$  = Bias voltage.
- $V_g$  = Potential height
- $S$  = Potential steepness.

# Goals

- To set and to solve a problem with boundary conditions when an electron is injected into a wire.

# Goals

- To set and to solve a problem with boundary conditions when an electron is injected into a wire.
- To calculate the transmission and reflection coefficients as functions of energy of injected electron and bias.

# Goals

- To set and to solve a problem with boundary conditions when an electron is injected into a wire.
- To calculate the transmission and reflection coefficients as functions of energy of injected electron and bias.
- To represent solutions in graphical form.



# Goals

- To set and to solve a problem with boundary conditions when an electron is injected into a wire.
- To calculate the transmission and reflection coefficients as functions of energy of injected electron and bias.
- To represent solutions in graphical form.
- Optional: to calculate a conductance.

# Goals

- To set and to solve a problem with boundary conditions when an electron is injected into a wire.
- To calculate the transmission and reflection coefficients as functions of energy of injected electron and bias.
- To represent solutions in graphical form.
- Optional: to calculate a conductance.

## Remark

Matlab was used to achieve the goals.

# Table of Contents

1 Introduction

2 Theory

3 Results

4 Conclusion

# Finite derivatives

- $f'(x) = \frac{f(x+h)-f(x+k)}{h-k}$

# Finite derivatives

- $f'(x) = \frac{f(x+h)-f(x+k)}{h-k}$
- Forward:  $\frac{f(x+h)-f(x)}{h}$

# Finite derivatives

- $f'(x) = \frac{f(x+h)-f(x+k)}{h-k}$
- Forward:  $\frac{f(x+h)-f(x)}{h}$
- Backward:  $\frac{f(x)-f(x-k)}{k}$

# Finite derivatives

- $f'(x) = \frac{f(x+h)-f(x+k)}{h-k}$
- Forward:  $\frac{f(x+h)-f(x)}{h}$
- Backward:  $\frac{f(x)-f(x-k)}{k}$
- Central:  $\frac{f(x-h/2)-f(x+h/2)}{h}$

# Finite derivatives

- $f'(x) = \frac{f(x+h)-f(x+k)}{h-k}$
- Forward:  $\frac{f(x+h)-f(x)}{h}$
- Backward:  $\frac{f(x)-f(x-k)}{k}$
- Central:  $\frac{f(x-h/2)-f(x+h/2)}{h}$
- Second order:  $\frac{f(x-h)-2f(x)+f(x+h)}{h^2}$



# Finite steps in differential equations

Solve the stationary Schrödinger equation which is a second order differential equation:

# Finite steps in differential equations

Solve the stationary Schrödinger equation which is a second order differential equation:  $E\psi(x) = \left(\frac{-\hbar^2}{2m^*} \frac{\partial^2}{\partial x^2} + V(x)\right)\psi(x)$

# Finite steps in differential equations

Solve the stationary Schrödinger equation which is a second order differential equation:  $E\psi(x) = (\frac{-\hbar^2}{2m^*} \frac{\partial}{\partial x} + V(x))\psi(x)$

- Second order differential equation without any first order terms  $y''(x) = g(y(x), x)$

# Finite steps in differential equations

Solve the stationary Schrödinger equation which is a second order differential equation:  $E\psi(x) = (\frac{-\hbar^2}{2m^*} \frac{\partial}{\partial x} + V(x))\psi(x)$

- Second order differential equation without any first order terms  $y''(x) = g(y(x), x)$
- Boundary conditions:  $y(x_0) = y_0$  and  $y(x_N) = y_N$ , on the interval  $[x_0, x_N]$  where  $d = (\frac{x_0 - x_N}{N})$ .

# Finite steps in differential equations

Solve the stationary Schrödinger equation which is a second order differential equation:  $E\psi(x) = (\frac{-\hbar^2}{2m^*} \frac{\partial}{\partial x} + V(x))\psi(x)$

- Second order differential equation without any first order terms  $y''(x) = g(y(x), x)$
- Boundary conditions:  $y(x_0) = y_0$  and  $y(x_N) = y_N$ , on the interval  $[x_0, x_N]$  where  $d = (\frac{x_0 - x_N}{N})$ .
- $h = d$  and  $x = nd$  yields  $dg(y(nd), nd) + 2y(nd) - (y((n+1)d) + y((n-1)d)) = 0$ .
- $N + 1$  equations with  $N + 1$  unknowns.

# Quantum barrier problem

Solve the stationary Schrödinger equation. With

$$k = \sqrt{\frac{2m^*}{\hbar^2}(E - \beta eV_{Sd})} \text{ and } k' = \sqrt{\frac{2m^*}{\hbar^2}(E + (1 - \beta)eV_{Sd})}$$

# Quantum barrier problem

Solve the stationary Schrödinger equation. With

$$k = \sqrt{\frac{2m^*}{\hbar^2}(E - \beta eV_{sd})} \text{ and } k' = \sqrt{\frac{2m^*}{\hbar^2}(E + (1 - \beta)eV_{sd})}$$

- Boundary conditions:  $y_0 = I \exp(-ikx_0) + r \exp(ikx_0)$  and  $y_N = t \exp(-ik'x_N)$

# Quantum barrier problem

Solve the stationary Schrödinger equation. With

$$k = \sqrt{\frac{2m^*}{\hbar^2}(E - \beta eV_{sd})} \text{ and } k' = \sqrt{\frac{2m^*}{\hbar^2}(E + (1 - \beta)eV_{sd})}$$

- Boundary conditions:  $y_0 = I \exp(-ikx_0) + r \exp(ikx_0)$  and  $y_N = t \exp(-ik'x_N)$
- We have put  $I = 1$ , which gives  $y_0 = \exp(-ikx_0) + r \exp(ikx_0)$  to make the equations easier to solve.



# Quantum barrier problem

Solve the stationary Schrödinger equation. With

$$k = \sqrt{\frac{2m^*}{\hbar^2}(E - \beta eV_{sd})} \text{ and } k' = \sqrt{\frac{2m^*}{\hbar^2}(E + (1 - \beta)eV_{sd})}$$

- Boundary conditions:  $y_0 = l \exp(-ikx_0) + r \exp(ikx_0)$  and  $y_N = t \exp(-ik'x_N)$
- We have put  $l = 1$ , which gives  $y_0 = \exp(-ikx_0) + r \exp(ikx_0)$  to make the equations easier to solve.
- $R$  and  $T$  give  $N + 3$  unknowns but only  $N + 1$  equations.

# Quantum barrier problem

Solve the stationary Schrödinger equation. With

$$k = \sqrt{\frac{2m^*}{\hbar^2}(E - \beta eV_{sd})} \text{ and } k' = \sqrt{\frac{2m^*}{\hbar^2}(E + (1 - \beta)eV_{sd})}$$

- Boundary conditions:  $y_0 = l \exp(-ikx_0) + r \exp(ikx_0)$  and  $y_N = t \exp(-ik'x_N)$
- We have put  $l = 1$ , which gives  $y_0 = \exp(-ikx_0) + r \exp(ikx_0)$  to make the equations easier to solve.
- $R$  and  $T$  give  $N + 3$  unknowns but only  $N + 1$  equations.
- Continuous at boundaries yielding:  $N + 3$  unknowns and  $N + 3$  equations which will have a unique solution.

# Table of Contents

1 Introduction

2 Theory

**3 Results**

4 Conclusion

## Numerical values


The program produces the following data, as well as images of the wave-functions and the potential barriers.

$$R = |r|^2 / (|r|^2 + |t|^2)$$


$$T = |t|^2 / (|r|^2 + |t|^2)$$

$$C \propto T / (R + T)$$


**Figure:** Amplitudes of wave-functions (upper graph) and potential barriers (lower graph) for the case:  $E=1$ ,  $\beta = 0.5$ ,  $x_1 = 4$ ,  $x_2 = 6$ ,  $V_{sd} = 0.3$ ,  $V_g = 0.6$



**Figure:** Amplitudes of wave-functions (upper graph) and potential barriers (lower graph) for the case:  $E=1$ ,  $\beta = 0.5$ ,  $x_1 = 4$ ,  $x_2 = 6$ ,  $V_{sd} = 0.6$ ,  $V_g = 0.3$



**Figure:** Amplitudes of wave-functions (upper graph) and potential barriers (lower graph) for the case:  $E=1.5$ ,  $\beta = 0.5$ ,  $x_1 = 4$ ,  $x_2 = 6$ ,  $V_{sd} = V_g = 0.3$



# Table of Contents

1 Introduction

2 Theory

3 Results

**4 Conclusion**



Something.