

SHETH L.U.J & M V COLLEGE

PRACTICAL NO 2 MOD 2

The screenshot displays the RStudio interface with the following components:

- Source Editor:** Contains R code for reading a CSV file and calculating city counts.
- Environment:** Lists objects in the global environment, including `city_df` (3 obs. of 2 variables).
- Files:** Shows a list of files in the current directory, including `medical_cost_prediction_dataset.csv` (392.7 KB).
- Console:** Displays the output of the R code, showing the column specification and the frequency table for city types.

```
1 library(dplyr)
2 df <- read.csv("medical_cost_prediction_dataset.csv")
3
4 print("---- Frequency Table: City Type ----")
5 city_counts <- table(df$city_type)
6 print(city_counts)
7
8 city_df <- df %>% count(city_type)
9 print(city_df)
```

Console Output:

```
> library(readr)
> medical_cost_prediction_dataset <- read_csv("medical_cost_prediction_dataset.csv")
Rows: 5000 Columns: 20
— Column specification —
chr  (5): gender, smoker, physical_activity_level, insurance_type, city_type
dbl  (15): age, bmi, diabetes, hypertension, heart_disease, asthma, daily_steps, sl...

i Use `spec()` to retrieve the full column specification for this data.
i Specify the column types or set `show_col_types = FALSE` to quiet this message.
> View(medical_cost_prediction_dataset)
> library(dplyr)
> df <- read_csv("medical_cost_prediction_dataset.csv")
> print("---- Frequency Table: City Type ----")
[1] "---- Frequency Table: City Type ----"
> city_counts <- table(df$city_type)
> print(city_counts)

      Rural Semi-Urban      Urban
      1023      1503      2474

> city_df <- df %>% count(city_type)
> print(city_df)
  city_type      n
1   Rural 1023
2 Semi-Urban 1503
3     Urban 2474
```