


SunilOS



Angular 8

www.sunilos.com
www.raystec.com



9/21/2019

Copyright (c) SunilOS (Rays)

1

1

SunilOS

Contents

☐ Introduction & Overview

☐ MVC Architecture

☐ Installation and Configuration

☐ Getting Started

☐ Variable and Operators

☐ Control Statements

☐ Directives

☐ Module

☐ Component

☐ Pipe

☐ Services

☐ Router

☐ Http Client

☐ Forms

9/21/2019

Copyright (c) SunilOS (Rays)

2

2

SunilOS

What is ANGULAR

☐ Angular is a JavaScript Framework

☐ Angular is used to build client-side applications using HTML

☐ Angular bootstraps JavaScript with HTML tags.

☐ Angular is used to make reach UI application.

☐ Angular enhances UI experience for User.

☐ Angular code is written in TypeScript language

- TypeScript is compiled into JavaScript
- JavaScript is used in HTML pages

Type Script

compile

JavaScript

use

HTML

9/21/2019

Copyright (c) SunilOS (Rays)


3

3


SunilOS

Angular enhances HTML

☐ Angular has set of directives to display dynamic contents at HTML page. Angular extends HTML node capabilities for a web application.



☐ Angular provides data binding and dependency injection that reduces line of code.



☐ Angular extends HTML attributes with Directives, and binds data to HTML with Expressions.

☐ Angular follows MVC Architecture

9/21/2019

Copyright (c) SunilOS (Rays)

4

4

SunilOS

Angular – REST Web Services

☐ Angular communicates with RESTful web services in modern applications

☐ RESTful Web Services are accessed by HTTP call

☐ RESTful Web Services exchange JSON data

Angular

HTTP

Web Services

JSON

9/21/2019

Copyright (c) SunilOS (Rays)

5

5

SunilOS

Angular Application

☐ An application is a Module

☐ Module contains components

☐ Component uses Services

☐ Services contains data and reusable business methods

☐ Basic building block of Angular is Component

☐ It is said that Angular follows Component/Service architecture. Internally it follows MVC Architecture

9/21/2019

Copyright (c) SunilOS (Rays)

6

6

Angular Application (Contd.)

- An Application is a Module
- Modules are reusable
- One Module's components and services can be used by another module

9/21/2019 Copyright (c) SunilOS (Rays) 7

7

MVC Architecture

9/21/2019 Copyright (c) SunilOS (Rays) 8

8

MVC Architecture

- View:**
contains display logics, developed using HTML and Angular Directives
- Controller:**
Contains navigation logic.
Decides data and view to be displayed
- Model:**
Carry data between View and Controller

9/21/2019 Copyright (c) SunilOS (Rays) 9

9

Installation and Configuration

9/21/2019 Copyright (c) SunilOS (Rays) 10

10

Install Node

- Node.js development environment can be setup in Windows, Mac, Linux and Solaris.
- Following development environment and editor are required to develop a node application:
 - Node.js
 - Node Package Manager (NPM)
 - IDE (Integrated Development Environment) or TextEditor
- Download installer and editor from
 - <https://nodejs.org>: install node and npm
 - <https://code.visualstudio.com>: Visual Studio Code
- You can check npm version by following command
 - `npm -v`

9/21/2019 Copyright (c) SunilOS (Rays) 11

11

Install Angular CLI

- You can run following command to install Angular CLI.
- `npm install @angular/cli -g`
- After installation you can check version of Angular by running the following command:
 - `ng -version`
- CLI stand for Command Line Interface

9/21/2019 Copyright (c) SunilOS (Rays) 12

12

Angular Project

SunilOS

Angular provides CLI command to generate project template

THEProject

9/21/2019

Copyright (c) SunilOS (Rays)

13

13

Create Project

SunilOS

Angular project is created using command:

- ng new project-name

We are assuming project name is SOS

- ng new SOS
- Above command will create project directory structure. Default component and configuration files is generated inside c:/SOS folder.

Inside c:/SOS folder it will create following subfolders

- c:/SOS/e2e
- c:/SOS/node_modules
- c:/SOS/src/app

All components will be created in c:/sos/src/app folder

9/21/2019

Copyright (c) SunilOS (Rays)

14

14


Run the project

SunilOS

Run following command to run angular project

- c:/SOS>ng serve -o

It will start angular server at default port number #4200 and make application accessible using <http://localhost:4200>



9/21/2019


Copyright (c) SunilOS (Rays)

15

15

Project flow

SunilOS



9/21/2019

Copyright (c) SunilOS (Rays)

16

16

Project Key components

SunilOS

File app.module.ts contains configuration of the application.

File app-routing.module.ts contains url mapping of components. Components are accessed by their mapped urls.

File app.component.ts contains definition of Root-Component

File index.html is first page of application. It bootstraps root component.

For new UI screens new components are created called sub components.

9/21/2019


Copyright (c) SunilOS (Rays)

17

17

Getting Started

SunilOS



9/21/2019

Copyright (c) SunilOS (Rays)

18

18

19

20

21

22

23

24

Login controller

SunilOS

File login.component.ts

export class LoginComponent implements OnInit {

userId = 'Enter User ID';

password = '';

message = '';

constructor(private router: Router) {}

signIn() {

if(this.userId == 'admin'

&& this.password == 'admin'){

this.router.navigateByUrl('/welcome');

}else{

this.message = 'Invalid login id or password';

}

}

}

Router is injected

Navigate to Welcome page

9/21/2019

Copyright (c) SunilOS (Rays)

25

25

Login View

SunilOS

<H1>Login</H1>

<p style="color:red" >{{message}}</p>

<form >

User ID: <input [(ngModel)]= "userId" name="userid" type="text">

Password: <input [(ngModel)]= "password" name="password" type="password">

<button (click)="signIn()">Sign In</button>

</form>

Directive [(ngModel)] is used for two-way data binding with attributes userId and password of class LoginComponent.

Directive (click) is used to bind on-click event. Method signIn() is called when Sign-In button is clicked.

Directive ngModel is provided by inbuilt FormsModule module. This module will be imported in app.module.ts.

URL : <http://localhost:4200/login>

9/21/2019

Copyright (c) SunilOS (Rays)

26

26

Angular Module

SunilOS

Application is Module

A module can be reused in other applications

Module key elements are:

Components for view and controller

Directives for databinding

Pipes for formatting

Services for reusable operations.

One module can use another module like FormModule and RouteModule

Diagram showing three modules connected in a network.

9/21/2019

Copyright (c) SunilOS (Rays)

27

27

Module execution flow

SunilOS

Application executes main.ts file.

File main.ts configure app using app.module.ts file

File app.module.ts defines application module

Application displays index.html file.

File index.html bootstraps root component from app.component.ts

Diagram showing the flow: run -> main.ts -> configure -> app.module.ts -> bootstrap -> app.component.ts -> template -> app.component.html -> render -> Index.html <app-root>

9/21/2019

Copyright (c) SunilOS (Rays)

28

28

index.html

SunilOS

src/index.html: This the first file which executes alongside main.ts when the page loads.

<html lang="en">

<head>

<base href="/">

</head>

<body>

<app-root></app-root>

</body>

</html>

Diagram showing the nesting: index.html <app-root> contains app.component.html <router-outlet> which contains login.component.html

9/21/2019

Copyright (c) SunilOS (Rays)

29

29

app.module.ts

SunilOS

It defines module using @NgModule decorator (annotation).

It contains mappings of application elements; component, service, pipe etc. and other modules like ngRoute and FormModule.

This file location in project is src/app/app.module.ts.

9/21/2019

Copyright (c) SunilOS (Rays)

30

30

app.module.ts

SunilOS

```
import { FormsModule } from '@angular/forms';
import { AppRoutingModule } from './app-routing.module';
@NgModule({
  declarations: [
    AppComponent,
    LoginComponent,
    WelcomeComponent
  ],
  imports: [
    AppRoutingModule,
    FormsModule,
  ],
  providers: [
    UserService,
    MarksheetService,
  ],
  bootstrap: [AppComponent]
})
export class AppModule { }
```

Component

Modules

Services

Root Component

Module Class

9/21/2019

Copyright (c) SunilOS (Rays)

31

Components

SunilOS

- One component is created for one View page.
- You can generate component using following command:
 - ng g c Login
 - ng g c Welcome
- Component contains 4 files:
 - Controller .TS
 - View .HTML
 - Look & Feel .CSS
 - Unit Testcase
- Components are configured into app.module.ts file

Login

Root

Welcome

Dashboard

9/21/2019

Copyright (c) SunilOS (Rays)

32

Component (Contd.)

SunilOS

@Component

Root Component

Sub-Components

Routing Module

app.component.ts <class>

app.component.html <router-outlet> <html>

app-routing.module.ts <define routes>

Login Component

Welcome Component

Marksheet Component

data binding

url

9/21/2019

Copyright (c) SunilOS (Rays)

33

Root Component

SunilOS

- Application has one root-component app.component.ts
- Root component is bootstrapped with index.html
- Html template of root-component app.component.html has <router-outlet> tag.
- Tag <router-outlet> is replaced by sub-components at runtime.
- Tag <router-outlet> implements SPA

9/21/2019

Copyright (c) SunilOS (Rays)

34

app.component.ts controller

SunilOS

Metadata @Component is used to define component

```
import { Component } from '@angular/core';

@Component({
  selector: 'app-root',
  templateUrl: './app.component.html',
  //template: ` <div>{{title}}</div>`
})

export class AppComponent {
  title:string = 'SunilOS';
}
```

Import component

Metadata

View html

Template

Class

Attribute

9/21/2019


Copyright (c) SunilOS (Rays)

35

app.component.html View

SunilOS

- <div>
- <router-outlet></router-outlet>
- </div>
- <H4>Copyright (c) {{title}}</H4>



9/21/2019

Copyright (c) SunilOS (Rays)

36

Create sub-component- Login

SunilOS

File login.component.ts

export class LoginComponent implements OnInit {

userId = 'Enter User ID';

password = '';

message = '';

constructor(private router: Router) {}

signIn() {

if(this.userId == 'admin'

&& this.password == 'admin'){

this.router.navigateByUrl('/welcome');

}else{

this.message = 'Invalid login id or password';

}

}

}

Router is injected

Navigate to Welcome page

9/21/2019

Copyright (c) SunilOS (Rays)

37

37

Login View

SunilOS

<H1>Login</H1>

<p style="color:red">{{message}}</p>

<form >

User ID: <input [(ngModel)]='userId' name='userid' type='text">

Password: <input [(ngModel)]='password' name='password' type='password">

<button (click)="signIn()">Sign In</button>

</form>

Directive [(ngModel)] is used for two-way data binding with attributes userId and password of class LoginComponent.

Directive (click) is used to bind on-click event. Method signIn() is called when Sign-In button is clicked.

Directive ngModel is provided by inbuilt FormsModule module. This module will be imported in app.module.ts.

URL :http://localhost:4200/login

9/21/2019

Copyright (c) SunilOS (Rays)

38

38

Define Login-route

SunilOS

In order to access pages, define routes in app-routing.module.ts

const routes: Routes = [

{ path: 'login', component: LoginComponent},

{ path: 'welcome', component: WelcomeComponent}

];

@NgModule({

imports: [RouterModule.forRoot(routes)]

exports: [RouterModule]

})

Access pages using following URLs

http://localhost:4200/login

9/21/2019

Copyright (c) SunilOS (Rays)

39

39

Define variable

SunilOS

Optional keyword let is used to define a variable

let name = "ram" ;

let price = 100.10;

Optionally you can define data type of a variable. Data type is followed by variable name and separated by colon (:) character

let name:string = "ram" ;

let price:number = 100.10;

let flag:Boolean = true;

Just like JavaScript you can alternately use var keyword to define a variable.

var name = "ram" ;

var price = 100.10;

9/21/2019

Copyright (c) SunilOS (Rays)

40

40

Scope of class attributes

SunilOS

An instance/static variable, defined in a class, is called attribute or member variable

Scope of a variable can be public or private. Default scope is public

export class LoginComponent implements OnInit {

public userId:string = 'Enter User ID';

private password:string = '';

message:string = 'No message';

..

}

Attributes are called inside methods using this keyword.

9/21/2019

Copyright (c) SunilOS (Rays)

41

41

Define Mehods

SunilOS

An instance/static method can be defined in a class.

Scope of a method can be public or private. Default scope is public

Here is example signin() method of login components:

signin() {

if(this.userId == 'admin'

&& this.password == 'admin'){

this.router.navigateByUrl('/welcome');

}else{

this.message = 'Invalid login id or password';

}

}

}

9/21/2019

Copyright (c) SunilOS (Rays)

42

42

SunilOS

Static attributes and methods

❑ Keyword `static` is used to defined attributes and methods

○ `static` `PI:number = 3.14;`

❑ Memory is assigned only one its lifetime

❑ `static` `max(a:number, b:number){`

❑ `if(a> b){ return a; }`

❑ `else{ return b }`

❑ `}`

❑ Static methods are defined to use static attributes and can called with class name.

9/21/2019

Copyright (c) SunilOS (Rays)

43

43

SunilOS

Constants

❑ Constant variable is defined using `const` keyword

❑ `const` `PI:number = 3.14;`

9/21/2019

Copyright (c) SunilOS (Rays)

44

44

SunilOS

Constructor

❑ Class has only one constructor

❑ It is called at the time of class instantiation

❑ Services are injected in controller using constructor arguments:

❑ `export class LoginComponent implements OnInit {`

❑ `constructor(private router: Router) {`

❑ `}`

❑ `}`

❑ You can pass one or more arguments to constructor

9/21/2019

Copyright (c) SunilOS (Rays)

45

45

SunilOS

Class and Interface

❑ Angular uses Typescripts

❑ TypeScript is Object Oriented

❑ TS provides inheritance of *classes* and implementation of *Interfaces*

❑ A class can inherit another class using `extends` keyword

❑ Interface has abstract methods

❑ One class may implement multiple interfaces using `implements` keyword.

9/21/2019

Copyright (c) SunilOS (Rays)

46

46

SunilOS

OnInit interface

❑ A component must have to implement `OnInit` interface

❑ `export class LoginComponent implements OnInit {`

❑ `ngOnInit() { .. }`

❑ `}`

❑ Interface `OnInit` has one abstract method `ngOnInit()`

❑ This method is called after component instantiation

❑ You may write code inside this method to initialize your component

9/21/2019

Copyright (c) SunilOS (Rays)

47

47

SunilOS

Control Statements

❑ `if-else`

❑ `for` loop

❑ `while` loop

❑ `do-while` loop

9/21/2019

Copyright (c) SunilOS (Rays)

48

48

Copyright (c) Rays Technologies

8

if-else Statement

SunilOS

You can perform conditional operation using if-then-else statement.

```
var money = 100;
if ( money> 100 ){
  console.log('Wow! I can buy Pizza');
} else {
  console.log('Oh! I can not buy Pizza');
}
```

9/21/2019

Copyright (c) SunilOS (Rays)

49

49

For loop

SunilOS

var table = [2,4,6,8,10];

```
for (i=0; i<table.length; i++) {
  console.log('table['+i+']: ' + table[i]);
}
```

For in loop

```
for (i in table){
  console.log('table['+i+']: ' + table[i]);
}
```

9/21/2019

Copyright (c) SunilOS (Rays)

50

50

While Loop

SunilOS

var table = [2,4,6,8,10], var i=0;

```
while(i<table.length){
  console.log('table['+i+']: ' + table[i]);
  i++;
}
```

```
do{
  console.log('table['+i+']: ' + table[i]);
  i++;
}while(i<table.length)
```

9/21/2019

Copyright (c) SunilOS (Rays)

51

51

Switch Statement

SunilOS

var day = 1;

```
switch (day) {
  case 0:
    alert("Sunday");
    break;
  case 1:
    alert("Monday");
    break;
  ...
  default:
    alert("This day is yet to come, pl wait!!");
}
```

9/21/2019

Copyright (c) SunilOS (Rays)


52

52

Exception Handling

SunilOS


throw



- Exception cause abnormal termination of program or wrong execution result.
- JavaScript provides an exception handling mechanism to handle exceptions.

- Exception handling is managed by
 - try, catch, finally and throw keywords.
- Exception handling is done by try-catch-finally block.
- Exception raised in try block is caught by catch block.
- Block finally is optional and always executed.

catch



9/21/2019

Copyright (c) SunilOS (Rays)

53

53

try-catch-finally Statement

SunilOS

```
try {
  //contains normal flow of program that may raise an exception.
} catch (err) {
  //executes alternate flow of program. Receives err object.
} finally {
  //cleanup statements, this block is optional.
}
```

```
throw is used to raise an custom exception with an error message:
throw "Error message";
```

9/21/2019

Copyright (c) SunilOS (Rays)

54

54

Flow of execution

SunilOS

- try {
 - a
 - b //Throw Exception
 - c
- } catch (Exception e) {
- finally {

- Normal Flow
 - a b c f
- Exceptional Flow
 - a b d e f

9/21/2019Copyright (c) SunilOS (Rays)55

55

Data Binding

SunilOS

- It is data synchronization between View and Controller

9/21/2019Copyright (c) SunilOS (Rays)56

56

Data Binding (Contd.)

SunilOS

- Data Binding can be **One-way**, where data change in controller is reflected at view, or **Two-way**, where data changes are reflected in both directions; controller and view.
- The following types of bindings are supported by Angular:
 - One-way binding
 - Interpolation - {{attribute-name}}
 - Property Binding - [attribute-name]
 - Event Binding - (event)
 - Two-way binding - [(attribute-name)]

9/21/2019Copyright (c) SunilOS (Rays)57

57

Interpolation

SunilOS

- One-way data binding is done by directive {{}}, called interpolation.
- Attributes defined in controller can be displayed in html using {{}}.
- For example, message attribute defined in LoginComponent is displayed at login html using interpolation.

```
export class LoginComponent implements OnInit {  
  message = 'Invalid id or password';  
}  
  
<H1>Login</H1>  
<p style="color:red" >{{ message }}</p>
```

9/21/2019Copyright (c) SunilOS (Rays)58

58

Property Binding

SunilOS

- Property binding is used for one-way data binding
- It binds controller attribute with DOM property of HTML elements

- For example
 - <input type="text" [value]="message" >
 -

```
export class LoginComponent implements OnInit {  
  message = 'Invalid id or password';  
  imageUrl = 'login.gif';  
}
```

9/21/2019Copyright (c) SunilOS (Rays)59

59

Event Binding

SunilOS

- Html form events can be bound with component class methods using **(event)** directive.
- Followings are form events to be bind:
 - (click) : called on button click event
 - (change) : called on value change event
 - (keyup) : called on key up event
 - (blur) : called on blur event

9/21/2019Copyright (c) SunilOS (Rays)60

60

Event Binding

SunilOS

❑ For example, `signIn()` method in `LoginComponent` is bound with click event of submit button in login form.

❑ `export class LoginComponent implements OnInit {`

`signIn() { .. }`

`}`

❑ `<form >`

`User ID:<input [(ngModel)]='userId' >`

`Password: <input [(ngModel)]='password' >`

`<button (click)="signIn()" >Sign In</button>`

`</form>`

9/21/2019

Copyright (c) SunilOS (Rays)

61

61

Two-way data binding

SunilOS

❑ In two-way data binding, data will be changed in both directions; controller and view.

❑ If you change data at view then controller will be changed. If you change data at controller then view will be changed.

❑ Two-way data binding is done by directive `[(ngModel)]`.

❑ It is used to bind html form input elements with controller class attributes.

❑ For example login form elements are bound with `[(ngModel)]`:

○ User ID:<input [(ngModel)]='userId' >

○ Password: <input [(ngModel)]='password' >

9/21/2019

Copyright (c) SunilOS (Rays)

62

62

Routing

SunilOS


❑ Routing is used to define paths to navigate to the components (pages)

❑ One component has one or more routes

❑ Angular projects create `app-routing.module.ts`, which contains routes of application

❑ `RouterModule` is used to configure routes which is imported in `app.module.ts`

❑ Routes may contain URI variables



9/21/2019

Copyright (c) SunilOS (Rays)

63

63

Define routes

SunilOS

❑ In order to access pages, define routes in `app-routing.module.ts`

❑ `const routes: Routes = [`

`{ path: 'login', component: LoginComponent},`

`{ path: 'welcome', component: WelcomeComponent}`

`];`

❑ `@NgModule({`

`imports: [RouterModule.forRoot(routes)],`

`exports: [RouterModule]`

`});`

❑ Access pages using following URLs

○ <http://localhost:4200/login>

○ <http://localhost:4200/welcome>

9/21/2019

Copyright (c) SunilOS (Rays)

64

64

Route Parameters

SunilOS

❑ You can define parametrized routes for a component

❑ Route parameter is defined by colon (`:`) character and placeholder name.

❑ Here `:id`, `:deptid`, `:empid` are router parameter

○ {

○ `path: 'marksheet/:id',`

○ `component: MarkheetComponent`

○ }

○ {

○ `path: 'employee/:deptid/:empid',`

○ `component: EmployeeComponent`

○ }

9/21/2019

Copyright (c) SunilOS (Rays)

65

65

Read Route Parameters

SunilOS

❑ Path variables are read by `ActivatedRoute` service.

❑ Service is injected into component constructor

❑ Parameters read buy registering callback with `route.params.subscribe` method

○ `import {ActivatedRoute} from "@angular/router";`

○ `constructor(private route: ActivatedRoute) {`

○ `this.route.params.subscribe(params =>{`

○ `console.log(params["id"])`

○ `});`

○ `}`

9/21/2019

Copyright (c) SunilOS (Rays)

66

66

Copyright (c) Rays Technologies

11

Directives

SunilOS

❑ Directives are used to change DOM structure of an html page

❑ Angular has many pre-defined directives such as ***ngFor** and ***ngIf**

❑ You can create custom directives with help of @Directive decorator


❑ There are four types of directives:

○ Components directives

○ Structural directives

○ Attribute directives

○ Custom Directive



9/21/2019

Copyright (c) SunilOS (Rays)

67

67

Component Directive

SunilOS

❑ A component is also a directive-with-a-template.

❑ A @Component decorator is actually a @Directive decorator extended with template-oriented features.

9/21/2019

Copyright (c) SunilOS (Rays)

68

68

Structural Directive

SunilOS

❑ A structure directive iterates or conditionally manipulates DOM elements.

❑ Structural directives have a * sign before the directive name such as ***ngIf** and ***ngFor**

❑ Directive ***ngFor** is used to iterate and print list in html page.

❑ Directive ***ngIf** is used to conditionally display an html DOM element.

9/21/2019

Copyright (c) SunilOS (Rays)

69

69

*ngFor

SunilOS

❑ export class MarksheetListComponent implements OnInit {

❑ list = [

❑ { "id":1,"rollNo":"A1","name":"Rajesh Verma"},

❑ { "id":2,"rollNo":"A2","name":"Ashish Nehra"},

❑ { "id":3,"rollNo":"A3","name":"Manish"}

❑];

❑ }

❑ <table border="1">

❑ <tr *ngFor = "let e of list" >

❑ <td>{{e.id}}</td>

❑ <td>{{e.rollNo}}</td>

❑ <td>{{e.name}}</td>

❑ </tr>

❑ </table>

9/21/2019

Copyright (c) SunilOS (Rays)

70

70

*ngIf

SunilOS

❑ <p *ngIf="error" style="color:red" >

❑ {{message}}

❑ </p>

❑ You can use else with if directive

❑ <div *ngIf="success == true; then SUC else FAIL"></div>

❑ <ng-template #SUC >

❑ <p style="color:green" >{{message}}</p>

❑ </ng-template>

❑ <ng-template #FAIL>

❑ <p style="color:red">{{message}}</p>

❑ </ng-template>

9/21/2019

Copyright (c) SunilOS (Rays)

71

71

Attribute Directive

SunilOS

❑ Attribute directive alter the appearance or behavior of an existing HTML element.

❑ Attribute directive look like regular HTML attributes.

❑ The ngModel directive, which implements two-way data binding, is an example of an attribute directive.

❑ ngModel modifies the behavior of an existing element by setting its display property and responding to the changing events.

○ <input [(ngModel)] ="movie.name">

9/21/2019

Copyright (c) SunilOS (Rays)

72

72

Copyright (c) Rays Technologies

12

Custom Directive

SunilOS

You can define your own custom directive using @Directive decorator.

Custom directive can be generated by CLI command:

ng generate directive myDir

Above command will generate

@Directive({

selector: '[appMyDir]'

}

export class MyDirDirective {...}

9/21/2019

Copyright (c) SunilOS (Rays)

73

73

Pipe

SunilOS

Pipes are used to format the data.

Pipes can be used to change data from one format to another. In Angular JS it is used to call filters.

Pipe (|) character is used to apply pipe to an attribute.

For example

{{ name | uppercase }}

{{ name | lowercase }}

9/21/2019

Copyright (c) SunilOS (Rays)

74



Pipes

SunilOS

Angular have following inbuilt pipe

Lowercasepipe

Uppercasepipe

Datepipe

Currencypipe

Jsonpipe

Percentpipe

Decimalpipe

Slicepipe

You can create your own custom pipes

9/21/2019

Copyright (c) SunilOS (Rays)

75

75

Pipe examples

SunilOS

<div style = "width:50%;float:left;border:solid 1px black;">

<h1>change case pipe</h1>

{{title | uppercase}}

{{title | lowercase}}

<h1>Currency Pipe</h1>

{{6589.23 | currency:"USD"}}

{{6589.23 | currency:"USD":true}}

<h1>Date pipe</h1>

{{todaydate | date:'d/M/y'}}

{{todaydate | date:'shortTime'}}

<h1>Decimal Pipe</h1>

{{ 454.78787814 | number: '3.4-4' }}

// 3 is for main integer,4-4 are for integers to be displayed

9/21/2019

Copyright (c) SunilOS (Rays)

76

76

Services

SunilOS

Service contains business logics and data, shared by multiple Components

In general, services communicate with Rest Web APIs and perform CRUD operations

Component's controller calls service to perform business operations.

A service can be created by following CLI command:

ng generate service UserService

Or

ng g s UserService

Service class is decorated by @Injectable decorator.

@Injectable ()

export class UserService {

constructor(private http: HttpClient) { }

}

9/21/2019

Copyright (c) SunilOS (Rays)

77

77

UserService

SunilOS

Lets create user service

export class UserService {

authenticate(login:string, password:string, response)

{

...

}

}

Service is injected to component using constructor

export class LoginComponent implements OnInit {

public userId:string = 'Enter User ID';

public password:string = '';

constructor(private service:UserService) {

}

}

9/21/2019

Copyright (c) SunilOS (Rays)

78

78

Copyright (c) Rays Technologies

13

HttpClient Service

SunilOS

- ❑ HttpClient service is used to communicate with http server.
- ❑ It is contained by HttpClientModule module.
- ❑ Module HttpClientModule is imported in app.module.ts.
- ❑ Http Client is introduced in Angular 6.

```
//app.module.ts
import { HttpClientModule } from '@angular/common/http';
import { NgModule({
  imports: [
    BrowserModule,
    HttpClientModule
  ]
})
```

9/21/2019Copyright (c) SunilOS (Rays)79

79

HTTP Methods

SunilOS

- ❑ HttpClient contains get(), post(), put(),patch(), delete() methods to make http calls to the server.
- ❑ Methods get(url) and delete(url) receive one parameter; url (endpoint) whereas put(url,data),post(url,data) and patch(url,data) receive two parameters; url and data.
- ❑ Data is added to the request body. Usually data is a JSON object.
- ❑ All methods receive "httpOptions" as last optional parameter.
 - ❑ get(url [,httpOptions])
 - ❑ delete(url[,httpOptions])
 - ❑ put(url,data[,httpOptions])
 - ❑ post(url,data[,httpOptions])
 - ❑ patch(url,data[,httpOptions])
- ❑ Object HttpOptions contains request header information, query parameters and other configurable values.

9/21/2019Copyright (c) SunilOS (Rays)80

80

Observable Object

SunilOS

- ❑ All methods return Observable object.
 - o var obser = this.http.get(url);
- ❑ Observable object subscribes to a callback method. Callback method receives response JSON object.
 - o var obser = this.http.get(url);
 - o obser.subscribe(function(data){
 - o console.log(data);
 - o });
- ❑ Callback may be defied by Lambda Expression.
 - o this.http.get(url).subscribe((data) => {
 - o console.log(data);
 - o });

9/21/2019Copyright (c) SunilOS (Rays)81

81

Error Handling

SunilOS

- ❑ You can pass error handler callback as second parameter to subscribe method.
- ❑ Second callback is called when error is occurred
 - o this.http.get(url).subscribe(function
 - o success(data) {
 - o console.log("Success", data);
 - o }, function fail(data) {
 - o console.log("Fail", data.statusText);
 - o });
- ❑ Or callback can be defined by Lambda expression
 - o this.http.get(url).subscribe((data) => {
 - o console.log("Success", data);
 - o }, (data) => {
 - o console.log("Fail", data.statusText);
 - o });

9/21/2019Copyright (c) SunilOS (Rays)82

82

Forms

SunilOS

- ❑ Angular provides two approaches, **template-driven forms** and **model-driven reactive forms**
- ❑ Template driven approach makes use of built-in directives to build forms such as ngModel,ngModelGroup, and ngForm available from the FormsModule module.
- ❑ The model driven approach of creating forms in Angular makes use of FormControl,FormGroup and FormBuilder available from the ReactiveFormsModule module.

9/21/2019Copyright (c) SunilOS (Rays)83

83

Template Driven Form

SunilOS

- ❑ With a template driven form, most of the work is done in the template
- ❑ We need to import to FormsModule in app.module.ts

```
import { FormsModule } from '@angular/forms';

@NgModule({
  imports: [
    BrowserModule,
    FormsModule
  ],
```

9/21/2019Copyright (c) SunilOS (Rays)84

84

SunilOS

- ❑ In template driven forms, we need to create the model form controls by adding the **ngModel** directive and the name attribute.
- ❑ wherever we want Angular to access our data from forms, add **ngModel** to that tag as shown above in bold.
- ❑ The **ngForm** directive needs to be added to the form template

```

• <form #userlogin="ngForm"
•   (ngSubmit)="onClickSubmit (userlogin.value)" >
•   <input name="emailid" placeholder="emailid" ngModel>
•   <input name="passwd" placeholder="passwd" ngModel>
•   <input type = "submit" value = "submit">
• </form>

```

9/21/2019

Copyright (c) SunilOS (Rays)

85

SunilOS

- ❑ In the model driven form, we need to import the **ReactiveFormsModule** from `@angular/forms` and use the same in the imports array.

```
import { FormsModule } from '@angular/forms';

@NgModule({
  imports: [
    BrowserModule,
    ReactiveFormsModule
  ],
```

9/21/2019

Copyright (c) SunilOS (Rays)

86

SunilOS

```
export class LoginComponent {
  formData:
  ngOnInit() {
    this.formData = new FormGroup({
      emailId: new FormControl("xyz@gmail.com"),
      passwd: new FormControl("11234")
    });
  }
  onClickSubmit(data) { ... }
}
```

9/21/2019

Copyright (c) SunilOS (Rays)

87

SunilOS

```
<form [formGroup] = "formdata"
  (ngSubmit)="onClickSubmit(formdata.value)" >
  <input name="emailid" placeholder="emailid"
    formControlName="emailid">
  <input name="passwd" placeholder="passwd"
    formControlName="passwd">
  <input type = "submit" value="Log In">
</form>
```

9/21/2019

Copyright (c) SunilOS (Rays)

88

SunilOS

- ❑ You can use the built-in form validation or also use the custom validation approach
- ❑ we need to import Validators from **@angular/forms**
 - `import { FormGroup, FormControl, Validators } from '@angular/forms'`
- ❑ Angular has built-in validators such as **mandatory field, minlength, maxlength, and pattern**. These are to be accessed using the Validators module.
- ❑ You can just add validators or an array of validators required to tell Angular if a particular field is mandatory.

9/21/2019

Copyright (c) SunilOS (Rays)

89

SunilOS

```
export class AppComponent {
  formData:
  ngOnInit() {
    this.formData = new FormGroup({
      emailid: new FormControl("", Validators.compose([
        Validators.required,
        Validators.pattern("^[^ @]*@[^ @]*")
      ])),
      passwd: new FormControl("")
    });
  }
  onClickSubmit(data) {this.emailid = data.emailid;}
}
```

9/21/2019

Copyright (c) SunilOS (Rays)

90

login.component.html

SunilOS

```
<form [formGroup] = "formdata"
(ngSubmit)="onClickSubmit(formdata.value)" >
  <input type = "submit"
    [disabled] = "!formdata.valid"    value = "Log In">
</form>
```

9/21/2019

Copyright (c) SunilOS (Rays)

91

91

Disclaimer

SunilOS

- ❑ This is an educational presentation to enhance the skill of computer science students.
- ❑ This presentation is available for free to computer science students.
- ❑ Some internet images from different URLs are used in this presentation to simplify technical examples and correlate examples with the real world.
- ❑ We are grateful to owners of these URLs and pictures.

9/21/2019

Copyright (c) SunilOS (Rays)



92

92

Thank You!

SunilOS

GET IN TOUCH



www.SunilOS.com

9/21/2019

Copyright (c) SunilOS (Rays)

93

93