

HTML DOM Node — Access & Update

Quick-reference for selecting, reading, and mutating the DOM

■ Selecting Nodes		■ Node Properties		■ Tree Traversal	
getElementById	doc.getElementById('id')	id / className	el.id el.className	parentNode	el.parentNode
querySelector	doc.querySelector('css')	classList	el.classList	parentElement	el.parentElement
querySelectorAll	doc.querySelectorAll('css')	tagName / nodeName	el.tagName el.nodeName	children	el.children (HTMLCollection)
getElementsByClass	doc.getElementsByClassName('c')	nodeType	el.nodeType → 1=El 3=Txt	childNodes	el.childNodes (incl. text)
getElementsByTag	doc.getElementsByTagName('div')	innerHTML	el.innerHTML	firstChild	el.firstChild
getElementsByName	doc.getElementsByName('n')	innerText / textContent	el.innerText el.textContent	firstElementChild	el.firstElementChild
matches	el.matches('css')	value	el.value (inputs)	lastChild	el.lastChild
closest	el.closest('css')	checked / selected	el.checked el.selected	lastElementChild	el.lastElementChild
querySelector returns 1st match · querySelectorAll returns Node...		href / src	el.href el.src	nextSibling	el.nextSibling
		style	el.style.color	nextElementSibling	el.nextElementSibling
				previousSibling	el.previousSibling

■■ Attributes		■ classList API		■ Inline Style / CSSOM	
getAttribute	el.getAttribute('attr')	add	el.classList.add('foo')	set inline	el.style.fontSize = '16px'
setAttribute	el.setAttribute('k', 'v')	remove	el.classList.remove('foo')	remove inline	el.style.fontSize = ''
removeAttribute	el.removeAttribute('k')	toggle	el.classList.toggle('foo')	getComputed	getComputedStyle(el).color
hasAttribute	el.hasAttribute('k')	contains	el.classList.contains('foo')	cssText	el.style.cssText = 'color:red'
toggleAttribute	el.toggleAttribute('k')	replace	el.classList.replace('a', 'b')	setProperty	el.style.setProperty('--x', '1')
dataset	el.dataset.myKey	item	el.classList.item(0)	getPropertyValue	el.style.getPropertyValue('--x')
attributes	el.attributes (NamedNodeMap)				

■■ Create & Insert		■■ Remove & Replace		■ Events	
createElement	doc.createElement('div')	remove	el.remove()	addEventListener	el.addEventListener(evt, fn, opt)
createTextNode	doc.createTextNode('hi')	removeChild	parent.removeChild(el)	removeEventListener	el.removeEventListener(evt, fn)
createFragment	doc.createDocumentFragment()	replaceChild	parent.replaceChild(new, old)	dispatchEvent	el.dispatchEvent(new Event('x'))
cloneNode	el.cloneNode(true)	replaceWith	el.replaceWith(newEl)	once option	{once: true}
appendChild	parent.appendChild(el)	replaceChildren	parent.replaceChildren(a, b)	capture option	{capture: true}
prepend	parent.prepend(el)	innerHTML clear	parent.innerHTML = ''	passive option	{passive: true}
append	parent.append(el, 'text')	textContent clear	parent.textContent = ''	Event object: e.target e.currentTarget e.preventDefault() e.stopPropagation()	

■■ Geometry / Position		■ Forms & Input	
getBoundingClientRect	el.getBoundingClientRect()	value	input.value
offsetTop/Left	el.offsetTop el.offsetLeft	checked	input.checked
scrollTop/Left	el.scrollTop el.scrollLeft	focus / blur	el.focus() el.blur()
clientW/H	el.clientWidth el.clientHeight	click	el.click()
offsetW/H	el.offsetWidth el.offsetHeight	submit	form.submit()
scrollIntoView	el.scrollIntoView({behavior: 'smooth'})	reset	form.reset()
		validity	input.validity.valid
		reportValidity	input.reportValidity()

■ document shortcuts		■ MutationObserver		■ nodeType Values	
document.body	doc.body	create	new MutationObserver(cb)	1	ELEMENT_NODE
document.head	doc.head			2	ATTRIBUTE_NODE
document.title	doc.title	observe	obs.observe(el, config)	3	TEXT_NODE
document.URL	doc.URL	disconnect	obs.disconnect()	4	CDATA_SECTION_NODE
document.readyState	doc.readyState	config keys	childList,	7	PROCESSING_INSTRUCTION
document.activeElement	doc.activeElement		attributes,	8	COMMENT_NODE
document.forms	doc.forms		subtree,	9	DOCUMENT_NODE
document.cookie	doc.cookie	callback	characterData	10	DOCUMENT_TYPE_NODE
			cb(mutations, observer)	11	DOCUMENT_FRAGMENT_NODE

Each mutation: type · target · addedNodes · removedNodes · oldValue

All methods available on the `document` or `element` objects · `NodeList` from `querySelectorAll` is static; `HTMLCollection` from `getElementsBy*` is live · Use optional chaining `el?.method()` for null safety