

NAME:-RISHIKESH SHEDE

CLASS:- SYBTECH-C

BATCH:- C-2

ROLL NO:- 223053

GR NO:- 17U208

ASSIGNMENT NO.3.

Aim :-

There are flight paths between cities. If there is a flight between city A and city B then there is an edge between the cities. The cost of the edge can be the time that flight takes to reach city B from A, or the amount of fuel used for the journey. Represent this as a graph. The node can be represented by airport name or name of the city. Use adjacency list representation of the graph or use adjacency matrix representation of the graph. Justify the storage representations used .

Objective:-To learn adjacency list representation of graph.

Theory:-

Following two are the most commonly used representations of a graph.

1. Adjacency Matrix

2. Adjacency List

There are other representations also like, Incidence Matrix and Incidence List. The choice of the graph representation is situation specific. It totally depends on the type of operations to be performed and ease of use.

Adjacency Matrix:

Adjacency Matrix is a 2D array of size $V \times V$ where V is the number of vertices in a graph. Let the 2D array be $adj[][]$, a slot $adj[i][j] = 1$ indicates that there is an edge from vertex i to vertex j . Adjacency matrix for undirected graph is always symmetric.

Adjacency Matrix is also used to represent weighted graphs. If $adj[i][j] = w$, then there is an edge from vertex i to vertex j with weight w .

NAME:-RISHIKESH SHEDE

CLASS:- SYBTECH-C

BATCH:- C-2

ROLL NO:- 223053

GR NO:- 17U208

The adjacency matrix for the above example graph is:

	0	1	2	3	4
0	0	1	0	0	1
1	1	0	1	1	1
2	0	1	0	1	0
3	0	1	1	0	1
4	1	1	0	1	0

Adjacency List:

An array of lists is used. Size of the array is equal to the number of vertices. Let the array be array[]. An entry array[i] represents the list of vertices adjacent to the i th vertex. This representation can also be used to represent a weighted graph. The weights of edges can be represented as lists of pairs. Following is adjacency list representation of the above graph.

Algorithm:-

1.BFS :-

- **Step 1:** SET STATUS = 1 (ready state)
for each node in G

NAME:-RISHIKESH SHEDE

CLASS:- SYBTECH-C

BATCH:- C-2

ROLL NO:- 223053

GR NO:- 17U208

- **Step 2:** Enqueue the starting node A and set its STATUS = 2 (waiting state)
- **Step 3:** Repeat Steps 4 and 5 until QUEUE is empty
- **Step 4:** Dequeue a node N. Process it and set its STATUS = 3 (processed state).
- **Step 5:** Enqueue all the neighbours of N that are in the ready state (whose STATUS = 1) and set their STATUS = 2 (waiting state)
[END OF LOOP]
- **Step 6:** EXIT

2.DFS :-

- **Step 1:** SET STATUS = 1 (ready state) for each node in G
- **Step 2:** Push the starting node A on the stack and set its STATUS = 2 (waiting state)
- **Step 3:** Repeat Steps 4 and 5 until STACK is empty
- **Step 4:** Pop the top node N. Process it and set its STATUS = 3 (processed state)
- **Step 5:** Push on the stack all the neighbours of N that are in the ready state (whose STATUS = 1) and set their STATUS = 2 (waiting state)
[END OF LOOP]
- **Step 6:** EXIT

Program Code:-

NAME:-RISHIKESH SHEDE

CLASS:- SYBTECH-C

BATCH:- C-2

ROLL NO:- 223053

GR NO:- 17U208

```
#include <iostream>
```

```
#include<iomanip>
```

```
using namespace std;
```

```
const int MAX=30;
```

```
class Queue //Queue for BFS TRAVERSAL
```

```
{
```

```
    int front,rear;
```

```
    string data[MAX];
```

```
public:
```

```
    Queue()
```

```
{
```

```
        front=-1;
```

```
        rear=-1;
```

```
}
```

```
    bool empty()
```

```
{
```

```
        if(rear== -1)
```

```
            return 1;
```

```
        else
```

```
            return 0;
```

```
}
```

NAME:-RISHIKESH SHEDE

CLASS:- SYBTECH-C

BATCH:- C-2

ROLL NO:- 223053

GR NO:- 17U208

```
bool inqueue(string str)
{
    if(front==-1 && rear==-1)
    {
        front=rear=0;
        data[rear]=str;
        return true;
    }
    else
    {
        rear=rear+1;
        data[rear]=str;
        return true;
    }
}

string dequeue()
{
    string p;
    if(front==rear)
    {
        p=data[front];
        front=-1;
        rear=-1;
    }
}
```

NAME:-RISHIKESH SHEDE

CLASS:- SYBTECH-C

BATCH:- C-2

ROLL NO:- 223053

GR NO:- 17U208

```
        }
        else
        {
            p=data[front];
            front=front+1;
        }
        return p;
    }

};
```

class node //node class for each airport

```
{
    node *next;
    string city;
    int timeCost;
public:
    friend class graph;
    node()
    {
        next=NULL;
        city="";
        timeCost=-1;
    }
};
```

NAME:-RISHIKESH SHEDE

CLASS:- SYBTECH-C

BATCH:- C-2

ROLL NO:- 223053

GR NO:- 17U208

```
    }
    node(string city,int weight)
    {
        next=NULL;
        this->city=city;
        timeCost=weight;
    }
};

class graph //Contains total graph of airports
{
    node *head[MAX];
    int n;
    int visited[MAX];
public:
    graph(int num)
    {
        n=num;
        for(int i=0;i<n;i++)
            head[i]=NULL;
    }

    void insert(string city1,string city2,int time);
    void insertUndirected(string city1,string city2,int time);
    void readdata(int gType);
```

NAME:-RISHIKESH SHEDE

CLASS:- SYBTECH-C

BATCH:- C-2

ROLL NO:- 223053

GR NO:- 17U208

```
int getIndex(string s1);
void outFlights();
void inFlights();
void DFS(string str);
void BFS();
void dfsTraversal();

};
void graph::BFS()
{
    string str=head[0]->city;
    int j;
    //node *p;
    for(int i=0;i<n;i++)
        visited[i]=0;
    Queue queue;
    queue.inqueue(str);
    int i=getIndex(str);
    cout<<"BFS Traversal: \n";
    cout<<" "<<str<<" ";
    visited[i]=1;
    while(!queue.empty())
    {
```


NAME:-RISHIKESH SHEDE

CLASS:- SYBTECH-C

BATCH:- C-2

ROLL NO:- 223053

GR NO:- 17U208

```
        string p=queue.dequeue();
        i=getindex(p);

        //visited[i]=1;

        for(node *q=head[i];q!=NULL;q=q->next)
        {
            i=getindex(q->city);
            str=q->city;
            if(!visited[i])
            {
                queue.inqueue(q->city);
                visited[i]=1;
                cout<<" "<<str<<" ";
            }
        }
    }
    cout<<"\n";
}

void graph::dfsTraversal()
{
    for( inti=0;i<n;i++)
```

NAME:-RISHIKESH SHEDE

CLASS:- SYBTECH-C

BATCH:- C-2

ROLL NO:- 223053

GR NO:- 17U208

```
        visited[i]=0;
        cout<<"\nDFS TRAVERSAL: \n";
        DFS(head[0]->city);
        cout<<"\n";
    }
void graph::DFS(string str)
{
    node *p;
    int i=getindex(str);

    cout<<" "<<str<<" ";
    p=head[i];
    visited[i]=1;
    while(p!=NULL)
    {
        str=p->city;
        i=getindex(str);
        if(!visited[i])
            DFS(str);
        p=p->next;
    }
}
```

NAME:-RISHIKESH SHEDE

CLASS:- SYBTECH-C

BATCH:- C-2

ROLL NO:- 223053

GR NO:- 17U208

void graph::inFlights()

```
{
    int count[n];
    for(int i=0;i<n;i++)
        count[i]=0;
    cout<<"==== In degree =====\n";
    for(int i=0;i<n;i++)
    {
        cout<<"\n"<<setw(8)<<"Source"<<setw(8)<<"Destin."<<setw(8)<<"Time";
        for(int j=0;j<n;j++)
        {
            node *p=head[j]->next;
            while(p!=NULL)
            {
                if(p->city==head[i]->city)
                {
                    count[i]=count[i]+1;
                    cout<<"\n"<<setw(8)<<head[j]-
>city<<setw(8)<<head[i]->city<<setw(8)<<p->timeCost;
                }

                p=p->next;
            }
        }
    }
```

NAME:-RISHIKESH SHEDE

CLASS:- SYBTECH-C

BATCH:- C-2

ROLL NO:- 223053

GR NO:- 17U208

```
        cout<<"\nFlights to "<<head[i]->city<<" = "<<count[i]<<endl;
        cout<<"-----\n";
    }

}

void graph::outFlights()
{
    int count;
    for(int i=0;i<n;i++)
    {
        node *p=head[i]->next;
        count=0;
        cout<<"\n"<<setw(8)<<"Source"<<setw(8)<<"Destin."<<setw(8)<<"Time";
        if(p==NULL)
        {
            cout<<"\nNo Flights from "<<head[i]->city;
        }
        else
        {
            while(p!=NULL)

            {
                cout<<"\n"<<setw(8)<<head[i]->city<<setw(8)<<p-
>city<<setw(8)<<p->timeCost;
```

NAME:-RISHIKESH SHEDE

CLASS:- SYBTECH-C

BATCH:- C-2

ROLL NO:- 223053

GR NO:- 17U208

```
                count++;
                p=p->next;
            }
        }
        cout<<"\nNo. of flights: "<<count<<endl;;
        cout<<"-----\n";
    }
}

int graph::getindex(string s1)
{
    for(int i=0;i<n;i++)
    {
        if(head[i]->city==s1)
            return i;
    }
    return -1;
}

void graph::insert(string city1,string city2,int time)
{
    node *source;
    node *dest=new node(city2,time);

    int ind=getindex(city1); //for getting head nodes index in array
```

NAME:-RISHIKESH SHEDE

CLASS:- SYBTECH-C

BATCH:- C-2

ROLL NO:- 223053

GR NO:- 17U208

```
        if(head[ind]==NULL)
            head[ind]=dest;
        else
        {
            source=head[ind];
            while(source->next!=NULL)
                source=source->next;
            source->next=dest;
        }
    }
}

void graph::insertUndirected(string city1,string city2,int time)
{
    node *source;
    node *dest=new node(city2,time);
    node *dest2=new node(city1,time); //for second flight insertion

    int ind=getindex(city1); //for getting head nodes index in array
    int ind2=getindex(city2);
    /* if(head[ind]==NULL && head[ind2]==NULL) //when no flights in graph
    {
        head[ind]=dest;
        head[ind2]=dest2;
    }
}
```

NAME:-RISHIKESH SHEDE

CLASS:- SYBTECH-C

BATCH:- C-2

ROLL NO:- 223053

GR NO:- 17U208

else if(head[ind]==NULL && head[ind2]!=NULL) //no flight in first list but flight in second list

```
{
    head[ind]=dest; //inserted first flight
    source=head[ind2];
    while(source->next!=NULL)
        source=source->next;
    source->next=dest2;
}
else if(head[ind]!=NULL && head[ind2]==NULL)
{
    head[ind2]=dest2; //inserted first flight
    source=head[ind];
    while(source->next!=NULL)
        source=source->next;
    source->next=dest;
}
else
{*/
    source=head[ind];
    while(source->next!=NULL)
        source=source->next;
    source->next=dest;
```

NAME:-RISHIKESH SHEDE

CLASS:- SYBTECH-C

BATCH:- C-2

ROLL NO:- 223053

GR NO:- 17U208

```
        source=head[ind2];
        while(source->next!=NULL)
            source=source->next;
        source->next=dest2;

    //}
}
void graph::readdata(int gType)
{
    string city1,city2,tmpcity;
    int fcost;
    int flight;
    cout<<"\nEnter City Details:\n ";
    for(int i=0;i<n;i++)
    {
        head[i]=new node;
        cout<<"Enter City "<<i+1<<" ";
        cin>>tmpcity;
        head[i]->city=tmpcity;
    }
    cout<<"\nEnter Number of Flights to insert: ";
    cin>>flight;
    if(gType==1)
```


NAME:-RISHIKESH SHEDE

CLASS:- SYBTECH-C

BATCH:- C-2

ROLL NO:- 223053

GR NO:- 17U208

```
{
    for(int i=0;i<flight;i++)
    {
        cout<<"\nEnter Source:";
        cin>>city1;
        cout<<"Enter Destination:";
        cin>>city2;
        cout<<"Enter Time:";
        cin>>fcost;
        insert(city1,city2,fcost);
    }
}
else
{
    for(int i=0;i<flight;i++)
    {
        cout<<"\nEnter Source:";
        cin>>city1;
        cout<<"Enter Destination:";
        cin>>city2;
        cout<<"Enter Time:";
        cin>>fcost;
        insertUndirected(city1,city2,fcost);
    }
}
```

NAME:-RISHIKESH SHEDE

CLASS:- SYBTECH-C

BATCH:- C-2

ROLL NO:- 223053

GR NO:- 17U208

```
        //cout<<"\ninserted"<<i+1;
    }
}
}
int main() {
    int number,choice;
    int graphype;
    cout<<"-----INDIA AIRLINES PVT LTD-----"
        <<"\n0. Undirected\n1.Directed\nEnter Flight data Insertion Type:";
    cin>>graphype;
    cout<<"\nENter Number of Airport Stations:";
    cin>>number;
    graph g1(number);
    g1.readdata(graphype);
    do
    {
        cout<<"----- Menu -----"
            <<"\n1.Incoming Flights(In degree)"
            <<"\n2.Outgoing Flights(Out degree)"
            <<"\n3.DFS"
            <<"\n4.BFS"
            <<"\n5.Exit"
            <<"\nEnter your choice: ";
```

NAME:-RISHIKESH SHEDE

CLASS:- SYBTECH-C

BATCH:- C-2

ROLL NO:- 223053

GR NO:- 17U208


```
        cin>>choice;
        switch(choice)
        {
        case 1:
                cout<<" " <<endl;
                g1.inFlights();
                break;
        case 2:
                g1.outFlights();
                break;
        case 3:
                g1.dfsTraversal();
                break;
        case 4:
                g1.BFS();
                break;
        default:
                cout<<"\nWrong Choice";
        }
    }while(choice!=5);

    return 0;
```

NAME:-RISHIKESH SHEDE
CLASS:- SYBTECH-C
BATCH:- C-2
ROLL NO:- 223053
GR NO:- 17U208

}

Output Screenshots:-



```
C:\Users\Aaditya\Desktop\SD Codes\SD_3.exe
-----INDIA AIRLINES PVT. LTD-----
0. Undirected
1.Directed
Enter Flight data Insertion Type:0

Enter Number of Airport Stations:3

Enter City Details:
Enter City 1 Pune
Enter City 2 Mumbai
Enter City 3 Hyderabad

Enter Number of Flights to insert: 5

Enter Source:Pune
Enter Destination:Mumbai
Enter Time:4

Enter Source:Mumbai
Enter Destination:Pune
Enter Time:3

Enter Source:Hyderabad
Enter Destination:Pune
Enter Time:7

Enter Source:Hyderabad
Enter Destination:Mumbai
Enter Time:2

Enter Source:Mumbai
Enter Destination:Hyderabad
Enter Time:2

----- Menu -----
1.Incoming Flights(In degree)
2.Outgoing Flights(Out degree)
3.DFS
4.BFS
5.Exit
Enter your choice: 1

===== In degree =====

Source Destin.   Time
Mumbai   Pune      4
Mumbai   Pune      3
Hyderabad Pune      7
Flights to Pune = 3

-----
```

NAME:-RISHIKESH SHEDE

CLASS:- SYBTECH-C

BATCH:- C-2

ROLL NO:- 223053

GR NO:- 17U208

```
C:\Users\USER\Documents\sd3.exe
===== In degree =====
Source Destin. Time
chennai mumbai 9
nagpur mumbai 9
nagpur mumbai 9
Flights to mumbai = 3
-----
Source Destin. Time
mumbai chennai 9
nagpur chennai 9
nagpur chennai 9
Flights to chennai = 3
-----
Source Destin. Time
mumbai nagpur 9
mumbai nagpur 9
chennai nagpur 9
chennai nagpur 9
Flights to nagpur = 4
-----
----- Menu -----
1.Incoming Flights(In degree)
2.Outgoing Flights(Out degree)
3.DFS
4.BFS
5.Exit
Enter your choice: 2

Source Destin. Time
mumbai chennai 9
mumbai nagpur 9
mumbai nagpur 9
No. of flights: 3
-----
Source Destin. Time
chennai mumbai 9
chennai nagpur 9
chennai nagpur 9
No. of flights: 3
-----
```

```
C:\Users\USER\Documents\sd3.exe
Source Destin. Time
chennai mumbai 9
chennai nagpur 9
chennai nagpur 9
No. of flights: 3
-----
Source Destin. Time
nagpur mumbai 9
nagpur chennai 9
nagpur chennai 9
nagpur mumbai 9
No. of flights: 4
-----
----- Menu -----
1.Incoming Flights(In degree)
2.Outgoing Flights(Out degree)
3.DFS
4.BFS
5.Exit
Enter your choice: 3
DFS TRAVERSAL:
mumbai chennai nagpur
----- Menu -----
1.Incoming Flights(In degree)
2.Outgoing Flights(Out degree)
3.DFS
4.BFS
5.Exit
Enter your choice: 4
BFS Traversal:
mumbai chennai nagpur
----- Menu -----
1.Incoming Flights(In degree)
2.Outgoing Flights(Out degree)
3.DFS
4.BFS
5.Exit
Enter your choice: 5_
```

NAME:-RISHIKESH SHEDE

CLASS:- SYBTECH-C

BATCH:- C-2

ROLL NO:- 223053

GR NO:- 17U208

Conclusion:- Thus, we have studied adjacency graph representation.