~\AppData\Local\Packages\5319275A.WhatsAppDesktop_cv1g1gvanyjgm\LocalState\sessions\293C6C483966420D624234E5865437FD4D5B4047\transfers\2026-44\01_Exp_1_U2.CPP

```
1
2                //               Name = Chandrashekhar Patil
3                //             RollN0 = 16
4               //                unit = 2
5                //    OPP Expriment No = 1
6
7
8
9
10
11
12
13
14 #include <iostream>
15 #include <string>
16 using namespace std;
17
18 class Employee {
19 private:
20     int empId;
21     string name;
22     float basicSalary;
23     float bonus;
24     float totalSalary;
25
26 public:
27     // Default constructor
28     Employee() {
29         empId = 0;
30         name = "Unknown";
31         basicSalary = 0;
32         bonus = 0;
33         totalSalary = 0;
34     }
35
36     // Parameterized constructor
37     Employee(int id, string n, float salary, float b) {
38         empId = id;
39         name = n;
40         basicSalary = salary;
41         bonus = b;
42         calculateTotalSalary();
43     }
44
45     void calculateTotalSalary() {
46         totalSalary = basicSalary + bonus;
47     }
48
49     void display() {
50         cout << "Employee ID: " << empId << endl;
51         cout << "Name: " << name << endl;
52         cout << "Basic Salary: " << basicSalary << endl;
53         cout << "Bonus: " << bonus << endl;
54         cout << "Total Salary: " << totalSalary << endl;
55     }
56 };
57
58 int main() {
59     // Using default constructor
60     Employee emp1;
61     cout << "Default Constructor - Employee 1:" << endl;
62     emp1.display();
63
64     cout << "\n-------------------------" << endl;
65
66     // Using parameterized constructor
67     Employee emp2(101, "John Doe", 50000, 10000);
```

```
    cout << "Parameterized Constructor - Employee 2:" << endl;
    emp2.display();

    cout << "\n-------------------------" << endl;

    // Taking input for parameterized constructor
    int id;
    string name;
    float salary, bonus;
    cout << "Enter Employee ID: ";
    cin >> id;
    cin.ignore();
    cout << "Enter Name: ";
    getline(cin, name);
    cout << "Enter Basic Salary: ";
    cin >> salary;
    cout << "Enter Bonus: ";
    cin >> bonus;

    Employee emp3(id, name, salary, bonus);
    cout << "\nEmployee 3 Details:" << endl;
    emp3.display();

    return 0;
}
```