Operator	Condition	Example
=	Case sensitive exact string comparison (**notice the single equals**)	col_name **=** "abc"
!= or <>	Case sensitive exact string inequality comparison	col_name **!=** "abcd"
LIKE	Case insensitive exact string comparison	col_name **LIKE** "ABC"
NOT LIKE	Case insensitive exact string inequality comparison	col_name **NOT LIKE** "ABCD"
%	Used anywhere in a string to match a sequence of zero or more characters (only with LIKE or NOT LIKE)	col_name **LIKE** "%AT%" (matches "AT", "ATTIC", "CAT" or even "BATS")
_	Used anywhere in a string to match a single character (only with LIKE or NOT LIKE)	col_name **LIKE** "AN_" (matches "AND", but not "AN")
IN (...)	String exists in a list	col_name **IN** ("A", "B", "C")
NOT IN (...)	String does not exist in a list	col_name **NOT IN** ("D", "E", "F")

Operator	Condition	SQL Example
=, !=, <, <=, >, >=	Standard numerical operators	col_name **!=** 4
BETWEEN ... AND ...	Number is within range of two values (inclusive)	col_name **BETWEEN** 1.5 **AND** 10.5
NOT BETWEEN ... AND ...	Number is not within range of two values (inclusive)	col_name **NOT BETWEEN** 1 **AND** 10
IN (...)	Number exists in a list	col_name **IN** (2, 4, 6)
NOT IN (...)	Number does not exist in a list	col_name **NOT IN** (1, 3, 5)

Limiting results to a subset

Another clause which is commonly used with the **ORDER BY** clause are the **LIMIT** and **OFFSET** clauses, which are a useful optimization to indicate to the database the subset of the results you care about. The **LIMIT** will reduce the number of rows to return, and the optional **OFFSET** will specify where to begin counting the number rows from.

Select query with limited rows

```
SELECT column, another_column, …
FROM mytable
WHERE condition(s)
ORDER BY column ASC/DESC
LIMIT num_limit OFFSET num_offset;
```