

Many of the slides in this lecture are either from or adapted from slides provided by the authors of the textbook "Computer Systems: A Programmer's Perspective," 2nd Edition and are provided from the website of Carnegie-Mellon University, course 15-213, taught by Randy Bryant and David O'Hallaron in Fall 2010. These slides are indicated "Supplied by CMU" in the notes section of the slides.

Data Types on Intel x86

- "Integer" data of 1, 2, or 4 bytes (plus 8 bytes on x86-64)
  - data values
    - » whether signed or unsigned depends on interpretation
  - addresses (untyped pointers)

- Floating-point data of 4, 8, or 10 bytes

- No aggregate types such as arrays or structures
  - just contiguously allocated bytes in memory

Supplied by CMU.



Most instructions come in three (on IA32) or four (on x86-64) forms, one for each possible operand size.



Supplied by CMU.



Supplied by CMU.

Note that though *esp* and *ebp* have special uses, they may also be used in both source and destination operands.

Note that some assemblers (in particular, those of Intel and Microsoft) place the operands in the opposite order. Thus the example of the slide would be "addl %eax, 8(%ebp)". The order we use is that used by gcc, known as the "AT&T syntax" because it was used in the original Unix assemblers, written at Bell Labs, then part of AT&T.

`movl` Operand Combinations

	Source	Dest	Src, Dest	C Analog
`movl`	*Imm*	*Reg*	`movl $0x4,%eax`	`temp = 0x4;`
		Mem	`movl $-147,(%eax)`	`*p = -147;`
	Reg	*Reg*	`movl %eax,%edx`	`temp2 = temp1;`
		Mem	`movl %eax,(%edx)`	`*p = temp;`
	Mem	*Reg*	`movl (%eax),%edx`	`temp = *p;`

Cannot (normally) do memory-memory transfer with a single instruction

Supplied by CMU.

Simple Memory Addressing Modes

- **Normal (R) Mem[Reg[R]]**
  - register R specifies memory address

```
movl (%ecx),%eax
```

- **Displacement D(R) Mem[Reg[R]+D]**
  - register R specifies start of memory region
  - constant displacement D specifies offset

```
movl 8(%ebp),%edx
```


Supplied by CMU.

If one thinks of there being an array of registers, then “Reg[R]” selects register “R” from this array.

Using Simple Addressing Modes

```c
void swap(int *xp, int *yp)
{
  int t0 = *xp;
  int t1 = *yp;
  *xp = t1;
  *yp = t0;
}
```

```
swap:
   pushl %ebp
   movl  %esp,%ebp
   pushl %ebx

   movl  8(%ebp), %edx
   movl  12(%ebp), %ecx
   movl  (%edx), %ebx
   movl  (%ecx), %eax
   movl  %eax, (%edx)
   movl  %ebx, (%ecx)

   popl  %ebx
   popl  %ebp
   ret
```

Set Up

Body

Finish

Supplied by CMU.

Understanding Swap

```c
void swap(int *xp, int *yp)
{
  int t0 = *xp;
  int t1 = *yp;
  *xp = t1;
  *yp = t0;
}
```



Register	Value
%edx	xp
%ecx	yp
%ebx	t0
%eax	t1

```
movl  8(%ebp), %edx    # edx = xp
movl  12(%ebp), %ecx   # ecx = yp
movl  (%edx), %ebx     # ebx = *xp (t0)
movl  (%ecx), %eax     # eax = *yp (t1)
movl  %eax, (%edx)     # *xp = t1
movl  %ebx, (%ecx)     # *yp = t0
```


Supplied by CMU.



Supplied by CMU.



Supplied by CMU.



Supplied by CMU.



Supplied by CMU.



Supplied by CMU.



Supplied by CMU.



Supplied by CMU.

Quiz 1

```
movl -4(%ebp), %eax
movl (%eax), %eax
movl (%eax), %eax
movl %eax, -8(%ebp)
```



Which C statements best describe the assembler code?

```
// a
int x;
int y;
y = x;
```

```
// b
int *x;
int y;
y = *x;
```

```
// c
int **x;
int y;
y = **x;
```

```
// d
int ***x;
int y;
y = ***x;
```

Complete Memory-Addressing Modes

- **Most general form**

  D(Rb,Ri,S)   Mem[Reg[Rb]+S*Reg[Ri]+D]

  - **D: constant "displacement"**
  - **Rb: base register: any of 8 integer registers**
  - **Ri: index register: any, except for `%esp`**
    - **unlikely you'd use `%ebp` either**
  - **S: scale: 1, 2, 4, or 8**

- **Special cases**

(Rb,Ri)	Mem[Reg[Rb]+Reg[Ri]]
D(Rb,Ri)	Mem[Reg[Rb]+Reg[Ri]+D]
(Rb,Ri,S)	Mem[Reg[Rb]+S*Reg[Ri]]
D	Mem[D]

Supplied by CMU.

Address-Computation Examples

%edx	0xf000
%ecx	0x0100

Expression	Address Computation	Address
0x8(%edx)	**0xf000 + 0x8**	**0xf008**
(%edx,%ecx)	**0xf000 + 0x0100**	**0xf100**
(%edx,%ecx,4)	**0xf000 + 4*0x0100**	**0xf400**
0x80(,%edx,2)	**2*0xf000 + 0x80**	**0x1e080**

Supplied by CMU.

Address-Computation Instruction

- `leal` src, dest
  - src is address mode expression
  - set dest to address denoted by expression
- Uses
  - computing addresses without a memory reference
    - » e.g., translation of `p = &x[i];`
  - computing arithmetic expressions of the form x + k*y
    - » k = 1, 2, 4, or 8
- Example

```
int mul12(int x)
{
   return x*12;
}
```

Converted to ASM by compiler:

```
movl 8(%ebp), %eax         # get arg
leal (%eax,%eax,2), %eax   # t <- x+x*2
sall $2, %eax              # return t<<2
```


Supplied by CMU.

Note that a function returns a value by putting it in %eax.

Quiz 2

What value ends up in %ecx?

```
movl $1000,%eax
movl $1,%ebx
movl 2(%eax,%ebx,4),%ecx
```

a) **0x02030405**
b) **0x05040302**
c) **0x06070809**
d) **0x09080706**

1009:	0x09
1008:	0x08
1007:	0x07
1006:	0x06
1005:	0x05
1004:	0x04
1003:	0x03
1002:	0x02
1001:	0x01
%eax → 1000:	0x00

Hint:



Supplied by CMU.

Note that %ebp/%rbp may be used as a base register as on IA32, but they don't have to be used that way. This will become clearer when we explore how the runtime stack is accessed.

32-bit Instructions on x86-64

- addl 4(%rdx), %eax
  - memory address must be 64 bits
  - operands (in this case) are 32-bit
    - » result goes into %eax
      - lower half of %rax
      - upper half is filled with zeroes

On x86-64, for instructions with 32-bit (long) operands that produce 32-bit results going into a register, the register must be a 32-bit register; the higher-order 32 bits are filled with zeroes.

32-bit code for swap

```c
void swap(int *xp, int *yp)
{
  int t0 = *xp;
  int t1 = *yp;
  *xp = t1;
  *yp = t0;
}
```

```
swap:
  pushl %ebp
  movl  %esp,%ebp
  pushl %ebx
```

Set Up

```
  movl   8(%ebp), %edx
  movl   12(%ebp), %ecx
  movl   (%edx), %ebx
  movl   (%ecx), %eax
  movl   %eax, (%edx)
  movl   %ebx, (%ecx)
```

Body

```
  popl   %ebx
  popl   %ebp
  ret
```

Finish

Supplied by CMU.



Supplied by CMU.

Note that no more than six arguments can be passed in registers. If there are more than six arguments (which is unusual), then remaining arguments are passed on the stack, and referenced via %rsp.

64-bit code for long int swap

```
void swap(long *xp, long *yp)
{
  long t0 = *xp;
  long t1 = *yp;
  *xp = t1;
  *yp = t0;
}
```

```
swap_l:
                                  } Set Up

    movq    (%rdi), %rdx          }
    movq    (%rsi), %rax          } Body
    movq    %rax, (%rdi)          }
    movq    %rdx, (%rsi)          }

    ret                           } Finish
```

- **64-bit data**
  - **data held in registers `%rax` and `%rdx`**
  - **`movq` operation**
    - » **"q" stands for quad-word**

Supplied by CMU.



Supplied by CMU.

Note that normally one does not ask gcc to produce assembler code, but instead it compiles C code directly into machine code (producing an object file). Note also that the gcc command actually invokes a script; the compiler (also known as gcc) compiles code into either assembler code or machine code; if necessary, the assembler (as) assembles assembler code into object code. The linker (ld) links together multiple object files (containing object code) into an executable program.

Object Code

Code for `sum`

```
0x401040 <sum>:
    0x55
    0x89
    0xe5
    0x8b
    0x45
    0x0c
    0x03
    0x45
    0x08
    0x5d
    0xc3
```

- Total of 11 bytes
- Each instruction: 1, 2, or 3 bytes
- Starts at address `0x401040`

- **Assembler**
  - translates `.s` into `.o`
  - binary encoding of each instruction
  - nearly-complete image of executable code
  - missing linkages between code in different files
- **Linker**
  - resolves references between files
  - combines with static run-time libraries
    - » e.g., code for `printf`
  - some libraries are *dynamically linked*
    - » linking occurs when program begins execution

Supplied by CMU.

Instruction Format



This is taken from Intel Architecture Software Developer’s Manual, Volume 2: Instruction Set Reference; Order Number 243191, Intel Corporation, 1999.

Disassembling Object Code

Disassembled

```
080483c4 <sum>:
 80483c4:  55         push   %ebp
 80483c5:  89 e5      mov    %esp,%ebp
 80483c7:  8b 45 0c   mov    0xc(%ebp),%eax
 80483ca:  03 45 08   add    0x8(%ebp),%eax
 80483cd:  5d         pop    %ebp
 80483ce:  c3         ret
```

- **Disassembler**

  `objdump -d <file>`

  – useful tool for examining object code

  – analyzes bit pattern of series of instructions

  – produces approximate rendition of assembly code

  – can be run on either executable or object (`.o`) file

Supplied by CMU.

Alternate Disassembly

Object

```
0x401040:
    0x55
    0x89
    0xe5
    0x8b
    0x45
    0x0c
    0x03
    0x45
    0x08
    0x5d
    0xc3
```

Disassembled

```
Dump of assembler code for function sum:
0x080483c4 <sum+0>:     push   %ebp
0x080483c5 <sum+1>:     mov    %esp,%ebp
0x080483c7 <sum+3>:     mov    0xc(%ebp),%eax
0x080483ca <sum+6>:     add    0x8(%ebp),%eax
0x080483cd <sum+9>:     pop    %ebp
0x080483ce <sum+10>:    ret
```

- **Within gdb debugger**

```
gdb <file>
disassemble sum
```

– **disassemble procedure**

```
x/11xb sum
```

– **examine the 11 bytes starting at** `sum`

Supplied by CMU.

How Many Instructions are There?

- We cover ~29
- Implemented by Intel:
  - 80 in original 8086 architecture
  - 7 added with 80186
  - 17 added with 80286
  - 33 added with 386
  - 6 added with 486
  - 6 added with Pentium
  - 1 added with Pentium MMX
  - 4 added with Pentium Pro
  - 8 added with SSE
  - 8 added with SSE2
  - 2 added with SSE3
  - 14 added with x86-64
  - 10 added with VT-x
  - 2 added with SSE4a
- Total: 198
- Doesn't count:
  - floating-point instructions
  - SIMD instructions
  - AMD-added instructions
  - undocumented instructions

The source for this is http://en.wikipedia.org/wiki/X86_instruction_listings, viewed on 9/18/2012, and also depends upon my ability to count.

Some Arithmetic Operations

- **Two-operand instructions:**

Format		Computation	
`addl`	Src,Dest	Dest = Dest + Src	
`subl`	Src,Dest	Dest = Dest - Src	
`imull`	Src,Dest	Dest = Dest * Src	
`sall`	Src,Dest	Dest = Dest << Src	Also called shll
`sarl`	Src,Dest	Dest = Dest >> Src	Arithmetic
`shrl`	Src,Dest	Dest = Dest >> Src	Logical
`xorl`	Src,Dest	Dest = Dest ^ Src	
`andl`	Src,Dest	Dest = Dest & Src	
`orl`	Src,Dest	Dest = Dest | Src	

  - watch out for argument order!
  - no distinction between signed and unsigned int (why?)

Supplied by CMU.

Some Arithmetic Operations

- **One-operand Instructions**

`incl`	Dest	= Dest + 1
`decl`	Dest	= Dest - 1
`negl`	Dest	= - Dest
`notl`	Dest	= ~Dest

- **See book for more instructions**

Supplied by CMU.

Arithmetic Expression Example

```
int arith(int x, int y, int z)
{
  int t1 = x+y;
  int t2 = z+t1;
  int t3 = x+4;
  int t4 = y * 48;
  int t5 = t3 + t4;
  int rval = t2 * t5;
  return rval;
}
```

```
arith:
    leal   (%rdi,%rsi), %eax
    addl   %edx, %eax
    leal   (%rsi,%rsi,2), %edx
    sall   $4, %edx
    leal   4(%rdi,%rdx), %ecx
    imull  %ecx, %eax
    ret
```


Supplied by CMU, but converted to x86-64.

Understanding `arith`

```c
int arith(int x, int y, int z)
{
  int t1 = x+y;
  int t2 = z+t1;
  int t3 = x+4;
  int t4 = y * 48;
  int t5 = t3 + t4;
  int rval = t2 * t5;
  return rval;
}
```

%rdx	z
%rsi	y
%rdi	x

```
    leal  (%rdi,%rsi), %eax
    addl  %edx, %eax
    leal  (%rsi,%rsi,2), %edx
    sall  $4, %edx
    leal  4(%rdi,%rdx), %ecx
    imull %ecx, %eax
    ret
```


Supplied by CMU, but converted to x86-64.

Understanding `arith`

```
int arith(int x, int y, int z)
{
  int t1 = x+y;
  int t2 = z+t1;
  int t3 = x+4;
  int t4 = y * 48;
  int t5 = t3 + t4;
  int rval = t2 * t5;
  return rval;
}
```

%rdx	z
%rsi	y
%rdi	x

```
leal   (%rdi,%rsi), %eax    # eax = x+y     (t1)
addl   %edx, %eax           # eax = t1+z    (t2)
leal   (%rsi,%rsi,2), %edx  # edx = 3*y     (t4)
sall   $4, %edx             # edx = t4*16   (t4)
leal   4(%rdi,%rdx), %ecx   # ecx = x+4+t4  (t5)
imull  %ecx, %eax           # eax *= t5     (rval)
ret
```


Supplied by CMU, but converted to x86-64.

By convention, the first three arguments to a procedure are placed in registers rdi, rsi, and rdx, respectively. Note that, also by convention, procedures put their return values in register eax/rax.

Observations about `arith`

```
int arith(int x, int y, int z)
{
  int t1 = x+y;
  int t2 = z+t1;
  int t3 = x+4;
  int t4 = y * 48;
  int t5 = t3 + t4;
  int rval = t2 * t5;
  return rval;
}
```

- Instructions in different order from C code
- Some expressions might require multiple instructions
- Some instructions might cover multiple expressions

```
leal   (%rdi,%rsi), %eax     # eax = x+y     (t1)
addl   %edx, %eax            # eax = t1+z    (t2)
leal   (%rsi,%rsi,2), %edx   # edx = 3*y     (t4)
sall   $4, %edx              # edx = t4*16   (t4)
leal   4(%rdi,%rdx), %ecx    # ecx = x+4+t4  (t5)
imull  %ecx, %eax            # eax *= t5     (rval)
ret
```


Supplied by CMU, but converted to x86-64.

Another Example

```
int logical(int x, int y)
{
  int t1 = x^y;
  int t2 = t1 >> 17;
  int mask = (1<<13) - 7;
  int rval = t2 & mask;
  return rval;
}
```

$2^{13} = 8192, 2^{13} - 7 = 8185$

```
xorl %esi, %edi       # edi = x^y        (t1)
sarl $17, %edi        # edi = t1>>17     (t2)
movl %edi, %eax       # eax = edi
andl $8185, %eax      # eax = t2 & mask (rval)
```


Supplied by CMU, but converted to x86-64.

Quiz 3

- **What is the final value in %esi?**

```
xorl %esi, %esi
incl %esi
sall %esi, %esi
addl %esi, %esi
```

a) 2
b) 4
c) 8
d) indeterminate