Showing results for https://patman89.github.io/DSW-PedroTobar/

Checker Input

Show ☐ source ☐ outline ☐ image report [Options...]

Check by [address ▾]

`https://patman89.github.io/DSW-PedroTobar/`

[Check]

Use the Message Filtering button below to hide/show particular messages, and to see total counts of errors and warnings.

[Message Filtering]

1. **Warning** Article lacks heading. Consider using `h2` - `h6` elements to [add identifying headings to all articles](#).

   From line 42, column 9; to line 42, column 17

   `>↵        <article>↵`

2. **Warning** Section lacks heading. Consider using `h2` - `h6` elements to [add identifying headings to all sections](#).

   From line 41, column 5; to line 41, column 13

   `ader>↵    <section>↵`

3. **Warning** The `charset` attribute on the `script` element is obsolete.

   From line 57, column 179; to line 57, column 254

   `dUNAD</a> <script async src="https://platform.twitter.com/widgets.js" charset="utf-8"></scri`

4. **Error** Attribute `clase` not allowed on element `section` at this point.

   From line 60, column 5; to line 60, column 31

   `side>↵    <section clase="objetivos">↵`

   Attributes for element section:
      Global attributes

5. **Error** No `p` element in scope but a `p` end tag seen.

   From line 65, column 86; to line 65, column 89

   `iseño web.</p>↵`

6. **Error** No `p` element in scope but a `p` end tag seen.

   From line 67, column 21; to line 67, column 24

   `        </p><br>↵`

7. **Error** Element `br` not allowed as child of element `ul` in this context. (Suppressing further errors from this subtree.)

   From line 70, column 163; to line 70, column 166

   `". </li> <br> <br>`

   Contexts in which element br may be used:
      Where phrasing content is expected.
   Content model for element ul:
      Zero or more li and script-supporting elements.

8. **Error** Element `br` not allowed as child of element `ul` in this context. (Suppressing further errors from this subtree.)

   From line 70, column 168; to line 70, column 171

   `li>  <br> <br>  ↵`

   Contexts in which element br may be used:
      Where phrasing content is expected.
   Content model for element ul:
      Zero or more li and script-supporting elements.

9. **Warning** Section lacks heading. Consider using `h2` - `h6` elements to [add identifying headings to all sections](#).

   From line 60, column 5; to line 60, column 31

   `side>↵    <section clase="objetivos">↵`

10. **Error** Stray start tag `script`.

    From line 87, column 1; to line 87, column 30

    `>↵</body>↵<script src="js/modernizr.js"></scri`