

UPDATED DATA MODEL (cohort leads + staged onboarding + merged insights + themes)
Below is the updated conceptual model (clean and buildable).

Identity & access

User

- user_id
- email
- password_hash
- status (invited, active, suspended)
- created_at
- last_login

Profile

- profile_id
- user_id
- title
- first_name
- surname
- role_title
- country_of_residence
- organisation_name
- professional_bio (<=200 words)
- visibility_setting (members_only / limited / hidden)
- updated_at

DomainTag

- tag_id
- name
- category (domain / geography / constituency / process)

UserTag

- user_id
- tag_id

Cohorts

Cohort

- cohort_id
- name (Academic, Policy, Industry, CSO)
- description

UserCohort (many-to-many)

- user_id
- cohort_id
- is_primary (boolean)

CohortLead (many-to-many)

- cohort_id
- user_id
- lead_role (lead / co_lead / deputy)
- start_date
- end_date (nullable)

Membership application / invite workflow (new)

CommunityApplication

- application_id
- submitted_by_email
- first_name
- surname
- country
- organisation
- role_title
- motivation_text
- cohort_interests (array or separate table)
- domain_interests (array or separate table)
- status (submitted / interviewing / approved / waitlist / decline

d)

- reviewed_by_user_id
- review_notes

- created_at
- updated_at

Invite

- invite_id
- application_id (nullable)
- email
- temp_password_hash (or token)
- invite_token
- expires_at
- used_at

Community spaces

Space (formerly CommunityGroup)

- space_id
- name
- space_type (cohort / constituency / working_group / geography)
- description
- visibility (public_members / private / invite_only)
- created_by
- created_at

SpaceMembership

- space_id
- user_id
- role (member / moderator / lead)
- joined_at

Discussions

Thread

- thread_id
- space_id
- author_id
- title
- body
- created_at

Comment

- comment_id
- thread_id
- author_id
- body
- created_at

Unified publishing: Insights / Knowledge hub

ContentItem

- content_id
- title
- content_type (blog, news, brief, report, event_output, learning_note)
- summary
- body (rich text)
- author_id
- publish_status (draft / published)
- visibility (public / members / restricted)
- published_at
- created_at

ContentAttachment

- attachment_id
- content_id
- file_url
- file_type
- title

ContentTagMap

- content_id

- tag_id

ContentCohortRelevance (optional but useful)

- content_id
- cohort_id

(This makes it easy to filter “relevant to Policy Cohort”, etc.)

Work With Us pipeline (new)

ServiceRequest

- request_id
- requester_name
- requester_email
- organisation
- country
- request_type (briefing / analysis / coordination / convening / o

ther)

- decision_context
- timeline
- details
- status (new / in_review / meeting / active / closed)
- assigned_to_user_id
- created_at

PartnershipLead

- lead_id
- name
- email
- organisation
- org_type
- focus_areas
- support_type
- budget_range (optional)
- success_definition
- status
- assigned_to_user_id
- created_at

CollaborationLead

- lead_id
- name
- email
- organisation
- collaboration_type
- proposal
- status
- assigned_to_user_id
- created_at

UPDATED PRODUCT ROADMAP (phased)

Phase 0 (Now): content + structure design

- Finalise site map + platform map
- Finalise tags taxonomy (domains + constituencies)
- Finalise onboarding forms + admin workflow

Phase 1: Website + publishing (public)

- Public website pages
- Unified Insights publishing (blog + resources combined)
- Admin CMS for posts, tags, attachments
- Work With Us forms → pipeline dashboard

Phase 2: Community (members-only)

- Application form (motivation)
- Admin interview workflow + approval
- Invite link + temporary password
- Full onboarding profile capture
- Member directory with cohort + tags
- Spaces (cohort + constituency + working groups)

- Discussions

Phase 3: Knowledge Hub (members-only)

- Same Insights library + restricted items
- Filters by content type, cohort relevance, tags
- Bookmarking / saved items (optional)

Phase 4: AI integration (RAG + LLM)

- Content indexing + embeddings
- Role-aware AI chat (“Ask PATNA”)
- Answers with citations back to ContentItems
- Later: summarise threads, recommend people/spaces

Small but important implementation note

Because AI comes later, ensure Phase 1–3 already enforce:

- consistent tagging
- content type discipline
- visibility rules
- clean metadata

That’s what makes Phase 4 easy instead of painful.

1) Platform sitemap

Public (no login)

- / Home
- /about About PATNA
- /what-we-do What We Do
- /focus-areas Focus Areas
- /insights Insights (merged Blog + Knowledge content; public item

s only)

- /insights/{slug} Insight detail
- /events Events (list)
- /events/{slug} Event detail
- /projects Projects (list)
- /projects/{slug} Project detail
- /community Community (explainer + “Join” CTA)
- /community/join Join PATNA Community (Expression of Interest for

m)

- /work-with-us Work With Us (three pathways)
- /work-with-us/request-support Request Support / Briefing form
- /work-with-us/partner Partner / Fund form
- /work-with-us/collaborate Collaborate / Co-create form
- /contact Contact
- /legal
- /legal/privacy
- /legal/terms
- /legal/accessibility

Auth (account access)

- /auth/login Login
- /auth/forgot-password Forgot password
- /auth/reset-password Reset password
- /auth/invite/{token} Accept invite + set new password (temporary

password flow if used)

Member (logged-in)

- /app Member dashboard
- /app/onboarding Complete onboarding (full profile capture)
- /app/profile My profile (view/edit)
- /app/profile/visibility Visibility settings
- /app/members Member directory
- /app/members/{id} Member profile
- /app/spaces Spaces directory (all spaces user can see)
- /app/spaces/{slug} Space home
- /app/spaces/{slug}/threads Threads list
- /app/spaces/{slug}/threads/new Create thread
- /app/spaces/{slug}/threads/{thread_id} Thread detail
- /app/insights Insights library (public + members-only items)
- /app/insights/{slug} Insight detail
- /app/insQ Tag filter UI, saved filters (optional later)
- /app/bookmarks Saved items (optional, Phase 3)
- /app/settings Account settings
- /app/settings/password
- /app/settings/notifications (optional)
- (Phase 4 later) /app/ai Ask PATNA (AI chat)

Admin (role-based access)

- /admin Admin dashboard
- /admin/applications Community applications (EOIs)
- /admin/applications/{id} Review application (status, notes)
- /admin/invites Invites management
- /admin/users Users
- /admin/users/{id} User detail + cohort/space assignment
- /admin/cohorts Cohorts & cohort leads
- /admin/spaces Spaces management (cohort/constituency/working gro

up/geography)

- /admin/content Content (Insights unified publishing)
- /admin/content/new
- /admin/content/{id}/edit
- /admin/tags Tag taxonomy (domain / constituency / geography / process)
- /admin/events Events CRUD (if kept separate from content)
- /admin/projects Projects CRUD (if kept separate from content)
- /admin/work-with-us Pipelines
- /admin/work-with-us/service-requests
- /admin/work-with-us/partnership-leads
- /admin/work-with-us/collaboration-leads

2) Screen list (with key actions)

Public

- Home
- Primary CTAs: Learn More, Join Community, Work With Us
- About
- What We Do
- Focus Areas
- Insights (Public)
- Filter by content type + tags
- Insight Detail
- Related insights, share, (optional) download attachments
- Community Landing
- Explains cohorts + how joining works
- Join Community (EOI Form)
- Submit short form (motivation)
- Work With Us Landing
- Choose: Request Support / Partner / Collaborate
- Request Support Form
- Partner / Fund Form
- Collaborate Form
- Projects list + detail (if needed)
- Events list + detail (if needed)
- Contact
- Legal pages

Auth

- Login
- Forgot password
- Reset password
- Accept Invite
- Enter temp password (if used) → set new password → proceed

Member (logged-in)

- Member Dashboard
- Quick links: spaces, directory, insights, complete profile
- Onboarding (Complete profile)
- Personal/professional info + cohort selection + tags + visibility

y

- My Profile
- Member Directory
- Filters: cohort(s), tags, geography
- Member Profile
- Spaces Directory
- Space Home
- About + pinned posts + join/leave (where permitted)
- Threads List
- Create Thread
- Thread Detail
- Comment, react, follow
- Insights Library (Members)
- Shows public + members/restricted (per access)
- Insight Detail (Members)

- Bookmarks (optional Phase 3)
 - Account Settings
- Admin
- Admin Dashboard
 - Applications list
 - Application review
 - Update status: submitted → interviewing → approved/waitlist/declined
- Add notes, assign reviewer
 - Invites management
 - Generate invite token, set expiry
 - Users management
 - Assign cohorts, spaces, roles
 - Cohorts management
 - Assign cohort leads (1+)
 - Spaces management
 - Create cohort/constituency/working group spaces
 - Content management
 - Create/edit/publish Insights (blog + briefs + reports, etc.)
 - Tags management
 - Work With Us pipelines
 - Triaging requests/leads, assigning owners, status updates

3) Database schema draft (Postgres SQL)

This is a practical starting schema. You can simplify further or extend later (Add more tables in Phase 4).

```
-- =====
-- Core: users + profiles
-- =====
```

```
create type user_status as enum ('invited', 'active', 'suspended');
create type visibility_setting as enum ('members_only', 'limited', 'hidden');
```

```
create table users (
  id          uuid primary key default gen_random_uuid(),
  email       citext unique not null,
  password_hash text not null,
  status      user_status not null default 'invited',
  created_at  timestampz not null default now(),
  last_login_at timestampz
);
```

```
create table profiles (
  user_id      uuid primary key references users(id) on delete cascade,
  title        text,
  first_name   text not null,
  surname      text not null,
  role_title   text,
  country_of_residence text,
  organisation_name text,
  professional_bio text, -- enforce 200 words in app layer
  visibility    visibility_setting not null default 'members_only',
  updated_at   timestampz not null default now()
);
```

```
-- =====
-- Cohorts + cohort leads
-- =====
```

```
create table cohorts (
  id          uuid primary key default gen_random_uuid(),
```

```

    name      text unique not null, -- Academic, Policy, Industry, CSO
description  text
);

create table user_cohorts (
    user_id      uuid references users(id) on delete cascade,
    cohort_id    uuid references cohorts(id) on delete cascade,
    is_primary   boolean not null default false,
    created_at   timestampz not null default now(),
    primary key (user_id, cohort_id)
);

create type cohort_lead_role as enum ('lead', 'co_lead', 'deputy');

create table cohort_leads (
    cohort_id    uuid references cohorts(id) on delete cascade,
    user_id      uuid references users(id) on delete cascade,
    lead_role    cohort_lead_role not null default 'lead',
    start_date   date,
    end_date     date,
    primary key (cohort_id, user_id)
);

-- Ensure at most one primary cohort per user (optional constraint)
create unique index ux_user_primary_cohort
on user_cohorts(user_id)
where is_primary = true;

-- =====
-- Tag taxonomy (domain/constituency/geography/process)
-- =====

create type tag_category as enum ('domain', 'geography', 'constituency', 'process');

create table tags (
    id           uuid primary key default gen_random_uuid(),
    name        text not null,
    category     tag_category not null,
    created_at   timestampz not null default now(),
    unique (category, name)
);

create table user_tags (
    user_id      uuid references users(id) on delete cascade,
    tag_id       uuid references tags(id) on delete cascade,
    primary key (user_id, tag_id)
);

-- =====
-- Community applications + invites (Join Community gate)
-- =====

create type application_status as enum ('submitted', 'interviewing', 'approved', 'waitlist', 'declined');

create table community_applications (
    id           uuid primary key default gen_random_uuid(),
    submitted_email citext not null,
    first_name   text,
    surname      text,
    country      text,

```



```

organisation      text,
role_title        text,
motivation_text   text not null,
status            application_status not null default 'submitted',
reviewed_by_user_id uuid references users(id) on delete set null,
review_notes      text,
created_at        timestamptz not null default now(),
updated_at        timestamptz not null default now()
);

-- Optional: store cohort interests as normalized rows
create table application_cohort_interests (
  application_id uuid references community_applications(id) on delete cascade,
  cohort_id      uuid references cohorts(id) on delete restrict,
  primary key (application_id, cohort_id)
);

-- Optional: store domain interests as normalized tags
create table application_tag_interests (
  application_id uuid references community_applications(id) on delete cascade,
  tag_id        uuid references tags(id) on delete restrict,
  primary key (application_id, tag_id)
);

create table invites (
  id                uuid primary key default gen_random_uuid(),
  application_id    uuid references community_applications(id) on delete set null,
  email            citext not null,
  invite_token      text unique not null,
  temp_password_hash text, -- if using temp password; else null and use magic link
  expires_at        timestamptz not null,
  used_at           timestamptz,
  created_at        timestamptz not null default now()
);

-- =====
-- Spaces (cohort / constituency / working group / geography)
-- =====

create type space_type as enum ('cohort', 'constituency', 'working_group', 'geography');
create type space_visibility as enum ('public_members', 'private', 'invite_only');
create type membership_role as enum ('member', 'moderator', 'lead');

create table spaces (
  id                uuid primary key default gen_random_uuid(),
  slug              text unique not null,
  name              text not null,
  space_type        space_type not null,
  description        text,
  visibility         space_visibility not null default 'public_members',
  created_by        uuid references users(id) on delete set null,
  created_at        timestamptz not null default now()
);

create table space_memberships (
  space_id          uuid references spaces(id) on delete cascade,
  user_id           uuid references users(id) on delete cascade,
  role              membership_role not null default 'member',
  joined_at         timestamptz not null default now(),

```

```

    primary key (space_id, user_id)
);

-- =====
-- Discussions
-- =====

create table threads (
    id          uuid primary key default gen_random_uuid(),
    space_id    uuid references spaces(id) on delete cascade,
    author_id   uuid references users(id) on delete set null,
    title       text not null,
    body        text not null,
    created_at  timestampz not null default now()
);

create table comments (
    id          uuid primary key default gen_random_uuid(),
    thread_id   uuid references threads(id) on delete cascade,
    author_id   uuid references users(id) on delete set null,
    body        text not null,
    created_at  timestampz not null default now()
);

-- Optional: tagging threads (use same tags table)
create table thread_tags (
    thread_id   uuid references threads(id) on delete cascade,
    tag_id      uuid references tags(id) on delete cascade,
    primary key (thread_id, tag_id)
);

-- =====
-- Unified publishing: Insights (blog + briefs + reports + event outputs)
-- =====

create type content_type as enum ('blog', 'news', 'brief', 'report', 'event_output', 'learning_note');
create type publish_status as enum ('draft', 'published');
create type content_visibility as enum ('public', 'members', 'restricted');

create table content_items (
    id          uuid primary key default gen_random_uuid(),
    slug        text unique not null,
    title       text not null,
    content_type content_type not null,
    summary     text,
    body        text, -- rich text stored as HTML/Markdown
    author_id   uuid references users(id) on delete set null,
    publish_status publish_status not null default 'draft',
    visibility   content_visibility not null default 'public',
    published_at timestampz,
    created_at  timestampz not null default now(),
    updated_at  timestampz not null default now()
);

create table content_attachments (
    id          uuid primary key default gen_random_uuid(),
    content_id   uuid references content_items(id) on delete cascade,
    title       text,
    file_url    text not null,
    file_type   text,
    created_at  timestampz not null default now()
);

```

```

);

create table content_tags (
    content_id uuid references content_items(id) on delete cascade,
    tag_id      uuid references tags(id) on delete cascade,
    primary key (content_id, tag_id)
);

-- Optional: explicit cohort relevance for content
create table content_cohort_relevance (
    content_id uuid references content_items(id) on delete cascade,
    cohort_id  uuid references cohorts(id) on delete cascade,
    primary key (content_id, cohort_id)
);

-- =====
-- Work With Us pipelines
-- =====

create type request_status as enum ('new', 'in_review', 'meeting_scheduled', 'active', 'closed');

create table service_requests (
    id                uuid primary key default gen_random_uuid(),
    requester_name    text not null,
    requester_email   citext not null,
    organisation       text,
    country           text,
    request_type       text, -- or enum if you want tight control
    decision_context   text,
    timeline           text,
    details            text not null,
    status             request_status not null default 'new',
    assigned_to_user_id uuid references users(id) on delete set null,
    created_at         timestampz not null default now()
);

create table partnership_leads (
    id                uuid primary key default gen_random_uuid(),
    name              text not null,
    email             citext not null,
    organisation       text,
    org_type          text,
    focus_areas       text,
    support_type       text,
    budget_range      text,
    success_definition text,
    status            request_status not null default 'new',
    assigned_to_user_id uuid references users(id) on delete set null,
    created_at         timestampz not null default now()
);

create table collaboration_leads (
    id                uuid primary key default gen_random_uuid(),
    name              text not null,
    email             citext not null,
    organisation       text,
    collaboration_type text,
    proposal           text not null,
    status            request_status not null default 'new',
    assigned_to_user_id uuid references users(id) on delete set null,
    created_at         timestampz not null default now()
);

```

);

```
-- =====  
-- Helpful indexes (starter set)  
-- =====
```

```
create index ix_threads_space_created on threads(space_id, created_at desc);  
create index ix_comments_thread_created on comments(thread_id, created_at asc);  
create index ix_content_published on content_items(publish_status, published_at  
desc);  
create index ix_space_type on spaces(space_type);
```

Notes (implementation choices you can decide quickly)

- Temp password vs magic link: the schema supports either (temp_password_hash optional).
- Bio word limit: easiest to enforce in the UI/API; DB can enforce max chars if you want.
- Events/Projects: you can either keep separate tables or publish them as content_type = event_output / news. I left them out of schema for simplicity, since you asked for merged blog+knowledge and admin-friendly publishing.

1) Role definitions

Platform roles (global)

- Visitor (not logged in)
- Applicant (submitted EOI form; not yet a member)
- Member (approved + onboarded)
- Cohort Lead (member with lead permissions for one/more cohorts)
- Moderator (member trusted to moderate one/more spaces; not necessarily cohort lead)

Secretariat Admin (full operational admin)

- Content Editor (optional separate role) (publishing without full admin powers)

Space roles (per space)

- Member
- Moderator
- Lead (used for cohort spaces; often cohort leads)

2) Permissions matrix (core)

Legend:  allowed |  allowed with constraints |  not allowed

A) Account & onboarding

Capability

Visitor

Applicant

Member

Cohort Lead

Moderator

Content Editor

Secretariat Admin

Submit "Join Community" EOI form



View application status (self)



(if they applied again)

Approve / decline applications



 recommend / shortlist only



Add interview notes to applications



 for their cohort only



Send invite link / issue temp password



Complete onboarding profile

⚠ only after invite

 Edit own profile

✓ Edit another member's profile

⚠ limited fields, cohort-related

Suspend / reactivate user

Constraint note (Cohort Leads): cohort leads can review and recommend candidates for their cohort, but final approval + invite issuance sits with Secretariat Admin (reduces risk).

B) Cohorts

Capability

Applicant

Cohort Lead

Moderator

Secretariat Admin

Join cohort

 request / apply
 assign within their cohort

 Assign member to cohort(s)

 for their cohort only

 Set member's primary cohort

 self-select
 recommend / request

 Manage cohort profile (description, info)

 propose edits

 Assign/remove cohort lead

 C) Spaces (cohort / constituency / working groups / geography)

Capability

Visitor

Applicant

Member

Cohort Lead

Moderator

Content Editor

Secretariat Admin

View public spaces list (teaser)















View member spaces list













Join/leave a space



depends on visibility



can invite to cohort space



can invite



Create a new space



request; admin creates



request; admin creates



Edit space settings



for cohort space only



for assigned spaces only



Assign moderators for a space



recommend



recommend



Pin cohort announcements in cohort space



if assigned



Visibility rules:



public_members: any member can join



private: only members invited/approved to join



invite_only: only admin (and optionally space leads) can add mem

bers

D) Discussions (threads, comments, reactions)

Capability

Visitor

Applicant

Member

Cohort Lead

Moderator

Content Editor

Secretariat Admin

Read discussions in member spaces





Create thread in a space they belong to



Comment in a thread



Edit own thread/comment



Delete own thread/comment



within time window



Hide/remove others' posts



in cohort space only



in assigned spaces



in cohort space only



in assigned spaces



for their space only



for assigned spaces



E) Member directory & messaging/contact
Capability

Visitor

Applicant
Member
Cohort Lead
Moderator
Content Editor
Secretariat Admin
View member directory



Filter members by cohort/tags



View full member profile



depends on visibility



Contact member



if member opted-in



Export directory (CSV)



F) Tags (domains, constituencies like SIDS/LDCs, geography, process)

Capability

Visitor

Applicant

Member

Cohort Lead

Moderator

Content Editor

Secretariat Admin

Select tags for own profile





Propose new tag



request



request



request



request



G) Content publishing (Insights + Knowledge Hub merged)

Capability

Visitor

Applicant

Member

Cohort Lead

Moderator

Content Editor

Secretariat Admin

Read public Insights



Create draft post



propose content



Edit own draft



Publish post



if allowed



if granted

Set visibility (public/members/restricted)

limited

Tag content + mark cohort relevance

for their cohort relevance

Upload attachments

Manage authors

limited

Recommended default:

- Publishing power stays with Secretariat Admin.
- Content Editor can draft + edit + schedule posts; admin approves

/publishes.

H) Work With Us pipeline (requests/leads)

Capability

Visitor

Applicant

Member

Cohort Lead

Moderator

Content Editor

Secretariat Admin

Submit Work With Us form

View own submitted ticket status



via email updates

View all tickets

if assigned

Assign owner / change status

if assigned

Add internal notes

if assigned

Convert lead → project/program

3) Recommended practical roles setup (minimal but sufficient)

To keep implementation simple, start with only these platform roles:

- Member
- Cohort Lead (flag on user + cohort_leads table)
- Moderator (space_memberships.role = moderator)
- Admin (secretariat)
- Content Editor (optional, if you want separation)

Everything else can be derived from status:

- Visitor (not logged in)
- Applicant (has application record, no user yet or status invited)

)

4) Enforcement rules (the “guardrails”)

These are small but important:

- Cohort lead scope Cohort leads can only manage:
- cohort space moderation
- cohort relevance tagging for content
- application recommendations for their cohort They cannot create invites or change user status.
- Space visibility overrides Even if someone is in a cohort, access still depends on:
- space visibility settings
- membership record

public. •

Publishing approvals At least one admin approves content set to