

Stopping all running Kubernetes Cluster using the Automation Account

Azure@DTIT Cloud February 8, 2023, 11:33 AM

Steps:

Create a managed identity in the subscription

Grant Contributor rights to the managed identity on the subscription scope (we will create a custom role with less rights in the near future)

Go to the automation account in resource group rg-automation of your subscription and add this managed identity to the automation account: Identity=> user managed identity => add the managed identity from above. Configure the following two variables in the automation account: (i) The PrincipalID of the managed identity. The variable name must be "aksStopIdentity". (ii) The subscription ID of the subscription. The variable name must be "subscriptionId"

Create a runbook for powershell, runtime 7.1(preview) and name it like you wishes. Suggestion: stopAksClusters

Create a schedule in the automation account, when you want to stop the Clusters

Associate the runbook with the schedule.

The example code on Powershell:

```
$id = Get-AutomationVariable -Name aksStopIdentity
$subid = Get-AutomationVariable -Name subscriptionId
write-output "Connecting..."
Connect-AzAccount -Identity -AccountId $id
write-output "setting context of subscription"
set-AzContext -subscriptionId $subid
get-azakscluster
$res = get-azakscluster | select-object -Property name,resourcegroupname
foreach ($rec in $res) {
    try {
        write-output "stopping Cluster $($rec.name) in resource group $($rec.resourcegroupname)"
        Stop-AzAksCluster -Name $($rec.name) -ResourceGroupName $($rec.resourcegroupname)
    }
    catch {
        Write-Error -Message $_.Exception
    }
}
```