



Try for free



Configuration (POST)

Retrieve and update a product's configuration from a configurator. Execute configuration rules and notify users of any violations for changes to product bundle, attributes, or product quantity within a bundle. Additionally, get pricing details for the configured bundle.

Resource



```
1 /connect/cpq/configurator/actions/configure
```

Resource example



```
1 https://yourInstance.salesforce.com/services/data/v67.0/connect/cpq/configurator/action
```

Available version

60.0

HTTP methods

POST

Request body for POST

JSON example

This example shows a sample to initiate a context based on a transaction ID.



```
1 {
2   "transactionLineId": "0QLDE000000IBXw4A0",
3   "transactionId": "0Q0xx0000000001GAA",
4   "correlationId": "c95246d4-102c-4ecd-a263-f74ac525d1e5",
5   "configuratorOptions": {
6     "executePricing": true,
7     "returnProductCatalogData": true
8   },
9   "qualificationContext": {
10    "accountId": "001xx0000000001AAA",
11    "contactId": "003xx0000000007AAI"
12  }
13 }
```

This example shows a sample to add, update, or delete a node in an existing context.



```
1 {
2   "transactionLineId": "0QLDE000000IBXw4A0",
3   "transactionId": "0Q0DE000000ISHJs81",
```



```
10     "validateAmendRenewCancel": true,
11     "executeConfigurationRules": true,
12     "addDefaultConfiguration": true
13 },
14 "contextResponseType": "Full",
15 "qualificationContext": {
16     "accountId": "001xx0000000001AAA",
17     "contactId": "003xx0000000007AAI"
18 },
19 "transactionContextId": "008d27d7-e004-4906-a949-ee7d7c323c77",
20 "addedNodes": [
21     {
22         "path": ["0Q0DE000000ISHJs81", "sti2_id"],
23         "addedObject": {
24             "id": "ref_sti2_id",
25             "SalesTransactionSource": "sti2_id",
26             "PricebookEntry": "01uxx0000000001AAA",
27             "ProductSellingModel": "0jPxx0000000001AAA",
28             "businessObjectType": "QuoteLineItem",
29             "Quantity": 10,
30             "UnitPrice": 2.0,
31             "Product": "01txx0000000001AAA"
32         }
33     },
34     {
35         "path": ["0Q0DE000000ISHJs81", "ref_sti2_id", "ref_stir1_id"],
36         "addedObject": {
37             "id": "ref_stir1_id",
38             "businessObjectType": "QuoteLineItemRelationship",
39             "MainItem": "0QLDE000000IBXw4A0",
40             "AssociatedItem": "ref_sti2_id",
41             "ProductRelatedComponent": "0dSxx0000000001AAA",
42             "ProductRelationshipType": "0yoxx0000000001AAA",
43             "AssociatedItemPricing": "IncludedInBundlePrice"
44         }
45     }
46 ],
47 "updatedNodes": [
48     {
49         "path": ["0Q0DE000000ISHJs81", "0QLDE000000IBXw4A0"],
50         "updatedAttributes": {
51             "Quantity": 5
52         }
53     }
54 ],
55 "deletedNodes": [
56     {
57         "path": ["0Q0DE000000ISHJs81", "0QLDE000000IBXw4A0"]
58     }
59 ]
60 ]
61 }
```

Properties

Name	Type	Description	Required or Optional	Available Version
addedNodes	Configurator Added Node Input[]	List of added context nodes that's passed to the product configurator.	Optional	60.0



Options	Options Input[]	configurator.		
context ResponseType	String	Specifies the type of transaction context response. Valid values are: • Delta—Returns the sales transaction items that are added or updated. • Full—Returns all sales transaction items in a transaction. • None—Returns empty transaction context response. • Product—Returns the sales transaction items related to the product that's being configured.	Required for large sales transactions with more than 1000 line items and less than 15K line items.	65.0
correlationId	String	ID that's specified for traceability of logs.	Optional	60.0
deletedNodes	Configurator Deleted Node Input[]	List of deleted context nodes that's passed to the product configurator.	Optional	60.0
qualification Context	User Context Input[]	Details such as account ID, contact ID, and context ID that are used for executing qualification rules.	Optional	60.0
transaction ContextId	String	ID of the transaction context.	Optional	60.0
transactionId	String	ID of the sales transaction that's being configured such as a quote or an order.	Required	60.0
transaction LineId	String	ID of the top-level line item that's being configured.	Optional	60.0
updatedNodes	Configurator Updated Node Input[]	List of updated context nodes that's passed to the product configurator.	Optional	60.0

Response body for POST

[Configuration Details](#)



Try for free



DEVELOPER CENTERS

- Heroku
- MuleSoft
- Tableau
- Commerce Cloud
- Lightning Design System
- Einstein
- Quip

POPULAR RESOURCES

- Documentation
- Component Library
- APIs
- Trailhead
- Sample Apps
- AppExchange

COMMUNITY

- Trailblazer Community
- Events and Calendar
- Partner Community
- Blog
- Salesforce Admins
- Salesforce Architects

© Copyright 2026 Salesforce, Inc. [All rights reserved](#). Various trademarks held by their respective owners. Salesforce, Inc. Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Legal](#) [Terms of Service](#) [Privacy Information](#) [Responsible Disclosure](#) [Trust](#) [Contact](#) [Use of Cookies](#)

[Cookie Preferences](#)  [Your Privacy Choices](#)

