



Configuration Load Instance (POST)

Create a session for the product configuration instance using the transaction ID. Get the session ID that includes the results of actions, such as configuration rules, qualification rules, and pricing management.

Resource

</>

🔍 | 📄

```
1 /connect/cpq/configurator/actions/load-instance
```

Resource example

</>

🔍 | 📄

```
1 https://yourInstance.salesforce.com/services/data/v67.0/connect/cpq/configur
```

Available version

60.0

HTTP methods

POST

Request body for POST

JSON example

</>

🔍 | 📄

```
1 {
2   "configuratorOptions":
3     {
4       "addDefaultConfiguration": true,
5       "executeConfigurationRules": true,
6       "executePricing": true,
7       "qualifyAllProductsInTransaction": true,
8       "validateAmendRenewCancel": true,
9       "validateProductCatalog": true
10    },
11   "qualificationContext": {
12     "accountId": "001DU000001nHUGYA2"
13   },
14   "transactionId": "0Q0DU000000XoN0AU"
15 }
```

Properties

▼

configuratorOptions	Configurator Options Input	List of the configurator options to execute.	Optional	60.0
contextMappingId	String	ID of the context mapping record.	Optional	60.0
qualificationContext	User Context Input	Context details that are used for the qualification rules.	Optional	60.0
transactionId	String	Transaction ID of the header entity that's used to create a session. For example, a Quote or an Order.	Required	60.0

Response body for POST

[Configuration Load Instance](#)

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

Share your feedback



- DEVELOPER CENTERS
- [Heroku](#)
[MuleSoft](#)
[Tableau](#)
[Commerce Cloud](#)
[Lightning Design System](#)
[Einstein](#)
[Quip](#)
- POPULAR RESOURCES
- [Documentation](#)
[Component Library](#)
[APIs](#)
[Trailhead](#)
[Sample Apps](#)
[AppExchange](#)
- COMMUNITY
- [Trailblazer Community](#)
[Events and Calendar](#)
[Partner Community](#)
[Blog](#)
[Salesforce Admins](#)
[Salesforce Architects](#)