



Configurator Delete Nodes (POST)

Delete nodes from a product configuration.

Resource

</>

🔍 | 📄

```
1 /connect/cpq/configurator/actions/delete-nodes
```

Resource example

</>

🔍 | 📄

```
1 https://yourInstance.salesforce.com/services/data/v67.0/connect/cpq/configura
```

Available version

60.0

HTTP methods

POST

Request body for POST

JSON example

</>

🔍 | 📄

```
1 {
2   "configuratorOptions": {
3     "executePricing": true,
4     "returnProductCatalogData": true,
5     "qualifyAllProductsInTransaction": true,
6     "validateProductCatalog": true,
7     "validateAmendRenewCancel": true,
8     "executeConfigurationRules": true,
9     "addDefaultConfiguration": true
10  },
11  "qualificationContext": {
12    "accountId": "001xx0000000001AAA",
13    "contactId": "003xx000000000D7AAI"
14  },
15  "contextId": "008d27d7-e004-4906-a949-ee7d7c323c77",
16  "deletedNodes": [
17    {
18      "path": ["0Q0DE000000ISHJs81", "0QLDE000000IBXw4A0"]
19    }
20  ]
21 }
```

Properties



Options	Options Input	configuration options to execute.			
contextId	String	ID of the context object that's being considered.	Required	60.0	
deletedNodes	Configurator Deleted Node Input[]	List of the nodes to be deleted.	Required	60.0	
qualification Context	User Context Input	Context details that are used for the qualification rules.	Optional	60.0	

Response body for POST

[Configurator Delete Nodes](#)

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

Share your feedback





DEVELOPER CENTERS

[Heroku](#)
[MuleSoft](#)
[Tableau](#)
[Commerce Cloud](#)
[Lightning Design System](#)
[Einstein](#)
[Quip](#)

POPULAR RESOURCES

[Documentation](#)
[Component Library](#)
[APIs](#)
[Trailhead](#)
[Sample Apps](#)
[AppExchange](#)

COMMUNITY

[Trailblazer Community](#)
[Events and Calendar](#)
[Partner Community](#)
[Blog](#)
[Salesforce Admins](#)
[Salesforce Architects](#)