

Product Configurator Business APIs

Use the Product Configurator Business APIs to customize a product or a service according to your business-specific requirements.

Perform product configuration-related operations by using the Product Configurator Business APIs. Integrate these APIs with any front-end application to access the configurator capabilities.

These APIs are stateless and don't recall prior user actions between calls unless state is explicitly persisted and reloaded.

For example, if a user deselects a child product and later reselects it, the engine treats the request as adding a new item that doesn't currently exist in the model. It can't infer that this request is a re-selection of a previously removed item. As a result, the original line item isn't restored and a new line item is created.

This table lists the available Product Configurator resources.

Resource	Description
/connect/cpq/configurator/actions/configure (POST)	Retrieve and update a product's configuration from a configurator. Execute configuration rules and notify users of any violations for changes to product bundle, attributes, or product quantity within a bundle. Additionally, get pricing details for the configured bundle.
/connect/cpq/configurator/actions/load-instance (POST)	Create a session for the product configuration instance using the transaction ID. Get the session ID that includes the results of actions, such as configuration rules, qualification rules, and pricing management.
/connect/cpq/configurator/actions/set-instance (POST)	Set a product configuration instance. This API is used in scenarios where the configuration instance is available in a different database than Salesforce and the product catalog management data is in Salesforce.
/connect/cpq/configurator/actions/get-instance (POST)	Fetch the JSON representation of a product configuration. Use the response to display the details of the product configuration instance on the Salesforce user interface, or save the product configuration instance to an external system.
/connect/cpq/configurator/actions/save-instance (POST)	Save a configuration instance after a successful product configuration.



/connect/cpq/configurator/actions/add-nodes (POST)	Add a node to the context through the runtime system without using the Salesforce user interface.
/connect/cpq/configurator/actions/update-nodes (POST)	Update nodes in a product configuration.
/connect/cpq/configurator/actions/delete-nodes (POST)	Delete nodes from a product configuration.
/revenue/product-configurator/rules/actions/execute (POST)	Run rules for a specific quote or order based on a context ID or transaction ID.

- [Resources](#)
Learn more about the available Product Configurator API resources.
- [Request Bodies](#)
Learn more about the available Product Configurator API request bodies.
- [Response Bodies](#)
Learn more about the available Product Configurator API response bodies.

See Also

- [Connect REST API Developer Guide: Introduction](#)
- [Salesforce Help: Product Configurator Permissions](#)

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

Share your feedback





DEVELOPER CENTERS

[Heroku](#)
[MuleSoft](#)
[Tableau](#)
[Commerce Cloud](#)
[Lightning Design System](#)
[Einstein](#)
[Quip](#)

POPULAR RESOURCES

[Documentation](#)
[Component Library](#)
[APIs](#)
[Trailhead](#)
[Sample Apps](#)
[AppExchange](#)

COMMUNITY

[Trailblazer Community](#)
[Events and Calendar](#)
[Partner Community](#)
[Blog](#)
[Salesforce Admins](#)
[Salesforce Architects](#)