



Configuration Get Instance Input

Input representation of the request to get a product configuration instance.

JSON example



```
1 {
2   "contextId": "008d27d7-e004-4906-a949-ee7d7c323c77"
3 }
```

Properties

Name	Type	Description	Required or Optional	Available Version
contextId	String	Transaction context ID of the product configuration instance that's to be fetched.	Required	60.0

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

Share your feedback



DEVELOPER CENTERS

- Heroku
- MuleSoft
- Tableau
- Commerce Cloud

POPULAR RESOURCES

- Documentation
- Component Library
- APIs
- Trailhead

COMMUNITY

- Trailblazer Community
- Events and Calendar
- Partner Community
- Blog



Try for free



© Copyright 2026 Salesforce, Inc. [All rights reserved](#). Various trademarks held by their respective owners. Salesforce, Inc. Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Legal](#) [Terms of Service](#) [Privacy Information](#) [Responsible Disclosure](#) [Trust](#) [Contact](#) [Use of Cookies](#)
[Cookie Preferences](#) ☒ [Your Privacy Choices](#)