



Try for free

Configuration Load Instance Input

Input representation of the request to load a product configuration instance.

JSON example

</>

1 {
2 "configuratorOptions":
3 {
4 "addDefaultConfiguration": true,
5 "executeConfigurationRules": true,
6 "executePricing": true,
7 "qualifyAllProductsInTransaction": true,
8 "validateAmendRenewCancel": true,
9 "validateProductCatalog": true
10 },
11 "qualificationContext": {
12 "accountId": "001DU000001nHUGYA2"
13 },
14 "transactionId": "0Q0DU000000XoN0AU"
15 }

🌐 | 📄

Properties

Name	Type	Description	Required or Optional	Available Version
configurator Options	Configurator Options Input	List of the configurator options to execute.	Optional	60.0
contextMapping Id	String	ID of the context mapping record.	Optional	60.0
qualification Context	User Context Input	Context details that are used for the qualification rules.	Optional	60.0
transactionId	String	Transaction ID of the header entity that's used to create a session. For example, a Quote or an Order.	Required	60.0

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

Share your feedback



Try for free



MuleSoft
Tableau
Commerce Cloud
Lightning Design System
Einstein
Quip

Component Library
APIs
Trailhead
Sample Apps
AppExchange

Events and Calendar
Partner Community
Blog
Salesforce Admins
Salesforce Architects

© Copyright 2026 Salesforce, Inc. [All rights reserved](#). Various trademarks held by their respective owners. Salesforce, Inc. Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Legal](#) [Terms of Service](#) [Privacy Information](#) [Responsible Disclosure](#) [Trust](#) [Contact](#) [Use of Cookies](#)

[Cookie Preferences](#)  [Your Privacy Choices](#)