

[Try for free](#)

Developers



Request Bodies

[Product Configurator](#) / [Product Configurator Business APIs](#) / [Request Bodies](#)

Request Bodies

Learn more about the available Product Configurator API request bodies.

- [Configuration Get Instance Input](#)
Input representation of the request to get a product configuration instance.
- [Configuration Load Instance Input](#)
Input representation of the request to load a product configuration instance.
- [Configuration Save Input](#)
Input representation of the details to save a configuration.
- [Configuration Update Input](#)
Input representation of the details to update a configuration.
- [Configuration Save Instance Input](#)
Input representation of the request to save a product configuration instance.
- [Configuration Set Instance Input](#)
Input representation of the request to set a product configuration instance.
- [Configurator Add Nodes Input](#)
Input representation of the request to add nodes within a root node.
- [Configurator Added Node Input](#)
Input representation of the nodes to be added to a product configuration.
- [Configurator Delete Nodes Input](#)
Input representation of the request to delete nodes from a product configuration.
- [Configurator Deleted Node Input](#)
Input representation of the nodes to be deleted from a product configuration.
- [Configurator Input](#)
Input representation of the request to modify the product configuration.
- [Configurator Options Input](#)
Input representation of the request to get the product configuration options that's passed to the configurator.
- [Configuration Rule Input](#)
Input representation of the details of a configuration rule.
- [Configurator Update Nodes Input](#)
Input representation of the request to update the nodes in a product configuration.
- [Configurator Updated Node Input](#)
Input representation of the nodes to be updated in a product configuration.
- [Product Quantity Set Configurator Input](#)
Input representation of the request to set the quantity of a product.
- [User Context Input](#)
Input representation of the request to get the context details of a user, which are used for qualification rules.

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

[Share your feedback](#)



Try for free



- | | | |
|-------------------------|-------------------|-----------------------|
| MuleSoft | Component Library | Events and Calendar |
| Tableau | APIs | Partner Community |
| Commerce Cloud | Trailhead | Blog |
| Lightning Design System | Sample Apps | Salesforce Admins |
| Einstein | AppExchange | Salesforce Architects |
| Quip | | |

© Copyright 2026 Salesforce, Inc. [All rights reserved.](#) Various trademarks held by their respective owners. Salesforce, Inc. Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Legal](#) [Terms of Service](#) [Privacy Information](#) [Responsible Disclosure](#) [Trust](#) [Contact](#) [Use of Cookies](#) [Cookie Preferences](#)

[Your Privacy Choices](#)