



Try for free

User Context Input

Input representation of the request to get the context details of a user, which are used for qualification rules.

JSON example

</>

1 "qualificationContext": {
2 "accountId": "001DU000001nHUGYA2",
3 "contactId": "003xx00000000D7AAI"
4 }

🌑 | 📄

Properties

Name	Type	Description	Required or Optional	Available Version
accountId	String	ID of the account in a user context.	Optional	60.0
contactId	String	ID of the contact in a user context.	Optional	60.0
contextId	String	ID of the context that represents the created session.	Optional	60.0

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

Share your feedback



DEVELOPER CENTERS

Heroku

MuleSoft

Tableau

Commerce Cloud

POPULAR RESOURCES

Documentation

Component Library

APIs

Trailhead

COMMUNITY

Trailblazer Community

Events and Calendar

Partner Community

Blog



Try for free



© Copyright 2026 Salesforce, Inc. [All rights reserved](#). Various trademarks held by their respective owners. Salesforce, Inc. Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Legal](#) [Terms of Service](#) [Privacy Information](#) [Responsible Disclosure](#) [Trust](#) [Contact](#) [Use of Cookies](#) [Cookie Preferences](#)
 [Your Privacy Choices](#)