



Try for free

Saved Configuration (GET, POST)

Save and reuse a record's configurations, and get a list of the saved configurations for a record.

Resource



```
1 /connect/cpq/configurator/saved-configuration
```

Resource example



```
1 https://yourInstance.salesforce.com/services/data/v67.0/connect/cpq/configurat
```

Available version

63.0

HTTP methods

GET, POST

Request parameters for GET

Parameter Name	Type	Description	Required or Optional	Available Version
referenceRecordId	String	ID of the record whose saved configurations must be retrieved.	Required	63.0

Response body for GET

[Configuration List](#)

Request body for POST

JSON example



```
1 {
2   "data": "{&quot;LegalEntity&quot;;null,&quot;ProductName&quot;;&quot;Monito
3   "description": "This configuration is saved for reuse.",
4   "name": "Favorite Configuration",
5   "referenceRecordId": "01txx0000006iCFAAY"
6 }
```

Properties



		details of the sales transaction, formatted as a string.			
description	String	Description of the saved configuration.	Optional	63.0	
name	String	Name of the saved configuration.	Optional	63.0	
referenceRecordId	String	ID of the record for which the configuration must be saved.	Required	63.0	

Response body for POST

[Configuration Record Save](#)

- See Also
- [Salesforce Help: Considerations to Save and Reuse Configurations](#)

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

Share your feedback





DEVELOPER CENTERS

[Heroku](#)
[MuleSoft](#)
[Tableau](#)
[Commerce Cloud](#)
[Lightning Design System](#)
[Einstein](#)
[Quip](#)

POPULAR RESOURCES

[Documentation](#)
[Component Library](#)
[APIs](#)
[Trailhead](#)
[Sample Apps](#)
[AppExchange](#)

COMMUNITY

[Trailblazer Community](#)
[Events and Calendar](#)
[Partner Community](#)
[Blog](#)
[Salesforce Admins](#)
[Salesforce Architects](#)

