```
import * as React from 'react';
import * as ToastPrimitives from '@radix-ui/react-toast';
import { cva, type VariantProps } from 'class-variance-authority';
import { X } from 'lucide-react';
import { cn } from '@/shared/utils/cn';
const ToastProvider = ToastPrimitives.Provider;
const ToastViewport = React.forwardRef<</pre>
 React.ElementRef<typeof ToastPrimitives.Viewport>,
 React.ComponentPropsWithoutRef<typeof ToastPrimitives.Viewport>
>(({ className, ...props }, ref) => (
 <ToastPrimitives.Viewport
  ref={ref}
  className={cn(
       'fixed top-0 z-[100] flex max-h-screen w-full flex-col-reverse p-4 sm:bottom-0 sm:right-0
sm:top-auto sm:flex-col md:max-w-[420px]',
   className,
  )}
  {...props}
/>
));
ToastViewport.displayName = ToastPrimitives.Viewport.displayName;
const toastVariants = cva(
```

```
'group pointer-events-auto relative flex w-full items-center justify-between space-x-4
overflow-hidden
                   rounded-md
                                  border
                                            border-zinc-200
                                                               p-6
                                                                      pr-8
                                                                             shadow-lg
                                                                                          transition-all
data-[swipe=cancel]:translate-x-0
                                         data-[swipe=end]:translate-x-[var(--radix-toast-swipe-end-x)]
data-[swipe=move]:translate-x-[var(--radix-toast-swipe-move-x)] data-[swipe=move]:translate-x-[var(--radix-toast-swipe-move-x)]
data-[state=open]:animate-in
                                  data-[state=closed]:animate-out
                                                                        data-[swipe=end]:animate-out
data-[state=closed]:fade-out-80
                                                              data-[state=closed]:slide-out-to-right-full
data-[state=open]:slide-in-from-top-full
                                                        data-[state=open]:sm:slide-in-from-bottom-full
dark:border-zinc-800',
 {
  variants: {
   variant: {
     default:
      'border bg-white text-zinc-950 dark:bg-zinc-950 dark:text-zinc-50',
     destructive:
                 'destructive group border-red-500 bg-red-500 text-zinc-50 dark:border-red-900
dark:bg-red-900 dark:text-zinc-50',
   },
  },
  defaultVariants: {
   variant: 'default',
  },
 },
);
const Toast = React.forwardRef<
```

React.ElementRef<typeof ToastPrimitives.Root>,

```
VariantProps<typeof toastVariants>
>(({ className, variant, ...props }, ref) => {
 return (
  <ToastPrimitives.Root
   ref={ref}
   className={cn(toastVariants({ variant }), className)}
   {...props}
  />
 );
});
Toast.displayName = ToastPrimitives.Root.displayName;
const ToastAction = React.forwardRef<
 React.ElementRef<typeof ToastPrimitives.Action>,
 React.ComponentPropsWithoutRef<typeof ToastPrimitives.Action>
>(({ className, ...props }, ref) => (
 <ToastPrimitives.Action
  ref={ref}
  className={cn(
        'inline-flex h-8 shrink-0 items-center justify-center rounded-md border border-zinc-200
bg-transparent px-3 text-sm font-medium ring-offset-white transition-colors hover:bg-zinc-100
focus:outline-none focus:ring-2 focus:ring-zinc-950 focus:ring-offset-0 disabled:pointer-events-none
```

group-[.destructive]:hover:text-zinc-50 group-[.destructive]:focus:ring-red-500 dark:border-zinc-800

group-[.destructive]:border-zinc-100/40

group-[.destructive]:hover:bg-red-500

React.ComponentPropsWithoutRef<typeof ToastPrimitives.Root> &

disabled:opacity-50

group-[.destructive]:hover:border-red-500/30

'absolute right-2 top-2 rounded-md p-1 text-zinc-950/50 opacity-0 transition-opacity
hover:text-zinc-950 focus:opacity-100 focus:outline-none focus:ring-2 group-hover:opacity-100
group-[.destructive]:text-red-300 group-[.destructive]:hover:text-red-50
group-[.destructive]:focus:ring-red-400 group-[.destructive]:focus:ring-offset-red-600
dark:text-zinc-50/50 dark:hover:text-zinc-50',
className,
)}

className={cn(

toast-close=""

```
{...props}
  <X className="h-4 w-4" />
 </ToastPrimitives.Close>
));
ToastClose.displayName = ToastPrimitives.Close.displayName;
const ToastTitle = React.forwardRef<
 React.ElementRef<typeof ToastPrimitives.Title>,
 React.ComponentPropsWithoutRef<typeof ToastPrimitives.Title>
>(({ className, ...props }, ref) => (
 <ToastPrimitives.Title
  ref={ref}
  className={cn('text-sm font-semibold', className)}
  {...props}
/>
));
ToastTitle.displayName = ToastPrimitives.Title.displayName;
const ToastDescription = React.forwardRef<
 React.ElementRef<typeof ToastPrimitives.Description>,
 React.ComponentPropsWithoutRef<typeof ToastPrimitives.Description>
>(({ className, ...props }, ref) => (
 <ToastPrimitives.Description
  ref={ref}
  className={cn('text-sm opacity-90', className)}
```

```
{...props}
 />
));
ToastDescription.displayName = ToastPrimitives.Description.displayName;
type ToastProps = React.ComponentPropsWithoutRef<typeof Toast>;
type ToastActionElement = React.ReactElement<typeof ToastAction>;
export {
 type ToastProps,
 type ToastActionElement,
 ToastProvider,
 ToastViewport,
 Toast,
 ToastTitle,
 ToastDescription,
 ToastClose,
 ToastAction,
};
```