

```
'use client';
```

```
import * as React from 'react';
```

```
import * as SelectPrimitive from '@radix-ui/react-select';
```

```
import { Check, ChevronDown, ChevronUp } from 'lucide-react';
```

```
import { cn } from '@shared/utils/cn';
```

```
const Select = SelectPrimitive.Root;
```

```
const SelectGroup = SelectPrimitive.Group;
```

```
const SelectValue = SelectPrimitive.Value;
```

```
const SelectTrigger = React.forwardRef<
```

```
  React.ElementRef<typeof SelectPrimitive.Trigger>,
```

```
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.Trigger>
```

```
>(({ className, children, ...props }, ref) => (
```

```
  <SelectPrimitive.Trigger
```

```
    ref={ref}
```

```
    className={cn(
```

```
      'flex h-10 w-full items-center justify-between rounded-md border border-input bg-background  
px-3 py-2 text-sm ring-offset-background placeholder:text-muted-foreground focus:outline-none  
focus:ring-2 focus:ring-ring focus:ring-offset-0 disabled:cursor-not-allowed disabled:opacity-50  
[&>span]:line-clamp-1',
```

```
      className,
```

```

    })
    {...props}
  >
    {children}
    <SelectPrimitive.Icon asChild>
      <ChevronDown className="h-4 w-4 opacity-50" />
    </SelectPrimitive.Icon>
  </SelectPrimitive.Trigger>
));
SelectTrigger.displayName = SelectPrimitive.Trigger.displayName;

```

```

const SelectScrollUpButton = React.forwardRef<
  React.ElementRef<typeof SelectPrimitive.ScrollUpButton>,
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.ScrollUpButton>
>(({ className, ...props }, ref) => (
  <SelectPrimitive.ScrollUpButton
    ref={ref}
    className={cn(
      'flex cursor-default items-center justify-center py-1',
      className,
    )}
    {...props}
  >
    <ChevronUp className="h-4 w-4" />
  </SelectPrimitive.ScrollUpButton>
));

```

```
SelectScrollUpButton.displayName = SelectPrimitive.ScrollUpButton.displayName;
```

```
const SelectScrollDownButton = React.forwardRef<  
  React.ElementRef<typeof SelectPrimitive.ScrollDownButton>,  
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.ScrollDownButton>  
>(({ className, ...props }, ref) => (  
  <SelectPrimitive.ScrollDownButton  
    ref={ref}  
    className={cn(  
      'flex cursor-default items-center justify-center py-1',  
      className,  
    )}  
    {...props}  
  >  
    <ChevronDown className="h-4 w-4" />  
  </SelectPrimitive.ScrollDownButton>  
));  
  
SelectScrollDownButton.displayName =  
  SelectPrimitive.ScrollDownButton.displayName;
```

```
const SelectContent = React.forwardRef<  
  React.ElementRef<typeof SelectPrimitive.Content>,  
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.Content>  
>(({ className, children, position = 'popper', ...props }, ref) => (  
  <SelectPrimitive.Portal>  
    <SelectPrimitive.Content
```

```

ref={ref}

className={cn(
  'relative z-50 max-h-96 min-w-[8rem] overflow-hidden rounded-md border bg-popover
text-popover-foreground shadow-md data-[state=open]:animate-in data-[state=closed]:animate-out
data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95
data-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2
data-[side=left]:slide-in-from-right-2 data-[side=right]:slide-in-from-left-2
data-[side=top]:slide-in-from-bottom-2',
  position === 'popper' &&
  'data-[side=bottom]:translate-y-1 data-[side=left]:-translate-x-1 data-[side=right]:translate-x-1
data-[side=top]:-translate-y-1',
  className,
)}
position={position}
 {...props}
>
<SelectScrollUpButton />
<SelectPrimitive.Viewport
  className={cn(
    'p-1',
    position === 'popper' &&
    'h-[var(--radix-select-trigger-height)] w-full min-w-[var(--radix-select-trigger-width)]',
  )}
>
  {children}
</SelectPrimitive.Viewport>

```

```

    <SelectScrollDownButton />

  </SelectPrimitive.Content>

</SelectPrimitive.Portal>

));

SelectContent.displayName = SelectPrimitive.Content.displayName;

```

```

const SelectLabel = React.forwardRef<

  React.ElementRef<typeof SelectPrimitive.Label>,

  React.ComponentPropsWithoutRef<typeof SelectPrimitive.Label>

>(({ className, ...props }, ref) => (

  <SelectPrimitive.Label

    ref={ref}

    className={cn('py-1.5 pl-8 pr-2 text-sm font-semibold', className)}

    {...props}

  />

));

SelectLabel.displayName = SelectPrimitive.Label.displayName;

```

```

const SelectItem = React.forwardRef<

  React.ElementRef<typeof SelectPrimitive.Item>,

  React.ComponentPropsWithoutRef<typeof SelectPrimitive.Item>

>(({ className, children, ...props }, ref) => (

  <SelectPrimitive.Item

    ref={ref}

    className={cn(

      'relative flex w-full cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm

```

```

outline-none focus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none
data-[disabled]:opacity-50',

  className,

)}

{...props}
>

<span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">

  <SelectPrimitive.ItemIndicator>

    <Check className="h-4 w-4" />

  </SelectPrimitive.ItemIndicator>

</span>

<SelectPrimitive.ItemText>{children}</SelectPrimitive.ItemText>

</SelectPrimitive.Item>

));

SelectItem.displayName = SelectPrimitive.Item.displayName;

const SelectSeparator = React.forwardRef<

  React.ElementRef<typeof SelectPrimitive.Separator>,

  React.ComponentPropsWithoutRef<typeof SelectPrimitive.Separator>

>(({ className, ...props }, ref) => (

  <SelectPrimitive.Separator

    ref={ref}

    className={cn('-mx-1 my-1 h-px bg-muted', className)}

    {...props}

  />

```

```
));
```

```
SelectSeparator.displayName = SelectPrimitive.Separator.displayName;
```

```
export {
```

```
  Select,
```

```
  SelectGroup,
```

```
  SelectValue,
```

```
  SelectTrigger,
```

```
  SelectContent,
```

```
  SelectLabel,
```

```
  SelectItem,
```

```
  SelectSeparator,
```

```
  SelectScrollUpButton,
```

```
  SelectScrollDownButton,
```

```
};
```