```
import * as React from "react"
import * as AccordionPrimitive from "@radix-ui/react-accordion"
import { ChevronDown } from "lucide-react"
import { cn } from "@/lib/utils"
const Accordion = AccordionPrimitive.Root
const AccordionItem = React.forwardRef<
 React.ElementRef<typeof AccordionPrimitive.Item>,
 React.ComponentPropsWithoutRef<typeof AccordionPrimitive.Item>
>(({ className, ...props }, ref) => (
 <AccordionPrimitive.Item
  ref={ref}
  className={cn("border-b", className)}
  {...props}
/>
))
AccordionItem.displayName = "AccordionItem"
const AccordionTrigger = React.forwardRef<</pre>
 React.ElementRef<typeof AccordionPrimitive.Trigger>,
 React.ComponentPropsWithoutRef<typeof AccordionPrimitive.Trigger>
>(({ className, children, ...props }, ref) => (
```

"use client"

```
<AccordionPrimitive.Header className="flex">
  <AccordionPrimitive.Trigger
   ref={ref}
   className={cn(
         "flex flex-1 items-center justify-between py-4 font-medium transition-all hover:underline
[&[data-state=open]>svg]:rotate-180",
     className
   )}
   {...props}
  >
   {children}
   <ChevronDown className="h-4 w-4 shrink-0 transition-transform duration-200" />
  </AccordionPrimitive.Trigger>
 </AccordionPrimitive.Header>
))
AccordionTrigger.displayName = AccordionPrimitive.Trigger.displayName
const AccordionContent = React.forwardRef<
 React.ElementRef<typeof AccordionPrimitive.Content>,
 React.ComponentPropsWithoutRef<typeof AccordionPrimitive.Content>
>(({ className, children, ...props }, ref) => (
 <AccordionPrimitive.Content
  ref={ref}
     className="overflow-hidden text-sm transition-all data-[state=closed]:animate-accordion-up
data-[state=open]:animate-accordion-down"
  {...props}
```