

Shell Cheat Sheet

Patrick Bucher

2017-05-18

Contents

Commands	2
Files and Directories	2
File Attributes	3
Searching Files	3
File Transfer	3
Archives	3
Text	3
Spelling	4
Document Preparation	4
Text Editors	4
Miscellaneous	4
Date and Time	5
Math	5
Documentation	5
Printing	5
Programming	6
Shell Scripting	6
Scripting Languages	6
Building, Debugging	6
System Administration	6
Processes	7
User Administration	7
Networking	7
Encoding, Decoding, Checksums, Encryption, Decryption	7
Shell Programming	8
Output Redirection	8
Variables	8

Commands

Files and Directories

- **cd**: change the working directory
 - **cd**: change to home directory
 - **cd . .**: change to parent directory
 - **cd /home/joe**: change to directory using a absolute path
 - **cd docs/letters**: change to directory using a relative path
- **cp**: copy files and directories
 - **cp [source] [destination]**: copy source file to destination
 - **-f**: force overwrite an existing file
 - **-i**: prompt before overwrite
 - **-n**: don't overwrite an existing file
 - **-r**: copy a directory recursively
- **dd**: convert and copy a file
 - **dd if=[in] of=[out] bs=[n]**: copy from in to out, n bytes at a time
- **du**: estimate file space usage
 - **-h**: print sizes in human readable format
 - **-s**: display only a total for each argument
- **ln**: make links between files
 - **ln [target] [link name]**: create a (hard) link to target
 - **-s**: make a symbolic link instead of a hard link
- **ls**: list directory contents
 - **-a**: also display hidden entries (starting with ".")
 - **-h**: print human readable sizes (in combination with **-l**)
 - **-l**: long listing format (**ll** is short for **ls -l**)
 - **-r**: reverse order
 - **-R**: list files recursively
 - **-t**: sort by modification time, newest first
- **mkdir**: make directories
 - **make foo bar**: create the directories "foo" and "bar"
- **mv**: move (rename) files
 - **mv [source] [destination]**
 - **-f**: force overwrite an existing file
 - **-i**: prompt before overwrite
 - **-n**: don't overwrite an existing file
- **pwd**: print name of current/working directory
- **rm**: remove files or directories
 - **-d**: remove empty directories
 - **-f**: force overwrite an existing file
 - **-i**: prompt before every removal
 - **-r**: delete a directory recursively

- `touch`: change file timestamps – or create a new file
 - `-c`: don't create a new file

File Attributes

- `basename`: strip directory and suffix from filenames
- `cleannname`: clean a path name
- `chmod`: change file mode bits
- `chown`: change file owner and group
- `file`: determine file type
- `fsize`: print file information
- `mtime`: print file information

Searching Files

- `find`
- `locate`
- `updatedb`

File Transfer

- `ftp`
- `rsync`
- `scp`
- `sftp`

Archives

- `ar`: create, modify, and extract from archives
- `tar`
- `zip`
- `unrar`
- `unzip`

Text

- `cat`: concatenate files and print on the standard output
- `cut`: remove sections from each line of files
- `fmt`: simple optimal text formatter
- `fold`: wrap each input line to fit in specified width

- `diff`: compare files line by line
- `freq`: print histogram of character frequencies
- `grep`: print lines matching a pattern
- `head`: output the first part of files
- `join`: join lines of two files on a common field
- `look`: display lines beginning with a given string
- `read`: copies one line from a file to standard output
- `sed`: stream editor for filtering and transforming text
- `sort`: sort lines of text files
- `split`: split a file into pieces
- `strings`: print the strings of printable characters in files
- `tail`: output the last part of files
- `tee`: read from standard input and write to standard output and files
- `tr`: translate or delete characters
- `wc`: print newline, word, and byte counts for each file
- `uniq`: report or omit repeated lines

Spelling

- `aspell`
- `hunspell`

Document Preparation

- `troff`: the troff processor of the groff text formatting system

Text Editors

- `ed`: line-oriented text editor
- `emacs`: GNU project Emacs editor
- `vi`: screen oriented (visual) display editor based on `ex`
- `vim`: Vi IMproved, a programmers text editor
 - `vim -p [files]`: open multiple files in tabs

Miscellaneous

- `acpi`: show battery status and other ACPI information
- `ascii`: interpret ASCII characters
- `chroot`
- `curl`
- `cmp`: compare two files byte by byte

- dmesg
- eval
- expr
- hexdump: display file contents in hexadecimal, decimal, octal, or ascii
- halt
- history:
- lspci
- pwgen: generate pronounceable passwords
- rsync:
- shutdown
- scp
- unicode: interpret unicode characters
- wget
- xrandr
- yes

Date and Time

- cal: display a calendar
- date: print or set the system date and time

Math

- bc: an arbitrary precision calculator language (interactive)
- dc: reverse-polish desk calculator (interactive)
- factor: factor numbers
- hoc: interactive floating point language
- primes: list prime numbers
- rand: generate pseudo-random bytes

Documentation

- apropos: search the manual page names and descriptions
- man: an interface to the on-line reference manuals
- type: write a description of command type
- whatis: display one-line manual page descriptions

Printing

- lpadmin
- cancel: cancel jobs

- `lpr`: print files

Programming

Shell Scripting

- `alias`: define or display aliases
- `break`: exit from `for`, `while`, or `until` loop
- `echo`: display a line of text
- `export`: set the export attribute for variables
- `getflags`: command-line parsing for shell scripts
- `printf`: format and print data
- `sleep`: delay for a specified amount of time
- `test`: check file types and compare values
- `xargs`: build and execute command lines from standard input

Scripting Languages

- `awk`: pattern-directed scanning and processing language
- `perl`: the Perl language interpreter
- `python`: an interpreted, interactive, object-oriented programming language
- `sh`: shell, the standard command language interpreter

Building, Debugging

- `gcc`: GNU project C and C++ compiler
- `gdb`: the GNU Debugger
- `make`: GNU make utility to maintain groups of programs
- `mk`: maintain (make) related files
- `strip`: discard symbols from object files
- `valgrind`:
- `yacc`: parser generator

System Administration

- `df`: report file system disk space usage
- `fdisk`: manipulate disk partition table
- `fsck`
- `mkfs`: build a Linux filesystem
- `mount`
- `su`: run a command with substitute user and group ID

- `sudo`: execute a command as another user
- `systemctl`: control the `systemd` system and service manager
- `uname`

Processes

- `bg`: run jobs in the background
- `kill`: terminate a process
- `killall`: terminate a process by name
- `nice`: run a program with modified scheduling priority
- `nohup`: run a command immune to hangups, with output to a non-tty
- `ps`: report a snapshot of the current processes
- `top`: display Linux processes (interactive)

User Administration

- `groupadd`: create a new group
- `groupdel`: delete a group
- `groupmems`: administer members of a users's primary group
- `groupmod`: modify a group definition on the system
- `groups`: display current group names
- `id`: print real and effective user and group IDs
- `passwd`: change user password
- `useradd`: create a new user or update default new user information
- `userdel`: delete a user account and related files
- `usermod`: modify a user account
- `users`: print the user names of users currently logged in

Networking

- `ip`: show/manipulate routing, devices, policy routing and tunnels
- `ping`: send ICMP ECHO_REQUEST to network hosts

Encoding, Decoding, Checksums, Encryption, Decryption

- `base32`: base32 encode/decode data and print to standard output
- `base64`: base64 encode/decode data and print to standard output
- `sha1sum`
- `sha256sum`
- `sha512sum`
- `shasum`

- `sum`

Shell Programming

Output Redirection

```
wc -l * | sort -n -r  
wc -l >std-out 2>std.err
```

Variables

- `$IFS`: internal field separator