

Alsurvey.me v2.0 — API Documentation

Base URL

Production: <https://aisurvey.me/api>
Development: <http://localhost:3000/api>

Authentication

All admin endpoints require NextAuth.js session authentication. Include session cookie or use Bearer token.

Public Endpoints

POST `/api/survey/submit`

Submit a completed survey response.

Request Body:

```
{
  "surveyId": "string (cuid)",
  "answers": [
    {
      "questionId": "string (cuid)",
      "value": "string"
    }
  ],
  "conversationHistory": [
    {
      "role": "user | assistant",
      "content": "string"
    }
  ],
  "language": "nl | de | en | fr | es | pt | it",
  "respondentName": "string (optional)",
  "respondentEmail": "string (optional)"
}
```

Response: 201 Created

```
{
  "success": true,
  "responseId": "string",
  "tacitKnowledgeScore": 75.5
}
```

POST /api/conversation

Send a message in an AI conversation and receive a response.

Request Body:

```
{
  "surveyId": "string (cuid)",
  "message": "string",
  "conversationHistory": [
    { "role": "user | assistant", "content": "string" }
  ],
  "language": "nl",
  "currentQuestionIndex": 0,
  "responseId": "string (optional)"
}
```

Response: 200 OK

```
{
  "reply": "string",
  "isComplete": false,
  "currentQuestionIndex": 1,
  "qualityScore": {
    "relevance": 0.85,
    "depth": 0.72,
    "completeness": 0.90
  },
  "entitiesExtracted": ["SAP MM", "procurement process"],
  "tacitScoreUpdate": {
    "depth": 68,
    "uniqueness": 72,
    "actionability": 65,
    "composite": 68.3
  }
}
```

POST /api/signup

Register a new admin user.

Request Body:

```
{
  "name": "string",
  "email": "string",
  "password": "string"
}
```

Admin Endpoints

All require authenticated session (role: ADMIN or SUPER_ADMIN)

Surveys

Method	Endpoint	Description
GET	/api/admin/surveys	List all surveys
POST	/api/admin/surveys	Create new survey
GET	/api/admin/surveys/[id]	Get survey details
PUT	/api/admin/surveys/[id]	Update survey
DELETE	/api/admin/surveys/[id]	Delete survey
POST	/api/admin/surveys/[id]/toggle	Toggle survey active status
POST	/api/admin/surveys/[id]/duplicate	Duplicate a survey

Create Survey Body (v2.0 additions):

```
{
  "title": "string",
  "description": "string",
  "language": "nl",
  "domainTemplate": "sap-knowledge | healthcare | it-operations | government | general",
  "whyProtocolDepth": 3
}
```

Questions

Method	Endpoint	Description
GET	/api/admin/questions?surveyId=xxx	List questions for survey
POST	/api/admin/questions	Create question
PUT	/api/admin/questions/[id]	Update question
DELETE	/api/admin/questions/[id]	Delete question

Responses

Method	Endpoint	Description
GET	/api/admin/responses?surveyId=xxx	List responses
GET	/api/admin/responses/export?surveyId=xxx&format=csv	Export responses

Analysis

Method	Endpoint	Description
POST	/api/admin/analyze	Run AI analysis on responses
GET	/api/admin/analyses?surveyId=xxx	List saved analyses
POST	/api/admin/free-prompt	Free-form AI prompt on response data

Users & Translations

Method	Endpoint	Description
GET	/api/admin/users	List admin users
GET	/api/admin/translations	Get translations
POST	/api/admin/translate-dynamic	Translate dynamic content

Voice Agent

Method	Endpoint	Description
GET/POST	/api/admin/voice-agent-questions	Manage voice agent questions
POST	/api/vapi/assistant	VAPI assistant configuration
POST	/api/vapi/phone	Initiate phone call
POST	/api/vapi/webhook	VAPI event webhook

v2.0 New Endpoints

Knowledge Graph

GET /api/admin/knowledge-graph

Query knowledge graph nodes and edges.

Query Parameters:

- `surveyId` (optional) — Filter by survey
- `type` (optional) — Filter by node type
- `search` (optional) — Search node labels
- `limit` (default: 100)

Response:

```
{
  "nodes": [
    {
      "id": "string",
      "label": "SAP MM Module",
      "type": "CONCEPT",
      "properties": {},
      "surveyId": "string",
      "createdAt": "ISO date"
    }
  ],
  "edges": [
    {
      "id": "string",
      "sourceId": "string",
      "targetId": "string",
      "type": "RELATES_TO",
      "weight": 0.85,
      "properties": {}
    }
  ],
  "stats": {
    "totalNodes": 150,
    "totalEdges": 280,
    "nodesByType": { "CONCEPT": 45, "SKILL": 30 }
  }
}
```

POST /api/admin/knowledge-graph

Add nodes/edges to the knowledge graph.

Request Body:

```
{
  "action": "addNode | addEdge | deleteNode | deleteEdge",
  "data": { ... }
}
```

Tacit Knowledge Score

GET `/api/admin/tacit-score`

Get TK-Score analytics.

Query Parameters:

- `surveyId` (optional)
- `responseId` (optional)
- `aggregate` — `survey` | `response` | `overall`

Response:

```
{
  "scores": [
    {
      "responseId": "string",
      "depth": 72,
      "uniqueness": 68,
      "actionability": 80,
      "composite": 73.2,
      "respondentName": "string"
    }
  ],
  "aggregation": {
    "avgComposite": 65.4,
    "maxComposite": 92.1,
    "minComposite": 23.0,
    "totalResponses": 45,
    "highValueResponses": 12
  }
}
```

Expert Profiles

GET `/api/admin/expert-profiles`

List identified knowledge experts.

Query Parameters:

- `domain` (optional) — Filter by domain
- `risk` (optional) — Filter by risk level (LOW, MEDIUM, HIGH, CRITICAL)

Response:

```
{
  "experts": [
    {
      "id": "string",
      "name": "string",
      "email": "string",
      "domains": ["SAP MM", "Procurement"],
      "tacitScore": 85.2,
      "riskLevel": "HIGH",
      "totalSessions": 5,
      "lastActive": "ISO date"
    }
  ]
}
```

POST /api/admin/expert-profiles

Create or update an expert profile.

Integration

POST /api/admin/integration

Manage Knowledge-OS integrations.

Request Body:

```
{
  "action": "status | configure | test | sync",
  "module": "edi | learning-me | knowledge-graph",
  "config": { ... }
}
```

Error Responses

All endpoints return consistent error format:

```
{
  "error": "Human-readable error message",
  "code": "ERROR_CODE",
  "details": { ... }
}
```

Status Code	Meaning
400	Bad Request — Invalid parameters
401	Unauthorized — No valid session
403	Forbidden — Insufficient permissions
404	Not Found
429	Rate Limited
500	Internal Server Error

Rate Limiting

- Public endpoints: 60 requests/minute per IP
- Admin endpoints: 120 requests/minute per session
- AI conversation: 30 requests/minute per session