

Datenbank Hotel Projekt


Zoe Isler, Patrick Günthard

20. Mai 2016

Inhaltsverzeichnis

1	Neues ERD	1
2	Änderungen	1
3	SQL	3

1 Neues ERD



2 Änderungen

Es wurde eine neue Tabelle hinzugefügt: Tabelle **preis**. [Abbildung 1]

Die Felder *Preis* und *Rabatt* wurden von der Tabelle *position* nach *preis* verschoben. Von [Abbildung 2] zu [Abbildung 3]




Abbildung 1: preis

position			
PK	PositionID	INT	NN
FK	BuchungID	INT	NN
FK	LeistungID	INT	NN
FK	UserID	INT	NN
	Anzahl	INT	NN
	Preis	DOUBLE	NN
	Rabatt	DOUBLE	NN
	Datum	DATE	NN

Abbildung 2: Tabelle *position* vor der Veränderung

position			
PK	PositionID	INT	NN
FK	BuchungID	INT	NN
FK	LeistungID	INT	
FK	UserID	INT	
	Anzahl	INT	
	Datum	DATE	

Abbildung 3: Tabelle *position* **nach** der Veränderung

3 SQL

```
— MySQL dump 10.13  Distrib 5.6.24, for Win32 (x86)
```

```
—
```

```
— Host: localhost    Database: hotel
```

```
—
```

```
— Server version      5.6.24
```

```
/*!40101 SET @OLD_CHARACTER_SET_CLIENT=@@CHARACTER_SET_CLIENT */;
```

```
/*!40101 SET @OLD_CHARACTER_SET_RESULTS=@@CHARACTER_SET_RESULTS */;
```

```
/*!40101 SET @OLD_COLLATION_CONNECTION=@@COLLATION_CONNECTION */;
```

```
/*!40101 SET NAMES utf8 */;
```

```
/*!40103 SET @OLD_TIME_ZONE=@@TIME_ZONE */;
```

```
/*!40103 SET TIME_ZONE= '+00:00' */;
```

```
/*!40014 SET @OLD_UNIQUE_CHECKS=@@UNIQUE_CHECKS, UNIQUE_CHECKS=0 */;
```

```
/*!40014 SET @OLD_FOREIGN_KEY_CHECKS=@@FOREIGN_KEY_CHECKS, FOREIGN_KEY_CHECKS=0
```

```
/*!40101 SET @OLD_SQL_MODE=@@SQL_MODE, SQL_MODE= 'NO_AUTO_VALUE_ON_ZERO' */;
```

```
/*!40111 SET @OLD_SQL_NOTES=@@SQL_NOTES, SQL_NOTES=0 */;
```

```
DROP DATABASE IF EXISTS 'hotel';
```

```
CREATE DATABASE 'hotel';
```

```
USE hotel;
```

```
—
```

```
— Table structure for table 'benutzer'
```

```
—
```

```
DROP TABLE IF EXISTS 'benutzer';
/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!40101 SET character_set_client = utf8 */;
CREATE TABLE 'benutzer' (
  'UserID' int(11) NOT NULL AUTO_INCREMENT,
  'Benutzer' varchar(20) NOT NULL DEFAULT '',
  'Passwort' varchar(20) NOT NULL DEFAULT '',
  'GanzerName' varchar(50) NOT NULL DEFAULT '',
  PRIMARY KEY ('UserID')
) ENGINE=InnoDB AUTO_INCREMENT=15 DEFAULT CHARSET=utf8;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table 'benutzer'
--

LOCK TABLES 'benutzer' WRITE;
/*!40000 ALTER TABLE 'benutzer' DISABLE KEYS */;
INSERT INTO 'benutzer' VALUES (1,'Admin','777','Administrator'),(2,'Heinz','2000
/*!40000 ALTER TABLE 'benutzer' ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table 'buchung'
--

DROP TABLE IF EXISTS 'buchung';
/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!40101 SET character_set_client = utf8 */;
CREATE TABLE 'buchung' (
  'BuchungID' int(11) NOT NULL DEFAULT '0',
  'PersID' int(11) DEFAULT NULL,
  'Ankunft' datetime DEFAULT NULL,
  'Abreise' datetime DEFAULT NULL,
  PRIMARY KEY ('BuchungID'),
  KEY 'PersID' ('PersID'),
  CONSTRAINT 'buchung_ibfk_1' FOREIGN KEY ('PersID') REFERENCES 'person' ('PersID')
) ENGINE=InnoDB DEFAULT CHARSET=utf8;
/*!40101 SET character_set_client = @saved_cs_client */;
```

--- *Dumping data for table 'buchung'*

```
LOCK TABLES 'buchung' WRITE;
/*!40000 ALTER TABLE 'buchung' DISABLE KEYS */;
/*!40000 ALTER TABLE 'buchung' ENABLE KEYS */;
UNLOCK TABLES;
```

--- *Table structure for table 'leistung'*

```
DROP TABLE IF EXISTS 'leistung';
/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!40101 SET character_set_client = utf8 */;
CREATE TABLE 'leistung' (
  'LeistungID' int(11) NOT NULL DEFAULT '0',
  'Beschreibung' varchar(70) DEFAULT NULL,
  PRIMARY KEY ('LeistungID')
) ENGINE=InnoDB DEFAULT CHARSET=utf8;
/*!40101 SET character_set_client = @saved_cs_client */;
```

--- *Dumping data for table 'leistung'*

```
LOCK TABLES 'leistung' WRITE;
/*!40000 ALTER TABLE 'leistung' DISABLE KEYS */;
INSERT INTO 'leistung' VALUES (1,'Zimmerreservation_inklusive_erste_Nacht\r'),(2
/*!40000 ALTER TABLE 'leistung' ENABLE KEYS */;
UNLOCK TABLES;
```

--- *Table structure for table 'preis'*

```
DROP TABLE IF EXISTS 'preis';
CREATE TABLE 'preis' (
  'PreisID' INTEGER NOT NULL AUTO_INCREMENT,
  'Preis' DOUBLE NOT NULL,
  'Rabatt' DOUBLE NOT NULL DEFAULT 0,
```

```

'Datum'           DATE    NOT NULL,
'LeistungID '     INTEGER NOT NULL,
PRIMARY KEY('PreisID ')
);

```

— *Table structure for table ‘person’*

```
DROP TABLE IF EXISTS 'person';

/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!40101 SET character_set_client = utf8 */;

CREATE TABLE 'person' (
    'PersID' int(11) NOT NULL AUTO INCREMENT,
    'Vorname' varchar(30) NOT NULL DEFAULT '',
    'Name' varchar(30) NOT NULL DEFAULT '',
    'Strasse' varchar(30) DEFAULT NULL,
    'Ort' varchar(30) DEFAULT NULL,
    'Anrede' varchar(10) DEFAULT NULL,
    'Privattelefon' varchar(20) DEFAULT NULL,
    'Eingabedatum' datetime DEFAULT NULL,
    PRIMARY KEY ('PersID')
) ENGINE=InnoDB AUTO INCREMENT=2040 DEFAULT CHARSET=utf8;

/*!40101 SET character_set_client = @saved_cs_client */;
```

— *Dumping data for table 'person'*

```
LOCK TABLES 'person' WRITE;
/*!40000 ALTER TABLE 'person' DISABLE KEYS */;
```

'Sehr geehrte Person' VALUES ('(1870ergüchMaderBoedSchlievejL34ergsdavois4FräsPankher Medina', 'Sommer', 'Kantonsstrasse', 'Moerschwil', 'Sehr geehr', '031 381 38 25', '0000-00-00 00:00:00'), ('Russo', 'Zabel-Krueger-Damm 115', 'Berling', 'Sehr geehr', '071 245 8619', '0000-00-00 00:00:00'), ('Postfach 3', 'Hyogo', 'Dear Kazut', NULL, '0000-00-00 00:00:00'), (1030, 'Brigitte', 'H

'Orion', 'Avda._de_Goya,_12', 'Gerlingen', 'Sehr_geehr', **NULL**, '2018-07-20_00:00:00'), (1865, 'Kri

```
/*!40000 ALTER TABLE 'person' ENABLE KEYS */;
UNLOCK TABLES;
```

```
—
— Table structure for table 'position'
—
```

```
DROP TABLE IF EXISTS 'position' ;
/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!40101 SET character_set_client = utf8 */;
CREATE TABLE 'position' (
  'PositionID' int(11) NOT NULL AUTO_INCREMENT,
  'BuchungID' int(11) DEFAULT NULL,
  'LeistungID' int(11) DEFAULT NULL,
  'UserID' int(11) DEFAULT NULL,
  'Anzahl' int(11) DEFAULT NULL,
  'Preis' decimal(9,2) DEFAULT NULL,
  'Rabatt' decimal(4,2) DEFAULT NULL,
  'Datum' datetime DEFAULT NULL,
PRIMARY KEY ('PositionID'),
KEY 'BuchungID' ('BuchungID'),
KEY 'LeistungID' ('LeistungID'),
KEY 'UserID' ('UserID'),
CONSTRAINT 'position_ibfk_1' FOREIGN KEY ('BuchungID') REFERENCES 'buchung' ('BuchungID'),
CONSTRAINT 'position_ibfk_2' FOREIGN KEY ('LeistungID') REFERENCES 'leistung' ('LeistungID'),
CONSTRAINT 'position_ibfk_3' FOREIGN KEY ('UserID') REFERENCES 'benutzer' ('UserID'),
ENGINE=InnoDB AUTO_INCREMENT=56387 DEFAULT CHARSET=utf8;
/*!40101 SET character_set_client = @saved_cs_client */;
```

```
—
— Dumping data for table 'position'
—
```

```
LOCK TABLES 'position' WRITE;
/*!40000 ALTER TABLE 'position' DISABLE KEYS */;
/*!40000 ALTER TABLE 'position' ENABLE KEYS */;
UNLOCK TABLES;
/*!40103 SET TIME_ZONE=@OLD_TIME_ZONE */;

/*!40101 SET SQL_MODE=@OLD_SQL_MODE */;
/*!40014 SET FOREIGN_KEY_CHECKS=@OLD_FOREIGN_KEY_CHECKS */;
/*!40014 SET UNIQUE_CHECKS=@OLD_UNIQUE_CHECKS */;
```

```
/*!40101 SET CHARACTER_SET_CLIENT=@OLD_CHARACTER_SET_CLIENT */;  
/*!40101 SET CHARACTER_SET_RESULTS=@OLD_CHARACTER_SET_RESULTS */;  
/*!40101 SET COLLATION_CONNECTION=@OLD_COLLATION_CONNECTION */;  
/*!40111 SET SQL_NOTES=@OLD_SQL_NOTES */;
```

— *Dump completed on 2016-04-13 13:54:00*