

Parlé Technical Documentation

Patrick Günthard

August 11, 2016

Contents

1 Database	1
2 REST Interface	1
2.1 User Services	1
2.1.1 Search all Users	1
2.1.2 Search User By Id	1
2.1.3 Set User Status	2
2.1.4 Login	2
2.1.5 Signup	3
2.1.6 Delete User	3
2.1.7 Search Users by Name	3
2.2 Chat Services	4
2.2.1 Chatlist	4
2.2.2 Chat messages	4

1 Database

TODO

2 REST Interface

2.1 User Services

2.1.1 Search all Users

1. Method

GET

2. Path

/parle/users/all

3. Parameters

none

4. Return

```
[
  {
    "userId" : "number",
    "userName" : "string",
    "userPassword" : "string",
    "userStatus" : "string"
  }
]
```

2.1.2 Search User By Id

1. Method

GET

2. Path

/parle/users/user/{userId}/

3. Parameters

Path Parameter:

userId

4. Return

```
{
  "userId" : "number",
  "userName" : "string",
  "userStatus" : "string"
}
```

2.1.3 Set User Status

1. Method

POST

2. Path

/parle/users/status/

3. Parameters

POST Parameters

```
{
  "userId" : "number",
  "userStatus" : "string"
}
```

4. Return

```
{
  "userId" : "number",
  "userStatus" : "string"
}
```

2.1.4 Login

1. Method

POST

2. Path

/parle/users/login

3. Parameters

POST Parameters

```
{
  "userName" : "string",
  "userPassword" : "string"
}
```

4. Return

(a) Login Successful

```
{
  "userId" : "number"
}
```

(b) Login Failed HTTP Status: 401

wrong password

2.1.5 Signup

1. Method

POST

2. Path

/parle/users/signup/

3. Parameters

POST Parameters

```
{
  "userName" : "string",
  "userPassword" : "string"
}
```

4. Return

```
{
  "userId" : "number"
}
```

2.1.6 Delete User

1. Method

POST

2. Path

/parle/users/delete

3. Parameters

```
{
  "userId" : "number"
}
```

4. Return

```
{
  "userId" : "number"
}
```

2.1.7 Search Users by Name

1. Method

POST

2. Path

/parle/users/search/

3. Parameters

POST Parameters

```
{
  "searchUserName" : "string"
}
```

4. Return

```
[
  {
    "userId" : "number",
    "userName" : "string",
    "userStatus" : "string"
  }
]
```

2.2 Chat Services

2.2.1 Chatlist

1. Method

GET

2. Path

/parle/chats/list/{userId}

3. Parameters

Path Parameters

userId

4. Return

```
[
  {
    "userId" : "number",
    "userName" : "string",
    "userStatus" : "string",
    "chatName" : "string"
  }
]
```

2.2.2 Chat messages

1. Method

GET

2. Path

/parle/chats/messages/{chatId}