catmech: when the favored model did not win

A case study in testing an idea until the evidence said no. Patrick Iben, independent biostatistician. Status on November 1, 2026: experimental R package, version 0.5.0. Not published, with no outside users, peer review or clinical validation.

Simulations that favored the new model
Model looked strong
Uncertainty ranges 30% to 38% narrower than the old default

Two public datasets, recording differences
Model lost or tied
Simple method lower error on ClinicalTrials.gov, tied on NHANES at a 25% audit

A real facility audit, not patient values
Inconclusive
Lower error on two of three slopes, but ranges covered 35% to 72%; a recount's, 90% to 97%

Clustered-audit option, on held-out items
PARTIAL
Helped on two of five; error up to 14% higher on the other three

Merged-paper idea, in simulation
NO-GO
Targeting by network position did not beat auditing the most suspicious records

Audit-size planner, on public data
NO-GO
Median error of 11.3% to 16.8% at the smallest audit, against a 10% limit

The problem

Records contain mistakes, and checking every record against its source is expensive, so studies often check only a sample, called an audit. The analyst then has two poor options: discard the unchecked recorded values and lose precision, or trust them and risk a distorted answer. The project asked whether a model could use recorded values without trusting them.

What was built

catmech is an R package that fills in unchecked values several plausible ways (multiple imputation), logs every replacement, and refuses to run when the data cannot support a request. Version 0.4 added the favored idea: a model that estimates how likely each record is to be wrong. It was tested against a deliberately plain baseline, linear imputation given the recorded value. A separate plain-Python script recomputes the reported summaries from the raw results.

What the evidence showed


Simulations favored the model. Its uncertainty ranges were 30% to 38% narrower than the old default, and it passed its coverage screen (how often the ranges contain the truth) in three of four main scenarios. Those scenarios used the kind of error the model assumes. It failed narrowly in the fourth, and clearly with extreme values in the data, audits selected on the true value, and noisy checked values that went undeclared.

Real data did not. On real recording differences in ClinicalTrials.gov and NHANES, the simple baseline matched or beat the model at a 25% audit. Across all nine real-data scenarios, the model was never clearly better. It also could not tell which records were wrong (AUC 0.54 and 0.50, where 0.50 is a coin flip). The useful result was plainer: keeping the recorded value nearly halved the error compared with discarding it, and the baseline got that gain with fewer assumptions.

Two more ideas failed their tests. A merged paper would have argued that audits in cluster trials should follow the direction in which errors spread between sites. In simulation, audits helped, but direction added nothing. An audit-size planner's median error stayed within 7.8% for larger audits but missed the 10% limit at the smallest, 30 of 600 records. The rule had no exception for that pattern, so the verdict stands.

A clustered-audit option came out partial. Resampling audited facilities in each imputation helped where the simple method fell short and raised error elsewhere, and a single audit cannot show which case applies.

Typical error, simple method against new model



Keeping the recorded value nearly halved the error. RMSE of the estimated slope at a 25% audit, 1,000 cohorts of 600. "All references" uses every checked value: a benchmark, not a usable method.

The decision

- **Recommend the simple baseline first when an interval is needed.** It is now a package option. The new model stays for gross errors, untested on real data, where the baseline's 95% ranges covered only 64.7% in simulation, against 94.0%.
- **Do not write the merged paper** on that thesis.
- **Keep the planner as a documented calculation,** labeled not validated, **and the clustered-audit option as experimental.** Nothing was retuned after viewing.
- **Claim no new statistical method.**

Technical sidebar

Target: each pool's regression coefficient using every reference, in cohorts of 600 resampled from pools of 27,208 and 3,908 rows, with 1,000 cohorts at a 25% audit and m = 20. Coverage, linear MI against the contamination model: 91.8% and 91.2% on ClinicalTrials.gov, 93.9% and 94.5% on NHANES. The oracle covered 91.2% and 94.9%, so coverage was judged against it. Paired MSE difference on ClinicalTrials.gov: 1.31e-4 (MCSE 2.2e-5). Every study had a written plan before its evaluation run, and earlier looks are disclosed. The planner test was prospective for the code but not fully blind, because earlier tables from those pools had been seen.

Limits and AI disclosure. No dataset here is a patient-level clinical source-data audit, and on ClinicalTrials.gov both values are sponsor-entered. Simulation data are synthetic. OpenAI Codex and Anthropic Claude Code were used for code drafting, literature search, adversarial review, test construction and simulation orchestration, and Claude Code helped draft this page. No AI system is listed as an author, and AI review is not peer review. Patrick retains responsibility for the scientific claims, intended-use decisions and release.

Sources in `validation/`: `REAL_DATA_SYNTHESIS.md`, `CONTAMINATION_SYNTHESIS.md`, `merged-audit-pilot/README.md`, `AUDIT_PLAN_SYNTHESIS.md`, `REAL_AUDIT_SYNTHESIS.md`, `CLUSTERED_SYNTHESIS.md`. Every number is traced in `docs/case-study/FACT_CHECK.md`.