ø.	AddressTest	
0.4	streetAndNumber	String
0.4	city	String
0.4	zipCode	String
0.4	state	String
0 +	country	String
0 4	expected Street And Numbe	rString
0 4	expectedCity	String
0.	expectedZipCode	String
0.	expectedState	String
0.	expectedCountry	String
0.4	address A	ddress
(b) +	notAddressClass	String
-	setUp()	void
9.0	getStreetAndNumber()	void
*	setStreetAndNumber()	void
*	getCity()	void
*	setCity()	void
	getZipCode()	void
*	setZipCode()	void
9.0	getState()	void
9.0	setState()	void
9.0	getCountry()	void
9.0	setCountry()	void
40	testEquals()	void
40	testHashCode()	void
# 4	testToString()	void

6 %	RestaurantTest	
0.4	restaurantName	String
0.4	address	Address
0.4	menu	Menu
0.4	openOrClosed	Boolean
0.4	expectedRestaurantName String	
0.4	expectedAddress	Address
0.4	expectedMenu	Menu
0.4	expectedOpenOrClosedBoolean	
0.4	restaurant	Restaurant
9.4	notRestaurantClass	String
0.5	setUp()	void
6.	getRestaurantName()	void
8.	setRestaurantName()	void
8.	getAddress()	void
8.	setAddress()	void
8.	getMenu()	void
8.	setMenu()	void
8.	getOpenOrClosed()	void
6.0	setOpenOrClosed()	void
8.	testEquals()	void
8.	testHashCode()	void
8.	testToString()	void

Ø-	MenuTest	
0.4	meals	List <string></string>
0.4	desserts	List <string></string>
0.4	beverages	List <string></string>
0.4	drinks	List <string></string>
0.4	expectedMeals	List <string></string>
0.4	${\sf expectedDesserts}$	List <string></string>
	expectedBeveragesList <string></string>	
0.4	expectedDrinks	List <string></string>
0.4	menu	Menu
	notMenuClass	String
0.5	setUp()	void
6.2	getMeals()	void
60.0	setMeals()	void
6.2	getDesserts()	void
40	setDesserts()	void
40	getBeverages()	void
6.2	setBeverages()	void
6.7	getDrinks()	void
6.2	setDrinks()	void
8.	testToString()	void
8.	testEquals()	void
# m	testHashCode()	void

0 %	Address	
0.4	streetAndNumber	String
0.4	city	String
0.4	zipCode	String
0.4	state	String
0.4	country	String
0.5	Address(String, String, String, String	, String)
0.5	getStreetAndNumber()	String
0.5	setStreetAndNumber(String)	void
0.5	getCity()	String
0.5	setCity(String)	void
0.5	getZipCode()	String
0.4	setZipCode(String)	void
0.4	getState()	String
0.5	setState(String)	void
0.5	getCountry()	String
0.5	setCountry(String)	void
0.5	equals(Object)	boolean
0.5	hashCode()	int
8.5	toString()	String

■ ■ Menu	
■ meals	List <string></string>
desserts	List <string></string>
	List <string></string>
	List <string></string>
■ Menu(List <string>, List<string< p=""></string<></string>	g>, List <string>, List<string>)</string></string>
equals(Object)	boolean
	int
■ ■ getMeals()	List <string></string>
■ setMeals(List <string>)</string>	void
■ ■ getDesserts()	List <string></string>
■ setDesserts(List <string>)</string>	void
■ ■ getBeverages()	List <string></string>
■ setBeverages(List <string>)</string>	void
■ ■ getDrinks()	List <string></string>
■ setDrinks(List <string>)</string>	void
■ toString()	String

0 %	Restaurant	
0.4	restaurantName	String
0.4	address	Address
0.4	menu	Menu
0.4	openOrClosed	Boolean
■ Restaurant(String, Address, Menu, Boolean)		
0.5	getRestaurantName()	String
0.5	setRestaurantName(String)	void
-	getAddress()	Address
0.5	setAddress(Address)	void
0.5	getMenu()	Menu
0.5	setMenu(Menu)	void
0.5	getOpenOrClosed()	Boolean
0.5	set Open Or Closed (Boolean)	void
	equals(Object)	boolean
	hashCode()	int
8.5	toString()	String