

COS214 Practical 4

Courtesy of

- Patrick Simuyemba : u25632354
- N'des Junior Lungwangu : u25069366
- member3 : never showed up

Task 1: Design the System

Domain: Software delivery workflow

Problem

- A software-delivery workflow is not a flat list of jobs. Work is nested (epics, stories, and unit tasks), each item moves through a lifecycle, the same tree must be walkable in more than one order, and extra concerns such as priority or extra personnel must be stacked onto a task without rewriting the task types. The demo tree we actually built is **Website Relaunch with Backend Work / Frontend Work** and the unit tasks under them.

Complete UML diagram




Figure 1: Complete UML Diagram of the design of our System

GoF Participants in [Iterator, Composite, decorator, State]

Iterator

- Iterator: **Iterator**
- ConcreteIterator: **TGIterator**, **StateIterator**
- Aggregate: **Task**
- ConcreteAggregate: **TaskDecorator**, **UnitTask**, **TaskGroup**

Composite

- Component: **Task**
- Leaf: **UnitTask**
- Composite: **TaskGroup**

Decorator

- Component: `Task`
- ConcreteComponent: `UnitTask`
- Decorator: `TaskDecorator`
- ConcreteDecorator: `PersonnelDecorator`, `PriorityDecorator`

State

- State: `TaskState`
- context: `Task`
- ConcreteState: `Design`, `Implementation`, `UnderReview`, `Deployed`

Rationale for important design and ownership decisions

- A `Task` starts in `Design` (the constructor does `state = new Design(this)`). Over its lifetime it can move `Design` -> `Implementation` -> `Under Review` -> `Deployed`. `UnderReview` can send work back to `Implementation` (reject). `Deployed` is absorbing, it just says the task is already deployed. `updateState(requested, testPassed)` is the event. The current concrete state decides if the request is legal. Illegal requests print `Invalid Request` and `delete requested` so we don't leak the object that nobody adopted. A task owns its `TaskState` and deletes it in the destructor / `setState`.
- A `TaskGroup` contains sub tasks and naturally owns these sub tasks. When the `TaskGroup` goes out of scope, it must delete its sub tasks appropriately. `add` ignores null and duplicates. `remove` takes a child out of the vector but does not delete it (so we can wrap it and add it back, like in the sprint fast-track scenario).
- Features can be added to a task dynamically. For example, you can raise the priority of a task through the `PriorityDecorator` and add personnel to work on a task through the `PersonnelDecorator`. The decorator owns the `Task` which it is decorating and must delete it when it goes out of scope. `updateState` and `logState` just forward into `wrappedTask`.
- Two iterators: `TGIterator` walks the children vector of a group (order as stored). `StateIterator` is meant to pick children matching a lifecycle. `begin()` / `end()` return fresh `Iterator*` each time so two clients can walk the same group independently. Client has to `delete` those pointers.

Task 2: Implement the core model

Task 3: Dynamic Behaviour and Design Decisions

Task 4: UML Diagram Portfolio

Object diagram




Figure 2: Object diagram of nested task objects

State diagram

- Snapshot of Task lifecycle through Design and Implementation (This idea applies to other states)




Figure 3: State diagram of a Task lifecycle

Activity diagram 1 - status walk of Website Relaunch

- Assemble the epic then walk it with TGIterator

Visual Paradigm Standard(Patrick Simuyumba(University of Pretoria))




Figure 4: Activity diagram 1: traverse a work group

Activity diagram 2 - lifecycle requests

- updateState through UnitTask / Design / Implementation swimlanes.

Visual Paradigm Standard(Patrick Simuyumba(University of Pretoria))




Figure 5: Activity diagram 2: updateState through Design then Implementation

Activity diagram 3 - decorator stack then update

- Personnel and Priority forward updateState into UnitTask / Design.




Figure 6: Activity diagram 3: decorator forwarding

Task 5: Debugging and Memory Investigation

GDB: traversal

```

gdb ./taskforge
(gdb) break TGIterator::operator++
(gdb) run
(gdb) print (*current)->getDescription()
(gdb) continue
  
```

First hit after `project->begin()` is Backend Work, next is Frontend Work. That is what I expected: TGIterator only walks the top-level children vector of Website Relaunch, it does not by itself walk into Design DB schema. `logState` on a group still dumps the nested leaves because `TaskGroup::logState` recurses.

GDB: decorator / state

```

(gdb) break TaskDecorator::updateState
(gdb) break Design::updateState
(gdb) run
(gdb) backtrace
  
```

On the stacked task (PersonnelDecorator wrapping PriorityDecorator wrapping the unit task) the stack is `main -> decorator updateState -> Task::updateState -> Design::updateState`. `print testPassed` and `print requested->state()`.

Valgrind

`make mem`

Bug

Symptom: Design -> Implementation prints the new status, but Valgrind still complains about the state object.

Cause: `Design::updateState` calls `context->setState(requested)`. `Task::setState` does `delete this->state`, and that pointer is the same `Design` whose `updateState` has not hit `}` yet. `setState` does not call `updateState`; `updateState` called `setState`, then C++ returns into a destroyed object. Decorator `updateState` only forwards, so the delete still happens on the inner `UnitTask`'s `Design`.

Task 6: Docker and GitHub Workflow

- `github`: https://github.com/patrickkaleo/COS214_P4

Dockerfile is Ubuntu 22.04 with `g++`, `make`, `gdb`, `valgrind`. It copies `makefile`, `include/`, `src/` and makes `taskforge`. Default cmd is `./taskforge`.

```
docker build -t taskforge .
docker run --rm taskforge
docker run --rm --entrypoint make taskforge mem
```

GDB inside docker needs `ptrace`:

```
docker run --rm -it --cap-add=SYS_PTRACE --security-opt seccomp=unconfined --entrypoint gdb taskforge .
```

Reflection

- Work was split along the four patterns and kept on two branches, `dev` and `ndes`. We integrated by merge and pull rather than a single end-of-week dump. There are no GitHub pull requests; collaboration shows up in those branches and in merge commit `4f84853`.
- Patrick Simuyemba (`u25632354`) owned the repo setup, Task 1 design, most of the Composite and Iterator core (Task 2), the UML activity and object diagrams (Task 4), and Tasks 5-6 (GDB/Valgrind, Dockerfile, `taskforge` Makefile, README). N'des Junior Lungwangu (`u25069366`) owned State and Decorator and the demo `main`.
- Patrick's line starts at `ed53f64` and `f638ecc` (1 Sep): initial repo, `submission.md`, and the PDF/zip scripts. `329dd78` (2 Sep) is Task 1 - domain, class diagram, and GoF mapping. `77bd118`, `7bbe88a`, and `eeaff87` (3-5 Sep) are the Task 2 iterator slice: `begin()/end()`, iterator interfaces, and `TGIterator`. `dee0338` (5 Sep) is the overlapping Decorator and Iterator work. `cea6a01` (6 Sep) updates the Task 4 figures.
- N'des appears on `dev` from `d45ebe6` (3 Sep, names and delegation). `b13f6c6` (4 Sep) adds constructors and `setState`. `4f84853` (6 Sep, *Decorator fixes*) is a merge with two parents: N'des's decorator branch and Patrick's iterator line. That is the integration point. `a58bb04` (6 Sep, on `ndes`) is the Task 2 demo, brought onto `dev` with `git pull origin ndes`.
- `dev` was the integration branch; `ndes` was N'des's feature line. The two histories met in `4f84853` and in the later fast-forward of `ndes` onto `dev`.

Task 7: Integration and Demonstration