

Phaco meta analysis

Patrick Mineault

14/02/2017

Contents


Analysis of full dataset	1
Main analysis: 12-month+ follow up	1
AACG	4
Meds	5
Correlation between meds and drop in IOP	7
Separate meta-analysis for each time period	9
6 month follow-up	9
12-month follow up	10
Last period	12
Correlation among time points	13
Multivariate inference	19
Meta-regression	21
Small study bias	28
Alternative filterings of the data	31
Prospective studies only	31
Meds	31
Excluding washout studies	32
Last period	32
Meds	34
Sensitivity to missingness	37
MIGS	39

Analysis of full dataset

Main analysis: 12-month+ follow up

```
df_ <- df %>%
  filter(!is.na>LastPeriodAbsIOPChangeMean), subtype != "AACG", MIGsYorN == 'N') %>%
  mutate(subtype=factor(subtype))
m <- metagen>LastPeriodAbsIOPChangeMean,
      LastPeriodAbsIOPChangeStdDev / sqrt>LastPeriodEyes),
      study.name,
      data=df_,
      byvar=subtype,
```

```
        n.e=LastPeriodEyes)
forest(m,
      comb.fixed=FALSE,
      digits=1,
      digits.se = 2,
      overall=FALSE,
      leftcols=c("studlab", "TE", "seTE", "n.e"),
      leftlabs=c("Study", "ΔIOP", "SE", "eyes"))
```



AACG

```
df_ <- df %>%
  filter(!is.na>LastPeriodAbsIOPChangeMean), subtype == "AACG", MIGsYorN == 'N') %>%
  mutate(subtype=factor(subtype)) %>% dplyr::arrange(Year)
m <- metagen>LastPeriodAbsIOPChangeMean,
      LastPeriodAbsIOPChangeStdDev / sqrt>LastPeriodEyes),
      study.name,
      data=df_,
      n.e>LastPeriodEyes, comb.fixed = FALSE)
print(m)

df_ <- df %>%
  filter(!is.na>LastPeriodAbsIOPChangeMean), subtype == "AACG", MIGsYorN == 'N') %>%
  mutate(subtype=factor(subtype)) %>% dplyr::arrange(Year)
m <- metagen>RxChangeMean,
      RxChangeStdDev / sqrt>LastPeriodEyes),
      study.name,
      data=df_,
      n.e>LastPeriodEyes, comb.fixed = FALSE)
print(m)


df_ %>% dplyr::select(RxPreOpMean, RxPostOpMean)
```

```
##                                     95%-CI %W(random)
## Lam et al. (2008)      -47.1000 [-50.0948; -44.1052]      26.8
## Lee et al. (2010)      -35.8000 [-39.6379; -31.9621]      25.9
## Husain et al. (2012) -44.5000 [-52.0026; -36.9974]      20.6
## Hou et al. (2015)      -35.9600 [-39.0429; -32.8771]      26.7
##
## Number of studies combined: k = 4
##
##                                     95%-CI      z  p-value
## Random effects model -40.665 [-47.1528; -34.1772] -12.28 < 0.0001
##
## Quantifying heterogeneity:
## tau^2 = 38.5307; H = 3.36 [2.26; 4.99]; I^2 = 91.1% [80.4%; 96.0%];
## Rb = 87.9% [68.9%; 100.0%]
##
## Test of heterogeneity:
##      Q d.f.  p-value
## 33.84    3 < 0.0001
##
## Details on meta-analytical method:
## - Inverse variance method
## - DerSimonian-Laird estimator for tau^2
##                                     95%-CI %W(random)
## Lam et al. (2008)      -0.3600 [-0.5876; -0.1324]      100.0
## Lee et al. (2010)      NA                                0.0
## Husain et al. (2012)   NA                                0.0
## Hou et al. (2015)      NA                                0.0
##
## Number of studies combined: k = 1
##
```

```
##                                     95%-CI      z  p-value
## Random effects model -0.36 [-0.5876; -0.1324] -3.10  0.0019
##
## Quantifying heterogeneity:
## tau^2 = 0; H = NA; I^2 = NA;
## Rb = NA
##
## Details on meta-analytical method:
## - Inverse variance method
## - DerSimonian-Laird estimator for tau^2
## RxPreOpMean RxPostOpMean
## 1          0.39          0.03
## 2           NA          0.10
## 3           NA           NA
## 4           NA          0.48
```

Meds

```
df_ <- df %>%
  filter(!is.na(LastPeriodAbsIOPChangeMean),
         df$subtype != "AACG", MIGsYorN == 'N') %>%
  mutate(subtype=factor(subtype))
m <- metagen(RxChangeMean,
             RxChangeStdDev / sqrt(LastPeriodEyes),
             study.name,
             data=df_,
             byvar=subtype,
             n.e=LastPeriodEyes)
forest(m,
       comb.fixed=FALSE,
       digits=1,
       digits.se = 2,
       overall=FALSE,
       leftcols=c("studlab", "TE", "seTE", "n.e"),
       leftlabs=c("Study", "ΔIOP", "SE", "eyes"))
```



Correlation between meds and drop in IOP

How is IOP drop related to change in meds? Two hypotheses:

- Those studies that see the largest IOP drops also have drop in meds, as doctors see that can use the newfound *slack* to decrease the number of meds people take
- The studies that see the largest IOP drops are those that don't change meds, because dropping meds would also increase IOP


So which is it?

```
df_ <- df %>% mutate(RxChangeSEM = RxChangeStdDev / sqrt>LastPeriodEyes),
                    LastPeriodAbsIOPChangeSEM = LastPeriodAbsIOPChangeStdDev / sqrt>LastPeriodEyes))

ggplot(df_, aes(x =LastPeriodAbsIOPChangeMean,
                xmin=LastPeriodAbsIOPChangeMean - 1.96*LastPeriodAbsIOPChangeSEM,
                xmax=LastPeriodAbsIOPChangeMean + 1.96*LastPeriodAbsIOPChangeSEM,
                y =RxChangeMean,
                ymin=RxChangeMean - 1.96*RxChangeSEM,
                ymax=RxChangeMean + 1.96*RxChangeSEM,
                color=subtype
            )) + geom_errorbar() + geom_errorbarh()
```

Warning: Removed 17 rows containing missing values (geom_errorbar).

Warning: Removed 15 rows containing missing values (geom_errorbarh).




```
ggplot(df_ %>% filter(subtype=='OAG' & MIGsYorN == 'N'),
       aes(x =LastPeriodAbsIOPChangeMean,
```

```

xmin=LastPeriodAbsIOPChangeMean - 1.96*LastPeriodAbsIOPChangeSEM,
xmax=LastPeriodAbsIOPChangeMean + 1.96*LastPeriodAbsIOPChangeSEM,
y =RxChangeMean,
ymin=RxChangeMean - 1.96*RxChangeSEM,
ymax=RxChangeMean + 1.96*RxChangeSEM,
label=study.name
)) + geom_errorbar(alpha=.2) + geom_errorbarh(alpha=.2) + ggtitle('OAG only') + geom_text_rep

```

OAG only



There is an apparent positive correlation between the two effect sizes: studies with larger drops in IOP also tend to see larger drops in Rx.

```

draw.corr <- function(x.mean, x.sem, y.mean, y.sem) {
  d_ <- data.frame(x = rnorm(n = length(x.mean), mean=x.mean, sd = x.sem),
                  y = rnorm(n = length(x.mean), mean=y.mean, sd = y.sem))
  with(d_ %>% filter(!is.na(x) & !is.na(y)), cor(x, y))
}

cat("Mean +- SE correlation, all studies\n")

## Mean +- SE correlation, all studies

df_ <- df %>% filter(subtype=='OAG', MIGsYorN == 'N')
drawn.corr <- with(df_, replicate(n = 100,
  draw.corr(LastPeriodAbsIOPChangeMean,
            LastPeriodAbsIOPChangeStdDev / sqrt(LastPeriodEyes),
            RxChangeMean,
            RxChangeStdDev / sqrt(LastPeriodEyes))))
mean(drawn.corr)

```



```
## [1] 0.3812048
sd(drawn.corrs)

## [1] 0.1348602
cat("Mean +- SE correlation, no washout\n")

## Mean +- SE correlation, no washout
df_ <- filter.data(df, 'nowashout') %>% filter(subtype=='OAG', MIGsYorN == 'N')
drawn.corrs <- with(df_, replicate(n = 100,
                                draw.corr(LastPeriodAbsIOPChangeMean,
                                           LastPeriodAbsIOPChangeStdDev / sqrt(LastPeriodEyes),
                                           RxChangeMean,
                                           RxChangeStdDev / sqrt(LastPeriodEyes))))
mean(drawn.corrs)

## [1] -0.02253974
sd(drawn.corrs)

## [1] 0.1941081
```


However, this effect goes away when we focus on the studies which don't have washout.

Separate meta-analysis for each time period

```
df <- read.data(fill.last = FALSE)
```

6 month follow-up


```
df_ <- df %>%
  filter(!is.na(SixMoAbsIOPChangeMean), subtype != "AACG") %>%
  mutate(subtype=factor(subtype))
m <- metagen(SixMoAbsIOPChangeMean,
             SixMoAbsIOPChangeStdDev / sqrt(SixMoEyes),
             study.name,
             data=df_,
             byvar=subtype,
             n.e=SixMoEyes)
forest(m,
       comb.fixed=FALSE,
       digits=1,
       digits.se = 2,
       overall=FALSE,
       leftcols=c("studlab", "TE", "seTE", "n.e"),
       leftlabs=c("Study", "ΔIOP", "SEM", "eyes"))
```



12-month follow up


```
df_ <- df %>%
  filter(!is.na(OneYAbsIOPChangeMean), subtype != "AACG", MIGsYorN == 'N') %>%
  mutate(subtype=factor(subtype))
m <- metagen(OneYAbsIOPChangeMean,
  OneYAbsIOPChangeStdDev / sqrt(OneYEyes),
  study.name,
  data=df_,
  byvar=subtype,
  n.e=OneYEyes)
```

```
forest(m,
  comb.fixed=FALSE,
  digits=1,
  digits.se = 2,
  overall=FALSE,
  leftcols=c("studlab", "TE", "seTE", "n.e"),
  leftlabs=c("Study", "ΔIOP", "SEM", "eyes"))
```



Last period

```
df_ <- df %>%
  filter(!is.na>LastPeriodAbsIOPChangeMean), subtype != "AACG", MIGsYorN == 'N') %>%
  mutate(subtype=factor(subtype))
m <- metagen>LastPeriodAbsIOPChangeMean,
      LastPeriodAbsIOPChangeStdDev / sqrt>LastPeriodEyes),
      study.name,
      data=df_,
      byvar=subtype,
      n.e>LastPeriodEyes)
forest(m,
  comb.fixed=FALSE,
  digits=1,
  digits.se = 2,
  overall=FALSE,
  leftcols=c("studlab", "TE", "seTE", "n.e"),
  leftlabs=c("Study", "ΔIOP", "SEM", "eyes"))
```



Correlation among time points

Measure the correlation between different outcomes (IOP at 6 months vs. 12 months).

```
ggplot(df %>% filter(subtype != 'AACG') %>% mutate(subtype = factor(subtype)),
  aes(x = SixMoAbsIOPChangeMean,
      xmin=SixMoAbsIOPChangeMean - 1.96*SixMoAbsIOPChangeStdDev / sqrt(SixMoEyes),
      xmax=SixMoAbsIOPChangeMean + 1.96*SixMoAbsIOPChangeStdDev / sqrt(SixMoEyes),
      y = OneYAbsIOPChangeMean,
```


```

    ymin= OneYAbsIOPChangeMean - 1.96*OneYAbsIOPChangeStdDev / sqrt(OneYEyes),
    ymax= OneYAbsIOPChangeMean + 1.96*OneYAbsIOPChangeStdDev / sqrt(OneYEyes),
    label=study.name,
    color=subtype
  )) +
  geom_abline(slope = 1, color="gray70") +
  geom_errorbar() +
  geom_errorbarh() +
  xlab('ΔIOP at 6 months') +
  ylab('ΔIOP at one year') +
  coord_fixed(xlim=c(-18, 0), ylim=c(-18,0))

```

Warning: Removed 22 rows containing missing values (geom_errorbar).

Warning: Removed 22 rows containing missing values (geom_errorbarh).



It's very clear that six months and 12 months IOP are highly correlated.

Similarly for one-year vs. last period:

```

ggplot(df %>% filter(subtype != 'AACG') %>% mutate(subtype = factor(subtype)),
  aes(y = LastPeriodAbsIOPChangeMean,
    ymin=LastPeriodAbsIOPChangeMean - 1.96*LastPeriodAbsIOPChangeStdDev / sqrt(LastPeriodEyes),
    ymax=LastPeriodAbsIOPChangeMean + 1.96*LastPeriodAbsIOPChangeStdDev / sqrt(LastPeriodEyes),
    x = OneYAbsIOPChangeMean,
    xmin= OneYAbsIOPChangeMean - 1.96*OneYAbsIOPChangeStdDev / sqrt(OneYEyes),
    xmax= OneYAbsIOPChangeMean + 1.96*OneYAbsIOPChangeStdDev / sqrt(OneYEyes),
    label=study.name,
    color=subtype
  )

```


```

    )) +
    geom_abline(slope = 1, color="gray70") +
    geom_errorbar() + geom_errorbarh() +
    coord_fixed(xlim=c(-20, 0), ylim=c(-20,0))

```

```
## Warning: Removed 22 rows containing missing values (geom_errorbar).
```

```
## Warning: Removed 22 rows containing missing values (geom_errorbarh).
```



Again, correlations are very high. Present this in another way.

```
library(reshape2)
```

```
##
```

```
## Attaching package: 'reshape2'
```

```
## The following object is masked from 'package:tidyr':
```

```
##
```

```
## smiths
```

```
nd <- melt(df %>%
```

```
  filter(MIGsYorN == 'N',
```

```
        subtype != 'AACG',
```

```
        1*is.na(SixMoAbsIOPChangeMean) +
```

```
        1*is.na(OneYAbsIOPChangeMean) +
```

```
        1*is.na>LastPeriodAbsIOPChangeMean) < 2) %>%
```

```
  mutate(SixMoChangeSEM = SixMoAbsIOPChangeStdDev / sqrt(SixMoEyes),
```


```
         OneYChangeSEM = OneYAbsIOPChangeStdDev / sqrt(OneYEyes),
```

```
         LastPeriodChangeSEM = LastPeriodAbsIOPChangeStdDev / sqrt>LastPeriodEyes)) %>%
```

```

      select(study.name, subtype,
             SixMoAbsIOPChangeMean,
             OneYAbsIOPChangeMean,
             LastPeriodAbsIOPChangeMean,
             SixMoChangeSEM,
             OneYChangeSEM,
             LastPeriodChangeSEM), id.vars=c("study.name", "subtype"))
nd$metric <- substr(nd$variable, nchar(as.character(nd$variable)) - 3, nchar(as.character(nd$variable)))
nd$period <- substr(nd$variable, 0, 4)
df_ <- dcast(nd, formula = study.name + subtype + period ~ metric)
df_ <- df_ %>% mutate(period = factor(period, c('SixM', 'OneY', 'Last')),
                    g = paste(study.name, as.character(subtype))) %>% filter(!is.na(Mean))
ggplot(df_, aes(y =Mean,
               ymin=Mean - 1.96*eSEM,
               ymax=Mean + 1.96*eSEM,
               x = period,
               label=study.name,
               group=g)) +
  geom_ribbon(alpha=.02) +
  geom_line(alpha=.5, aes(color=subtype)) +
  coord_cartesian(y=c(-15, 0)) + ggtitle('Time course of IOP per study') + theme(plot.title = element_t

```

It's remarkable how consistent measurements are between time periods. At most, we find a change of ± 2.5 mm Hg between the first and last period.

```
df_ <- df %>% filter(subtype=='OAG')
drawn.corr <- with(df_, replicate(n = 100,
  draw.corr(SixMoAbsIOPChangeMean,
    SixMoAbsIOPChangeStdDev / sqrt(SixMoEyes),
    OneYAbsIOPChangeMean,
    OneYAbsIOPChangeStdDev / sqrt(OneYEyes))))
cat("Mean +- SE correlation, OAG only\n")

## Mean +- SE correlation, OAG only
```

```

print(mean(drawn.corrs))

## [1] 0.6287425
print(sd(drawn.corrs))

## [1] 0.1808015
df_ <- df
drawn.corrs <- with(df_, replicate(n = 100,
                                   draw.corr(SixMoAbsIOPChangeMean,
                                              SixMoAbsIOPChangeStdDev / sqrt(SixMoEyes),
                                              OneYAbsIOPChangeMean,
                                              OneYAbsIOPChangeStdDev / sqrt(OneYEyes))))
cat("Mean +- SE correlation, All subtypes\n")

## Mean +- SE correlation, All subtypes
print(mean(drawn.corrs))

## [1] 0.9912487
print(sd(drawn.corrs))

## [1] 0.003900496
cat("Regression of one year against 6 months")

## Regression of one year against 6 months
print(summary(lm(OneYAbsIOPChangeMean ~ SixMoAbsIOPChangeMean,
                 df,
                 weights = OneYAbsIOPChangeStdDev / sqrt(OneYEyes))))

##
## Call:
## lm(formula = OneYAbsIOPChangeMean ~ SixMoAbsIOPChangeMean, data = df,
##     weights = OneYAbsIOPChangeStdDev/sqrt(OneYEyes))
##
## Weighted Residuals:
##      Min       1Q   Median       3Q      Max
## -1.54354 -0.22175  0.06606  0.24424  2.17907
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    -0.18172    0.25885  -0.702    0.492
## SixMoAbsIOPChangeMean  0.98209    0.01326  74.083 <2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.8044 on 18 degrees of freedom
## (25 observations deleted due to missingness)
## Multiple R-squared:  0.9967, Adjusted R-squared:  0.9965
## F-statistic: 5488 on 1 and 18 DF,  p-value: < 2.2e-16

```

This is also reflected in the correlations - even accounting for noise, the correlations are $> .9$ between month 6 and month 12.

Multivariate inference

Let's use mvmeta to infer the effect size for all periods together.

```
library(mvmeta)
```

```
## This is mvmeta 0.4.7. For an overview type: help('mvmeta-package').
```

```
fill.na <- function(x, y, z) {
  return(ifelse(!is.na(x),
                x,
                ifelse(is.na(y),
                      z,
                      ifelse(is.na(z),
                            y,
                            sqrt((y**2 + z**2) / 2 )))))
}

get.correlation.matrices.tri <- function(x, y, z, assumed.rho) {
  S <- list()
  for(i in 1:length(x)) {
    xx <- fill.na(x[i], y[i], z[i])
    yy <- fill.na(y[i], x[i], z[i])
    zz <- fill.na(z[i], x[i], y[i])
    S[[i]] <- matrix(c(xx ** 2, xx * yy * assumed.rho, xx * zz * assumed.rho ** 2,
                      xx * yy * assumed.rho, yy ** 2, zz * yy * assumed.rho,
                      xx * zz * assumed.rho ** 2, zz * yy * assumed.rho, zz * zz), ncol=3)
  }
  S
}

df_ <- df %>% filter(!is.na>LastPeriodAbsIOPChangeStdDev) |
  !is.na(SixMoAbsIOPChangeStdDev) |
  !is.na(OneYAbsIOPChangeStdDev), subtype %in% c('OAG', 'ACG'), MIGsYorN == 'N')

thefit <- mvmeta(cbind(SixMoAbsIOPChangeMean, OneYAbsIOPChangeMean, LastPeriodAbsIOPChangeMean) ~ subtype,
  S=get.correlation.matrices.tri(df_$SixMoAbsIOPChangeStdDev / sqrt(df_$SixMoEyes),
                                df_$OneYAbsIOPChangeStdDev / sqrt(df_$OneYEyes),
                                df_$LastPeriodAbsIOPChangeStdDev / sqrt(df_$LastPeriodEyes), .7),
  data=df_,
  method="reml")

summary(thefit)
```

```
## Call: mvmeta(formula = cbind(SixMoAbsIOPChangeMean, OneYAbsIOPChangeMean,
## LastPeriodAbsIOPChangeMean) ~ subtype, S = get.correlation.matrices.tri(df_$SixMoAbsIOPChangeStdDev/
## df_$OneYAbsIOPChangeStdDev/sqrt(df_$OneYEyes), df_$LastPeriodAbsIOPChangeStdDev/sqrt(df_$LastPeriod
## 0.7), data = df_, method = "reml")
##
## Multivariate random-effects meta-regression
## Dimension: 3
## Estimation method: REML
##
## Fixed-effects coefficients
## SixMoAbsIOPChangeMean :
```

```
##           Estimate Std. Error      z Pr(>|z|) 95%ci.lb 95%ci.ub
## (Intercept)  -5.9092    0.7536 -7.8415  0.0000  -7.3862  -4.4322
## subtypeOAG    2.9191    1.0558  2.7648  0.0057   0.8497   4.9884
##
## (Intercept) ***
## subtypeOAG **
## OneYAbsIOPChangeMean :
##           Estimate Std. Error      z Pr(>|z|) 95%ci.lb 95%ci.ub
## (Intercept)  -6.0973    0.7637 -7.9839  0.0000  -7.5941  -4.6004
## subtypeOAG    3.3817    1.0607  3.1882  0.0014   1.3028   5.4606
##
## (Intercept) ***
## subtypeOAG **
## LastPeriodAbsIOPChangeMean :
##           Estimate Std. Error      z Pr(>|z|) 95%ci.lb 95%ci.ub
## (Intercept)  -6.2665    0.6835 -9.1681  0.0000  -7.6061  -4.9268
## subtypeOAG    3.5782    0.9378  3.8157  0.0001   1.7402   5.4162
##
## (Intercept) ***
## subtypeOAG ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Between-study random-effects (co)variance components
## Structure: General positive-definite
##
##           Std. Dev      Corr
## SixMoAbsIOPChangeMean    2.9873 SixMoAbsIOPChangeMean
## OneYAbsIOPChangeMean     3.0257    0.9969
## LastPeriodAbsIOPChangeMean 2.6062    0.9901
##
## SixMoAbsIOPChangeMean    OneYAbsIOPChangeMean
## OneYAbsIOPChangeMean
## LastPeriodAbsIOPChangeMean    0.9823
##
## Multivariate Cochran Q-test for residual heterogeneity:
## Q = 1520.2986 (df = 62), p-value = 0.0000
## I-square statistic = 95.9%
##
## 36 studies, 68 observations, 6 fixed and 6 random-effects parameters
##      logLik      AIC      BIC
## -118.9294  261.8587  287.3844
```

```
newdata <- data.frame(subtype=c('OAG', 'ACG'))
pred <- predict(thefit, newdata, se=TRUE)
newdata$SixMoAbsIOPChangeMean <- pred$fit[,1]
newdata$OneYAbsIOPChangeMean <- pred$fit[,2]
newdata$LastPeriodAbsIOPChangeMean <- pred$fit[,3]
newdata$SixMoAbsIOPChangeSEM <- pred$se[,1]
newdata$OneYAbsIOPChangeSEM <- pred$se[,2]
newdata$LastPeriodAbsIOPChangeSEM <- pred$se[,3]
```


```
library(reshape2)
nd <- melt(newdata)
```

```
## Using subtype as id variables
```

```

nd$period <- substr(nd$variable, 0, 4)
nd$metric <- substr(nd$variable, nchar(as.character(nd$variable)) - 3, nchar(as.character(nd$variable)))
df_ <- dcast(nd, formula = subtype + period ~ metric)
df_$period <- factor(df_$period, c('SixM', 'OneY', 'Last'))
ggplot(df_, aes(x=period,
                y=Mean,
                ymin=Mean - 1.96*eSEM,
                ymax=Mean + 1.96*eSEM,
                group=subtype,
                fill=subtype)) + geom_ribbon(alpha=.2) + geom_line(aes(color=subtype)) + ylab("Inferred

```



Meta-regression

Consider relationships between different covariates and outcomes. Focus on the IOP drop at one year and its correlation with different factors.

```

df <- read.data()

## These retrospective studies are losing eyes per period - not impossible, but unusual:
## Mathalone et al. (2005)
## Leelachaikul et al. (2005)
## Shoji et al. (2007)
## Liu et al. (2011)
## Arthur et al. (2014)
## Tetz et al. (2015)

```

```
## These retrospective studies are gaining eyes as the study goes
## Samuelson et al. (2011)
df_ <- df %>% filter(!is.na>LastPeriodAbsIOPChangeMean),
                      subtype != "AACG",
                      MIGsYorN == 'N') %>%
  mutate(coarseWashoutType=factor(washout.type, c("None", "Partial", "Pre", "Both")),
         subtype=relevel(factor(subtype), ref="OAG"))
levels(df_$coarseWashoutType) <- c("None", "None", "Pre", "Both")

m <- metagen>LastPeriodAbsIOPChangeMean,
      LastPeriodAbsIOPChangeStdDev / sqrt>LastPeriodEyes),
      study.name,
      data=df_,
      byvar=subtype,
      n.e=OneYEyes)

# Leveled against OAG
print(metareg(~ LastPeriodEyes, x=m))
```

```
##
## Mixed-Effects Model (k = 33; tau^2 estimator: DL)
##
## tau^2 (estimated amount of residual heterogeneity):      25.5650 (SE = 9.4030)
## tau (square root of estimated tau^2 value):             5.0562
## I^2 (residual heterogeneity / unaccounted variability): 98.53%
## H^2 (unaccounted variability / sampling variability):    67.85
## R^2 (amount of heterogeneity accounted for):             0.00%
##
## Test for Residual Heterogeneity:
## QE(df = 31) = 2103.4367, p-val < .0001
##
## Test of Moderators (coefficient(s) 2):
## QM(df = 1) = 0.8172, p-val = 0.3660
##
## Model Results:
##
##              estimate      se      zval      pval      ci.lb      ci.ub
## intrcpt          -3.5035  1.4564  -2.4055  0.0161  -6.3580  -0.6489 *
## LastPeriodEyes    -0.0231  0.0256  -0.9040  0.3660  -0.0733   0.0270
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

print(metareg(~ Year, x=m))
```

```
##
## Mixed-Effects Model (k = 33; tau^2 estimator: DL)
##
## tau^2 (estimated amount of residual heterogeneity):      21.8899 (SE = 8.0755)
## tau (square root of estimated tau^2 value):             4.6787
## I^2 (residual heterogeneity / unaccounted variability): 98.30%
## H^2 (unaccounted variability / sampling variability):    58.68
## R^2 (amount of heterogeneity accounted for):             7.84%
##
```

```

## Test for Residual Heterogeneity:
## QE(df = 31) = 1818.9826, p-val < .0001
##
## Test of Moderators (coefficient(s) 2):
## QM(df = 1) = 0.0863, p-val = 0.7690
##
## Model Results:
##
##           estimate      se      zval      pval      ci.lb      ci.ub
## intrcpt    90.1158   322.2445    0.2797    0.7797   -541.4717   721.7034
## Year      -0.0471    0.1603   -0.2937    0.7690    -0.3614    0.2672
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

print(metareg(~ PreOpIOPMean * subtype + coarseWashoutType + AgeMean + Male, x=m))

## Warning in metafor::rma.uni(yi = TE, sei = seTE, data = dataset, mods =
## formula, : Studies with NAs omitted from model fitting.
##
## Mixed-Effects Model (k = 28; tau^2 estimator: DL)
##
## tau^2 (estimated amount of residual heterogeneity):      0.7168 (SE = 0.4429)
## tau (square root of estimated tau^2 value):             0.8466
## I^2 (residual heterogeneity / unaccounted variability): 60.81%
## H^2 (unaccounted variability / sampling variability):    2.55
## R^2 (amount of heterogeneity accounted for):             97.28%
##
## Test for Residual Heterogeneity:
## QE(df = 18) = 45.9263, p-val = 0.0003
##
## Test of Moderators (coefficient(s) 2,3,4,5,6,7,8,9,10):
## QM(df = 9) = 316.5158, p-val < .0001
##
## Model Results:
##
##           estimate      se      zval      pval      ci.lb
## intrcpt        -4.5154   6.4041   -0.7051    0.4808   -17.0672
## PreOpIOPMean   -0.1719   0.1532   -1.1223    0.2617    -0.4721
## subtypeACG       9.9779   3.3923    2.9414    0.0033     3.3292
## subtypePXG      12.4617   4.6754    2.6654    0.0077     3.2980
## coarseWashoutTypePre  1.3583   1.4319    0.9486    0.3428    -1.4481
## coarseWashoutTypeBoth -1.8649   1.3670   -1.3642    0.1725    -4.5442
## AgeMean         0.0891   0.0683    1.3042    0.1922    -0.0448
## Male           -0.0232   0.0238   -0.9748    0.3297    -0.0698
## PreOpIOPMean:subtypeACG -0.6667   0.1807   -3.6904    0.0002    -1.0208
## PreOpIOPMean:subtypePXG -0.6791   0.2347   -2.8933    0.0038    -1.1391
##
##           ci.ub
## intrcpt         8.0364
## PreOpIOPMean     0.1283
## subtypeACG      16.6266 **
## subtypePXG      21.6253 **
## coarseWashoutTypePre  4.1647
## coarseWashoutTypeBoth  0.8144

```

```

## AgeMean                0.2229
## Male                   0.0234
## PreOpIOPMean:subtypeACG -0.3126 ***
## PreOpIOPMean:subtypePXG -0.2191 **
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

# Leveled against ACG
df_ <- df_ %>% mutate(subtype=relevel(factor(subtype), ref="ACG"))

m <- metagen(LastPeriodAbsIOPChangeMean,
             LastPeriodAbsIOPChangeStdDev / sqrt(LastPeriodEyes),
             study.name,
             data=df_,
             byvar=subtype,
             n.e=OneYEyes)

print(metareg(~ LastPeriodEyes, x=m))

##
## Mixed-Effects Model (k = 33; tau^2 estimator: DL)
##
## tau^2 (estimated amount of residual heterogeneity):      25.5650 (SE = 9.4030)
## tau (square root of estimated tau^2 value):             5.0562
## I^2 (residual heterogeneity / unaccounted variability): 98.53%
## H^2 (unaccounted variability / sampling variability):    67.85
## R^2 (amount of heterogeneity accounted for):             0.00%
##
## Test for Residual Heterogeneity:
## QE(df = 31) = 2103.4367, p-val < .0001
##
## Test of Moderators (coefficient(s) 2):
## QM(df = 1) = 0.8172, p-val = 0.3660
##
## Model Results:
##
##              estimate      se      zval      pval      ci.lb      ci.ub
## intrcpt          -3.5035  1.4564  -2.4055  0.0161  -6.3580  -0.6489 *
## LastPeriodEyes    -0.0231  0.0256  -0.9040  0.3660  -0.0733   0.0270
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

print(metareg(~ Year, x=m))

##
## Mixed-Effects Model (k = 33; tau^2 estimator: DL)
##
## tau^2 (estimated amount of residual heterogeneity):      21.8899 (SE = 8.0755)
## tau (square root of estimated tau^2 value):             4.6787
## I^2 (residual heterogeneity / unaccounted variability): 98.30%
## H^2 (unaccounted variability / sampling variability):    58.68
## R^2 (amount of heterogeneity accounted for):             7.84%
##

```



```

## Test for Residual Heterogeneity:
## QE(df = 31) = 1818.9826, p-val < .0001
##
## Test of Moderators (coefficient(s) 2):
## QM(df = 1) = 0.0863, p-val = 0.7690
##
## Model Results:
##
##          estimate      se      zval      pval      ci.lb      ci.ub
## intrcpt    90.1158  322.2445   0.2797  0.7797  -541.4717  721.7034
## Year      -0.0471   0.1603  -0.2937  0.7690   -0.3614   0.2672
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

print(metareg(~ PreOpIOPMean * subtype + coarseWashoutType + AgeMean + Male, x=m))

## Warning in metafor::rma.uni(yi = TE, sei = seTE, data = dataset, mods =
## formula, : Studies with NAs omitted from model fitting.
##
## Mixed-Effects Model (k = 28; tau^2 estimator: DL)
##
## tau^2 (estimated amount of residual heterogeneity):      0.7168 (SE = 0.4429)
## tau (square root of estimated tau^2 value):             0.8466
## I^2 (residual heterogeneity / unaccounted variability): 60.81%
## H^2 (unaccounted variability / sampling variability):    2.55
## R^2 (amount of heterogeneity accounted for):             97.28%
##
## Test for Residual Heterogeneity:
## QE(df = 18) = 45.9263, p-val = 0.0003
##
## Test of Moderators (coefficient(s) 2,3,4,5,6,7,8,9,10):
## QM(df = 9) = 316.5158, p-val < .0001
##
## Model Results:
##
##          estimate      se      zval      pval      ci.lb
## intrcpt          5.4625  6.4172   0.8512  0.3946  -7.1149
## PreOpIOPMean     -0.8386  0.1066  -7.8633 <.0001  -1.0476
## subtypeOAG       -9.9779  3.3923  -2.9414  0.0033 -16.6266
## subtypePXG        2.4838  4.0456   0.6139  0.5393  -5.4455
## coarseWashoutTypePre  1.3583  1.4319   0.9486  0.3428  -1.4481
## coarseWashoutTypeBoth -1.8649  1.3670  -1.3642  0.1725  -4.5442
## AgeMean           0.0891  0.0683   1.3042  0.1922  -0.0448
## Male             -0.0232  0.0238  -0.9748  0.3297  -0.0698
## PreOpIOPMean:subtypeOAG  0.6667  0.1807   3.6904  0.0002   0.3126
## PreOpIOPMean:subtypePXG -0.0124  0.1985  -0.0625  0.9501  -0.4014
##
##          ci.ub
## intrcpt    18.0399
## PreOpIOPMean -0.6296 ***
## subtypeOAG  -3.3292 **
## subtypePXG   10.4130
## coarseWashoutTypePre  4.1647
## coarseWashoutTypeBoth  0.8144

```

```

## AgeMean                0.2229
## Male                   0.0234
## PreOpIOPMean:subtypeOAG 1.0208 ***
## PreOpIOPMean:subtypePXG 0.3765
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

# Leveled against PXG
df_ <- df_ %>% mutate(subtype=relevel(factor(subtype), ref="ACG"))

m <- metagen(LastPeriodAbsIOPChangeMean,
             LastPeriodAbsIOPChangeStdDev / sqrt(LastPeriodEyes),
             study.name,
             data=df_,
             byvar=subtype,
             n.e=OneYEyes)

print(metareg(~ LastPeriodEyes, x=m))

##
## Mixed-Effects Model (k = 33; tau^2 estimator: DL)
##
## tau^2 (estimated amount of residual heterogeneity):    25.5650 (SE = 9.4030)
## tau (square root of estimated tau^2 value):          5.0562
## I^2 (residual heterogeneity / unaccounted variability): 98.53%
## H^2 (unaccounted variability / sampling variability):  67.85
## R^2 (amount of heterogeneity accounted for):          0.00%
##
## Test for Residual Heterogeneity:
## QE(df = 31) = 2103.4367, p-val < .0001
##
## Test of Moderators (coefficient(s) 2):
## QM(df = 1) = 0.8172, p-val = 0.3660
##
## Model Results:
##
##              estimate      se      zval      pval      ci.lb      ci.ub
## intrcpt          -3.5035  1.4564  -2.4055  0.0161  -6.3580  -0.6489 *
## LastPeriodEyes    -0.0231  0.0256  -0.9040  0.3660  -0.0733   0.0270
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

print(metareg(~ Year, x=m))

##
## Mixed-Effects Model (k = 33; tau^2 estimator: DL)
##
## tau^2 (estimated amount of residual heterogeneity):    21.8899 (SE = 8.0755)
## tau (square root of estimated tau^2 value):          4.6787
## I^2 (residual heterogeneity / unaccounted variability): 98.30%
## H^2 (unaccounted variability / sampling variability):  58.68
## R^2 (amount of heterogeneity accounted for):          7.84%
##

```

```

## Test for Residual Heterogeneity:
## QE(df = 31) = 1818.9826, p-val < .0001
##
## Test of Moderators (coefficient(s) 2):
## QM(df = 1) = 0.0863, p-val = 0.7690
##
## Model Results:
##
##          estimate      se      zval      pval      ci.lb      ci.ub
## intrcpt    90.1158  322.2445   0.2797  0.7797  -541.4717  721.7034
## Year      -0.0471   0.1603  -0.2937  0.7690   -0.3614   0.2672
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

print(metareg(~ PreOpIOPMean * subtype + coarseWashoutType + AgeMean + Male, x=m))

## Warning in metafor::rma.uni(yi = TE, sei = seTE, data = dataset, mods =
## formula, : Studies with NAs omitted from model fitting.
##
## Mixed-Effects Model (k = 28; tau^2 estimator: DL)
##
## tau^2 (estimated amount of residual heterogeneity):      0.7168 (SE = 0.4429)
## tau (square root of estimated tau^2 value):             0.8466
## I^2 (residual heterogeneity / unaccounted variability): 60.81%
## H^2 (unaccounted variability / sampling variability):    2.55
## R^2 (amount of heterogeneity accounted for):             97.28%
##
## Test for Residual Heterogeneity:
## QE(df = 18) = 45.9263, p-val = 0.0003
##
## Test of Moderators (coefficient(s) 2,3,4,5,6,7,8,9,10):
## QM(df = 9) = 316.5158, p-val < .0001
##
## Model Results:
##
##          estimate      se      zval      pval      ci.lb
## intrcpt          5.4625  6.4172   0.8512  0.3946  -7.1149
## PreOpIOPMean     -0.8386  0.1066  -7.8633 <.0001  -1.0476
## subtypeOAG       -9.9779  3.3923  -2.9414  0.0033 -16.6266
## subtypePXG        2.4838  4.0456   0.6139  0.5393  -5.4455
## coarseWashoutTypePre  1.3583  1.4319   0.9486  0.3428  -1.4481
## coarseWashoutTypeBoth -1.8649  1.3670  -1.3642  0.1725  -4.5442
## AgeMean           0.0891  0.0683   1.3042  0.1922  -0.0448
## Male             -0.0232  0.0238  -0.9748  0.3297  -0.0698
## PreOpIOPMean:subtypeOAG  0.6667  0.1807   3.6904  0.0002   0.3126
## PreOpIOPMean:subtypePXG -0.0124  0.1985  -0.0625  0.9501  -0.4014
##
##          ci.ub
## intrcpt    18.0399
## PreOpIOPMean -0.6296 ***
## subtypeOAG   -3.3292 **
## subtypePXG   10.4130
## coarseWashoutTypePre  4.1647
## coarseWashoutTypeBoth  0.8144

```

```
## AgeMean          0.2229
## Male             0.0234
## PreOpIOPMean:subtypeOAG  1.0208 ***
## PreOpIOPMean:subtypePXG  0.3765
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1



# Restricted to OAG only
df %>%
  filter(subtype == 'OAG', washout.type != 'Both', !is.na>LastPeriodAbsIOPChangeStdDev)) %>%
  summarize(min = min(PreOpIOPMean),
            max = max(PreOpIOPMean),
            sd = sd(PreOpIOPMean),
            mean = mean(PreOpIOPMean))

##      min max      sd      mean
## 1 16.2 23.8 2.012705 18.12571
```


Small study bias

```
df_ <- df %>% filter(!is.na(df$LastPeriodAbsIOPChangeMean),
                    df$subtype != "AACG",
                    MIGsYorN == 'N') %>% mutate(subtype=factor(subtype))
for(l in levels(df_$subtype)) {
  m <- metagen>LastPeriodAbsIOPChangeMean,
          LastPeriodAbsIOPChangeStdDev / sqrt>LastPeriodEyes),
          study.name,
          data=df_ %>% filter(subtype == l),
          n.e>LastPeriodEyes)
  funnel(m)
  title(paste('Funnel plot', l))
}
```

Funnel plot ACG




Funnel plot PXG



Alternative filterings of the data

Prospective studies only




Meds

```
df_ <- df %>%
  filter(!is.na(RxChangeMean), !is.na(RxChangeStdDev),
         df$subtype != "AACG", MIGsYorN == 'N') %>%
  mutate(subtype=factor(subtype))
m <- metagen(RxChangeMean,
             sqrt(RxPostOpStdDev** 2 + RxPreOpStdDev ** 2) / sqrt>LastPeriodEyes),
           study.name,
           data=df_,
```

```

byvar=subtype,
n.e=LastPeriodEyes)
forest(m,
  comb.fixed=FALSE,
  digits=1,
  digits.se = 2,
  overall=FALSE,
  leftcols=c("studlab", "TE", "seTE", "n.e"))

```



Excluding washout studies

Last period

```

df_ <- df %>%
  filter(!is.na(LastPeriodAbsIOPChangeMean), subtype != "AACG", MIGsYorN == 'N') %>%
  mutate(subtype=factor(subtype))


```



```

m <- metagen(LastPeriodAbsIOPChangeMean,
             LastPeriodAbsIOPChangeStdDev / sqrt(LastPeriodEyes),
             study.name,
             data=df_,
             byvar=subtype,
             n.e=LastPeriodEyes)
forest(m,
       comb.fixed=FALSE,
       digits=1,
       digits.se = 2,
       overall=FALSE,
       leftcols=c("studlab", "TE", "seTE", "n.e"))

```



Meds

```
df_ <- df %>%
  filter(!is.na(RxChangeMean), !is.na(RxChangeStdDev),
```

```

      df$subtype != "AACG", MIGsYorN == 'N') %>%
  mutate(subtype=factor(subtype))
m <- metagen(RxChangeMean,
             sqrt(RxPostOpStdDev** 2 + RxPreOpStdDev ** 2) / sqrt>LastPeriodEyes),
             study.name,
             data=df_,
             byvar=subtype,
             n.e>LastPeriodEyes)
forest(m,
       comb.fixed=FALSE,
       digits=1,
       digits.se = 2,
       overall=FALSE,
       leftcols=c("studlab", "TE", "seTE", "n.e"))

```

```

## Warning in grid.Call(L_textBounds, as.graphicsAnnot(x$label), x$x, x
## $y, : conversion failure on 'Hayashi et al. (2001)†' in 'mbcsToSbcs': dot
## substituted for <e2>

```

```

## Warning in grid.Call(L_textBounds, as.graphicsAnnot(x$label), x$x, x
## $y, : conversion failure on 'Hayashi et al. (2001)†' in 'mbcsToSbcs': dot
## substituted for <80>

```

```

## Warning in grid.Call(L_textBounds, as.graphicsAnnot(x$label), x$x, x
## $y, : conversion failure on 'Hayashi et al. (2001)†' in 'mbcsToSbcs': dot
## substituted for <a0>

```

```

## Warning in grid.Call(L_textBounds, as.graphicsAnnot(x$label), x$x, x
## $y, : conversion failure on 'Hayashi et al. (2001)†' in 'mbcsToSbcs': dot
## substituted for <e2>

```

```

## Warning in grid.Call(L_textBounds, as.graphicsAnnot(x$label), x$x, x
## $y, : conversion failure on 'Hayashi et al. (2001)†' in 'mbcsToSbcs': dot
## substituted for <80>

```

```

## Warning in grid.Call(L_textBounds, as.graphicsAnnot(x$label), x$x, x
## $y, : conversion failure on 'Hayashi et al. (2001)†' in 'mbcsToSbcs': dot
## substituted for <a0>

```

```

## Warning in grid.Call.graphics(L_text, as.graphicsAnnot(x$label), x$x, x
## $y, : conversion failure on 'Hayashi et al. (2001)†' in 'mbcsToSbcs': dot
## substituted for <e2>

```

```

## Warning in grid.Call.graphics(L_text, as.graphicsAnnot(x$label), x$x, x
## $y, : conversion failure on 'Hayashi et al. (2001)†' in 'mbcsToSbcs': dot
## substituted for <80>

```

```

## Warning in grid.Call.graphics(L_text, as.graphicsAnnot(x$label), x$x, x
## $y, : conversion failure on 'Hayashi et al. (2001)†' in 'mbcsToSbcs': dot
## substituted for <a0>

```

```

## Warning in grid.Call.graphics(L_text, as.graphicsAnnot(x$label), x$x, x
## $y, : conversion failure on 'Hayashi et al. (2001)†' in 'mbcsToSbcs': dot
## substituted for <e2>


```

```

## Warning in grid.Call.graphics(L_text, as.graphicsAnnot(x$label), x$x, x
## $y, : conversion failure on 'Hayashi et al. (2001)†' in 'mbcsToSbcs': dot
## substituted for <80>

```

```
## Warning in grid.Call.graphics(L_text, as.graphicsAnnot(x$label), x$x, x
## $y, : conversion failure on 'Hayashi et al. (2001)†' in 'mbcsToSbcs': dot
## substituted for <a0>
```



Sensitivity to missingness

Simulate what the results would look like if there was no effect in the eyes lost to follow up ($\Delta IOP = 0$).

```
meta.analysis.with.sensitivity <- function(missingness='zero') {
  df <- read.data()
  df <- filter.data(df, 'prospective')

  df_ <- df %>%
    filter(!is.na>LastPeriodAbsIOPChangeMean), subtype != "AACG") %>%
    mutate(subtype=factor(subtype))

  # Simulate a 0 effect in the unobserved fraction.
  df.missing <- df_
  if(missingness == 'zero') {
    # Zero out.
    df.missing <- df.missing %>% mutate>LastPeriodEyes = PreOpEyes - LastPeriodEyes,
      LastPeriodAbsIOPChangeMean = 0)
  } else {
    # Add 5 mm Hg to each missing eye.
    df.missing <- df.missing %>% mutate>LastPeriodEyes = PreOpEyes - LastPeriodEyes,
      LastPeriodAbsIOPChangeMean = LastPeriodAbsIOPChangeMean + 5)
  }


  df_ <- rbind(df_, df.missing)
  # Aggregate two by two
  for(i in seq(nrow(df.missing), 1)) {
    idx <- rep(FALSE, nrow(df_))
    idx[i] <- TRUE
    idx[i*2] <- TRUE
    df_ <- agg.arms(df_, idx)
  }

  df_ <- df_ %>% dplyr::arrange(Year, study.name)

  m <- metagen>LastPeriodAbsIOPChangeMean,
    LastPeriodAbsIOPChangeStdDev / sqrt>LastPeriodEyes),
    study.name,
    data=df_,
    byvar=subtype,
    n.e=LastPeriodEyes)
  forest(m,
    comb.fixed=FALSE,
    digits=1,
    digits.se = 2,
    overall=FALSE,
    leftcols=c("studlab", "TE", "seTE", "n.e"),
    leftlabs=c("Study", " $\Delta IOP$ ", "SE", "eyes"))
}


meta.analysis.with.sensitivity()
grid.text(paste0("Simulated net change IOP when  $\Delta IOP = 0$  in eyes lost to follow up"), .5, .97, gp=gpar(
```

Simulated net change IOP when $\Delta IOP = 0$ in eyes lost to follow up



```
meta.analysis.with.sensitivity('five')
grid.text(paste0("Simulated net change IOP when  $\Delta IOP = 5$  mm Hg higher in eyes lost to follow up"), .5,
```

Simulated net change IOP when $\Delta\text{IOP} = 5$ mm Hg higher in eyes lost to follow up



MIGS

We don't report these results because it's a bit misleading – the studies aren't very similar to each other, and we don't use the information in their control arms. We can do a much better job through, for example, network meta-analysis, which we plan to do in a future paper.

```
df <- read.data(drop.migs = FALSE)
```

```
## These retrospective studies are losing eyes per period - not impossible, but unusual:
## Mathalone et al. (2005)
## Leelachaikul et al. (2005)
## Shoji et al. (2007)
## Liu et al. (2011)
```

```
## Arthur et al. (2014)
## Tetz et al. (2015)

## These retrospective studies are gaining eyes as the study goes

## Samuelson et al. (2011)

df_ <- df %>%
  filter(!is.na(LastPeriodAbsIOPChangeMean), subtype != "AACG", MIGsYorN == 'Y') %>%
  mutate(subtype=factor(subtype)) %>% dplyr::arrange(TypesofMIGSifany, Year)
m <- metagen(LastPeriodAbsIOPChangeMean,
             LastPeriodAbsIOPChangeStdDev / sqrt(LastPeriodEyes),
             study.name,
             data=df_,
             n.e=LastPeriodEyes)

forest(m,
       comb.fixed=FALSE,
       digits=1,
       digits.se = 2,
       overall=TRUE,
       leftcols=c("studlab", "TE", "seTE", "n.e", "TypesofMIGSifany"),
       leftlabs=c("Study", "TE", "seTE", "Total", "Type"))
```

