| deterioration rate<br>0.0039 -<br>0.0037 -<br>0.0036 -<br>0.0035 -<br>0.0036 -<br>0.0027 -<br>0.0020 -<br>0.0025 -<br>0.0025 -<br>0.0025 -<br>0.0021 -<br>0.0021 - | 1.5 1.6 1.6 1.3 1.6 1.1 1.1 1.1 1.3 1.1 1.0 1.3 1.5 1.4 1.2 1.5 1.3 1.2 1.1 1.1 | 1.5 1.3 1.3 1.3 1.1 1.8 1.0 1.5 1.8 1.0 1.0 1.2 2.0 1.7 1.2 1.2 1.2 1.1 1.5 0.8 | 1.1 1.1 1.7 1.9 1.2 1.7 1.2 1.3 2.0 1.2 0.8 1.0 1.6 1.4 1.0 1.5 1.5 1.3 1.5 | 1.3 1.2 1.0 1.1 1.8 1.1 1.1 1.4 0.8 1.4 1.0 1.1 1.5 1.5 1.4 1.4 0.9 0.9 0.9 0.9 | 0.8 1.1 1.3 1.4 1.1 1.0 1.4 0.8 1.0 1.1 1.2 1.3 1.0 1.1 0.8 1.1 0.8 1.1 0.9 1.1 | 1.1 1.1 1.0 0.8 0.9 1.1 0.9 1.2 1.2 0.8 0.9 0.8 1.0 0.9 1.0 1.2 0.6 1.0 1.0 1.3 | 1.2<br>1.0<br>0.8<br>1.0<br>1.0<br>0.9<br>1.1<br>1.0<br>1.1<br>0.7<br>0.8<br>0.8<br>1.1<br>0.8<br>1.2<br>0.7<br>1.1<br>0.8<br>1.2 | - 1.75<br>- 1.50<br>- 1.25<br>- 1.00<br>- 0.75 |
|--|---|---|---|---|---|---|---|--|
|  |   |   |   |   |   |   |   | - 0.75   |
| 0.0021   |   | 0.525   | 0.55  | 0.575<br>shold de   | 0.6   | 0.9   | 0.65  |  |