

<https://leetcode.com/problems/two-sum/>

```
#O(N) Time, O(N) Space
class Solution(object):
    def twoSum(self, nums, target):
        dictionary = {}
        for key, value in enumerate(nums):
            complement = target-value
            if complement in dictionary:
                return [dictionary[complement],key]
            else:
                dictionary[value] = key
```

We will want to use a HashMap(dictionary) for this solution. We will also want to use the enumerate function to iterate through the values in nums so that we can keep the value of the counter. The solution we are looking for is “x+y=target”. If we want to solve for y, we will rearrange this to “y = target-x”, y being the complement, target being the target number we’re trying to sum up to, and value being the current value for our iteration. During our iteration if we find the complement in our dictionary, we are going to return the index of complement and our current index. Otherwise, we set the index of our value to our current key.

Traverse array, if complement is in dictionary, return both its index and our current index, if not then set the index of our current value to our current index.

<https://leetcode.com/problems/reorder-data-in-log-files/>

```
#O(NLogN) Time, O(N) Space
class Solution(object):
    def reorderLogFiles(self, logs):
        letter_list=[]
        digit_list=[]
        for log in logs:
            if log[-1].isdigit():
                digit_list.append(log)
            else:
                letter_list.append(log)
        letter_list = sorted(letter_list, key=lambda letter: (letter.split()[1:],letter.split()[0]))
        return letter_list+digit_list
```

We can have two arrays, one for letters and one for digits. We iterate through each log and check the last index to see if it is a digit or not. If it is, we will add it to the digit array and if it is not, we will add it to the letter array. We will then use a lambda sort function that first checks the suffix and then checks the identifier if there is a tie in suffixes. After the letter array is sorted, we will merge the letter array and digit array (letter array first).

Check if digit or letter log, sort letter log by suffixes then identifiers, merge lists.

<https://leetcode.com/problems/second-highest-salary/>

```
SELECT
IFNULL (
    (SELECT DISTINCT Salary
     FROM Employee
     ORDER BY Salary DESC
     LIMIT 1 OFFSET 1), NULL)
AS SecondHighestSalary
```

Use SELECT and test IFNULL, SELECT DISTINCT will return only different values from the Employee table, ORDER BY DESC so you can get the highest salaries first and use LIMIT 1 which takes an OFFSET argument of 1 (one from the top of the list) if there are no results from the test then return NULL, set as the alias SecondHighestSalary.

## <https://leetcode.com/problems/valid-parentheses/>

#O(N) Time, O(N) Space

```
class Solution:
    def isValid(self, s: str) -> bool:
        stack = []
        dict = {"]": "[", "}": "{", ")": "("}
        for bracket in s:
            if bracket in dict.values():
                stack.append(bracket)
            elif bracket in dict.keys():
                if stack == []:
                    return False
                elif dict[bracket] != stack.pop():
                    return False
            else:
                return False
        return stack == []
```

We can use a stack and a HashMap for this solution. We iterate through the brackets string and check whether the bracket is an opening or closing bracket. If it is an opening bracket, we push it onto the stack. If it is a closing bracket, we ensure the stack is not empty and then pop the stack to see if this value matches the value of bracket in our dictionary. At the end of the function we should have an empty stack, so we return whether this is true or not.

Use a stack and a dictionary of bracket values, if opening bracket push onto stack, if closing bracket check for empty string and if the value in dictionary matches this popped stack value, return if stack is empty.

## <https://leetcode.com/problems/maximum-subarray/>

#O(N) Time, O(1) Space

```
class Solution:
    def maxSubArray(self, nums: List[int]) -> int:
        for i in range(1, len(nums)):
            if nums[i-1] > 0:
                nums[i] += nums[i-1]
        return max(nums)
```

We can use Kadane's algorithm for this solution. The question is asking for the maximum contiguous subarray, so we will check for positive subarrays. We iterate through the array starting from the second index and we check if the previous element is positive. If it is, we add it to our current element and continue. Once we are out of the for loop we return the max element, this would be the maximum sum out of all the contiguous subarrays.

Iterate through the array starting from the second index, if the previous element is positive then add it to our current element, return max element in array.

## <https://leetcode.com/problems/valid-palindrome-ii/>

```
class Solution:
    def validPalindrome(self, s: str) -> bool:
        left = 0
        right = len(s) - 1
        while left < right:
            if s[left] == s[right]:
                left += 1
                right -= 1
            else:
                substring_one = s[left:right]
                substring_two = s[left+1:right+1]
                return substring_one==substring_one[::-1] or substring_two==substring_two[::-1]
        return True
```

You start with a typical while loop that checks if the left index matches the right and move inwards, if you have mismatched elements you try to test two substrings, one without the left index included and one without the right index included.

## <https://leetcode.com/problems/best-time-to-buy-and-sell-stock/>

```
#O(N) Time, O(1) Space
class Solution:
    def maxProfit(self, prices):
        max_profit = 0
        min_price = float('inf')
        for price in prices:
            min_price = min(min_price, price)
            max_profit = max(max_profit, price - min_price)
        return max_profit
```

We initialize our max\_profit to 0, as this would be the base case. We set our min\_price to infinity so we can override it with any price within our input. We then iterate through our prices and set the minimum price to the lowest number between our current min\_price and the current price in our iteration. We also set the max profit to the highest number between our current max\_profit and the current price in our iteration minus our min\_price. We do this so that we only keep the highest max\_profit, and to check if we are still at the base case of no profit. Return the max\_profit.

**Iterate through prices to find minimum price and subtract it from the current price and see if this value is higher than the current maximum profit, if it is then save this value.**

## <https://leetcode.com/problems/merge-two-sorted-lists/>

```
#O(N) Time, O(N) Space
class Solution:
    def mergeTwoLists(self, l1: ListNode, l2: ListNode) -> ListNode:
        dummy = ListNode(0)
        prev = dummy
        while l1 is not None and l2 is not None:
            if l1.val <= l2.val:
                prev.next = l1
                l1 = l1.next
            else:
                prev.next = l2
                l2 = l2.next
            prev = prev.next
        prev.next = l1 if l1 is not None else l2
        return dummy.next
```

We first set a dummy head as a placeholder. We do this because the current node is 0, and the head we will be returning will be a node from one of the two lists and that actual head will be set after this dummy one. Afterwards, we will set the previous node to the dummy so that we can take a step forward in the merged list. We will then iterate through both lists while neither one of them is null and see if the current node value in the first list is less than or equal to the current node value in the second list. If it is, we set the previous value's next value to the current node in the first list and step forward in list one. If it is not, we set the previous value's next value to the current node in the second list and step forward in list two. After the previous value's next value has been set from one of the two conditions set previously, we set that value as the previous value to step forward in the merged list. Once we are out of the while loop, it means one of the lists are null. So, we glue the non-null list onto the end of our merged list since it is already sorted. Once we are done, we return all the values after our dummy head.

**Make a dummy head and while neither input lists are null, set the lesser or equal node as the next value in our merged list, once we've reached the end of an input list we will attach the other list to the end of our merged list and return everything after the dummy head.**

<https://leetcode.com/problems/reverse-linked-list/>

#O(N) Time, O(1) Space

```
class Solution:
    def reverseList(self, head: ListNode) -> ListNode:
        pointer_one = None
        pointer_two = head
        while pointer_two != None:
            pointer_three = pointer_two.next
            pointer_two.next = pointer_one
            pointer_one = pointer_two
            pointer_two = pointer_three
        return pointer_one
```

We can solve this question by iterating through the linked list and setting the next node as the previous node, thus reversing the list. We will do this by utilizing three pointers. We will want these pointers to keep track of the current node, the previous node, and the next node. We will initialize pointer one as None, as initially the head will have no previous node, and the second pointer as the head node. While the current node in our iteration (initially the head) is not none, we will set a third pointer to the next node of the current node. We want to do this because once we override pointer\_two.next and set it to the previous node, we will lose our bridge to get to the next node. The third pointer is just a placeholder. Once we set the third pointer to the next node, we will override the reference to our next node by setting it to the previous node, pointer\_one. We then move both our current node pointer (pointer two) and our previous node pointer (pointer one) forward. We will return pointer one at the end as it will be the new head.

Traverse the linked list and set the next node to the previous node by using three pointers to keep track of the previous, current, and next nodes.

<https://leetcode.com/problems/add-strings/>

#O(N) Time, O(N) Space

```
class Solution:
    def addStrings(self, num1: str, num2: str) -> str:
        result = ''
        carry, index_one, index_two = 0, len(num1) - 1, len(num2) - 1
        while index_one >= 0 or index_two >= 0:
            current_sum = carry
            if index_one >= 0:
                current_sum += int(num1[index_one])
                index_one -= 1
            if index_two >= 0:
                current_sum += int(num2[index_two])
                index_two -= 1
            result += str(current_sum % 10)
            carry = current_sum // 10
        if carry > 0:
            result += str(carry)
        return result[::-1]
```

We can solve this question by starting from the ones position of each string and adding that number to our sum. Similarly, we will move to the tens, hundreds, and thousands position after. We will mod our current sum by 10 in each iteration so that we know if we need to carry over any values, we can keep track of this. We will find the carry value at the end of each iteration by dividing our current sum by 10 and initializing our current sum to the carry value at the beginning of the next iteration. If there are any carry values left over once we have broken out of our while loop, we will append the value to the end of our string, then return the reversed string since it will be backwards.

Traverse strings backwards adding the values in each position while still including carry-overs and return reversed string.

<https://leetcode.com/problems/move-zeroes/>

#O(N) Time, O(1) Space

```
class Solution:
    def moveZeroes(self, nums: List[int]) -> None:
        pointer_one = 0
        for pointer_two in range(0, len(nums)):
            if nums[pointer_two] != 0:
                nums[pointer_one], nums[pointer_two] = nums[pointer_two], nums[pointer_one]
                pointer_one += 1
        return nums
```

We can solve this problem using two pointers. If the order of the non-zero values did not matter, we could have a left pointer and a right pointer then move them inwards swapping right zeros with left non-zeros. Since the order does matter however, we will use two pointers initialized at zero. If the value at the second pointer is a non-zero value, we will swap it with the value at the first pointer and move both pointers forward. If it is a zero, we will only move the second pointer forward until we find a non-zero again to swap with the zero at the first pointer.

Traverse the list using two pointers, one lagging on zeros and one finding non-zeros, if the second pointer finds a non-zero then swap the value with the first pointer and move the first pointer forward.

<https://leetcode.com/problems/happy-number/>

#O(log N) Time, O(log N) Space

```
class Solution:
    def isHappy(self, n: int) -> bool:
        seen = set()
        square_sum = 0
        while square_sum != 1:
            square_sum = 0
            while n > 0:
                square_sum += (n % 10) ** 2
                n = n // 10
            if square_sum in seen:
                return False
            else:
                n = square_sum
                seen.add(n)
        return True
```

We can solve this question by using a set to keep track of the square sums. We will initialize the square sum to be 0 as we have no sum to process initially. We will then make two while loops, the outer will run until we have a square sum equal to 1, the inner will run while our n (our initial input or the previous iteration's square sum) has digits left to process. Before the inner loop, we will set the square sum back to zero so that we are not adding to the previous iteration's square sum. The inner loop will process each digit of n, square it, add it to the square sum, and remove it from n by utilizing the mod and division operators. Once we have our square sum, we are going to see if it is in the set. If it is, we return false and break out of the loop. If it is not, we will add it to the set and set n equal to it so it can be processed in the next iteration. If we have reached the end of the outer loop it is because we have a square sum that equals 1, so we return true.

Use a set to keep track of previous square sums we have seen, process new square sums by squaring each digit and adding them all together.

<https://leetcode.com/problems/reverse-integer/>

```
class Solution:
    def reverse(self, x: int) -> int:
        reversed_int = 0
        is_negative = x < 0
        x = abs(x)
        while x != 0:
            reversed_int *= 10
            reversed_int += x%10
            x //= 10
        if reversed_int > 2**31:
            return 0
        if is_negative == True:
            return -reversed_int
        else:
            return reversed_int
```

We will first check if x is negative so we know whether the final int will need to be negative as well. We will then convert x to positive by taking the absolute value so we can process each digit individually. We will make a while loop for chopping off each digit from x and it will run until there are no more digits to chop. We will start by multiplying the output integer “reversed\_int” by 10 so that we will have a placeholder for the next digit. Then we will add the last digit to our output by modding x by 10. After that, we will chop off the digit by dividing x by 10, ensuring it does not convert to a float by using “//” instead of “/”. If our reversed integer is larger than a 32-bit signed integer ( $2^{31}$ ), we return 0. Otherwise, we return our reversed integer, negative if the input was negative.

Check if input is negative and add each individual digit to output while using multiplication by ten as a digit placeholder, modulus by 10 as a digit parser and division by 10 as a digit remover, also check if 32-bit signed and return negative if negative.

<https://leetcode.com/problems/merge-sorted-array/>

#O(M) Time, O(1) Space

```
class Solution:
    def merge(self, nums1: List[int], m: int, nums2: List[int], n: int) -> None:
        pointer_one, pointer_two = m - 1, n - 1
        pointer_three = len(nums1) - 1
        while pointer_one >= 0 and pointer_two >= 0:
            if nums1[pointer_one] < nums2[pointer_two]:
                nums1[pointer_three] = nums2[pointer_two]
                pointer_two -= 1
            else:
                nums1[pointer_three] = nums1[pointer_one]
                pointer_one -= 1
            pointer_three -= 1
        nums1[:pointer_two + 1] = nums2[:pointer_two + 1]
```

We can solve this using three pointers and iterating through both arrays from the end to the beginning. We set the first pointer to be  $m - 1$  (the size of non-zero elements in nums1, minus one to avoid index out of bounds errors), we set the second pointer to be  $n - 1$  (also for the reason just mentioned), and the third pointer to be  $\text{len}(\text{nums1}) - 1$  (this will be at the end of nums1 after the non-zero elements and the zeros as well. Once we set our pointers, we will create a while loop that will run while both pointer one and pointer two are greater than zero so that we do not throw an index out of bounds error. It will check for the smaller of the two elements and set the index the third pointer is aimed at to the smaller number and decrement the smaller number pointer, and the third pointer. If both numbers are equal, no swapping or inserting will need to be done so we can continue. Once we have broken out of the while loop it means that one of the pointers has reached the beginning of its array so we can prepend the remaining elements from nums2 into nums1 (the “+ 1” in “nums2[:pointer\_two + 1]” is because the ending index of string slicing is exclusive).

Traverse both arrays from the end to the beginning using three pointers to keep track of the end of both non-zero arrays and also the end of the larger array that will house all the elements, check which element is smaller and set the third pointer’s index to it, once the traversal is done then prepend any remaining elements from the smaller array into the larger one.

<https://leetcode.com/problems/add-binary/>

```
class Solution:
    def addBinary(self, a, b) -> str:
        x, y = int(a, 2), int(b, 2)
        while y:
            answer = x ^ y
            carry = (x & y) << 1
            x, y = answer, carry
        return bin(x)[2:]
```

<https://leetcode.com/problems/climbing-stairs/>

#O(N) Time, O(1) Space

```
class Solution:
    def climbStairs(self, n: int) -> int:
        a, b = 1, 1
        for i in range(0, n):
            a, b = b, a + b
        return a
```

## <https://leetcode.com/problems/verifying-an-alien-dictionary/>

#O(N) Time, where N is sum of lengths of all words, O(1) Space

```
class Solution(object):
    def isAlienSorted(self, words, order):
        order_index = {}
        for index, char in enumerate(order):
            order_index[char] = index
        for i in range(len(words) - 1):
            first_difference = False
            word_one = words[i]
            word_two = words[i+1]
            for char_pointer in range(min(len(word_one), len(word_two))):
                if word_one[char_pointer] != word_two[char_pointer]:
                    first_difference = True
                    if order_index[word_one[char_pointer]] > order_index[word_two[char_pointer]]:
                        return False
                    else:
                        break
            if len(word_one) > len(word_two) and not first_difference:
                return False
        return True
```

We can solve this problem by creating an index of the order for the characters in the “order” string we are given. We will make a HashMap to keep track of this. We will then use a for loop to iterate through each character in the order and map them to their index. We will make another for loop to iterate through each word in the words array (remember, there can be more than two words, so we will compare two words at a time). The two words we will be comparing will be the current index in the iteration, and the word in the index directly after it. We will also need another for loop that iterates through each character within each word until we find a difference. We will set a pointer to the same character index in each word and see if they are different (if they are the same, we move on). If they are different, we check if the order of the first word’s character (it is index in the dictionary) is higher than the second word’s character. If it is return False, if it is not then we will break out of the loop because the words are sorted and we will compare the next two words. If we have gone through all the characters in the smaller word and have not found a difference between it and the characters in the larger word, we will check if the length of the words. If the length of the first word is larger than the second word, that means the second word has null characters that are smaller than the remaining characters in the first word and thus is false. If we have completed all iterations, we will return True because that would mean we have successfully broken out of all loops or there were words that are the same.

Use a dictionary to keep track of each the order of each character in the order we’re given, iterate through the characters in two words and see if they are different and if they’re different then see if the order of the first word’s character is less than the order of the second word’s character, if completed all iterations through smaller word’s characters then check if length of first word is smaller than the second word, if it is not then return false, if all iterations are complete return True.

## <https://leetcode.com/problems/roman-to-integer/>

#O(N) Time, O(1) Space

```
class Solution:
    def romanToInt(self, s: str) -> int:
        translation = {'M': 1000, 'D': 500, 'C': 100, 'L': 50, 'X': 10, 'V': 5, 'I': 1}
        output_sum = 0
        for i in range(0, len(s) - 1):
            if translation[s[i]] < translation[s[i+1]]:
                output_sum -= translation[s[i]]
            else:
                output_sum += translation[s[i]]
        return output_sum + translation[s[-1]]
```

We can solve this problem by traversing the string and comparing each character with the character next to it. If the current character is less than the next character, it means we have a number like ‘IX’. If we encounter this, we can subtract the number we are currently at ‘I’ or 1. This way, during our next iteration when we add 10, our sum will have a net result of 9 added (IX). Our for loop will stop one before the end of the array to avoid an index out of bounds error, so we will want to always add the last character by returning the output sum plus the last character in the string.

Traverse string and compare the current character with the next character, if it is less then subtract it from the sum, if it higher then add it to the output sum, return output sum plus the last character in the string.



<https://leetcode.com/problems/first-unique-character-in-a-string/>

#O(N) Time, O(1) Space

```
class Solution:
    def firstUniqChar(self, s: str) -> int:
        seen = {}
        for char in s:
            if char in seen:
                seen[char] += 1
            else:
                seen[char] = 1
        for i in range(0, len(s)):
            if seen[s[i]] == 1:
                return i
        return -1
```

We can solve this problem by using a HashMap and doing two passes. We will make a for loop that iterates through all the characters in the string and check if they are already in the seen dictionary. If they are, we will increment their count. If they are not, we will set their count to 1. We will then make another for loop for our second pass. We will iterate through the string once more and see if the character at our current index has a count of 1 in our dictionary. If it does, we will return our current index. If nothing gets returned from our traversal, it means that the string is empty or has no unique values, so we return -1.

Use a HashMap and traverse the string twice, once to count the occurrence of each character in the string, another to see if there are any characters with the value of 1 in the dictionary, return index if it exists and return -1 if nothing was returned.

<https://leetcode.com/problems/most-common-word/>

#O(P+B) Time for the size of paragraph and banned, O(P) Space for count of paragraph words

```
class Solution:
    def mostCommonWord(self, paragraph: str, banned: List[str]) -> str:
        for char in "?!',;,.":
            paragraph = paragraph.replace(char, " ")
        seen = {}
        output_string = ''
        count = 0
        for word in paragraph.lower().split():
            if word in banned:
                continue
            elif word in seen:
                seen[word] += 1
            else:
                seen[word] = 1
            if seen[word] > count:
                count = seen[word]
                output_string = word
        return output_string
```

<https://leetcode.com/problems/valid-palindrome/>

#O(N) Time, O(1) Space

```
class Solution:
    def isPalindrome(self, s: str) -> bool:
        if len(s) == 0:
            return True
        left = 0
        right = len(s) - 1
        letters_numbers = 'abcdefghijklmnopqrstuvwxyz0123456789'
        s = s.lower()
        while left < right:
            if s[left] != s[right]:
                if s[left] not in letters_numbers:
                    left += 1
                elif s[right] not in letters_numbers:
                    right -= 1
                else:
                    return False
            else:
                left += 1
                right -= 1
        return True
```

We can solve this question using two pointers. We are only looking for alphanumeric characters (letters and digits), so we will create a reference string that holds all the letters and numbers that would possibly be compared. We will then create a left and right pointer that will compare two characters at a time. Since the check is not case-sensitive, we will convert it to lowercase. If our left and right pointers do not match, we check if they are actually letters or numbers. If they are not, we continue. If they are, we return false as the string is not a valid palindrome.

Use two pointers and a reference string of alphanumeric characters, convert string to lowercase, if there is not a match in characters under the pointers we check if they're alphanumeric, return false if they are but continue if they aren't.

<https://leetcode.com/problems/single-number/>

#O(N) Time, O(N) Space

#Another way to solve this is to return  $2 * \text{sum}(\text{set}(\text{nums})) - \text{sum}(\text{nums})$

#This is because  $c = 2 * (a+b+c) - (a+a+b+b+c)$

```
class Solution:
    def singleNumber(self, nums: List[int]) -> int:
        seen = {}
        for num in nums:
            if num in seen.keys():
                seen[num] += 1
            else:
                seen[num] = 1
        for i in range(0, len(nums)):
            if seen[nums[i]] == 1:
                return nums[i]
```

We can solve this problem using the same solution as the 'first unique character in a string' problem. We create a HashMap of integers in our array as keys, and a count of their occurrence in the array as their values during our first pass. In our second pass, we see if there is a value in the seen dictionary of 1 and return the key (the num).

Use a HashMap and traverse the array twice, once to count the occurrence of each integer in the array, another to see if there are any integer keys with the value of 1 the dictionary and to return it.

<https://leetcode.com/problems/missing-number/>

#O(N) Time, O(1) Space

**class Solution:**

```
def missingNumber(self, nums: List[int]) -> int:
    #N*(N+1)
    #-----
    # 2
    expected_sum = len(nums) * (len(nums) + 1) // 2
    actual_sum = sum(nums)
    return expected_sum - actual_sum
```

We can solve this problem by calculating the sum of the series and subtracting it by the sum of the array. This will give us the missing integer. The sum of the series is  $N*(N+1)/2$  where N is the number of elements in the series (the length of the array in our case). The sum of the array is the sum of all the elements in the array.

**Calculate  $N*(N+1)/2$  minus the sum of elements in the array.**

<https://leetcode.com/problems/palindrome-number/>

#O(N) Time, O(1) Space

**class Solution:**

```
def isPalindrome(self, x: int) -> bool:
    if x < 0:
        return False
    result = 0
    input_int = x
    while x != 0:
        result *= 10
        result += x%10
        x //= 10
    return input_int == result
```

**If the integer is negative then return false, otherwise create an output int variable that you will use to reverse the integer by using a while loop and multiplying the output int by ten to create a placeholder then adding the last digit of x by modding x by ten, then removing the last digit from x by dividing x by ten, compare the input int to the output and return true or false.**

<https://leetcode.com/problems/string-compression/>

#O(N) Time, O(1) Space

```
class Solution:
    def compress(self, chars):
        write_pointer = read_pointer = 0
        while(read_pointer < len(chars)):
            char = chars[read_pointer]
            count = 0
            while(read_pointer < len(chars) and chars[read_pointer] == char):
                read_pointer += 1
                count += 1
            chars[write_pointer] = char
            write_pointer += 1
            if count > 1:
                for digit in str(count):
                    chars[write_pointer] = digit
                    write_pointer += 1
        return write_pointer
```

<https://leetcode.com/problems/longest-common-prefix/>

#O(N) Time, O(1) Space

```
class Solution:
    def longestCommonPrefix(self, strs: List[str]) -> str:
        if len(strs) == 0:
            return ""
        shortest_word = min(strs)
        for i in range(0, len(shortest_word)):
            for compare in strs:
                if compare[i] != shortest_word[i]:
                    return shortest_word[:i]
        return shortest_word
```

We can solve this problem by iterating through each string in the array and comparing the characters until we find a difference. We'll first check and see if we received an empty array and return an empty string. We'll then get the shortest string in the array, as it will stop us from getting an index out of bounds error when we do our traversals. We'll then make a for loop that iterates through each character in the shortest word. Within that for loop we'll make another for loop that will iterate through every other string in the array. We'll then make an if/then statement that checks if the character at the ith index matches with the string it's being compared to. If it doesn't, we'll return the string up until that index. This will repeat until we have returned only the common characters and we'll return them.

**Get the shortest string, iterate through the characters in that string and within each iteration if there is a mismatch between the character index in another string, return the shortest string up until that index and return the shortest string at the end. '**

<https://leetcode.com/problems/subdomain-visit-count/>

```
class Solution:
    def subdomainVisits(self, cpdomains):
        #split string on " " to get count and whole domain
        #split string on "." to get subdomains
        #the subdomains need slight modification to fit question parameters
        #add the count to each subdomain (by using hash to keep track)
        #convert the key, value pair into a string and append to list that will be returned as the answer
        visit = {}
        for pair in cpdomains:
            count, domain = pair.split(" ") #count and domain, seperated by whitespace
            subs = []
            subs = domain.split(".") #split the domain
            subs[0] = domain #redefine the domains according to question
            index = domain.find(".")
            subs[1] = domain[index+1:]
            for d in subs: #set the count for each domain/subdomain
                if d not in visit:
                    visit[d] = int(count)
                else:
                    visit[d] += int(count)
        pairs = [] #create a list of strings from the hashmap
        for s in visit:
            temp = str(visit[s]) + " " + str(s)
            pairs.append(temp)

        return pairs
```

<https://leetcode.com/problems/logger-rate-limiter/>

#O(N) Time, O(N) Space

```
class Logger:

    def __init__(self):
        self.dictionary = {}

    def shouldPrintMessage(self, timestamp: int, message: str) -> bool:
        for i in list(self.dictionary):
            if timestamp - self.dictionary[i] >= 10:
                del self.dictionary[i]
            else:
                break
        if message not in self.dictionary:
            self.dictionary[message] = timestamp
            return True
        else:
            return False
```