


Transfer stylów

Źródło: https://www.tensorflow.org/hub/tutorials/tf2_arbitrary_image_stylization

Import TF2 ze wszystkimi zależnościami

A screenshot of a code editor with a dark background. On the left side, there is a play button icon inside a square box. The code is written in a light-colored font and is as follows:

```
import functools
import os

from matplotlib import gridspec
import matplotlib.pyplot as plt
import numpy as np
import tensorflow as tf
import tensorflow_hub as hub

print("TF Version: ", tf.__version__)
print("TF Hub version: ", hub.__version__)
print("Eager mode enabled: ", tf.executing_eagerly())\
```

Ustawienie ładowania obrazka oraz sposobu wyświetlenia

```

# @title Define image loading and visualization functions { display-mode: "form" }

def crop_center(image):
    """Returns a cropped square image."""
    shape = image.shape
    new_shape = min(shape[1], shape[2])
    offset_y = max(shape[1] - shape[2], 0) // 2
    offset_x = max(shape[2] - shape[1], 0) // 2
    image = tf.image.crop_to_bounding_box(
        image, offset_y, offset_x, new_shape, new_shape)
    return image

@functools.lru_cache(maxsize=None)
def load_image(image_url, image_size=(256, 256), preserve_aspect_ratio=True):
    """Loads and preprocesses images."""
    # Cache image file locally.
    image_path = tf.keras.utils.get_file(os.path.basename(image_url)[-128:], image_url)
    # Load and convert to float32 numpy array, add batch dimension, and normalize to range [0, 1]
    img = tf.io.decode_image(
        tf.io.read_file(image_path),
        channels=3, dtype=tf.float32)[tf.newaxis, ...]
    img = crop_center(img)
    img = tf.image.resize(img, image_size, preserve_aspect_ratio=True)
    return img

def show_n(images, titles=('',)):
    n = len(images)
    image_sizes = [image.shape[1] for image in images]
    w = (image_sizes[0] * 6) // 320
    plt.figure(figsize=(w * n, w))
    gs = gridspec.GridSpec(1, n, width_ratios=image_sizes)
    for i in range(n):
        plt.subplot(gs[i])
        plt.imshow(images[i][0], aspect='equal')
        plt.axis('off')
        plt.title(titles[i] if len(titles) > i else '')
    plt.show()

```

Wczytanie i pokazanie dwóch obrazków, gdzie `content_image_url` – to nasz główny obrazek, `style_image_url` – styl do zamiany pierwszego obrazka

```

!le images { display-mode: "form" }

: 'https://images.gnwdn.com/2018/usgamer/witcher-3-cirilla.png/EG11/thumbnail/1920x1080/forma
https://makehome.pl/14575-home_default/recznie-malowany-obraz-na-plotnie-kolorowy-lew.jpg' #
: 500 # @param {type:"integer"}

: size can be arbitrary.
(output_image_size, output_image_size)
:ion model was trained with image size 256 and it's the
: size for the style image (though, other sizes work as |
: id to different results).
: 56, 256) # Recommended to keep it at 256.

id_image(content_image_url, content_img_size)
image(style_image_url, style_img_size)
: .avg_pool(style_image, ksize=[3,3], strides=[1,1], padding='SAME')
: ge, style_image], ['Content image', 'Style image'])

```

Wczytanie modułu TF

```

# Load TF Hub module.

hub_handle = 'https://tfhub.dev/google/magenta/arbitrary-image-stylization-v1-256/2'
hub_module = hub.load(hub_handle)

```

Ustawienie stylizacji obrazu

```

outputs = hub_module(content_image, style_image)
stylized_image = outputs[0]

```

Demonstracja stylizacji obrazu


```

[35] # Stylize content image with given style image.
      # This is pretty fast within a few milliseconds on a GPU.

      outputs = hub_module(tf.constant(content_image), tf.constant(style_image))
      stylized_image = outputs[0]

# Visualize input images and the generated stylized image.
show_n([content_image, style_image, stylized_image], titles=['Original content image', 'Style image', 'Stylized image'])

```



Wykrywanie obiektów

Źródło: https://www.tensorflow.org/hub/tutorials/object_detection

Wymagane importy bibliotek z funkcjami

```
# For running inference on the TF-Hub module.
import tensorflow as tf

import tensorflow_hub as hub

# For downloading the image.
import matplotlib.pyplot as plt
import tempfile
from six.moves.urllib.request import urlopen
from six import BytesIO

# For drawing onto the image.
import numpy as np
from PIL import Image
from PIL import ImageColor
from PIL import ImageDraw
from PIL import ImageFont
from PIL import ImageOps

# For measuring the inference time.
import time

# Print Tensorflow version
print(tf.__version__)

# Check available GPU devices.
print("The following GPU devices are available: %s" % tf.test.gpu_device_name())
```

Funkcje do pobierania obrazów i ich wizualizacji

```
[ ] def display_image(image):
    fig = plt.figure(figsize=(20, 15))
    plt.grid(False)
    plt.imshow(image)

def download_and_resize_image(url, new_width=256, new_height=256,
                               display=False):
    _, filename = tempfile.mkstemp(suffix=".jpg")
    response = urlopen(url)
    image_data = response.read()
    image_data = BytesIO(image_data)
    pil_image = Image.open(image_data)
    pil_image = ImageOps.fit(pil_image, (new_width, new_height), Image.ANTIALIAS)
    pil_image_rgb = pil_image.convert("RGB")
    pil_image_rgb.save(filename, format="JPEG", quality=90)
    print("Image downloaded to %s." % filename)
    if display:
        display_image(pil_image)
    return filename

def draw_bounding_box_on_image(image,
                               ymin,
                               xmin,
                               ymax,
                               xmax,
                               color,
                               font,
                               thickness=4,
                               display_str_list=()):
    """Adds a bounding box to an image."""
    draw = ImageDraw.Draw(image)
    im_width, im_height = image.size
    (left, right, top, bottom) = (xmin * im_width, xmax * im_width,
                                   ymin * im_height, ymax * im_height)
    draw.line([(left, top), (left, bottom), (right, bottom), (right, top),
               (left, top)],
              width=thickness,
              fill=color)

    # If the total height of the display strings added to the top of the bounding
    # box exceeds the top of the image, stack the strings below the bounding box
    # instead of above.
    display_str_heights = [font.getsize(ds)[1] for ds in display_str_list]
    # Each display_str has a top and bottom margin of 0.05x.
    total_display_str_height = (1 + 2 * 0.05) * sum(display_str_heights)
```

```
[ ] if top > total_display_str_height:
    text_bottom = top
else:
    text_bottom = top + total_display_str_height
# Reverse list and print from bottom to top.
for display_str in display_str_list[::-1]:
    text_width, text_height = font.getsize(display_str)
    margin = np.ceil(0.05 * text_height)
    draw.rectangle([(left, text_bottom - text_height - 2 * margin),
                    (left + text_width, text_bottom)],
                  fill=color)
    draw.text((left + margin, text_bottom - text_height - margin),
              display_str,
              fill="black",
              font=font)
    text_bottom -= text_height - 2 * margin

def draw_boxes(image, boxes, class_names, scores, max_boxes=10, min_score=0.1):
    """Overlay labeled boxes on an image with formatted scores and label names."""
    colors = list(ImageColor.colormap.values())

    try:
        font = ImageFont.truetype("/usr/share/fonts/truetype/liberation/LiberationSansNarrow-Regular.ttf",
                                   25)
    except IOError:
        print("Font not found, using default font.")
        font = ImageFont.load_default()

    for i in range(min(boxes.shape[0], max_boxes)):
        if scores[i] >= min_score:
            ymin, xmin, ymax, xmax = tuple(boxes[i])
            display_str = "{}: {}".format(class_names[i].decode("ascii"),
                                          int(100 * scores[i]))
            color = colors[hash(class_names[i]) % len(colors)]
            image_pil = Image.fromarray(np.uint8(image)).convert("RGB")
            draw_bounding_box_on_image(
                image_pil,
                ymin,
                xmin,
                ymax,
                xmax,
                color,
                font,
                display_str_list=[display_str])
            np.copyto(image, np.array(image_pil))
    return image
```

Łaďadowanie obrazu i jego wyŝwietlenie

```
[ ] # By Heiko Gorski, Source: https://commons.wikimedia.org/wiki/File:Naxos\_Taverna.jpg
image_url = "https://upload.wikimedia.org/wikipedia/commons/6/60/Naxos_Taverna.jpg"
downloaded_image_path = download_and_resize_image(image_url, 1280, 856, True)
```

Pobranie modułu InceptionResNet V2, który cechuje się wysoką dokłaďnoŝcią

```
[ ] module_handle = "https://tfhub.dev/google/faster_rcnn/openimages_v4/inception_resnet_v2/1"

detector = hub.load(module_handle).signatures['default']
```

```
INFO:tensorflow:Saver not created because there are no variables in the graph to restore
INFO:tensorflow:Saver not created because there are no variables in the graph to restore
```

```
▶ def load_img(path):
    img = tf.io.read_file(path)
    img = tf.image.decode_jpeg(img, channels=3)
    return img
```

```
▶ def run_detector(detector, path):
    img = load_img(path)

    converted_img = tf.image.convert_image_dtype(img, tf.float32)[tf.newaxis, ...]
    start_time = time.time()
    result = detector(converted_img)
    end_time = time.time()

    result = {key:value.numpy() for key,value in result.items()}

    print("Found %d objects." % len(result["detection_scores"]))
    print("Inference time: ", end_time-start_time)

    image_with_boxes = draw_boxes(
        img.numpy(), result["detection_boxes"],
        result["detection_class_entities"], result["detection_scores"])

    display_image(image_with_boxes)
```

Uruchomienie programu w celu wykrycia przedmiotów widocznych na obrazku

```
run_detector(detector, downloaded_image_path)
```