Lab 02

Week 10

6733172621 Patthadon Phengpinij
Collaborators. Claude (for LaTeX styling and grammar checking)

1 Grover's Search Algorithm

The whole lab is done on local jupyter notebook. All codes and experiments are performed in the notebook provided in the appendix.

The answers and code solutions are provided
in the appendix located on the next page...

APPENDIX 1

Lab 02 | Code Solution

lab-02-code

October 24, 2026

1 Lab 2: Grover's Search Algorithm

Duration: 90 minutes. The theory was covered in the lecture; in this lab you build the two ingredients of Grover's algorithm (the oracle and the diffuser), assemble the algorithm, and run it on the simulator.

Part
Setup
Part 1) Searching classically
Part 2) The uniform superposition and the geometric picture
Part 3) The oracle
Part 4) The diffuser
Part 5) Grover's algorithm
Part 6) How many iterations?
Problems 1–4

How to use this notebook - **Exercises** — highlighted in yellow boxes. Write your code between the `### FILL YOUR CODE IN HERE` markers in the cell below the exercise text. - **Check** cells test your code. If they print a success message you can move on; if they raise an error, read the message. - **Q** — questions are highlighted in green boxes. Answer in the cell below each box.

1.1 Setup

Run this cell first to check your Python version.

[1]:
```
import sys

recommended = (3, 10)
current = sys.version_info[:2]

if current < recommended:
    print(f"You are using Python {current[0]}.{current[1]}. Python {recommended[0]}.
  ↪{recommended[1]} or later is recommended.")
else:
    print(f"Python {current[0]}.{current[1]} — looks good!")
```

```
Python 3.10 — looks good!
```

Next, run the cell below to install and upgrade the required packages. If the upgrade process causes dependency conflicts with packages already installed in your local environment, **create a new Python environment** (Python 3.12 recommended) and continue the lab there.

For guidance on setting up a clean environment and installing Qiskit, refer to the IBM Quantum documentation: https://quantum.cloud.ibm.com/docs/guides/install-qiskit

[2]:
```
# Install required packages.
# Run this cell the first time you use this notebook (or in a new environment),
# then comment the line below out on subsequent runs.

# %pip install --upgrade 'qiskit[visualization]>=2.5.0' qiskit-aer matplotlib
```

Once you have installed and upgraded the libraries, please restart the Python kernel and rerun the notebook starting from the Import Libraries cell below.

[3]:
```python
# Import Libraries
import numpy as np
from IPython.display import display

# Importing standard Qiskit libraries
import qiskit
import qiskit_aer
from qiskit import QuantumCircuit, transpile
from qiskit_aer import AerSimulator
from qiskit.quantum_info import Statevector, Operator
from qiskit.visualization import plot_histogram
from matplotlib import pyplot as plt

sim = AerSimulator()

def run(qc, shots=1024):
    """Simulate a circuit and return the measurement counts."""
    return sim.run(transpile(qc, sim), shots=shots).result().get_counts()

def amplitudes(qc):
    """Real part of the statevector amplitudes of a circuit (final measurements are ignored)."""
    return np.real(Statevector(qc.remove_final_measurements(inplace=False)).data)

print(f"Qiskit version: {qiskit.__version__}")
print(f"Qiskit Aer version: {qiskit_aer.__version__}")
```

```
Qiskit version: 2.5.2
Qiskit Aer version: 0.17.2
```

Run the next cell. It defines the plotting helpers used throughout the lab — you do not need to read it.

[4]:
```python
# Plotting helpers (you do not need to read this cell)

def _colors(N, marked):
    return ["crimson" if x in marked else "steelblue" for x in range(N)]

def plot_amplitudes(amps, marked, title, ax=None, mean=None):
    """Bar chart of (real) amplitudes, one bar per basis state x. Solutions are red."""
    ax = ax or plt.figure(figsize=(11, 3)).gca()
    N = len(amps)
    ax.bar(range(N), amps, color=_colors(N, marked))
    ax.axhline(0, color="black", lw=0.8)
    if mean is not None:
        ax.axhline(mean, color="green", ls="--", label=f"mean = {mean:.3f}")
        ax.legend(loc="upper right")
    ax.set_xticks(range(N))
    ax.set_xlabel("basis state $x$")
    ax.set_title(title)

def plot_probabilities(counts, marked, title):
    """Bar chart of measured probabilities, indexed by the integer x. Solutions are red."""
    N = 2 ** len(next(iter(counts)))
    shots = sum(counts.values())
    probs = np.zeros(N)
    for bits, c in counts.items():
        probs[int(bits, 2)] = c / shots
    plt.figure(figsize=(12, 3.5))
    plt.bar(range(N), probs, color=_colors(N, marked))
    plt.xticks(range(N))
```

```
    plt.xlabel("measured state $x$")
    plt.ylabel("probability")
    plt.title(title)
    plt.show()

def success_probability(counts, marked):
    """Fraction of the shots in which a solution was measured."""
    shots = sum(counts.values())
    return sum(c for bits, c in counts.items() if int(bits, 2) in marked) / shots
```

Run the next cell. It defines the check functions — you do not need to read it.

[5]:
```
# Check functions (you do not need to read this cell)

def _ideal_oracle(n, marked):
    """The ideal phase oracle V as an Operator: -1 on the marked basis states, +1 on all others.
    """
    return Operator(np.diag([-1.0 if x in marked else 1.0 for x in range(2**n)]))

def _ideal_diffuser(n):
    N = 2**n
    u = np.ones(N) / np.sqrt(N)
    return Operator(2 * np.outer(u, u) - np.eye(N))

def _flipped_states(U):
    """For a diagonal unitary: which basis states get a relative sign of -1."""
    d = np.diag(U.data)
    d = d * np.conj(d[0])                       # remove the global phase
    flipped = [x for x in range(len(d)) if d[x].real < 0]
    if len(flipped) > len(d) // 2:              # state 0 itself was marked: take the complement
        flipped = [x for x in range(len(d)) if x not in flipped]
    return flipped

def _check_no_measurement(qc, what):
    assert qc.count_ops().get('measure', 0) == 0, f"{what} must not contain a measurement"

def check_classical_search(search):
    import random
    rng = random.Random(1)
    for n in range(2, 7):
        for trial in range(100):
            M = rng.randint(1, 2**n // 2)
            marked = rng.sample(range(2**n), M)
            f = SearchOracle(n, marked)
            x = search(f)
            assert x in f._marked, f"n = {n}, marked = {sorted(f._marked)}: you returned {x!r},␣
    ↪which is not a solution."
            assert f.queries <= 2**n, f"n = {n}: you used {f.queries} queries, but there are only␣
    ↪{2**n} candidates."
    print("classical_search always returns a solution")

def check_phase_oracle(make_oracle):
    for n, marked in [(2, [0]), (3, [5]), (4, [3, 6, 13]), (4, [0, 15]), (5, [7, 14, 21, 28])]:
        qc = make_oracle(n, marked)
        assert qc.num_qubits == n, f"phase_oracle({n}, ...) should act on {n} qubits, yours has␣
    ↪{qc.num_qubits}"
        _check_no_measurement(qc, "phase_oracle")
        U = Operator(qc)
        if U.equiv(_ideal_oracle(n, marked)):
            continue
        if not np.allclose(U.data, np.diag(np.diag(U.data))):
```

```
            raise AssertionError(f"n = {n}, marked = {marked}: the oracle is not diagonal, so it␣
↪moves basis states "
                                 "instead of only changing their sign. Did you undo every X gate␣
↪after the MCZ, "
                                 "and put the two H gates on the *target* qubit n-1?")
        raise AssertionError(f"n = {n}, marked = {marked}: your oracle flips the sign of␣
↪{_flipped_states(U)} "
                             f"instead of {sorted(marked)}. Check which qubits get the X gates␣
↪(bit j of w is (w >> j) & 1).")
    print("phase_oracle is correct")

def check_kickback_oracle(make_oracle):
    for n, marked in [(2, [0]), (3, [5]), (4, [3, 6, 13]), (4, [0, 15])]:
        qc = make_oracle(n, marked)
        assert qc.num_qubits == n + 1, f"kickback_oracle({n}, ...) should act on {n + 1} qubits␣
↪(data + ancilla)"
        _check_no_measurement(qc, "kickback_oracle")
        test = QuantumCircuit(n + 1)
        test.h(range(n))
        test.compose(qc, inplace=True)
        sv = Statevector(test).data
        assert np.allclose(sv[2**n:], 0), (f"n = {n}, marked = {marked}: the ancilla q_{n} is not␣
↪back in |0> "
                                           "at the end. Did you prepare |-> with X then H, and␣
↪undo it with H then X?")
        expected = np.array([(-1) ** (x in marked) for x in range(2**n)]) / np.sqrt(2**n)
        assert np.allclose(sv[:2**n], expected) or np.allclose(sv[:2**n], -expected), \
            f"n = {n}, marked = {marked}: the data register does not carry the phases (-1)^f(x)."
    print("kickback_oracle is correct: it acts exactly like phase_oracle")

def check_diffuser(make_diffuser):
    for n in (2, 3, 4, 5):
        qc = make_diffuser(n)
        assert qc.num_qubits == n, f"diffuser({n}) should act on {n} qubits, yours has {qc.
↪num_qubits}"
        _check_no_measurement(qc, "diffuser")
        U = Operator(qc)
        if U.equiv(_ideal_diffuser(n)):
            continue
        if U.equiv(_ideal_oracle(n, [0])):
            raise AssertionError(f"n = {n}: your circuit flips only |0...0> - that is the middle␣
↪part. The H layers are missing.")
        if U.equiv(_ideal_oracle(n, [2**n - 1])):
            raise AssertionError(f"n = {n}: your circuit flips only |1...1> - that is a bare MCZ.␣
↪The X and H layers are missing.")
        if U.equiv(Operator(np.eye(2**n))):
            raise AssertionError(f"n = {n}: your diffuser does nothing. Did you forget the MCZ in␣
↪the middle?")
        raise AssertionError(f"n = {n}: the diffuser is not 2|phi><phi| - I. The order is H layer,␣
↪X layer, MCZ, X layer, H layer.")
    print("diffuser is correct")

def check_grover_circuit(make_circuit):
    n, marked = 4, [3, 6, 13]
    oracle = phase_oracle(n, marked)
    for k, p_expected, tol in [(0, 3 / 16, 0.06), (1, 0.949, 0.05), (2, 0.616, 0.07)]:
        qc = make_circuit(oracle, n, k)
        assert qc.count_ops().get('measure', 0) == n, f"grover_circuit should measure all {n}␣
↪qubits (qc.measure_all())"
        p = success_probability(run(qc, shots=8192), marked)
```

```
        hint = {0: "with 0 iterations the state should be |phi>: a Hadamard on every qubit,␣
↪nothing else.",
                1: "is the order 'oracle, then diffuser'? Is the diffuser applied on all n qubits?
↪",
                2: "is the loop running `iterations` times, applying the oracle AND the diffuser␣
↪each time?"}[k]
        assert abs(p - p_expected) < tol, f"k = {k}: P(solution) should be about {p_expected:.
↪2f}, you got {p:.2f} - {hint}"
        print(f"   k = {k}: P(solution) = {p:.3f}  (expected {p_expected:.3f})")
    print("grover_circuit is correct")

def check_optimal_iterations(optimal):
    for N, M, k_expected in [(16, 3, 1), (16, 1, 3), (16, 4, 1), (32, 4, 2), (32, 16, 0), (1024,␣
↪1, 25)]:
        theta, k, p = optimal(N, M)
        assert isinstance(k, (int, np.integer)), f"k must be an integer, you returned {k!r} - use␣
↪int(round(...))"
        assert np.isclose(theta, np.arcsin(np.sqrt(M / N))), f"N = {N}, M = {M}: theta should be␣
↪arcsin(sqrt(M/N))"
        assert k == k_expected, f"N = {N}, M = {M}: k should be {k_expected}, you returned {k}"
        assert np.isclose(p, np.sin((2 * k + 1) * theta) ** 2), f"N = {N}, M = {M}: P_success␣
↪should be sin^2((2k+1) theta)"
    print("optimal_iterations is correct")
```

1.2 The search problem

We are given a function

$$f : \{0,1\}^n \to \{0,1\}, \qquad f(x) = \begin{cases} 1 & x \text{ is a solution} \\ 0 & \text{otherwise} \end{cases}$$

as a black box (an **oracle**): we can evaluate f, but we know nothing else about it.

There are $N = 2^n$ candidates and M of them are solutions. The task is to **find a solution**.

- **Classically** there is nothing better than trying inputs one after the other: $O(N)$ queries.
- **Grover's algorithm** needs only $O(\sqrt{N/M})$ queries — a *quadratic* speed-up. For $n = 20$ that is about 1 000 instead of 1 000 000.

Throughout the lab we use the running example $n = 4$ ($N = 16$) with the three solutions $x \in \{3, 6, 13\}$.

1.3 Part 1) Searching classically

1.3.1 1.1 A classical black box

`SearchOracle(n, marked)` hides the solutions. You can only call it as `f(x)` with an integer `x` from `0` to `2**n - 1`; it returns `1` for a solution and `0` otherwise, and counts every call in `f.queries`.

(Please don't peek at `f._marked` — that would be opening the box!)

[6]:
```
class SearchOracle:
    """Black box for the search problem: f(x) = 1 if x is a solution, else 0. Counts every query.
↪"""
    def __init__(self, n, marked):
        self.n, self.N = n, 2**n
        self._marked = set(marked)
        self.queries = 0

    def __call__(self, x):
```

```
        self.queries += 1
        return int(x in self._marked)
```

1.3.2 Exercise 1: Write a classical search

Write `classical_search(f)` that returns **one** solution, i.e. an integer `x` with `f(x) == 1`. You may only use `f(x)` and `f.N`.

[7]:
```
def classical_search(f):
    """Return an x with f(x) == 1. f.N is the number of candidates (inputs are 0 ... f.N - 1)."""
    # Loop over the candidates x = 0, 1, ..., f.N - 1, query f(x), and return the first x with f(x) == 1.
    ### FILL YOUR CODE IN HERE
    for x in range(f.N):
        if f(x) == 1:
            return x
    ###
```

[8]:
```
# Check
check_classical_search(classical_search)
```

```
classical_search always returns a solution
```

1.3.3 1.2 How many queries?


Run your search on 2000 random instances with $N = 16$ and $M = 3$ and look at how many queries it needed.

[9]:
```
import random

n, M = 4, 3
queries = []
for seed in range(2000):
    marked = random.Random(seed).sample(range(2**n), M)
    f = SearchOracle(n, marked)
    classical_search(f)
    queries.append(f.queries)

print(f"queries needed: min = {min(queries)}, mean = {np.mean(queries):.2f}, max = {max(queries)}")
plt.hist(queries, bins=np.arange(0.5, max(queries) + 1.5))
plt.xlabel("number of queries")
plt.ylabel("number of instances")
plt.title(f"Classical search, N = {2**n}, M = {M}")
plt.show()
```

```
queries needed: min = 1, mean = 4.26, max = 14
```



Q1. Our example has $N = 16$ and $M = 3$. *(Keep these numbers in mind: at the end of Part 5 we compare them with Grover's algorithm after one oracle call.)*

Q1.1 If you are allowed only **one** query, what is the probability that you find a solution?

Q1.2 How many queries does your search need in the worst case?

Your answer:

Q1.1 With one query we test one candidate. $M = 3$ of the $N = 16$ candidates are solutions, so the probability of hitting one is $M/N = 3/16 = 0.1875$.

Q1.2 The worst case is when all $N - M = 13$ non-solutions are tested first. The next query must then be a solution, so the worst case is $N - M + 1 = 14$ queries. This matches `max = 14` in the experiment above. The average was about 4.3, close to $(N + 1)/(M + 1) = 17/4 = 4.25$.

1.4 Part 2) The uniform superposition and the geometric picture

1.4.1 2.1 The starting state $|\phi\rangle$

Grover's algorithm starts from the equal superposition of **all** candidates,


$$|\phi\rangle = H^{\otimes n}|0\rangle^{\otimes n} = \frac{1}{\sqrt{N}} \sum_{x=0}^{N-1} |x\rangle.$$

Measuring $|\phi\rangle$ is random guessing: every outcome has probability $1/N$.

> **Convention.** Qiskit is *little-endian*: qubit q_j carries bit j of the integer x, so the basis state of the integer w has qubit q_j equal to `(w >> j) & 1`.
>
> A counts key like `'1101'` is read as $q_3q_2q_1q_0$, and `int('1101', 2) == 13` is exactly the integer it represents. The helper functions use this everywhere.

[10]:
```
n = 4
qc = QuantumCircuit(n)
qc.h(range(n))          # |phi>
qc.measure_all()
counts = run(qc, shots=8192)
plot_histogram(counts, figsize=(11, 3), title="Measuring |phi>: every state has probability about 1/16")
```

[10]:



1.4.2 2.2 The geometric picture

Let $|a\rangle$ be the equal superposition of the M solutions and $|a_\perp\rangle$ the equal superposition of the $N - M$ non-solutions. The starting state lies in the plane spanned by these two,

$$|\phi\rangle = \cos\theta\,|a_\perp\rangle + \sin\theta\,|a\rangle, \qquad \sin\theta = \sqrt{\tfrac{M}{N}},$$


a small angle θ above the "bad" axis.

In the lecture there was a single target, so $|a\rangle$ was one basis state and $\sin\theta = 1/\sqrt{N}$. Here we allow M solutions: $|a\rangle$ is their equal superposition, and the only change is $\sin\theta = \sqrt{M/N}$. For $M = 1$ everything below reduces to the lecture.

Each Grover iteration rotates the state by 2θ toward $|a\rangle$ — that is the whole algorithm. Stop when the state is close to the solution axis and measure.

Run the cell to see the picture.

[11]:
```
# The geometric picture (run to display)
th = np.deg2rad(26)
fig, ax = plt.subplots(figsize=(4.6, 3.6))
ax.set_aspect("equal"); ax.axis("off")
ax.annotate("", xy=(1.15, 0), xytext=(0, 0), arrowprops=dict(arrowstyle="->", color="gray"))
ax.annotate("", xy=(0, 1.15), xytext=(0, 0), arrowprops=dict(arrowstyle="->", color="gray"))
ax.text(1.17, 0, r"$|a_\perp\rangle$ (bad)", va="center", fontsize=10, color="gray")
ax.text(0, 1.19, r"$|a\rangle$ (good)", ha="center", fontsize=10, color="gray")
ax.annotate("", xy=(np.cos(th), np.sin(th)), xytext=(0, 0), arrowprops=dict(arrowstyle="->", color="steelblue", lw=2.2))
ax.text(np.cos(th) + 0.03, np.sin(th), r"$|\phi\rangle$", color="steelblue", fontsize=13)
ax.annotate("", xy=(np.cos(3*th), np.sin(3*th)), xytext=(0, 0), arrowprops=dict(arrowstyle="->", color="crimson", lw=2.2, linestyle="--"))
ax.text(np.cos(3*th) - 0.02, np.sin(3*th) + 0.05, r"$WV|\phi\rangle$", color="crimson", fontsize=13)
a = np.linspace(0, th, 30);       ax.plot(0.32*np.cos(a), 0.32*np.sin(a), color="steelblue", lw=1)
ax.text(0.37, 0.06, r"$\theta$", color="steelblue", fontsize=12)
a = np.linspace(th, 3*th, 40);    ax.plot(0.62*np.cos(a), 0.62*np.sin(a), color="dimgray", lw=1.2)
ax.text(0.30, 0.52, r"$+2\theta$ per iteration", color="dimgray", fontsize=10)
ax.set_xlim(-0.1, 1.5); ax.set_ylim(-0.1, 1.35)
ax.set_title(r"One Grover iteration $WV$ rotates the state by $2\theta$", fontsize=10)
plt.show()
```



Q2. For our example ($N = 16$, $M = 3$):

Q2.1 Compute θ in degrees.

Q2.2 By how many degrees does one Grover iteration rotate the state, and where is the state after one iteration?

Q2.3 How many iterations would you choose?

Your answer:

Q2.1 $\sin\theta = \sqrt{M/N} = \sqrt{3/16} = 0.433$, so $\theta = \arcsin(0.433) \approx 25.66^\circ$.

Q2.2 One iteration rotates the state by $2\theta \approx 51.3^\circ$ towards $|a\rangle$. It moves from $\theta \approx 25.7^\circ$ to $3\theta \approx 77.0^\circ$, only 13° short of $|a\rangle$. A measurement then gives a solution with probability $\sin^2(3\theta) \approx 0.949$.

Q2.3 One iteration. $k_{\text{opt}} = \text{round}\left(\frac{\pi}{4\theta} - \frac{1}{2}\right) = \text{round}(1.25) = 1$. A second iteration would take the state to $5\theta \approx 128^\circ$, past $|a\rangle$, and P would drop to $\sin^2(5\theta) \approx 0.62$.

1.5 Part 3) The oracle

1.5.1 3.1 The phase oracle V

Grover's algorithm uses the oracle in the form of a **phase flip** — the operator $V = U_f$ of the lecture: it multiplies every solution by -1 and leaves the other states alone,

$$V|x\rangle = (-1)^{f(x)}|x\rangle \qquad \Longrightarrow \qquad V|a_\perp\rangle = |a_\perp\rangle, \quad V|a\rangle = -|a\rangle.$$

In the 2-D picture this is a **reflection about the bad axis** $|a_\perp\rangle$.

Building V one solution at a time. Pick one solution and call it w; in our example w is one of the integers 3, 6, 13.

We first build a circuit that flips the sign of the single basis state $|w\rangle$ and leaves every other basis state alone. Doing this once for each solution in `marked` gives V.

The gate that flips the sign of a single basis state is the **multi-controlled** Z (MCZ) on all n qubits: it multiplies $|1\ldots1\rangle$ by -1 and does nothing to the other $2^n - 1$ basis states.

To flip $|w\rangle$ instead of $|1\ldots1\rangle$, sandwich the MCZ between X gates:

1. apply X to every qubit whose bit of w is **0** — this turns $|w\rangle$ into $|1\dots1\rangle$ (and no other state into $|1\dots1\rangle$);
2. apply the MCZ — it flips the sign of this one state;
3. apply the same X gates again — this turns $|1\dots1\rangle$ back into $|w\rangle$.

Worked example: $w = 13$, $n = 4$. In binary $13 = 1101$. Qiskit is little-endian, so bit j sits on qubit q_j:

qubit	q_3	q_2	q_1	q_0
bit of $w = 13$	1	1	**0**	1
step 1 and step 3: X gate?	–	–	**X**	–

Only q_1 gets an X. Step 1 turns $|1101\rangle$ into $|1111\rangle$, step 2 multiplies it by -1, and step 3 turns it back into $|1101\rangle$, now with a minus sign.

Any other basis state is turned into something other than $|1111\rangle$ in step 1, is untouched by the MCZ, and returns to itself in step 3.

Here is the circuit:

Qiskit has no `mcz` gate, but $HXH = Z$, so an MCZ is an `mcx` with an H before and after on the target qubit:

```
qc.h(n - 1)
qc.mcx(list(range(n - 1)), n - 1)     # controls must be a list
qc.h(n - 1)
```

For several solutions, repeat the X-sandwich once for every w in `marked`.

1.5.2 Exercise 2: Build the phase oracle

Complete `phase_oracle(n, marked)` so that it flips the sign of every basis state `w` in `marked`. The list `zero_qubits` (the qubits whose bit of `w` is 0) is computed for you.

Hint: use a loop, `for j in zero_qubits: qc.x(j)`. (Qiskit raises an error for `qc.x([])` when the list is empty, which happens for $w = 11\dots1$.)

[12]:
```
def phase_oracle(n, marked):
    """V on n qubits: multiply every |w> with w in `marked` by -1."""
    qc = QuantumCircuit(n, name="Oracle")
    for w in marked:
        zero_qubits = [j for j in range(n) if ((w >> j) & 1) == 0]   # qubits where bit j of w is␣
↪0


        # For this w, add the three steps of the X-sandwich:
        #   step 1: X on every qubit in zero_qubits
        #   step 2: MCZ on all n qubits  (h on the target n-1, mcx with the controls as a list, h␣
↪on the target again)
        #   step 3: X on every qubit in zero_qubits again
        ### FILL YOUR CODE IN HERE
        for j in zero_qubits:                                        # step 1: |w> -> |1...1>
            qc.x(j)
        qc.h(n - 1)                                                  # step 2: MCZ = H . MCX . H␣
↪on the target
        qc.mcx(list(range(n - 1)), n - 1)
        qc.h(n - 1)
        for j in zero_qubits:                                        # step 3: |1...1> -> |w>
            qc.x(j)
        ###
```

```
        qc.barrier()                                                    # only to make the drawing␣
↪readable
    return qc
```

[13]:
```
# Check
check_phase_oracle(phase_oracle)
phase_oracle(4, [3, 6, 13]).draw(output='mpl')
```

```
phase_oracle is correct
```

[13]:




Apply your oracle to $|\phi\rangle$ and look at the amplitudes: the solutions should be negative, everything else positive.

[14]:
```
n, marked = 4, [3, 6, 13]
N = 2**n


qc_oracle = QuantumCircuit(n)
qc_oracle.h(range(n))                                    # |phi>
qc_oracle.compose(phase_oracle(n, marked), inplace=True)

plot_amplitudes(amplitudes(qc_oracle) * np.sqrt(N), marked,
                r"Amplitudes ($\times\sqrt{N}$) after the oracle: solutions (red) are negative")
plt.show()
```



Now add a measurement directly after the oracle and run the circuit.

[15]:
```
qc = qc_oracle.copy()
qc.measure_all()
plot_probabilities(run(qc, shots=8192), marked, "Measuring directly after the oracle")
```



Q3. The histogram above was measured directly after the oracle.

Q3.1 What does the histogram look like? Compare it with the histogram of $|\phi\rangle$ in Part 2.

Q3.2 Why does the oracle alone not help us find a solution? *Hint: a measurement only sees the probabilities* $|a_x|^2$. *What does a sign change do to them?*

Your answer:

Q3.1 The histogram is flat. Every state, solutions included, has probability about $1/16 = 0.0625$. It looks the same as the histogram of $|\phi\rangle$ in Part 2, within the shot noise.

Q3.2 The oracle only changes the **sign** of the solutions' amplitudes, $\frac{1}{4} \to -\frac{1}{4}$. A measurement only sees $|a_x|^2$, and $|-\frac{1}{4}|^2 = |\frac{1}{4}|^2$. So the probabilities are exactly those of $|\phi\rangle$, and measuring now is still random guessing. The information is stored in a relative phase that the measurement cannot see. The diffuser is what turns this sign difference into a difference in magnitude: it reflects every amplitude about the mean, so the negative amplitudes grow and the positive ones shrink.

1.5.3 3.2 Relation to the Lab 1 oracle (reading)

In Lab 1 the oracle wrote $f(x)$ into an output qubit, $U_f|x\rangle|y\rangle = |x\rangle|y \oplus f(x)\rangle$.

With the output qubit prepared in $|-\rangle$, phase kickback gives $U_f|x\rangle|-\rangle = (-1)^{f(x)}|x\rangle|-\rangle$ — exactly the phase oracle V.

So Grover's oracle is the Lab 1 oracle plus the trick from the Deutsch algorithm; here we simply build V directly.

1.6 Part 4) The diffuser

The oracle marks the solutions; the **diffuser** W — the *Grover diffusion operator* of the lecture — amplifies them.

It is the reflection about the starting state $|\phi\rangle$, and up to a global phase

$$W = 2|\phi\rangle\langle\phi| - I = H^{\otimes n}\, X^{\otimes n}\, \mathrm{MCZ}\, X^{\otimes n}\, H^{\otimes n}\,:$$

the X-sandwiched MCZ from Part 3 with $w = 0$, between two layers of H.

1.6.1 Exercise 3: Build the diffuser

Complete `diffuser(n)` from the formula above (read it right to left). Build the MCZ as in Exercise 2.

Hint: `qc.h(range(n))` applies H to every qubit.


[16]:
```
def diffuser(n):
    """W = 2|phi><phi| - I  (up to a global phase): reflection about the uniform superposition |
phi>."""
    qc = QuantumCircuit(n, name="Diffuser")
```

```
    # Add the gates of W = H X MCZ X H, reading the formula from right to left
    # (the rightmost factor is applied first). The MCZ is built as in Exercise 2.
    ### FILL YOUR CODE IN HERE
    qc.h(range(n))
    qc.x(range(n))
    qc.h(n - 1)                          # MCZ = H . MCX . H on the target
    qc.mcx(list(range(n - 1)), n - 1)
    qc.h(n - 1)
    qc.x(range(n))
    qc.h(range(n))
    ###
    return qc
```

[17]:
```
# Check
check_diffuser(diffuser)
diffuser(4).draw(output='mpl')
```

```
diffuser is correct
```

[17]:



1.7 Part 5) Grover's algorithm

One **Grover iteration** is: the oracle, then the diffuser. The oracle is a reflection about $|a_\perp\rangle$, the diffuser a reflection about $|\phi\rangle$, and two reflections make a rotation — by 2θ, toward $|a\rangle$ (the derivation is in the appendix).

In formulas the iteration is written WV (first V, then W); in code it is simply the two sub-circuits appended one after the other.

The full algorithm is

1. prepare $|\phi\rangle = H^{\otimes n}|0\rangle^{\otimes n}$;
2. repeat k times: apply the oracle, then apply the diffuser;
3. measure all qubits.

The oracle is passed in as a circuit, so the same `grover_circuit` works for any oracle, not only for `phase_oracle(n, marked)`.

1.7.1 Exercise 4: Assemble Grover's algorithm

Complete `grover_circuit(oracle, n, iterations)` following the three steps above; each step has its own block in the cell.

[18]:
```
def grover_circuit(oracle, n, iterations):
    """|phi>, then `iterations` Grover iterations (oracle, then diffuser), then measure all␣
  ↪qubits."""
    qc = QuantumCircuit(n)

    # 1. prepare |phi>: a Hadamard on every qubit
    ### FILL YOUR CODE IN HERE
    qc.h(range(n))
    ###


    # 2. repeat `iterations` times: append the oracle, then append the diffuser(n)
    #    (qc.compose(sub, inplace=True) appends a sub-circuit)
    ### FILL YOUR CODE IN HERE
    for _ in range(iterations):
        qc.compose(oracle, inplace=True)
        qc.compose(diffuser(n), inplace=True)
    ###

    # 3. measure all qubits (qc.measure_all())
    ### FILL YOUR CODE IN HERE
    qc.measure_all()
    ###
    return qc
```

[19]:
```
# Check
check_grover_circuit(grover_circuit)
grover_circuit(phase_oracle(4, [3, 6, 13]), 4, 1).draw(output='mpl', fold=-1)
```

```
  k = 0: P(solution) = 0.185  (expected 0.188)
  k = 1: P(solution) = 0.950  (expected 0.949)
  k = 2: P(solution) = 0.625  (expected 0.616)
grover_circuit is correct
```

[19]:




Run the algorithm with **one** iteration on our example and compare with the classical search of Part 1.

[20]:
```
n, marked = 4, [3, 6, 13]
shots = 8192

counts = run(grover_circuit(phase_oracle(n, marked), n, 1), shots=shots)
p = success_probability(counts, marked)
print(f"P(solution) after ONE oracle call: Grover = {p:.3f},  classical (one random query) =␣
  ↪{len(marked) / 2**n:.3f}")
plot_probabilities(counts, marked, f"Grover with k = 1: solutions {marked} (red) dominate")
```

```
P(solution) after ONE oracle call: Grover = 0.947,  classical (one random query)
= 0.188
```



1.8 Part 6) How many iterations?

After k iterations the state is

$$\cos\left((2k{+}1)\theta\right)|a_\perp\rangle + \sin\left((2k{+}1)\theta\right)|a\rangle, \qquad \theta = \arcsin\sqrt{M/N},$$

so the success probability is $P_k = \sin^2\left((2k{+}1)\theta\right)$.

We want $(2k{+}1)\theta \approx \pi/2$:

$$k_{\text{opt}} = \text{round}\Big(\frac{\pi}{4\theta} - \frac{1}{2}\Big).$$

For small θ this is approximately $\frac{\pi}{4}\sqrt{N/M}$ — the famous square root.

More is not better: with too many iterations the state rotates *past* $|a\rangle$ and the probability drops again.

1.8.1 Exercise 5: Compute the optimal number of iterations

Complete `optimal_iterations(N, M)` so that it returns `(theta, k, p_success)` with $\theta = \arcsin\sqrt{M/N}$, $k = \text{round}(\pi/4\theta - 1/2)$ as an **integer**, and $P = \sin^2((2k+1)\theta)$. Assume $1 \le M \le N$.

Hint: `np.arcsin`, `np.sqrt`, `np.pi`, `int(round(...))`.

[21]:
```
def optimal_iterations(N, M):
    """Return (theta, k, p_success) for N candidates and M solutions."""
    # theta     = arcsin(sqrt(M / N))                (in radians)
    # k         = round(pi / (4 theta) - 1/2)        as an int
    # p_success = sin^2((2k + 1) theta)
    ### FILL YOUR CODE IN HERE
    theta = np.arcsin(np.sqrt(M / N))
    k = int(round(np.pi / (4 * theta) - 1 / 2))
    p_success = np.sin((2 * k + 1) * theta) ** 2
    ###
    return theta, k, p_success
```

[22]:
```
# Check
check_optimal_iterations(optimal_iterations)

theta, k, p = optimal_iterations(16, 3)
print(f"N = 16, M = 3:  theta = {np.degrees(theta):.2f} deg,  k = {k},  P_success = {p:.4f}")
```

```
optimal_iterations is correct
N = 16, M = 3:  theta = 25.66 deg,  k = 1,  P_success = 0.9492
```

Now compare theory and simulator for $k = 0, 1, \ldots, 8$ iterations.

- **Left:** success probability against k.
- **Right:** the state in the $(|a_\perp\rangle, |a\rangle)$ plane, one arrow per iteration (solid up to the optimum, dashed beyond it).

[23]:
```
n, marked = 4, [3, 6, 13]
N, M = 2**n, len(marked)
theta, k_opt, _ = optimal_iterations(N, M)
oracle = phase_oracle(n, marked)


ks = range(9)
p_measured = [success_probability(run(grover_circuit(oracle, n, k), shots=4096), marked) for k in␣
  ↪ks]
for k, p in zip(ks, p_measured):
    print(f"k = {k}: P(solution) simulator = {p:.3f}   theory = {np.sin((2*k + 1) * theta)**2:.
  ↪3f}")

fig, (axL, axR) = plt.subplots(1, 2, figsize=(13, 4.2))

# Left: probability against the number of iterations
k_fine = np.linspace(0, max(ks), 300)
axL.plot(k_fine, np.sin((2*k_fine + 1) * theta)**2, color="steelblue", label=r"theory␣
  ↪$\sin^2((2k+1)\theta)$")
axL.scatter(list(ks), p_measured, color="crimson", zorder=3, label="simulator")
axL.axvline(k_opt, color="green", ls="--", label=f"optimal k = {k_opt}")
axL.set_xlabel("Grover iterations $k$"); axL.set_ylabel("P(solution)"); axL.set_ylim(0, 1.05)
axL.set_title("Too many iterations: over-rotation"); axL.legend()

# Right: the state vector in the 2-D plane
axR.set_aspect("equal"); axR.set_title(r"State in the $(|a_\perp\rangle,|a\rangle)$ plane")
k_show = k_opt + 2
arc = np.linspace(0, (2*k_show + 1) * theta, 200)
axR.plot(np.cos(arc), np.sin(arc), color="lightgray", lw=1)
axR.arrow(0, 0, 1, 0, head_width=0.03, color="gray"); axR.text(1.02, 0.02, r"$|a_\perp\rangle$")
axR.arrow(0, 0, 0, 1, head_width=0.03, color="gray"); axR.text(0.03, 1.05, r"$|a\rangle$")
for k in range(k_show + 1):
    ang = (2*k + 1) * theta
    color, style = ("crimson", "-") if k == k_opt else ("steelblue", "-") if k < k_opt else␣
  ↪("gray", "--")
    axR.arrow(0, 0, np.cos(ang), np.sin(ang), head_width=0.025, color=color, linestyle=style,␣
  ↪length_includes_head=True)
    axR.text(1.08*np.cos(ang), 1.08*np.sin(ang), f"k={k}", color=color, fontsize=9, ha="center",␣
  ↪va="center")
axR.set_xlim(-1.25, 1.25); axR.set_ylim(-0.25, 1.2)
plt.tight_layout()
plt.show()
```

```
k = 0: P(solution) simulator = 0.187   theory = 0.187
k = 1: P(solution) simulator = 0.950   theory = 0.949
k = 2: P(solution) simulator = 0.615   theory = 0.616
k = 3: P(solution) simulator = 0.000   theory = 0.000
k = 4: P(solution) simulator = 0.603   theory = 0.603
k = 5: P(solution) simulator = 0.960   theory = 0.955
k = 6: P(solution) simulator = 0.207   theory = 0.198
k = 7: P(solution) simulator = 0.176   theory = 0.177
k = 8: P(solution) simulator = 0.944   theory = 0.943
```



Q4. Read off the left plot.

Q4.1 What is $P(\text{solution})$ for $k = 2$ and for $k = 3$?

Q4.2 For which $k > 1$ does the probability become high again, and why?

Your answer:

Q4.1 $k = 2$: $P = \sin^2(5\theta) \approx 0.62$, since the state has over-rotated to $\approx 128°$. $k = 3$: $P = \sin^2(7\theta) \approx 0.000$, since the state is at $7\theta \approx 179.6°$, almost exactly $-|a_\perp\rangle$, so there is no solution component left.

Q4.2 It becomes high again at $k = 5$, with $P = \sin^2(11\theta) \approx 0.955$, and again at $k = 8$, with $P = \sin^2(17\theta) \approx 0.943$. Each iteration keeps rotating by the same $2\theta \approx 51.3°$, so the state goes round the circle in the $(|a_\perp\rangle, |a\rangle)$ plane. $P = \sin^2((2k+1)\theta)$ is periodic, and it is large whenever the angle is close to $90°$ *or* $270°$: the state $-|a\rangle$ gives the same probabilities as $|a\rangle$ (a global sign). - At $k = 5$: $11\theta \approx 282°$, near $270°$. - At $k = 8$: $17\theta \approx 436° = 360° + 76°$, near $90°$ again.

These later peaks need more oracle calls for no gain, so $k = 1$ remains the best choice.

1.9 Problems 1–4

The oracle is the **only** place where the problem enters; everything else is problem-independent.

The function below combines your pieces into one search:

- takes a Python predicate on n-bit integers,
- builds the oracle from its solutions,
- picks k with `optimal_iterations`,
- runs `grover_circuit` and reports the result.

Run the cell — there is nothing to fill in.

[24]:
```python
def grover_search(predicate, n, shots=4096):
    """Run Grover's algorithm for the solutions of `predicate` on n-bit integers.
    Returns (marked, k, p_theory, p_measured, counts)."""
    N = 2**n
    marked = [x for x in range(N) if predicate(x)]                # the solutions
    theta, k, p_theory = optimal_iterations(N, len(marked))       # how many iterations
    counts = run(grover_circuit(phase_oracle(n, marked), n, k), shots=shots)
    p_measured = success_probability(counts, marked)
    return marked, k, p_theory, p_measured, counts

# the running example must come out as before
marked, k, p_theory, p_measured, counts = grover_search(lambda x: x in (3, 6, 13), 4)
print(f"running example: k = {k}, P_theory = {p_theory:.3f}, P_measured = {p_measured:.3f}")
```


```
running example: k = 1, P_theory = 0.949, P_measured = 0.949
```

Run the cell below. It applies `grover_search` to four predicates on 5-bit integers ($N = 32$) and plots the histogram of each.


[25]:
```
n = 5
problems = {
    1: ("multiples of 5",          lambda x: x % 5 == 0),
    2: ("exactly three 1-bits",    lambda x: bin(x).count("1") == 3),
    3: ("perfect squares",         lambda x: int(np.sqrt(x)) ** 2 == x),
    4: ("x >= 16",                 lambda x: x >= 16),
}

for number, (name, predicate) in problems.items():
    marked, k, p_theory, p_measured, counts = grover_search(predicate, n)
    print(f"Problem {number} ({name}): M = {len(marked):2d}, k = {k}, P_theory = {p_theory:.3f},␣
 ↪P_measured = {p_measured:.3f}")
    plot_probabilities(counts, marked, f"Problem {number}: {name}  (M = {len(marked)}, k = {k})")
```


```
Problem 1 (multiples of 5): M =  7, k = 1, P_theory = 0.988, P_measured = 0.985
```





```
Problem 2 (exactly three 1-bits): M = 10, k = 1, P_theory = 0.957, P_measured =
0.962
```




```
Problem 3 (perfect squares): M =  6, k = 1, P_theory = 0.949, P_measured = 0.949
```




```
Problem 4 (x >= 16): M = 16, k = 0, P_theory = 0.500, P_measured = 0.501
```



The results (the measured values vary slightly from run to run):

Problem	predicate	M	k	P_{theory}	P_{measured}
1	multiples of 5	7	1	0.988	0.99
2	exactly three 1-bits	10	1	0.957	0.96
3	perfect squares	6	1	0.949	0.95
4	$x \geq 16$	16	0	0.500	0.50

Problem 4 stands out: $k = 0$ and $P = 1/2$, no better than guessing.

To see what is going on, run the cell below. It keeps $N = 32$ and varies the number of solutions $M = 1, 2, 4, 8, 16$ (the solutions are simply the integers $x < M$).

For comparison it also prints the average number of queries of the classical search from Part 1, which is about $(N + 1)/(M + 1)$.

[26]:
```
n = 5
N = 2**n
print(f"{'M':>3} {'theta':>7} {'k':>3} {'P_theory':>9} {'P_measured':>11} {'classical avg queries':
  ↪>22}")
for M in (1, 2, 4, 8, 16):
    marked, k, p_theory, p_measured, counts = grover_search(lambda x: x < M, n)
    theta = np.degrees(np.arcsin(np.sqrt(M / N)))
    print(f"{M:>3} {theta:>6.1f}° {k:>3} {p_theory:>9.3f} {p_measured:>11.3f} {(N + 1) / (M + 1):
  ↪>22.1f}")
```

```
  M   theta   k  P_theory  P_measured  classical avg queries
  1   10.2°   4     0.999       1.000                   16.5
```

2	14.5°	3	0.961	0.960	11.0
4	20.7°	2	0.945	0.947	6.6
8	30.0°	1	1.000	1.000	3.7
16	45.0°	0	0.500	0.502	1.9

Q5. Look at the table above ($N = 32$).

Q5.1 What happens to the number of iterations k as M grows? Why? *(Think of θ.)*

Q5.2 For $M = 16$: what is θ, and by how many degrees does one iteration rotate the state? Explain why Grover's algorithm cannot do better than $P = 1/2$ here.

Q5.3 Compare k with the classical average number of queries. For which kind of search problem is Grover's algorithm worth using?

Your answer:

Q5.1 k **decreases** as M grows: $4, 3, 2, 1, 0$ for $M = 1, 2, 4, 8, 16$. The starting angle $\theta = \arcsin\sqrt{M/N}$ grows with M ($10.2° \to 45°$), so $|\phi\rangle$ starts closer to $|a\rangle$. Each iteration also rotates by a bigger step 2θ, so fewer steps are needed to reach 90°: $k \approx \frac{\pi}{4}\sqrt{N/M}$.

Q5.2 $\theta = \arcsin\sqrt{16/32} = 45°$, and one iteration rotates by $2\theta = 90°$. The state is reachable only at the angles $(2k+1)\cdot 45° = 45°, 135°, 225°, \ldots$. Every one of these is an odd multiple of 45°, so $P = \sin^2((2k+1)45°) = \frac{1}{2}$ for **every** k. The rotation step is too coarse to ever land on $|a\rangle$: one iteration jumps from 45° straight over 90° to 135°. $k = 0$ (just measuring $|\phi\rangle$) is therefore already as good as it gets, and that is plain random guessing, since half of all inputs are solutions.

Q5.3 For $M = 1$, Grover needs $k = 4$ oracle calls against about 16.5 classical queries on average. For $M = 16$, it needs $k = 0$ against 1.9 classically, which is no real gain. The advantage is about $\sqrt{N/M}$ versus N/M, so it is large only when the solutions are **rare** ($M \ll N$) and N is large. Grover's algorithm is worth using for big, unstructured search problems with few solutions, where the oracle is expensive and classical search would need about N/M queries. When a large fraction of the inputs are solutions, random guessing already works and Grover adds nothing.

1.10 Appendix: why is one iteration a rotation by 2θ? (reading)

Notation used in this appendix ($N = 2^n$ candidates, M of them solutions):


- $|a\rangle$: the equal superposition of the M solutions; $|a_\perp\rangle$: the equal superposition of the $N - M$ non-solutions. They are orthogonal, and everything happens in the plane they span.
- $|\psi(\alpha)\rangle = \cos\alpha\,|a_\perp\rangle + \sin\alpha\,|a\rangle$: the state at angle α above the $|a_\perp\rangle$ axis.
- $|\phi\rangle = |\psi(\theta)\rangle$: the uniform superposition, with $\sin\theta = \sqrt{M/N}$.
- V: the oracle, $V|a_\perp\rangle = |a_\perp\rangle$ and $V|a\rangle = -|a\rangle$.
- $W = 2|\phi\rangle\langle\phi| - I$: the diffuser.
- WV: one Grover iteration (first V, then W).

Run the next cell for the picture (our example, $\theta \approx 25.7°$):

- the oracle reflects the state about the $|a_\perp\rangle$ axis,
- the diffuser reflects it about the line of $|\phi\rangle$,
- and the net effect is a rotation by 2θ.

[27]:
```
# The two reflections of one Grover iteration, drawn in the (|a_perp>, |a>) plane
theta = np.arcsin(np.sqrt(3 / 16))
deg = np.degrees(theta)
panels = [(f"1. start: |phi> at {deg:.1f}°",                    [theta],           None),
          (f"2. oracle: reflect about |a_perp>  ->  {-deg:.1f}°",    [theta, -theta],    0.0),
          (f"3. diffuser: reflect about |phi>  ->  {3*deg:.1f}°",  [-theta, 3*theta],  theta)]
fig, axes = plt.subplots(1, 3, figsize=(13, 4.3))
for ax, (title, angles, mirror) in zip(axes, panels):
    ax.set_aspect("equal"); ax.set_title(title, fontsize=10)
    ax.axhline(0, color="gray", lw=0.8); ax.axvline(0, color="gray", lw=0.8)
    ax.text(1.03, 0.03, r"$|a_\perp\rangle$"); ax.text(0.04, 1.03, r"$|a\rangle$")
    if mirror is not None:                                  # the mirror line of this reflection
```

```
        ax.plot([-1.15*np.cos(mirror), 1.15*np.cos(mirror)], [-1.15*np.sin(mirror), 1.15*np.
↪sin(mirror)],
                color="green", ls="--", lw=1.2, label="mirror line")
    if len(angles) == 2:
        a = angles[0]
        ax.arrow(0, 0, np.cos(a), np.sin(a), head_width=0.04, color="lightgray",␣
↪length_includes_head=True, label="before")
    a = angles[-1]
    ax.arrow(0, 0, np.cos(a), np.sin(a), head_width=0.04, color="crimson",␣
↪length_includes_head=True, label="after" if len(angles) == 2 else "|phi>")
    ax.set_xlim(-1.25, 1.25); ax.set_ylim(-1.25, 1.25); ax.set_xticks([]); ax.set_yticks([])
    ax.legend(loc="lower left", fontsize=8)
plt.tight_layout(); plt.show()
```



The derivation.

The oracle leaves $|a_\perp\rangle$ alone and flips $|a\rangle$, so it is the reflection about the $|a_\perp\rangle$ axis:

$$V|\psi(\alpha)\rangle = \cos\alpha\,|a_\perp\rangle - \sin\alpha\,|a\rangle = |\psi(-\alpha)\rangle.$$

The diffuser $W = 2|\phi\rangle\langle\phi| - I$ is the reflection about the line through $|\phi\rangle$: it keeps the component along $|\phi\rangle$ and flips the component perpendicular to it.

Reflecting the direction $-\alpha$ about the direction θ gives $2\theta - (-\alpha) = 2\theta + \alpha$:

$$WV|\psi(\alpha)\rangle = |\psi(\alpha + 2\theta)\rangle.$$

Two reflections about lines at angle θ to each other always compose to a rotation by 2θ.

Starting from $\alpha = \theta$, after k iterations

$$(WV)^k|\phi\rangle = \cos\left((2k{+}1)\theta\right)|a_\perp\rangle + \sin\left((2k{+}1)\theta\right)|a\rangle,$$

and measuring gives a solution with probability $\sin^2\left((2k{+}1)\theta\right)$, which is the formula of Part 6.

Why does the X-sandwiched MCZ realise $2|0\rangle\langle 0| - I$ up to a sign?

Flipping only $|0\ldots0\rangle$ is $I - 2|0\rangle\langle 0|$; multiplying by the global phase -1 gives $2|0\rangle\langle 0| - I$.

Global phases are unobservable, so the circuit is a valid diffuser — and the check functions compare operators only up to a global phase for the same reason.
