PDA: Software Development

Project Unit
Level 8

Iain Paterson
Cohort E15

P1
GitHub contributors page

P2
Project Brief for group project

Educational App

The BBC are looking to improve their online offering of educational content by developing some interactive apps that display information in a fun and interesting way.

Your task is to make an MVP to put forward to them - this may only be for a small set of information, and may only showcase some of the features to be included in the final app. You might use an API to bring in content or a database to store facts. The topic of the app is your choice, but here are some suggestions you could look into:

- Interactive timeline, e.g. of the history of computer programming
- Interactive map of a historical event - e.g. World War 1, the travels of Christopher Columbus

MVP

- Display some information about a particular topic in an interesting way
- Have some user interactivity using event listeners, e.g to move through different sections of content

P3
Screenshots of group planning stages

| As a...	I want to...	So that...
Young child	learn	know things
Someone who knows things	access a website	I can learn in my own time
Someone at home	access an age appropriate website	I understand what I am being taught
Website user	have clear instructions	I can use the website easily

User Journey

User journey

Your name   Animals of the world   Date   27/10/17

CODECLAN

User action

1 Start
Read welcome page and select area to learn about

User action

2
Hover over animal

User action

3
Hover off animal

User action

4
Hover over another animal

System response

-Detecting area clicked
-Send query to api
-Render area

System response

-Detect hover
-Open info box/window

System response

-Info box remains open

System response

-Event listeners
-Previous info box closes
-New info box opens

User action

5
Click on quiz button

User action

6
Completes quiz

User action

7

User action

8 End

System response

-Event listener
-Query db for info
-Render new page

System response

-Provide results
-Option to return to map

System response

System response

*Wireframes*

Home Page

Text

Animal Page

Button

Button

Text

**P4**

Acceptance Criteria

Acceptance Criteria	Expected Result/Output	Pass / Fail
User can select between pets in the vet and pets ready for adoption	A drop down menu allows user to filter between adoptable pets and pets in vets. Only showing filtered for pets	Pass
User can enter pet information and save it to a database	Clicking the 'create pet' button will save the given information to the database	Pass
User can delete pet information from the database	Once the 'delete' button has been pressed the pet information will be deleted from the database	Pass
User should be able to navigate to social media	Social media pages are displayed when the appropriate link has been pressed	Pass
User should be able to filter pets by type of animal	A dropdown displaying different types of animals is available for the user to select a type of pet. Once pressed only pets of that type will be displayed.	Fail

P5

Use of a Sitemap

P6
Use of Wireframes

Link 1 | Link 2 Link 3 | Link 4

HEADING

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nunc maximus, nulla ut commodo sagittis, sapien dui mattis dui, non pulvinar lorem felis nec erat Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nunc maximus, nulla ut commodo sagittis, sapien dui mattis dui, non pulvinar lorem felis nec erat Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nunc maximus, nulla ut commodo sagittis, sapien dui mattis dui, non pulvinar lorem felis nec erat Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nunc maximus, nulla ut commodo sagittis, sapien dui mattis dui, non pulvinar lorem felis nec erat Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nunc maximus, nulla ut commodo sagittis, sapien dui mattis dui, non pulvinar lorem felis nec erat v

Link 1 | Link 2 Link 3 | Link 4

HEADING

| Name |
| Type |
| Age |
| Date |

| Button |

P7
Sequence Diagrams

Collaboration Diagram

P8
Two Object Diagrams

Netflix Movie
Id: 212
Name: "Avatar"
Actors: "Sam Worthington","Zoe Saldana",
Director: "James Cameron"
Description: "Blue Aliens"
Genre_id : 4
Actor_id : 1386
Director_id : 345

Genre
Id: 4
Type: "Sci-Fi"

Actor
Id: 1386
Name: "Zoe Saldana"
Age: 32

Director
Id: 345
Name: "James Cameron"
Age: 60

Album
Id: 59
Name: "Feeling Strangely Fine"
Artist_id: 122
Genre_id: 5

Artist
Id: 122
Name: "Semisonic"

Genre
Id: 5
Type: "Indie"

P9

Algorithms implemented for a Black Jack card game app

makeDeck

```java
public void makeDeck() {
    for (Suit suit: Suit.values()) {
        for ( Value value: Value.values()){
            cardDeck.add( new Card( suit, value ));
        }
    }
}
```

Enums makeDeck uses

```java
public enum Suit {

    CLUBS,
    DIAMONDS,
    HEARTS,
    SPADES
}
```

```java
public enum Value {

    ACE,
    TWO,
    THREE,
    FOUR,
    FIVE,
    SIX,
    SEVEN,
    EIGHT,
    NINE,
    TEN,
    JACK,
    QUEEN,
    KING

}
```

This makeDeck algorithm was written to create a card deck from two sets of enums named Suit and Value. It firstly loops around the Suit enum to grab a card suit of either Clubs, Diamonds,

Hearts or Spades. Once a suit is selected it will then loop through the Value enum and select a value between a low Ace and the high King. It will then pair these selected Value enum with the selected Suit enum and add them as a Card to the card deck. It will then repeat this process another 51 times to create a deck of 52 cards.

cardNumberValue

```java
public int cardNumberValue( ) {
    if (value == Value.ACE)
        return 11;
    if (value == Value.JACK)
        return 10;
    if (value == Value.QUEEN)
        return 10;
    if (value == Value.KING)
        return 10;
    return value.ordinal() + 1;
}
```

The cardNumberValue algorithm is used to help assign a specific value to certain cards from the Value enum. Through the enum Ace would be assigned the value of 1, Jack would be 11, Queen would be 12 and King would be 13. For the purposes of the black jack card game Ace needs to equal 11 and Jack, Queen and King need to equal 10. So this algorithm takes the value of these cards and reassigns them to the appropriate value needed for the game. The value.ordinal() + 1 is there to add 1 to the initial values from the enum as they start from 0 to 12.

P10
Use of Pseudocode

```
def owner
    # select all entries from the owners table in database
    # select theses entries from the id assigned by the database
    # return all data about the owner from the assigned id
    # display the owner data by using the owner function
end
```

P11

A solo project I have worked on

https://github.com/patty-cc/BlackJackCardGame

P12

Screenshots of planning

Black Jack Card Game ☆ 🔒 Private

Plan ···

Create a class diagram

Create Inheritance diagram (if any)

Create wireframes for the look

User Journey

Add a card…

Research ···

Research rules of blackjack

Add a card…

Back end development ···

Create enum for suit

Create enum for card value

Create card class which takes in suit and value

Create Deck class which takes in 52 cards

Create a Player class

Create Game abstract class

Create BlackJack game class

Add a card…

Front end development ···

Source images for card game

Create welcome screen activity

Create Player name activity

Create BlackJack Game activity

Add a card…

| Button | Button |

| Text | Text | Button |

| Button | Button |

Text

Text

Text

| Button | Button |

abstract Game

Deck deck

players: ArrayList<Player>

getPlayers: AL<Players>

getNumberOfPlayers: () int

addPlayer: (Player)

interface Dealing

deal: () Card

BlackJackGame

Deck deck

dealRound: ()

winner: () String

enum Suit

HEARTS

SPADES

CLUBS

DIAMONDS

Deck

cardDeck<Card>

makeDeck: ()

shuffleDeck: ()

deal: () Card

Player

name: String

playerHand: ArrayList<Card>

getName: () String

getSize: () int

addCard: (Card)

enum Value

ACE

TWO

THREE

Card

Suit suit

Value value

getSuit: () Suit

getCardValue: () Value

P13
User input being processed

Register pet details

Name:

Alfie

Type:

Dog

Age:

7

Select Adoption Status:

At vets. Unavailable for adoption
✓ Ready for adoption

Date:

09/09/2017

Choose File dog.jpg

Add Pet

User input being used

More Info

Name: Alfie

Type: Dog

Age: 7

Adoptable: Ready for adoption

Date: 2017-09-09

Delete

P14
Interaction with data persistence

Register your details

First Name:

Test

Last Name:

Person

Address:

10 Test address

City:

Test City

Register

Conformation of data being saved

Registered Potential Owners

Register Owner

-
-
-
-

Iain
Paterson
8 Rowantree Grove
Edinburgh

-
-
-
-

Colleen
Strachan
32 Foxknowe Place
Livingston

-
-
-
-

Tommy
Richmond
7 Somewhere Street
Somewhere

-
-
-
-

Heather
Rae
12 Somewhere Upnorth
Aberdeen

-
-
-
-

Craig
Morton
16 Codeclan Place
Edinburgh

-
-
-
-

Harrison
Booth
11 Codeclan Way
Aberdeen

-
-
-
-

Test
Person
10 Test address
Test City

P15

The user requesting information, picking ready for adoption.

P16

An API being used within a program

The code that uses the API

```
                BeerContainer.jsx
37    componentDidMount() {
38      const url = 'https://api.punkapi.com/v2/beers';
39      const request = new XMLHttpRequest();
40      request.open('GET', url);
41      request.addEventListener('load',() => {
42        if (request.status !== 200) return;
43        const jsonString = request.responseText;
44        const data = JSON.parse(jsonString);
45        this.setState({beers: data});
46      })
47      request.send();
48    }
49
```

The API being used by the program

P17
Bug tracking report

Users must be able to able to add adoptee details			PASS
Users must be able to filter between adoptable and non-adoptable pets	FAIL	Implemented logic to backend ruby code to filter between pets adoption status	PASS
Users must be able to access social media pages through social media links	FAIL	Added anchor tags to social media image links	PASS
Users must be able to delete a pet from the database			PASS
Name fields should only accept letter characters and not accept numbers	FAIL	Implemented validation logic to only accept letter characters	PASS

P18
Demonstration of testing

Test one failing to pass

```
@Test
public void testCardHasValue() {
    card = new Card( Suit.DIAMONDS, Value.FIVE);
    assertEquals( 5, card.cardNumberValue());
}
```

The test is expecting the value of FIVE to be 5 but because the Value enum starts from the point of 0 FIVE currently equates to 4 so the test will fail.

Added code to make test pass


```
public int cardNumberValue( ) {

    return value.ordinal() + 1;

}
```

This code will make the enum value start from 1 instead of 0

Test now passing

Test two failing to pass


```
@Test
public void testCardValue() {
    card = new Card( Suit.HEARTS, Value.ACE );
    assertEquals( 11, card.cardNumberValue());
}
```

```
1 test failed – 39ms
▼ CardTest (com.example.user.blackjackcardgame) 39ms droid Studio.app/Contents/jre/jdk/Contents/Home/bin/java" ...
    testCardValue                39ms
                                        junit.framework.AssertionFailedError:
                                        Expected :11
                                        Actual   :0
                                        <Click to see difference>

                                            at junit.framework.Assert.fail(Assert.java:57)
                                            at junit.framework.Assert.failNotEquals(Assert.java:329)
                                            at junit.framework.Assert.assertEquals(Assert.java:78)
                                            at junit.framework.Assert.assertEquals(Assert.java:234)
                                            at junit.framework.Assert.assertEquals(Assert.java:241)
                                            at com.example.user.blackjackcardgame.CardTest.testCardValue(CardTest.java:39) <27 internal calls>
```

This test is failing as it is expecting the ACE to be of value 11 but currently it has a value of 0

Added code to make test pass


```
public int cardNumberValue( ) {
    if (value == Value.ACE)
        return 11;


    return value.ordinal() ;
}
```

Test now passing


```
1 test passed – 6ms
▼ CardTest (com.example.user 6ms    "/Applications/Android Studio.app/Contents/jre/jdk/Contents/Home/bin/java" ...
    testCardValue               6ms
                                        Process finished with exit code 0
```

Test three failing to pass


```
@Test
public void testCardGivesPrettyName() {
    card = new Card( Suit.DIAMONDS, Value.FIVE);
    assertEquals( "FIVE OF DIAMONDS", card.cardOutputName());
}
```



```
1 test failed – 32ms
▼ CardTest (com.example.use 32ms    "/Applications/Android Studio.app/Contents/jre/jdk/Contents/Home/bin/java" ...
    testCardGivesPrettyNam 32ms
                                        junit.framework.ComparisonFailure:
                                        Expected :FIVE OF DIAMONDS
                                        Actual   :FIVEDIAMONDS
                                        <Click to see difference>

                                            at junit.framework.Assert.assertEquals(Assert.java:100)
                                            at junit.framework.Assert.assertEquals(Assert.java:107)
                                            at com.example.user.blackjackcardgame.CardTest.testCardGivesPrettyName(CardTest.java:32) <27 internal calls>

                                        Process finished with exit code 255
```

This is test is failing because it is looking for the value of the card to be 'FIVE OF DIAMONDS' but currently due to the code it is thinking the card is 'FIVEDIAMONDS'

Code added to make test pass

```java
public String cardOutputName(){
    return value.toString() + " OF " + suit.toString();
}
```

Test now passing

```
                                                    1 test passed – 7ms
▼ CardTest (com.example.user 7ms    "/Applications/Android Studio.app/Contents/jre/jdk/Contents/Home/bin/java" ...
    testCardGivesPrettyName 7ms
                                    Process finished with exit code 0
```