

Search settings

ChromaDB directory

/home/patzer_adi/Documents/python/P;

Collection name

patent_rag_chunks

Patent results

10

Candidate chunks

50

☐ Use cross-encoder reranking

Reranker scores are raw logits, not probabilities.

Patent Intelligence

Inspectable patent search over the existing ChromaDB index

Describe the invention or feature you are looking for

A detective discovers a mysterious comic book that predicts the future.

Search patents

Results

Query: A detective discovers a mysterious comic book that predicts the future.

Collection chunks

67,303

Candidates

50

Patents shown

10

Embedding

0.63s

Vector search

0.88s

Retrieved chunks

50

Unique patents

22

Returned patents

10

Reranked

No

rank	patent_number	title	score	evidence_chunks	max_similarity	top3_mean_similarity
1	14905972	SYSTEMS AND METHODS USING ACOUSTIC COMMUNICATION	-0.5001	1	-0.5001	-0.5001
2	14991718	SYSTEMS, METHODS, AND DEVICES FOR SECURING CARGO	-0.5087	1	-0.5087	-0.5087
3	14903794	NETWORK APPARATUS AND COMMUNICATION CONTROL METHOD	-0.5247	4	-0.4963	-0.5532
4	14989163	IMAGE FORMING APPARATUS, IMAGE FORMING METHOD, AND NON-TRANSITORY COMF	-0.528	3	-0.5053	-0.5506
5	14991267	Start/Stop System For A Motor Vehicle Drive	-0.5353	9	-0.529	-0.5416
6	14987003	REAL-TIME DETERMINATION OF RESOURCE AVAILABILITY FOR USAGE	-0.538	4	-0.5266	-0.5494
7	14988666	BIOINFORMATICS SYSTEMS, APPARATUSES, AND METHODS EXECUTED ON AN INTEGR/	-0.5436	1	-0.5436	-0.5436
8	14904853	SYSTEMS AND METHODS FOR KEYWORD DETERMINATION AND DOCUMENT CLASSIFIC/	-0.5464	2	-0.5358	-0.5569
9	14997384	GUIDED EDIT OPTIMIZATION	-0.5505	1	-0.5505	-0.5505
10	14990445	POWER CONTROL UNIT WITH REMOTE SENSOR	-0.5524	1	-0.5524	-0.5524

1. 14905972 — SYSTEMS AND METHODS USING ACOUSTIC COMMUNICATION

Patent score

-0.5001

Max similarity

-0.5001

Top-3 mean

-0.5001

Evidence chunks

1

Decision

ACCEPTED

Retrieved 1 chunk(s) for this patent; showing the top 3 evidence chunks.

Chunk 26 · embedding rank 2 · similarity -0.5001

1 b k v n - k ± a n in correlation there is out = 1 n k = 0 n - 1 b k v n - k + a the above means that for out of correlation there is e { out } ≈ 0 e { out 2 } = σ v 2 n in correlation there is e { out } ≈ a var { out } = σ v 2 n, e { out 2 } = σ v 2 n + a 2 this means that the following two hypothesis exist, as shown through reference to fig. 6, which is a graph describing hypothesis selection, according to one embodiment of the present invention. reference is now made to fig. 6, which is a graph describing a hypothesis selection, according to one embodiment of the present invention. as seen in fig. 6, a threshold of a / 2 would be a good choice for the same miss detect and false alarm probabilities. the snr is snr = a 2 σ 2 this means that the width of the gaussian above is given by : σ v 2 n = a 2 n · snr for a given snr, increasing n would enable working with extremely low s

2. 14991718 — SYSTEMS, METHODS, AND DEVICES FOR SECURING CARGO

3. 14903794 — NETWORK APPARATUS AND COMMUNICATION CONTROL METHOD

Patent score

-0.5247

Max similarity

-0.4963

Top-3 mean

-0.5532

Evidence chunks

4

Decision

PENDING

Retrieved 4 chunk(s) for this patent; showing the top 3 evidence chunks.

Chunk 31 · embedding rank 1 · similarity -0.4963

the information indicating the transmission power of the discovery signal may be a statistic (an average value, a maximum value, a minimum value, a mode value, or the like) of the transmission power of the discovery signal in the ue 100 in its own cell. figs. 11 (a) and 11 (b) are diagrams illustrating the second operation pattern. as illustrated in figs. 11 (a) and 11 (b), the enb 200 increases the discovery time when the transmission power of the discovery signal is low but decreases the discovery time when the transmission power of the discovery signal is high. as the transmission power of the discovery signal decreases, an arrival range of the discovery signal decreases, and thus a probability that the discovery process will be performed successfully decreases. on the other hand, as the discovery time increases, the probability that the discovery process will be performed successfully increases. thus, when the transmission power of the discovery signal is low, the

probability that the discovery process will be performed successfully can be maintained at a certain level by increasing the discovery time. a sequence of notifying the ue 100 of the discovery time decided by the enb 200 is similar to that in

Chunk 35 · embedding rank 31 · similarity -0.5792

time to the enb 200. fig. 13 is a flowchart illustrating the discovery time calculation flow in the third operation pattern. as illustrated in fig. 13, a process of steps s231 to s234 is performed by each of the ues 100. in step s231, the enb 200 determines whether or not the number of ues that can be discovered in the minimum discovery time is equal to or more than a minimum of the number of discoverable ues based on the list of the inter - ue path losses acquired from the target ue 100. for example, when a value (that is, estimated reception power of the discovery signal) obtained by subtracting the inter - ue path loss from the transmission power of the discovery signal is equal to or more than a threshold value, it can be determined that it is possible to discover the neighboring ue 100 corresponding to the inter - ue path loss. when a determination result in step s231 is “ no , ” a loop for deciding the discovery time starts, and when the discovery time is less than the maximum discovery time (no in step s232), the unit discovery time

Chunk 41 · embedding rank 36 · similarity -0.5840

the information indicating the frequency band used for transmission and reception of the discovery signal by the ue 100. generally, as the frequency band is low, a radio wave is successfully propagated, and thus the enb 200 decreases the discovery time when the frequency band used for transmission and reception of the discovery signal is low. on the other hand, the enb 200 increases the discovery time when the frequency band used for transmission and reception of the discovery signal is high. (conclusion of embodiment) as described above, the enb 200 controls the discovery time based on the information on the ue 100 existing in the target area. as a result, the discovery time can adaptively be set according to the state of the ue 100 existing in the target area. thus, the discovery time can appropriately be set. other embodiments in the above embodiment, the enb 200 has been described as an example of the network apparatus according to the present invention, but the network apparatus according to the present invention is not limited to the enb 200 and may be a higher - level device (the mme 300, the oam, or the like) of the enb

▼ 4. 14989163 — IMAGE FORMING APPARATUS, IMAGE FORMING METHOD, AND NON-TRANSITORY COMPUTER READABLE MEDIUM

Patent score	Max similarity	Top-3 mean	Evidence chunks	Decision
-0.5280	-0.5053	-0.5506	3	ACCEPTED

Retrieved 3 chunk(s) for this patent; showing the top 3 evidence chunks.

Chunk 10 · embedding rank 3 · similarity -0.5053

##fter, the setting history information 18 is described with reference to fig. 2. fig. 2 is a diagram schematically illustrating an example of the setting history information 18. fig. 2 illustrates the content of a record 18a, which is one of plural records included in the setting history information 18. as described above, in the setting history information 18, past document information and past print setting information are associated with each other. as illustrated in fig. 2, past document information is information that includes a document id for uniquely identifying a past document, the document name of the past document, a user id for identifying a user who has given an instruction for a print process on the past document, information indicating a date and time when an output process was performed on the past document, and thumbnail images of the past document. as a matter of course, other pieces of information may be included in past document information. these pieces of information included in past document information are information included in the print job. therefore, past document information is extracted by the controller 30 when the print job relating to the past document is input. regarding the thumbnail images, images of a predetermined number of pages

Chunk 30 · embedding rank 21 · similarity -0.5627

in the past by the image forming apparatus 10) and the present print settings are different from past print settings that are set for the past document, a warning is output to the user prior to an output process on the present document. accordingly, the user may know prior to an output process that print settings that are set for the document which is presently printed are different from print settings used in printing of a similar document in the past. as a result, the user may take an appropriate action, such as applying past print settings, to the present print process, for example. according to this exemplary embodiment, past document information, which is information indicating a document printed in the past by the image forming apparatus 10, and past print setting information relating to the document are accumulated and stored as the setting history information 18 in association with each other. by storing the setting history information 18, it is possible to determine whether the present document is a document similar to a past document and it is also possible for the user, in a case where the present print settings are different from print settings for a similar past document, to retrieve the past print settings included in the setting history information 18 with a simple operation (by

Chunk 16 · embedding rank 35 · similarity -0.5838

whether the present document and the past document are similar documents. for example, in a case where the number of pages is set to “ 3 ” and the match rate is set to “ 90 % ”, thumbnail images of predetermined three pages (first three pages in this exemplary embodiment) of the present document and those of a past document are compared with each other and, if the match rate is 90 % or higher, the documents are determined to be similar documents. as described above, the comparison method based on thumbnail images may be regarded as a method of comparing the content of the present document with the content of a past document, thereby determining whether the documents are identical or similar to each other. as a method like this, a method of comparing sentences included in the present document with sentences included in a past document (the number of characters to be compared may be set as appropriate) or the like may be used in addition to the comparison based on thumbnail images. on the input screen illustrated in fig. 3, a user may check both the document name and the thumbnail. in this case, if the document name of a past document matches a regular expression of the

▼ 5. 14991267 — Start/Stop System For A Motor Vehicle Drive

Patent score	Max similarity	Top-3 mean	Evidence chunks	Decision
-0.5353	-0.5290	-0.5416	9	ACCEPTED

Retrieved 9 chunk(s) for this patent; showing the top 3 evidence chunks.

Chunk 38 · embedding rank 6 · similarity -0.5290

occur. what is stored in a memory within the ego vehicle 10 in this case is when change times from red to green have occurred for the light signal emitter 20. this approach uses the detected change times of the light signal emitter, i. e., historical data of the traffic control, in order to determine therefrom a future change time, i. e., the next change time, particularly via extrapolation. furthermore, the driving behavior of multiple vehicles (at the traffic light signal emitter 20) can be used as the basis for the historical data on the basis of which the future (subsequent) change time is extrapolated. to this end, previous stop phases of multiple vehicles, for example, the vehicle 30, are transmitted to the ego vehicle 10 directly or via the stationary database 40 by means of transmission to the radio interface 42 thereof. the transmission paths for these stop phases can be the same as for the time signal. a future change time is determined on the basis of the transmitted previous stop phases. the time curve of the traffic control is therefore inferred (for the future) on the basis of the preceding traffic flow. this is possible since the

Chunk 23 · embedding rank 10 · similarity -0.5440

signal emitter can be stored in a stationary database or in a memory in the vehicle. the delay can be based on the actual driveaway time instead of on the change time. this temporal relationship between the mentioned light signal emitters and the change time or the driveaway time represents the switching phases of the light signal emitters and, since it is usually constant, it can be used in future determination steps of the future change time. the delay or temporal relationship can be stored, in particular, with an individualizing descriptor of the light signal emitter (for example, the geographic position or the names of the intersecting streets, optionally including a location and / or country name and / or the type or orientation of the light signal emitter). in a step for determining a future change time, this delay or the temporal relationship can be used in order to correct the predetermined duration between the future change and the related event or to equate the predetermined duration to the delay or the temporal relationship. furthermore, a predetermined duration can be given as a specified standard value, which is corrected or replaced by a more appropriate value (for example, by

Chunk 9 · embedding rank 12 · similarity -0.5518

emitter from a red light to a green light. furthermore, the external information can also be historical data on change times of the light signal emitter so that a current state can be deduced on the basis of this information. information sources can be other vehicles, a stationary database, the control of the light signal emitter itself or optical signals of another light signal emitter which is controlled jointly with the aforementioned traffic light signal emitter or whose control is linked to the control of the traffic light signal emitter. according to a first embodiment of the invention, the determination step includes receiving a time signal which represents the future change time. alternatively, the time signal can characterize the time at which the change time occurs. in other words, the time signal itself can carry the change time as time information, or the time at which the time signal occurs characterizes the change time itself, for example, if the time signal occurs before the change time by a known duration. the time signal can be emitted, as a radio signal, from at least one further vehicle, from the traffic light signal emitter, or from a higher - order control of the traffic light signal emitter, in particular

▼ 6. 14987003 — REAL-TIME DETERMINATION OF RESOURCE AVAILABILITY FOR USAGE

Patent score	Max similarity	Top-3 mean	Evidence chunks	Decision
-0.5380	-0.5266	-0.5494	4	PENDING

Retrieved 4 chunk(s) for this patent; showing the top 3 evidence chunks.

Chunk 53 · embedding rank 5 · similarity -0.5266

may allow the system to access the user ' s accounts to determine any past / future funds that the user may receive from various resources. moreover, the system may determine the resources of the user that have yet to provide inflows (e. g., 401k accounts that cannot be accessed until a specific age, or the like). in some embodiments the system may estimate the future inflow of funds, for example, if the user receives the same payments continuously in consecutive time periods the system may continue to estimate the same fund receipts in future time periods. in some embodiments, the user may have resources that only the user is aware of, and as such the user may provide an indication of the unidentified resources to the system to include in the calculation of the user ' s resources and / or fund in - flows for the forecast interface. in some embodiments the unidentified resources may include money being paid back for a loan provided by the user that the system does know about, the user is a beneficiary of an account that the system does not know about, the user is a silent partner in business that the system does not know about, or

Chunk 58 · embedding rank 7 · similarity -0.5328

, for example, if the user makes the same payments continuously in consecutive time periods the system may continue to estimate the same payment in future time periods. for example, the system can determine the amount of funds that the user has sent for payment from various accounts within and outside of a financial institution over time. moreover, the system may determine the liabilities of the user that have yet to provide outflows (e. g., annuity payments that the user may make in the future, payments scheduled for a trust account, payments to fund a future resource purchase, or the like). in some embodiments the system may estimate the future outflow of funds, for example, if the user makes the same payments continuously in consecutive time periods the system may continue to estimate the same payments in future time periods. in some embodiments, the user may have liabilities that only the user is aware of, and as such the user may provide an indication of the unidentified liabilities to the system to include in the system ' s calculation of the user ' s liabilities and / or fund out - flows. in some embodiments the unidentified liabilities may include money the

Chunk 59 · embedding rank 42 · similarity -0.5888

to the system to include in the system ' s calculation of the user ' s liabilities and / or fund out - flows. in some embodiments the unidentified liabilities may include money the user is paying back for a loan provided to the user (e. g., loan from a family member or friend, or the like) that the system does know about, the user is supporting a dependent that the financial institution does not know about, the user is a silent partner in business that the system does not know about, or the like. block 516 illustrates that the system determines the estimated future outflows that the user pays based on the past outflows and future outflows. the system may determine the estimated outflows that the user may pay (e. g., may decide to pay, may be required to pay based on applicable laws, payments made to cover liabilities, or the like) in the future. the estimated outflows may be averaged over a one or more time periods (e. g., short term, long term, or the like), may be determined for one or more time periods, or may be determine until reaching

› 7. 14988666 — BIOINFORMATICS SYSTEMS, APPARATUSES, AND METHODS EXECUTED ON AN INTEGRATED CIRCUIT PROCESSING PLATFORM

› 8. 14904853 — SYSTEMS AND METHODS FOR KEYWORD DETERMINATION AND DOCUMENT CLASSIFICATION FROM UNSTRUCTURED TEXT

› 9. 14997384 — GUIDED EDIT OPTIMIZATION

› 10. 14990445 — POWER CONTROL UNIT WITH REMOTE SENSOR

› Pipeline inspection