



SAVITRIBAI PHULE PUNE UNIVERSITY

Supplement

LR

Verified all entries & found correct

Jr. Supervisor's Name, Signature & Date

Seat No. (in figures) MS 2506

Centre :

Seat No. (in words) MS Two five zero six

Day & Date : Tuesday, 18 Sept 2025

Examination : Test 3

Subject : Comp. Tech. mal lab - I

Section : I

Course/Paper No. SC - 504

Medium of Answer: English

Supplement No.: 0

= Total

7

Write the answer book in blue or black ink/ball pen only and use of pencils in case of diagrams & sketches.

Q. No./Q. No.

Q1.

a) #include <stdio.h>

int main()

{

int n, i;

printf("Enter a number negative number n is |n|")

scanf("%d\n", &n);

if (n > 0)

{ printf("It is a +ve number");

return 1;

}

i = -1; // initialize i = -1

while (i != n) // Good!

{ // while loop start

INSTRUCTIONS

सूचना

- DO NOT WRITE NUMBER ANYWHERE EXCEPT AT THE PLACE PROVIDED FOR. IF SEAT NUMBER IS WRITTEN ANY WHERE ELSE IT WILL BE TREATED AS UNFAIR MEANS AND THE PERFORMANCE WILL BE TREATED AS NULL AND VOID FOR THE ENTIRE EXAMINATION.
- नियोजित जागेशिवाय अन्यत्र आसन क्रमांक लिहू नका. अन्यत्र आसन क्रमांक लिहिल्यास ती गोष्ट अनुचित मानली जाईल आणि त्या संपूर्ण परीक्षेच्या संदर्भात परीक्षार्थी म्हणून त्यास बाद ठरविले जाईल.
- WRITE YOUR ANSWERS IN LEGIBLE HAND. ANSWERS WRITTEN IN AN UNDECIPHERABLE HAND ARE LIABLE TO BE MARKED AS ZERO.
- उत्तरे सुवाच्य अक्षरांत असावीत. अवाचनीय आणि अनाकलनीय अक्षरांत लिहिलेल्या उत्तरांना शून्य गुण दिले जातील.
- AN ACT OF COPYING OR OF IMPERSONATION AT AN EXAMINATION IS PUNISHABLE UNDER 'THE MAHARASHTRA PREVENTION OF MALPRACTICE AT UNIVERSITY, BOARD AND OTHER SPECIFIED EXAMINATIONS ORDINANCE, 1982'. THE ACT PASSED TO THE EFFECT.
- कोंपी करणे किंवा दुसऱ्याच्या नावावर परीक्षेस बसणे यांसारख्या कृती 'महाराष्ट्र-प्रीव्हेंशन ऑफ मालप्रॅक्टिस अँड युनिव्हर्सिटी, बोर्ड अँड अदर स्पेसिफाईड एक्झामिनेशन्स ऑर्डिनन्स, १९८२' त्यानुसार संमत केलेला कायदा या अन्वये दंडनीय असतील.
- Hollow Craft is to be pasted on space marked with dotted line.
- होलो क्राफ्ट स्टीकर विहित जागेवर लावावी.

प्र. क्र./Q. No.

Q. 12

a)

```
if (i % 2 == 0 && i % 3 != 0)
    i % 5 == 0
```

```
{
    printf("chill\n");
}
```

```
else if (i % 2 == 0 && i % 3 != 0)
```

```
{
    printf("

```

```
if (i % 2
```

```
printf("FizzTwos\n");
}
```

```
// end if
```

```
else if (i % 3 == 0 && i % 5 == 0)
```

```
{
```

```
if (i % 3 == 0)
```

```
printf("Fizz\n");
```

```
if (i % 5 == 0)
```

```
printf("Buzz\n");
}
```




Q. No.

Q10

a) `if (i % 3 == 0 || i % 5 == 0)`
 `printf("Epic combo");` // else block
 `if (i % 3 == 0)`
 `printf("Epic combo");`
 `else`
 `printf("Epic combo");`
 `if (i % 5 == 0)`
 `printf("Epic combo");`
 `else`
 `printf("Epic combo");`
 `return 0;` // loop
 `return 0;`
 // end main

b) `#include <stdio.h>`
 `int main()`
 `{`
 `int n;`

`printf("Enter a number n");`
 `scanf("%d", &n);`

`for (int i = 1; i <= n; i++)`

`{`
 `for (int j = 1; j <= i; j++)`

`{`
 `printf("%d ", j);`

`}`
 `printf("\n");`

`}` // j loop
 `}` // i loop

`return 0;`
 `}`

Q. 2. / 10 Marks

Q2.

a) #include <stdio.h>

int main()

{

int n;

int * arr;

printf("Enter a number n");
scanf("%d", &n);

b) #include <stdio.h>

int main

{

int n, i = 1, j = 1;

printf("Enter a number n");
scanf("%d", &n);

int j;

while (i <= n)

{

while (j <= n)

{

printf("%d", j++); // Print the increment

}

printf(" ");

i++;

}

// end while i

}

return

Almost correct
logicfor each i iteration j should
be reinitialized.



R. No./Q. No.

Q1-

b) return 0;
}

c) #include <stdio.h>
// Even roll number : for loop

int main()

{

int n;

int *arr;

int avg = 0;

printf("Enter a number n: \n");

scanf("%d", &n);

arr = (int *) malloc(n * sizeof(int));

printf("Enter elements in our dynamic array

for(int i=0; i<n; i++)

{

scanf("%d", &arr[i]);

~~avg = avg + arr[i];~~

}

for(int i=0; i<n; i++)

{

avg = avg + arr[i];

}

avg = avg / n;

Good!

6



Q. No.

Q 1.

c) `printf("Average is %d", avg);`
`& free(arr);` ✓ *Good!* ✓
`return 0;`
`}`

d) `#include <stdio.h>`

`int main()`

`{`

`int n;`

`int *arr;`

`int pos-count = 0;`

`int neg-count = 0;`

`int zero-count = 0;`

`printf("Enter the size of array: \n");`
`scanf("%d", &n);`

`arr = int (*int) malloc(n * size of (int));`

`printf("Enter integer elements in array:
 i.e +ve, -ve, and 0's \n");`

`for (int i = 0; i < n; i++)`
`{`

~~printf~~

`scanf("%d", &arr[i]);`

`}`



Q1-

d) for (int i = 0; i < n; i++)

{

if (arr[i] == 0)

zero-count++;

{

else if (arr[i] < 0)

neg-count++;

else if (~~arr[i] > 0~~)

pos-count++;

} // end for-loop

printf("Positive Count: %.d\n", pos-count);

printf("Negative Count: %.d\n", neg-count);

printf("Zero Count: %.d\n", zero-count);

printf("Pairs with Positive Sum!\n");

for (int i = 0; i < n; i++)

{

for (int j = i+1; j < n; j++)

{

if (arr[i] + arr[j] < 0)

{

printf("(%.d, %.d)\n", arr[i], arr[j]);

} // end for j

} // end for i

} // end for i

free(arr);

return 0;

{

true pairs are needed

Relax & be confident



R. No./Q. No.

$$1 - n$$

$$1:2 + 1 / -$$

$$19 \pm 2$$

$$-151 = -2$$

$$(0 > 2)$$

$$[1 + 1000] - 200$$

$$0$$

$$[1 + 1000] - 200$$

$$[1000 - 200] \times 10 = 100000$$

$$[1000 - 200] \times 10 = 100000$$

$$[1000 - 200] \times 10 = 100000$$

$$[1000 - 200] \times 10 = 100000$$

$$[1000 - 200] \times 10 = 100000$$

$$[1000 - 200] \times 10 = 100000$$

$$[1000 - 200] \times 10 = 100000$$

$$[1000 - 200] \times 10 = 100000$$

$$[1000 - 200] \times 10 = 100000$$

$$[1000 - 200] \times 10 = 100000$$