

# m\_utl\_ds2ddl.sas File Reference

## Utilities

Utility macro to create a Data Definition Language DDL script

---

### Description

This macro obtains all column, index and constraint information from a given dataset to be used to generate a Data Definition Language (DDL) file. The DDL file contains a SAS proc sql step to create a new instance of the given source dataset.

### Autors

Paul Alexander Canals y Trocha (paul.canals@gmail.com)

### Date

2021-01-27 00:00:00

### Version

21.1.01

### Link

<https://github.com/paul-canals/toolbox>

## Parameters

Input	help	Parameter, if set (Help or ?) to print the Help information in the log. In all other cases this parameter should be left out from the macro call.
Input	libnm	Parameter to specify the SAS library reference. The default value for LIBNM is: <code>_NONE_</code> .
Input	tblnm	Parameter to specify the SAS dataset or table. The default value for TBLNM is: <code>_NONE_</code> .
Input	ddl_file	Specifies the full path and name of the DDL file where the formatted output is written to. If the file that you specify does not exist, then it will be created for you. The default value for DDL_FILE is: <code>_NONE_</code> .
Input	prm_flg	Boolean [Y N] parameter to specify whether the output DDL contains the identical libref, table name, and credentials as the input source table or to parameterize this information by using SAS macro variables instead. If PRM_FLG=Y, the libref, table name and optional credentials are replaced by the PRM_LIB, PRM_TBL, and PRM_CREDS values. The default value is: N.
Input	prm_lib	Optional. Parameter to specify the output DDL SAS library reference name or the SAS macro variable name value (e.g. &libref.).
Input	prm_tbl	Optional. Parameter to specify the output DDL SAS dataset name or the SAS macro variable name value (e.g. &table.).
Input	prm_creds	Optional. String containing the output DDL SAS encryption key value information. The following parameter syntax is to be respected to work properly: encrypt=aes encryptkey= Alternatively a SAS macro variable name value can be used (e.g. &creds.).
Input	print	Boolean [Y N] parameter to generate the output by using proc report steps with style HtmlBlue. The default value for PRINT is: N.
Input	debug	Boolean [Y N] parameter to provide verbose mode information. The default value is: N.

## Returns

- Returns all column index information on a given table.

## Calls

- [m\\_utl\\_chk\\_table\\_exist.sas](#)
- [m\\_utl\\_create\\_dir.sas](#)
- [m\\_utl\\_get\\_sashelp.sas](#)
- [m\\_utl\\_get\\_tbl\\_columns.sas](#)
- [m\\_utl\\_get\\_tbl\\_constraints.sas](#)
- [m\\_utl\\_get\\_tbl\\_indexes.sas](#)
- [m\\_utl\\_hash\\_lookup.sas](#)
- [m\\_utl\\_nlobs.sas](#)
- [m\\_utl\\_print\\_message.sas](#)
- [m\\_utl\\_print\\_mtrace.sas](#)
- [m\\_utl\\_printto.sas](#)

## Usage

Example 1: Show help information:

```
%m_utl_ds2ddl(?)
```

For the next examples create a table with a couple of indexes:

```
proc sql noprint feedback stimer;
  CREATE TABLE WORK.BANKKONTO (
    MANDANT_ID          VARCHAR(8)      label='Mandant Identifier'
  , PARTNER_ID          NUMERIC(8)      label='Geschäftspartner Identifier'
  , KONTO_ID            NUMERIC(8)      label='Konto Identifier'
  , KONTO_WAEHRUNG_CD   VARCHAR(3)      label='Geschäftswährung'
  , KONTO_TYPE_CD       VARCHAR(32)     label='Konto Type Code'
  , SALDO_AMT           NUMERIC(8)      format=19.2 label='Saldo Betrag'
  , LOAD_DTTM           NUMERIC(20)     format=datetime20. label='Ladezeitstempel'
  , CONSTRAINT PRIM_KEY PRIMARY KEY (MANDANT_ID, KONTO_ID, LOAD_DTTM)
  );
  CREATE UNIQUE INDEX PARTNER_ID ON WORK.BANKKONTO (PARTNER_ID);
  CREATE INDEX IDX_BANKKONTO ON WORK.BANKKONTO (KONTO_ID, LOAD_DTTM);
quit;
```

Example 2: Create a Data Definition Language file for table bankkonto:

```
%m_utl_ds2ddl(
  libnm      = WORK
, tblnm      = bankkonto
, ddl_file   = %sysfunc(getoption(WORK))/bankkonto_work.sas
, print      = Y
, debug      = Y
);
```

Example 3: Create a DDL file for table bankkonto with libref parameter:

```
%m_utl_ds2ddl(
  libnm      = WORK
, tblnm      = bankkonto
, ddl_file   = %sysfunc(getoption(WORK))/bankkonto_libref.sas
, prn_flg    = Y
, prn_lib    = %nrstr(&libref.)
, print      = Y
, debug      = Y
);
```

Example 4: Create a DDL file for table bankkonto with creds parameter:

```
%m_utl_ds2ddl(
  libnm      = WORK
, tblnm      = bankkonto
, ddl_file   = %sysfunc(getoption(WORK))/bankkonto_creds.sas
, prn_flg    = Y
, prn_lib    = %nrstr(&libref.)
, prn_creds  = %nrstr(&creds.)
, print      = Y
, debug      = Y
);
```

## **Copyright**

Copyright 2008-2021 Paul Alexander Canals y Trocha.

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <<https://www.gnu.org/licenses/>>.