

m_utl_get_data_info.sas File Reference

Utilities

Utility macro to collect the user session library information

Description

This program collects the user session data library information from the SAS dictionary tables. The result list can be filtered using prefixes and/or wildcard list of search words.

Autors

Paul Alexander Canals y Trocha (paul.canals@gmail.com)

Date

2021-10-21 00:00:00

Version

21.1.10

Link

<https://github.com/paul-canals/toolbox>

Parameters

Input	help	Parameter, if set (Help or ?) to print the Help information in the log. In all other cases this parameter should be left out from the macro call.
Input	prefix	Optional. Specifies a textual string to filter the output returned by the dictionary tables.
Input	contains	Optional. Specifies a character search string to reduce the selected data libraries in the result to those having the contain parameter word value as part of the data library name.
Input	position	Optional. Indicator [START END] or left blank to determine where the parameter CONTAINS word value is positioned in the data library name.
Input	outlib	Specifies the LIBNAME name in which the output SAS datasets or database tables will be stored. The default value for OUTLIB is: _NONE_.
Input	debug	Boolean [Y N] parameter to provide verbose mode information. The default value is: N.

Returns

- WORK.data_info

Calls

- [m_utl_get_sashelp.sas](#)
- [m_utl_print_message.sas](#)
- [m_utl_print_mtrace.sas](#)
- [m_utl_quote_elems.sas](#)

Usage

Example 1: Show help information:

```
%m_utl_get_data_info(?)
```

Example 2: Get the data library list containing all libnames:

```
%m_utl_get_data_info(  
    outlib = WORK  
    , debug = Y  
);
```

Example 3: Get the data library list containing libnames with HELP:

```
%m_utl_get_data_info(  
    contains = HELP  
    , position = END  
    , outlib = WORK  
    , debug = Y  
);
```

Example 4: Get the data library list containing libnames with SAS or WORK:

```
%m_utl_get_data_info(  
    contains = SAS Work  
    , outlib = WORK  
    , debug = Y  
);
```

Example 5: Get the data library list containing libnames with prefix SAS:

```
%m_utl_get_data_info(  
    prefix = SAS  
    , outlib = WORK  
    , debug = Y  
);
```

Copyright

Copyright 2008-2021 Paul Alexander Canals y Trocha.

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <<https://www.gnu.org/licenses/>>.